

Client: _____ Project Name: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO #: _____ Quantity: _____

Notes: _____



Miniature Line Voltage Graze Fixture.

MODA MINI GRAZE GLOWDIM INTERIOR is an award winning, patented, miniature line voltage graze lighting system that combines the uniquely designed grazing optics of Mini Graze with the industry leading GLOWDIM technology. MODA GLOWDIM TECHNOLOGY enabled fixtures when wired to a DMX 512 Controller to transition at 100% from 2700K down to 1800K, or 3000K down to 2200K, when dimmed. Generally called "Dim to Warm" this feature strongly resembles incandescent illumination and transforms restaurants, bars and any hospitality location creating moods and warm environments. GLOWDIM utilizes MODA's high standard for perfect and precise illumination, with custom firmware programmed onto our microprocessors.

GLOWDIM is much more than "Dim to Warm". Fixtures that are called Dim to Warm all behave differently. Some can dim and turn orange. Some do not even dim much. Others you can see the transition steps. The majority just do a color adjustment and can only dim as low as 10%. This creates a flash effect when they are turned on. GLOWDIM does exactly what the name says. The MODA Microprocessor makes thousands of calculations so that the fixture gradually reduces its CCT and decreases its intensity creating a smooth dim from incandescent illumination down to true low intensity candle light. It is this reason we called this technology MODA GLOWDIM TECHNOLOGY and probably why it won the prestigious Product Innovation Award (PIA) 2017 for Components and Light Sources.

Unlike other fixtures which are much larger in physical size, MINI GRAZE utilizes the latest Advanced MODA Design and Electronic Engineering, ensuring fixtures are cool to the touch. This is achieved by designing a forward thinking fixture with intelligent driver technology and by under driving the most advanced LEDs in the World. Thus creating a fixture which is so cool it can be held after days of illumination. The L70 (longevity) of the fixture is extended and phosphor degradation kept to a minimum.

The Onboard American Microprocessor, programmed by our MODA Software Division with new Advanced Firmware ensures MINI GRAZE delivers smooth, no noise, flicker free and synchronized GLOWDIM dimming down to 0%. The actual dimming minimum value is dependent upon the dimmer selected. Link any combination of 1ft or 4ft fixtures and every fixture will dim to warm together, smoothly, synchronized from 100% to 0%. With no minimum run lengths required, just one 1ft fixture will dim seamlessly.

Wall wash any indoor application with its integral linear optic of 30° x 100° for a perfect asymmetric beam pattern with no color over angle, no striations and no dark spots up to 20ft (6m). Achieve long single runs of up to 160 feet decreasing the number of wiring circuits required in an installation. Another step forward in this category of small sized fixtures is the Universal power input. We designed a small MODA Micro Driver specific for MINI GRAZE enabling it to accept 100-277V AC 50/60Hz, thus decreasing the number of SKU's needed to be held by any of our Worldwide distributors and giving the installer a choice of power inputs from one fixture.

With the ability to mix our own phosphors we are able to make a revolutionary new standard for MODA offering a High Color Rendering Index of 96-98 with LEDs centered on The Planckian Locus for superior illumination. R1-R15 tested to TM30-15 with values in excess of 90, creating beautiful graze illumination. Single binning means every fixture will have the same CCT - something that MODA has been doing since 2006. A specialized curved polymer optical lens combined with a cleverly designed Light Chamber delivers a light bending, smooth 200 degree beam pattern perfect for cove installations with no color over angle, no striations, inter locking fields of light and no dark spots.

The fixture incorporates an integral, patented, toolless self-locking bracket which slides into any position and turns 170 degrees. Built-in male & female connectors with thumb latch connections for fast installation time. Lightweight aluminum construction for durability and excellent thermal characteristics. Quality American Made electronic components. Available in 1ft and 4ft sections.

Tested by Intertek to UL1598 for use in USA & Canada. CE Approved. WEE. RoHS Compliant. TM-30-15 Tested. US Patent No. D787,112 and D783,890.

Product Innovation Award (PIA) 2017 for Components and Light Sources. Product Innovation Award (PIA) Winner 2016 for Best Luminaires. LFI Innovation Award 2017 Finalist for Dynamic Color, Theatrical, Cove, Strips and Tape. Lux Award Commended for Interior Product of the Year 2016. Darc Awards Finalist for Best Architectural Lighting Product - Interior Luminaires 2016. International Design Excellence Award for Innovative Product Design Finalist 2016.

Designed & Developed by MODA LIGHT in Las Vegas, USA.

PAGE

3	FEATURES
4	1 FOOT
5	1 FOOT POLAR CANDELA & ILLUMINANCE AT DISTANCE
6	4 FOOT
7	4 FOOT POLAR CANDELA & ILLUMINANCE AT DISTANCE
8	TM30
9	TM30 / R VALUES / CHROMATICITY
10	DMX WIRING
11	GRAZING
12	ACCESSORIES: MOUNTING TRACK
13	ACCESSORIES: LOUVRES ASYMMETRIC
14	ACCESSORIES: LOUVRES SYMMETRIC
15	ACCESSORIES: LOUVRES HONEYCOMB
16	ACCESSORIES: CABLES
17	FIXTURES & ACCESSORIES

PHYSICAL

Dimensions	L: 1ft 3/32in (307.46mm) W: 1 1/4in(38mm) L: 4ft 1/8in (1.22m) H: 1 11/32in(34.5mm)
Weights	1ft: 0.38 lbs (0.17kg) 4ft: 1.22 lbs (0.55 kg)
Applications	Graze, Accent & Indirect General Illumination
Construction	6063 Aluminum Body, Polycarbonate Self-Locking Mounting Bracket and Optical Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	MODA Aluminum Heat Sink
Beam Angle	30° X 100°
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-4°F ~ 149°F (-20°C ~ 65°C)
Storage Temperature	-13°F ~ 158°F (-25°C ~ 70°C)
Humidity	20-70% Non Condensing

OUTPUT

CCT	2700K to 1800K 3000K to 2200K
SDCM	2 Step MacAdam Ellipse
Color Bin Tolerance	Zero Bin
CRI	98
Lumen Maintenance	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX 512
Power Factor	≥ 0.98

MODA TECHNOLOGY

moda**SOFTWARE**[™]

moda**HARDWARE**[™]

moda**DIM**[™]

moda**LED**[™]

moda**MICRO DRIVER**[™]

moda**PHOSPHOR**[™]

moda**ZERO BIN**[™]

moda**THERMAL MANAGEMENT**[™]

moda**GLOWDIM**[™]

moda**AIRFLOW**[™]

moda**COLOR RENDITION**[™]

moda**LOCK**[™]

moda**KWIK CONNECT**[™]




RoHS ✓



Certification Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.

Class 1

Warranty 5 Year Limited Warranty



0-10V

Standard Output	Lumens	CRI	Efficacy (120V)	Efficacy (240V)	Efficacy (277V)
2700K - 1800K	448.00	98	86.15	78.59	74.66
3000K - 2200K	489.00	98	94.03	85.78	81.5


SO Power Consumption

120V	5.8W	120V AC	120 ft
240V	5.8W	240V AC	240 ft
277V	6.2W	277V AC	240 ft


SO Max Continuous Run

POLAR CANDELA DISTRIBUTION


1800K




2700K



2200K




3000K




ILLUMINANCE AT A DISTANCE


1800K




2700K




2200K



3000K



Due to continuous improvements and innovations, specifications may change without notice.
Please refer to our website for current technical data. These figures are provided as a guideline only and may vary with differing power supplies and installations. All rights reserved. E&OE.



0-10V

CCT	Lumens	CRI	Efficacy (120V)	Efficacy (240V)	Efficacy (277V)
2700K - 1800K	1779	98	97.21	93.63	92.17
3000K - 2200K	1891	98	103.33	99.52	97.97

Power Consumption


120V	21.6W
240V	21.6W
277V	21.8W

Max Continuous Run


120V AC	120 ft
240V AC	240 ft
277V AC	240 ft

POLAR CANDELA DISTRIBUTION


1800K




2700K



2200K




3000K




1 FOOT ILLUMINANCE AT A DISTANCE


1800K




2700K




2200K




3000K




1800K TM30




Color Evaluation Sample




2200K TM30




Color Evaluation Sample




2700K TM30




Color Evaluation Sample



3000K TM30




Color Evaluation Sample



R VALUES

	1800K	2200K	2700K	3000K
R1	98	97	99	99
R2	99	98	99	99
R3	97	97	97	97
R4	98	94	99	99
R5	96	96	99	99
R6	96	94	97	97
R7	95	97	97	97
R8	94	97	95	95
R9	93	93	93	93
R10	97	98	98	98
R11	97	90	97	97
R12	88	92	87	87
R13	98	97	99	99
R14	95	96	97	97
R15	97	99	98	98



CIE 1931 CHROMATICITY DIAGRAM



CCT Coordinates

1800K	x: 0.5426	y: 0.4092	u: 0.3012	v: 0.5428
2200K	x: 0.5043	y: 0.4090	u: 0.2924	v: 0.5353
2700K	x: 0.4563	y: 0.4048	u: 0.2628	v: 0.5246
3000K	x: 0.4085	y: 0.3875	u: 0.2391	v: 0.5104

DMX Controller



Wiring Legend

1	Power 100-277V AC
2	DMX Controller
3	5 Pin Leader Cable
4	Junction Box
5	Wiring Nuts


5 Pin Leader Cable

	UL/cUL	CE/CCC*
A Live 100-277V	— Black	— Brown
B Neutral	== White	— Blue
C Ground	— Green	— Green/Yellow
D DMX Positive	— Purple	— Black
E DMX Negative	— Gray	— Gray


*Not illustrated

DMX Connectors


Male Output




Female Output




Angle Adjustment





Wallwash Optic.

Wall wash any indoor application with its integral linear optic of 30° x 100° for a precise beam pattern with no color over angle, no striations and no dark spots up to 20ft (6m).




Setback Chart

10ft Wall

1ft

Recommended Setback from wall is 1/8 of wall height.



MODA MINI GRAZE MOUNTING TRACK

Mounting Mini Graze.


Allows users to install Moda Mini Graze fixtures in a continuous linear position. Moda Mini Graze Mounting Tracks come packaged in 5 pieces of 4ft sections to create a continuous run of 20ft.

Options

Finish G - Gray

Length 4ft - 4' Sections




Quantity 5 Pieces (20ft)



Physical

Applications Graze, Accent

Construction Polycarbonate



MODA MINI COVE LOUVRES ASYMMETRIC

Asymmetric Mini Cove.

Provides light control and cutoff of glare for cove and wall grazing applications without causing significant light loss. For four foot fixtures use four of these louvres.

Options


Finish B - BLACK




Length 1ft

Physical

Applications Cove, Accent, Graze

Construction ABS





MODA MINI COVE LOUVRES SYMMETRIC

Symmetric Mini Cove.

Provides light control and cutoff of glare for cove and wall grazing applications without causing significant light loss. For four foot fixtures use four of these louvres.

Options


Finish B - BLACK



Length 1ft

Physical

Applications Cove, Accent, Graze

Construction ABS





MODA MINI COVE LOUVRES HONEYCOMB

Honeycomb Mini Cove.

Provides light control and cutoff of glare for cove and wall grazing semi direct view applications. For four foot fixtures use four of these louvres.

Options


Finish B - BLACK

Length 1ft

Physical


Applications Cove, Accent, Graze

Construction ABS




DMX LEADER CABLES


Moda Mini Cove Interior 5 Pin Leader Cables



Male Connector




Pin Assignment




	UL/cUL	EU/CCC
1	Live 100-277V	Black
2	Neutral	White
3	Ground	Green
4	Data Positive	Purple
5	Data Negative	Gray

DMX JUMPER CABLES


Moda Mini Cove Interior 5 Pin Jumper Cables




Connectors



Pin Assignment



	UL/cUL	EU/CCC
1	Live 100-277V	Black
2	Neutral	White
3	Ground	Green
4	Data Positive	Purple
5	Data Negative	Gray



	UL/cUL	EU/CCC
1	Data Negative	Gray
2	Data Positive	Purple
3	Ground	Green
4	Neutral	White
5	Live 100-277V	Black

ITEM	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Moda Mini Graze Interior Glowdim Standard Output Silver DMX 512 2700K-1800K HCRI 1FT	MMGI-S-S-DMX512-GD2718-1	147-1002	
Moda Mini Graze Interior Glowdim Standard Output Silver DMX 512 3000K-2200K HCRI 1FT	MMGI-S-S-DMX512-GD3022-1	147-1023	
Moda Mini Graze Interior Glowdim Standard Output Silver DMX 512 2700K-1800K HCRI 4FT	MMGI-S-S-DMX512-GD2718-4	147-3002	
Moda Mini Graze Interior Glowdim Standard Output Silver DMX 512 3000K-2200K HCRI 4FT	MMGI-S-S-DMX512-GD3022-4	147-3023	
ACCESSORIES	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Leader Cable US 5 Pin 10ft	Power to first fixture of run	MLCI-US-5PIN-W-10FT	299-0100
Leader Cable US 5 Pin 25ft	Power to first fixture of run	MLCI-US-5PIN-W-25FT	299-0102
Jumper Cable US 5 Pin 1ft	Connection between fixtures	MJCI-US-5PIN-W-1FT	299-1100
Jumper Cable US 5 Pin 4ft	Connection between fixtures	MJCI-US-5PIN-W-4FT	299-1102
Leader Cable EU 5 Pin 3m	Power to first fixture of run	MLCI-EU-5PIN-W-3M	299-0101
Leader Cable EU 5 Pin 7.62m	Power to first fixture of run	MLCI-EU-5PIN-W-7.62M	299-0103
Jumper Cable EU 5 Pin 300mm	Connection between fixtures	MJCI-EU-5PIN-W-300MM	299-1101
Jumper Cable EU 5 Pin 1m	Connection between fixtures	MJCI-EU-5PIN-W-1M	299-1103
Terminator 5 Pin	Must be fixed to last fixture for safety	MTI-5PIN-W	299-2100
Mounting Track	Allows user to install fixtures in a continuous linear position. Packaged in 5 ft sections in total of 20ft.	MMC-20-TRACK-1-\$1-G	299-3200
Symmetric Louvre	1ft Symmetric louvre for light control	N/A	299-4230
Asymmetric Louvre	1ft Asymmetric louvre for light control	N/A	299-4231
Honeycomb Louvre	1ft Honeycomb louvre for light control	N/A	299-4232
CONTROLS	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Kandi Touch	DMX 512 Controller Available in black and white	KND-TCH-B KND-TCH-W	250-0040 250-0041
CONTROL ACCESSORIES	DESCRIPTION	ORDERING NUMBER	PART NUMBER
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	N/A	250-0100
Shielded Cable 500ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-500FT	250-0251
Shielded Cable 1000ft	RS-458 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	BDL-9841-1000FT	250-0252