



Project Name: _____ SKU: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO #: _____ Quantity: _____

Notes: _____



PHYSICAL

Dimensions	L: 12 3/8in (318mm)	W: 2 7/16in (61mm)
	L: 47 5/16in (1202mm)	H: 2 3/8in (60mm)
Weight	12in: 1.0lbs (0.45kg)	
	48in: 3.1lbs (1.4kg)	
Applications	Cove, Accent, & Indirect General Illumination	
Construction	Pure Aluminum Body, Polycarbonate Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Dry/Damp Location IP44	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)	
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)	
Humidity	0-95% Non Condensing	

SPECIFICATIONS

	Lumens		Efficacy	
	1FT	4FT	1FT	4FT
LO	250 - 352	1002 - 1406	62 - 100	63 - 88
SO	339 - 493	1368 - 1966	68 - 99	71 - 103
SO+	790 - 801	3161 - 3208	79 - 80	79 - 80
HO	1040 - 1257	4164 - 5012	104 - 125	104 - 125
HO+	1085 - 1240	4300 - 4960	108 - 124	108 - 124

POWER CONSUMPTION

	120V - 277V AC	
	1FT	4FT
LO	4W	16W
SO	5W	19W
SO+	10W	40W
HO	10W	40W
HO+	10W	40W

OUTPUT

Colors	2200K*, 2700K, 3000K, 3500K, 4000K
Beam Angle	120°
CRI	94-98
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Single Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C
	70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

*2200K not available for SO+ or HO.

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	Electronic Low Voltage Reverse Phase Trailing Edge
Power Factor	≥ 0.98

MAX CONTINUOUS RUN

	120V AC	277V AC
LO	180ft	360ft
SO	120ft	240ft
SO+	60ft	120ft
HO	60ft	120ft
HO+	60ft	120ft

STANDARDS & CERTIFICATIONS



Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.

Certification	1
Warranty	3 Year Limited Warranty

FIXTURE		ORDERING SKU
ELV LO 1 FT	Moda Cove Interior Low Output Silver ELV Dimming 2200K HCRI 1FT	MCI-LO-S1-S-22H-1
	Moda Cove Interior Low Output Silver ELV Dimming 2700K HCRI 1FT	MCI-LO-S1-S-27H-1
	Moda Cove Interior Low Output Silver ELV Dimming 3000K HCRI 1FT	MCI-LO-S1-S-3H-1
	Moda Cove Interior Low Output Silver ELV Dimming 3500K HCRI 1FT	MCI-LO-S1-S-35H-1
	Moda Cove Interior Low Output Silver ELV Dimming 4000K HCRI 1FT	MCI-LO-S1-S-4H-1
ELV SO 1 FT	Moda Cove Interior Standard Output Silver ELV Dimming 2200K HCRI 1FT	MCI-SO-S1-S-22H-1
	Moda Cove Interior Standard Output Silver ELV Dimming 2700K HCRI 1FT	MCI-SO-S1-S-27H-1
	Moda Cove Interior Standard Output Silver ELV Dimming 3000K HCRI 1FT	MCI-SO-S1-S-3H-1
	Moda Cove Interior Standard Output Silver ELV Dimming 3500K HCRI 1FT	MCI-SO-S1-S-35H-1
	Moda Cove Interior Standard Output Silver ELV Dimming 4000K HCRI 1FT	MCI-SO-S1-S-4H-1
ELV SO+ 1 FT	Moda Cove Interior Standard Output Plus Silver ELV Dimming 2700K HCRI 1FT	MCI-SOP-S1-S-27H-1
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 3000K HCRI 1FT	MCI-SOP-S1-S-3H-1
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 3500K HCRI 1FT	MCI-SOP-S1-S-35H-1
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 4000K HCRI 1FT	MCI-SOP-S1-S-4H-1
ELV HO 1 FT	Moda Cove Interior High Output Silver ELV Dimming 2700K HCRI 1FT	MCI-HO-S1-S-27H-1
	Moda Cove Interior High Output Silver ELV Dimming 3000K HCRI 1FT	MCI-HO-S1-S-3H-1
	Moda Cove Interior High Output Silver ELV Dimming 3500K HCRI 1FT	MCI-HO-S1-S-35H-1
	Moda Cove Interior High Output Silver ELV Dimming 4000K HCRI 1FT	MCI-HO-S1-S-4H-1
ELV HO+ 1 FT	Moda Cove Interior High Output Plus Silver ELV Dimming 2200K HCRI 1FT	MCI-HOP-S1-S-22H-1
	Moda Cove Interior High Output Plus Silver ELV Dimming 2700K HCRI 1FT	MCI-HOP-S1-S-27H-1
	Moda Cove Interior High Output Plus Silver ELV Dimming 3000K HCRI 1FT	MCI-HOP-S1-S-3H-1
	Moda Cove Interior High Output Plus Silver ELV Dimming 3500K HCRI 1FT	MCI-HOP-S1-S-35H-1
	Moda Cove Interior High Output Plus Silver ELV Dimming 4000K HCRI 1FT	MCI-HOP-S1-S-4H-1
ELV LO 4 FT	Moda Cove Interior Low Output Silver ELV Dimming 2200K HCRI 4FT	MCI-LO-S1-S-22H-4
	Moda Cove Interior Low Output Silver ELV Dimming 2700K HCRI 4FT	MCI-LO-S1-S-27H-4
	Moda Cove Interior Low Output Silver ELV Dimming 3000K HCRI 4FT	MCI-LO-S1-S-3H-4
	Moda Cove Interior Low Output Silver ELV Dimming 3500K HCRI 4FT	MCI-LO-S1-S-35H-4
	Moda Cove Interior Low Output Silver ELV Dimming 4000K HCRI 4FT	MCI-LO-S1-S-4H-4
ELV SO 4 FT	Moda Cove Interior Standard Output Silver ELV Dimming 2200K HCRI 4FT	MCI-SO-S1-S-22H-4
	Moda Cove Interior Standard Output Silver ELV Dimming 2700K HCRI 4FT	MCI-SO-S1-S-27H-4
	Moda Cove Interior Standard Output Silver ELV Dimming 3000K HCRI 4FT	MCI-SO-S1-S-3H-4
	Moda Cove Interior Standard Output Silver ELV Dimming 3500K HCRI 4FT	MCI-SO-S1-S-35H-4
	Moda Cove Interior Standard Output Silver ELV Dimming 4000K HCRI 4FT	MCI-SO-S1-S-4H-4
ELV SO+ 4 FT	Moda Cove Interior Standard Output Plus Silver ELV Dimming 2700K HCRI 4FT	MCI-SOP-S1-S-27H-4
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 3000K HCRI 4FT	MCI-SOP-S1-S-3H-4
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 3500K HCRI 4FT	MCI-SOP-S1-S-35H-4
	Moda Cove Interior Standard Output Plus Silver ELV Dimming 4000K HCRI 4FT	MCI-SOP-S1-S-4H-4

	FIXTURE	ORDERING SKU
ELV HO 4FT	Moda Cove Interior High Output Silver ELV Dimming 2700K HCRI 4FT	MCI-HO-S1-S-27H-4
	Moda Cove Interior High Output Silver ELV Dimming 3000K HCRI 4FT	MCI-HO-S1-S-3H-4
	Moda Cove Interior High Output Silver ELV Dimming 3500K HCRI 4FT	MCI-HO-S1-S-35H-4
	Moda Cove Interior High Output Silver ELV Dimming 4000K HCRI 4FT	MCI-HO-S1-S-4H-4
ELV HO+ 4FT	Moda Cove Interior High Output Plus Silver ELV Dimming 2200K HCRI 4FT	MCI-HOP-S1-S-22H-4
	Moda Cove Interior High Output Plus Silver ELV Dimming 2700K HCRI 4FT	MCI-HOP-S1-S-27H-4
	Moda Cove Interior High Output Plus Silver ELV Dimming 3000K HCRI 4FT	MCI-HOP-S1-S-3H-4
	Moda Cove Interior High Output Plus Silver ELV Dimming 3500K HCRI 4FT	MCI-HOP-S1-S-35H-4
	Moda Cove Interior High Output Plus Silver ELV Dimming 4000K HCRI 4FT	MCI-HOP-S1-S-4H-4

ACCESSORIES	DESCRIPTION	ORDERING SKU
Leader Cable US 3 Pin 10FT	Power to first fixture of run	MLCI-US-3PIN-G-10FT
Leader Cable US 3 Pin 25FT	Power to first fixture of run	MLCI-US-3PIN-G-25FT
Jumper Cable US 3 Pin 1FT	Connection between fixtures	MJCI-US-3PIN-G-1FT
Jumper Cable US 3 Pin 4FT	Connection between fixtures	MJCI-US-3PIN-G-4FT
Leader Cable EU 3 Pin 3M	Power to first fixture of run	MLCI-EU-3PIN-G-3M
Leader Cable EU 3 Pin 10M	Power to first fixture of run	MLCI-EU-3PIN-G-10M
Jumper Cable EU 3 Pin 300MM	Connection between fixtures	MJCI-EU-3PIN-G-300MM
Jumper Cable EU 3 Pin 1M	Connection between fixtures	MJCI-EU-3PIN-G-1M
Terminator 3 Pin	Must be fixed to last fixture for safety	MTI-3PIN-G
Interior Bracket Lock	Holds fixture in place for vertical installation	MCGI-BL-G

CONTROLS	DESCRIPTION	ORDERING SKU
Bridge 1 US	Allows user to convert a 0-10V dimming signal into an ELV dimming signal. North American Model	250-0000