

Project Name: \_\_\_\_\_

SKU: \_\_\_\_\_

MODA Contact: \_\_\_\_\_



E-Mail: \_\_\_\_\_

Type: \_\_\_\_\_

PO #: \_\_\_\_\_

Quantity: \_\_\_\_\_

Notes: \_\_\_\_\_



### PHYSICAL

Dimensions	L: 12 3/8in (318mm)	W: 2 7/16in (61mm)
	L: 47 5/16in (1202mm)	H: 2 3/8in (60mm)
Weight	12in: 1.0lbs (0.45kg)	
	48in: 3.1lbs (1.4kg)	
Applications	Cove, Accent, & Indirect General Illumination	
Construction	Pure Aluminum Body, Polycarbonate Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Dry/Damp Location IP44	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)	
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)	
Humidity	0-95% Non Condensing	

### SPECIFICATIONS

	Lumens		Efficacy	
	1FT	4FT	1FT	4FT
SO	780	3120	78.00	78.00
HO	1082	4330	108.25	108.25
HO+	1247	4990	124.75	124.75

### POWER CONSUMPTION

	120V - 277V AC	
	1FT	4FT
SO/HO/HO+	10W	40W

### OUTPUT

CCT	3500K - 6500K
Beam Angle	120°
CRI	97
SDCM	2 Step MacAdam Ellipse
Color Bin Tolerance	Single Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C
	70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

### ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX512
Power Factor	≥ 0.98

### MAX CONTINUOUS RUN

	120V AC	277V AC
SO/HO/HO+	80ft	80ft

### STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	3 Year Limited Warranty

FIXTURE		ORDERING SKU
1 FT	Moda Cove Interior Standard Output Silver DMX512 Dynamic Cool 3500K-6500K HCRI 1FT	MCI-SO-S1-S-DC-1
	Moda Cove Interior High Output Silver DMX512 Dynamic Cool HCRI 3500K-6500K 1FT	MCI-HO-S1-S-DC-1
	Moda Cove Interior High Output Plus Silver DMX512 Dynamic Cool 3500K-6500K HCRI 1FT	MCI-HOP-S1-S-DC-1
4 FT	Moda Cove Interior Standard Output Silver DMX512 Dynamic Cool 3500K-6500K HCRI 4FT	MCI-SO-S1-S-DC-4
	Moda Cove Interior High Output Silver DMX512 Dynamic Cool 3500K-6500K HCRI 4FT	MCI-HO-S1-S-DC-4
	Moda Cove Interior High Output Plus Silver DMX512 Dynamic Cool 3500K-6500K HCRI 4FT	MCI-HOP-S1-S-DC-4

ACCESSORIES	DESCRIPTION	ORDERING SKU
Leader Cable US 8 Pin 10FT	Power to first fixture of run	MLCI-US-8PIN-G-10FT
Leader Cable US 8 Pin 25FT	Power to first fixture of run	MLCI-US-8PIN-G-25FT
Jumper Cable US 8 Pin 1FT	Connection between fixtures	MJCI-US-8PIN-G-1FT
Jumper Cable US 8 Pin 4FT	Connection between fixtures	MJCI-US-8PIN-G-4FT
Leader Cable EU 8 Pin 3M	Power to first fixture of run	MLCI-EU-8PIN-G-3M
Leader Cable EU 8 Pin 10M	Power to first fixture of run	MLCI-EU-8PIN-G-10M
Jumper Cable EU 8 Pin 300MM	Connection between fixtures	MJCI-EU-8PIN-G-300MM
Jumper Cable EU 8 Pin 1M	Connection between fixtures	MJCI-EU-8PIN-G-1M
Terminator 8 Pin	Must be fixed to last fixture for safety	MTI-8PIN-G
Interior Bracket Lock	Holds fixture in place for vertical installation	MCGI-BL-G

CONTROLS	DESCRIPTION	PART NUMBER	ORDERING SKU
Kandi Touch	DMX512 Wall Mounted Touch Panel Controller with Color Display	KND-TCH-B (Black)	250-0040
		KND-TCH-W (White)	250-0041
MODA Touch	DMX512 Wall Mounted Touch Panel Controller	MTCH-S1-B (Black)	MTCH-S1-B
		MTCH-S1-W (White)	MTCH-S1-W

CONTROL ACCESSORIES	DESCRIPTION	PART NUMBER	ORDERING SKU
Moda DMX Wiring Hub 2.0	Simplifies wiring and strengthens DMX signal.	N/A	250-0100
Shielded Cable 500FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-500FT	250-0251
Shielded Cable 1000FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-1000FT	250-0252