


Client: _____ Project Name: _____

MODA Contact: _____ E-Mail: _____

Type: _____ PO#: _____ Quantity: _____

Notes: _____



Specification Grade Premium Exterior Graze Fixture.

MODA GRAZE Exterior is a patent pending wall grazing lighting system designed for exterior applications. Utilizing MODA's latest DMX software, our onboard Microprocessor is uniquely programmed in-house with a firmware to receive DMX512 signals for full independent control of every 1ft section. Mix colors, including amber, to create amazing displays and color scenes using MODA controls. Wall wash any applications with a choice of 6°, 10°, 25°, 40°, 10°x40°, 30°x60°, or 30°x60°x5° beam patterns for HO. 100-277V, 50/60Hz power input allows these fixtures to be installed anywhere in the world. New patent pending locking bracket rotates 180° for a multitude of light directions. Rugged aluminum design. Protected from corrosion and harsh weather conditions by MODA GUARD—a tough seal which protects the fixture. Fast installation is achieved with MODA KWIK CONNECT plugs and install-integral thumb latch connectors. Available in 1ft & 4ft sections. Series is designed for driver or light engine to be factory replaced at its end of life or recycled.

Designed and developed in Las Vegas, USA by MODA.

PAGE

3	FEATURES
4	1 FOOT
5	4 FOOT
6	OPTIC FLEXIBILITY
7	OPTIC FLEXIBILITY CONTINUED
8	DMX WIRING
10	ACCESSORIES: CABLES
11	FIXTURES & ACCESSORIES

Dimensions	L: 12 1/2in (318mm) L: 47 3/8in (1204mm)	W: 2 13/16in (71mm) H: 2 9/16in (65mm)
Weight	12in: 1.3lbs (0.6kg) 48in: 4.9lbs (2.22kg)	
Applications	Graze, Accent, & Indirect General Illumination	
Construction	Pure Aluminum Body, Polycarbonate Mounting Bracket and Polycarbonate Optical Lens	
Ingress Protection	Wet Location IP66	
Thermal Management	Moda Aluminum Heat Sink	
Fixture Connections	Integral Male & Female Connectors	
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)	
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)	
Humidity	0-95% Non Condensing	

	Lumens		Efficacy	
OPTIC	1FT	4FT	1FT	4FT
6°	981	3474	98.10	86.85
10°	969	3462	96.90	86.55
25°	955	3448	95.50	86.20
40°	945	3438	94.50	85.95
10°x40°	936	3429	93.60	85.72
30°x60°	933	3426	93.30	85.65
30°x60°x5°	931	3424	93.10	85.60

	120V - 277V AC	
	1FT	4FT
HO	10W	40W


CCT	N/A
Beam Angle	6°, 10°, 25°, 40°, 10°x40°, 30°x60°, Forward Throw Asymmetric, or 30°x100° optic options
CRI	Variable for RGBA
Color Bin Tolerance	Zero Bin
Lumen Maintenance	90,000 Hours L70 @ 25°C 70,000 Hours L70 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

Input Voltage	100-277V AC 50Hz/60Hz
Control	DMX512
Power Factor	≥ 0.96

	120V AC	277V AC
HO	80ft	80ft


moda**KWIK CONNECT™**

Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, CCC, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	3 Year Limited Warranty



DMX


Optic	Lumens	Efficacy	Power Consumption	Max Run Lengths
6°	981	98.10	120-277V AC 10W	120-277V AC 80ft
10°	969	96.90		
25°	955	95.50		
40°	945	94.50		
10° x 40°	936	93.60		
30° x 60°	933	93.30		
30° x 60° x 5°	931	93.10		




DMX

Optic	Lumens	Efficacy	Power Consumption	Max Run Lengths
6°	3474	86.85	120-277V AC 40W	120-277V AC 80ft
10°	3462	86.55		
25°	3448	86.20		
40°	3438	85.95		
10° x 40°	3429	85.72		
30° x 60°	3426	85.65		
30° x 60° x 5°	3424	85.60		

6° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	51.74 fc	183.22 fc	0.3 ft	0.2 ft
4.0 ft	12.93 fc	45.80 fc	0.7 ft	0.6 ft
6.0 ft	6.46 fc	22.90 fc	1.1 ft	1.0 ft
8.0 ft	3.23 fc	11.45 fc	1.5 ft	1.4 ft
10.0 ft	1.61 fc	5.72 fc	2.0 ft	1.9 ft
12.0 ft	1.29 fc	4.58 fc	2.4 ft	2.3 ft

■ Vert. Spread: 6° ▲ Horiz. Spread: 6°

10° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	42.20 fc	150.78 fc	0.4 ft	0.3 ft
4.0 ft	10.55 fc	37.69 fc	0.8 ft	0.7 ft
6.0 ft	5.27 fc	18.84 fc	1.2 ft	1.1 ft
8.0 ft	2.63 fc	9.42 fc	1.6 ft	1.5 ft
10.0 ft	1.31 fc	4.71 fc	2.1 ft	2.0 ft
12.0 ft	1.05 fc	3.76 fc	2.5 ft	2.4 ft

■ Vert. Spread: 10° ▲ Horiz. Spread: 10°

25° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	25.82 fc	93.23 fc	0.5 ft	0.5 ft
4.0 ft	6.45 fc	23.30 fc	1.0 ft	1.0 ft
6.0 ft	3.22 fc	11.65 fc	1.5 ft	1.6 ft
8.0 ft	1.61 fc	5.82 fc	2.0 ft	2.2 ft
10.0 ft	0.80 fc	2.91 fc	2.5 ft	2.7 ft
12.0 ft	0.64 fc	2.33 fc	3.0 ft	3.2 ft

■ Vert. Spread: 25° ▲ Horiz. Spread: 25°

40° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	11.76 fc	42.81 fc	1.0 ft	0.8 ft
4.0 ft	2.94 fc	10.70 fc	1.9 ft	1.5 ft
6.0 ft	1.47 fc	5.35 fc	2.8 ft	2.4 ft
8.0 ft	0.73 fc	2.67 fc	3.8 ft	3.2 ft
10.0 ft	0.36 fc	1.33 fc	4.8 ft	4.0 ft
12.0 ft	0.29 fc	1.07 fc	5.7 ft	4.7 ft

■ Vert. Spread: 40° ▲ Horiz. Spread: 40°

10°x40° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	29.36 fc	107.55 fc	0.7 ft	0.5 ft
4.0 ft	7.34 fc	26.88 fc	1.5 ft	1.0 ft
6.0 ft	3.67 fc	13.44 fc	2.2 ft	1.4 ft
8.0 ft	1.83 fc	6.72 fc	3.0 ft	1.9 ft
10.0 ft	0.91 fc	3.36 fc	4.6 ft	2.4 ft
12.0 ft	0.73 fc	2.68 fc	4.4 ft	3.0 ft

■ Vert. Spread: 10° ■ Horiz. Spread: 40°

30°x60° Beam Angle



Polar Candela Distribution




Illuminance at a Distance


	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	73.62 fc	268.08 fc	1.3 ft	2.0 ft
4.0 ft	18.88 fc	68.02 fc	3.1 ft	4.7 ft
6.0 ft	9.33 fc	33.36 fc	4.0 ft	6.6 ft
8.0 ft	4.58 fc	16.73 fc	5.8 ft	9.3 ft
10.0 ft	2.38 fc	8.58 fc	7.0 ft	11.2 ft
12.0 ft	1.88 fc	6.86 fc	9.0 ft	14.0 ft

■ Vert. Spread: 30° ■ Horiz. Spread: 60°

30°x60°x5° Beam Angle




Polar Candela Distribution



Illuminance at a Distance

	Center Beam FC		Beam Width	
	1 Foot	4 Foot		
2.0 ft	10.89 fc	39.98 fc	1.3 ft	0.3 ft
4.0 ft	2.68 fc	9.92 fc	2.6 ft	0.9 ft
6.0 ft	1.33 fc	4.98 fc	3.9 ft	1.3 ft
8.0 ft	0.68 fc	2.48 fc	5.2 ft	1.6 ft
10.0 ft	0.33 fc	1.24 fc	6.5 ft	1.9 ft
12.0 ft	0.28 fc	0.99 fc	7.8 ft	2.6 ft













■ Vert. Spread: 30° ■ Horiz. Spread: 60°




Wiring Legend

- 1 Power 100-277V AC
- 2 DMX Splitter/Repeater
- 3 8 Pin Leader Cable
- 4 Junction Box
- 5 Wiring Nuts


8 Pin Leader Cable

		UL/cUL	CE/CCC*
A	100-277V AC	 Black	 Brown
B	Neutral	 White	 Blue
C	Ground	 Green	 Green/Yellow
D	Data Positive/DC +	 Orange	 Orange
E	Data Negative/DC -	 Yellow	 Yellow
F	DMX Shield	 Dark Blue	 Dark Blue
*Not illustrated			

DMX Connectors




Angle Adjustment




DMX LEADER CABLES

Moda Cove Exterior 8 Pin Leader Cables

	UL/cUL	EU/CCC
Lengths	25ft and 50ft	10m and 15m
Color	Black	Black




Connectors




DMX JUMPER CABLES

Moda Cove Exterior 8 Pin Jumper Cables


	UL/cUL	EU/CCC
Lengths	1ft and 4ft	300mm and 1m
Color	Black	Black



Connectors




Pin Assignment




		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	Ground	Green	Green/Yellow
4	DMX Positive	Orange	Orange
5	DMX Negative	Yellow	Yellow

Pin Assignment



		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	Ground	Green	Green/Yellow
4	DMX Positive	Orange	Orange
5	DMX Negative	Yellow	Yellow



		UL/cUL	EU/CCC
1	Live 100-277V	Black	Brown
2	Neutral	White	Blue
3	Ground	Green	Green/Yellow
4	DMX Positive	Orange	Orange
5	DMX Negative	Yellow	Yellow

MGE - HO - S1 - RGBA - -



COMPLETE SKU SAMPLE: MGE-HO-S1-RGBA-4-25

A - FIXTURE & LOCATION

MGE — Moda Graze Exterior

B - LIGHT OUTPUT

HO — High Output

C - SERIES NUMBER

S1 — Series 1

D - LED COLOR

RGBA — Red, Green, Blue and Amber

E - LENGTH

1 — 1 FT

4 — 4FT

F - OPTIC

6 — 6° x 6°

10 — 10° x 10°

25 — 25° x 25°

40 — 40° x 40°

140 — 10° x 40°

360 — 30° x 60°

365 — Forward Throw Asymmetric

ACCESSORIES	DESCRIPTION	SKU
Leader Cable US 8 Pin 25ft	Power to first fixture of run	MLCE-US-8PIN-B-25FT
Leader Cable US 8 Pin 50ft	Power to first fixture of run	MLCE-US-8PIN-B-50FT
Jumper Cable US 8 Pin 1ft	Connection between fixtures	MJCE-US-8PIN-B-1FT
Jumper Cable US 8 Pin 4ft	Connection between fixtures	MJCE-US-8PIN-B-4FT
Leader Cable EU 8 Pin 7.62m	Power to first fixture of run	MLCE-EU-8PIN-B-7.62M
Leader Cable EU 8 Pin 15m	Power to first fixture of run	MLCE-EU-8PIN-B-15M
Jumper Cable EU 8 Pin 300mm	Connection between fixtures	MJCE-EU-8PIN-B-300MM
Jumper Cable EU 8 Pin 1m	Connection between fixtures	MJCE-EU-8PIN-B-1M
Terminator 8 Pin	Must be fixed to last fixture for safety	MTE-8PIN-B
Exterior Bracket Lock	Holds fixture in place for vertical installations	MCGE-BL-G

CONTROLS	DESCRIPTION	PART NUMBER	ORDERING SKU
Kandi Touch	DMX512 Wall Mounted Touch Panel Controller with Color Display	KND-TCH-B (Black)	250-0040
		KND-TCH-W (White)	250-0041
MODA Touch*	DMX512 Wall Mounted Touch Panel Controller	MTCH-S1-B (Black)	MTCH-S1-B
		MTCH-S1-W (White)	MTCH-S1-W

* - MODA Touch default scene addressing can be found on MODA Touch Product Documentation and DMX Fixture Installation Guides.

CONTROL ACCESSORIES	DESCRIPTION	PART NUMBER	ORDERING SKU
Pathway DMX Splitter/Repeater	Wall-mount, 4 ports, E1.20 RDM Compliant, Small - 10in X 13in X 4 1/2in	PWREP WM P4 TERM RDM SML DMX-RDM	250-0153
Pathway DMX Splitter/Repeater	Wall-mount, 8 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P8 TERM RDM MED DMX-RDM	250-0154
Pathway DMX Splitter/Repeater	Wall-mount, 12 ports, E1.20 RDM Compliant, Medium - 10in X 23in X 4 1/2in	PWREP WM P12 TERM RDM MED DMX-RDM	250-0155
Shielded Cable 500FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-500FT	250-0251
Shielded Cable 1000FT	RS-485 Cable for DMX, 24 AWG stranded TC conductors, polyethylene insulation	SW-L-19827-1-1000FT	250-0252