

Beelink GTR9 Pro

UEFI BIOS Setup Reference

GTR9 Pro v2.2 · Latest BIOS · Configuration Settings Catalog — v1.5.2
AMD Strix Halo · Ryzen™ AI Max+ Platform · AMI Aptio V Firmware

Image & Extraction Summary

Field	Value
Board revision	Beelink GTR9 Pro v2.2
BIOS version	GTRPRPI1001C (current); GTRPR07 prior — 33,554,432 bytes / 32 MB
Flash package	GTRPRPI1001C (AfuEfi); GTRPR07_WinFlash (AFUWIN / AfuEfi)
BIOS vendor	American Megatrends International (AMI Aptio V)
SoC platform	AMD Strix Halo (Ryzen AI Max series APU)
Setup form-sets	7 — Aptio Setup, AMD CBS, AMD PBS, AMD Overclocking, AMD PMF, DASH/ASF, RAIDXpert2
Total forms	186
Configurable settings	1,018 (after de-duplication)

Image Lineage

Module (GUID)	Owns chapter	GTRPR07 vs GTRPRPI1001C
Setup (899407D7)	Aptio Setup tree	identical (SHA-256)
CbsSetupDxeSTXH (C5440ED5)	AMD CBS	identical (SHA-256)
AmdPbsSetupDxe (BBB77CB9)	AMD PBS	identical (SHA-256)
AodDxe (442BA91E)	AMD Overclocking	identical (SHA-256)
AmdCpmPmfBoardDxe (2C20B724)	AMD PMF	identical (SHA-256)
AmdRaid (AFD69E65)	RAIDXpert2	identical (SHA-256)

GTRPRPI1001C = GTRPR05 + PI 1.0.0c1 (AGESA / Platform Initialization microcode refresh). Setup interface, HII string packages, NVRAM values, and defaults apply unchanged to both images.

Coverage by Form-Set

Chapter	Form-set	Settings
Aptio Setup (Main tree)	Setup	161
AMD CBS	CbsSetupDxe	318
AMD PBS	AmdPbsSetupDxe	202
AMD Overclocking	AodDxe	153

AMD PMF	AmdCpmPmfBoardDxe	139
DASH / ASF	DashManagementDxe	8
RAIDXpert2	RAID formset	37
Total	7 form-sets · 186 forms	1,018

De-duplication (1,053 – 35 = 1,018)

Form	Form ID	Rows removed
Smart Fan Function	0x2737	21
View Associated Physical Disks	0x222	8
Display Configurations	0x10	4
Trusted Computing	0x271A	2
Total removed		35

Only byte-identical repeats removed. Distinct-hardware rows retained in full: PCI-E Device0–Device7, four CPU Smart Fan controllers, eight PPC Adjustment variants, three per-device Trusted Computing forms (0x2719 / 0x271A / 0x271B).

Marker Legend

Marker	Count	Meaning
■ default	988	Factory Standard default value
■ performance	421	Recommended value for Ryzen AI Max+ 395 + rationale
Tier tag	Count	Meaning
CHANGE	4	Change away from default for a clear gain
TUNE	375	Performance-relevant but workload-specific / expert-only
KEEP	42	Default already favors performance; leave it

Settings Table Format

Column	Contents
Setting	Option label as shown on the BIOS Setup screen
Type	Selection · Numeric · Checkbox · Text · Password · Ordered List · Date · Time
Options / Values / Range	Each choice with stored [NVRAM] value, or Min/Max/Step + default for numerics. Usable for AMISCE/SCEWIN scripting.

Notes

- Settings appear in firmware presentation order, grouped by the form-set that owns each menu.
- Many options are conditionally hidden (suppress-if / grayout-if); this catalog is a superset of any single unit's display.
- Defaults are compiled Standard Defaults; a unit's live values may differ.
- Generic UEFI network-stack driver forms (IPv4/IPv6/VLAN/HTTP/TLS/PXE) are out of scope (Appendix A).

Integrity (SHA256)

83bf8f716f81db007b1f34adf1fdd5441b697ad8f207a4357e74cb0c8d0523e5 GTR9Pro_BIOS_Settings.pdf