

OpenGraph Checker App Summary

=====

What it is

OpenGraph Checker is a Next.js web app that audits a URL's social metadata (Open Graph and Twitter tags), scores share readiness, and shows how link previews will look. It also layers in monitoring, analytics, and AI-assisted improvements for social CTR.

Who it's for

Primary persona: founders, indie hackers, developers, and small growth-focused teams (as listed in `playbook.md`).

What it does

- Audits any URL via `/api/inspect` and returns metadata, score, and prioritized issues.
- Shows live social previews for key platforms from extracted OG/Twitter fields.
- Suggests stronger title/description variants using Gemini (`src/app/api/suggest/route.ts`).
- Generates OG image concepts with Gemini and stores image logs in Supabase (`ai_images` table).
- Compares up to 3 sites side-by-side in `CompetitorBoard`.
- Provides monitoring and scan history views, including re-scan workflows.
- Tracks traffic/events with a pixel + `/api/track`, then visualizes funnels/sources in `AnalyticsDashboard`.

How it works (repo-based architecture)

- Frontend: Next.js App Router pages + React components under `src/app` and `src/components`.
- Core scan flow: `useScrape()` -> `POST /api/inspect` -> `axios+cheerio` scrape, then `Puppeteer+Chromium` fallback when blocked/timeouts.
- Data layer: Supabase clients (`browser/server/admin`) and SQL migrations for `scans`, `analytics_events`, `analytics_sites`, `profiles`, and `ai_images`.
- Billing/auth: Supabase auth + Stripe checkout/webhook routes that update profile tiering.
- Telemetry flow: layout injects `/public/pixel.js` -> `/api/track` -> `analytics_events` rows -> `AnalyticsDashboard` queries.
- Not found in repo: a complete architecture diagram and explicit production SLO/infra docs.

How to run (minimal)

- 1) Install deps: `npm install`
- 2) Set env vars in `.env.local` (at minimum: `NEXT_PUBLIC_SUPABASE_URL`, `NEXT_PUBLIC_SUPABASE_ANON_KEY`, `SUPABASE_SERVICE_ROLE_KEY`, `GEMINI_API_KEY`, `STRIPE_SECRET_KEY`, `STRIPE_WEBHOOK_SECRET`, and `NEXT_PUBLIC_STRIPE_PRICE_*` values used in code).
- 3) Start dev server: `npm run dev`
- 4) Open `http://localhost:3000`
- 5) Not found in repo: a canonical example env file documenting required values.