

Concepts in Machine Learning

Winter Institute in Data Science

Ryan T. Moore

2024-01-08

Building Models

Modeling Helper Functions

Example: `mtcars`

Example: Social Pressure Experiment (`recipes`)

Regularization Methods: LASSO, ridge regression, elastic nets

Building Models

How do we build models?

How do we build models?

What are our goals?

How do we build models?

What are our goals?

1. Generative modeling
2. Predictive modeling

How do we build models?

What are our goals?

1. Generative modeling
2. Predictive modeling

Breiman (2001)

How do we build models?

How do we build models?

- ▶ Theory
(novel theory, prior theory, prior findings)

How do we build models?

- ▶ Theory
(novel theory, prior theory, prior findings)
- ▶ Raw data
(“data look nonlinear, so $\dots + \beta x^2 + \dots$ ”)

How do we build models?

- ▶ Theory
(novel theory, prior theory, prior findings)
- ▶ Raw data
(“data look nonlinear, so $\dots + \beta x^2 + \dots$ ”)
- ▶ Specification searching
(repeat modeling with same data)

How do we build models?

- ▶ Theory
(novel theory, prior theory, prior findings)
- ▶ Raw data
(“data look nonlinear, so $\dots + \beta x^2 + \dots$ ”)
- ▶ Specification searching
(repeat modeling with same data)
- ▶ Training and testing
(repeat modeling, different data)

Which predictors should I include?

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)
- ▶ No irrelevant ones
(No included variable bias)

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)
- ▶ No irrelevant ones
(No included variable bias)

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)
- ▶ No irrelevant ones
(No included variable bias)

Helpful?

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)
- ▶ No irrelevant ones
(No included variable bias)

Helpful?

- ▶ Affect outcome
- ▶ Confounders
- ▶ Pre-treatment only
- ▶ Avoid post-treatment
- ▶ “In-horizon”
- ▶ Test something “out-of-horizon”

Which predictors should I include?

- ▶ All the important ones
(No omitted variable bias)
- ▶ No irrelevant ones
(No included variable bias)

Helpful?

- ▶ Affect outcome
- ▶ Confounders
- ▶ Pre-treatment only
- ▶ Avoid post-treatment
- ▶ “In-horizon”
- ▶ Test something “out-of-horizon”

(Sometimes it will depend on goals.)

What to include, when thousands of predictors?

What to include, when thousands of predictors?
“Machine learning”

What to include, when thousands of predictors?

“Machine learning”

(but “machine learning” can mean different things.)



Jake M. Grumbach

@JakeMGrumbach



I finally found it in real life: the consultant who runs OLS in Excel and calls it machine learning

9:17 AM · Jan 31, 2019 · Twitter for iPhone

54 Retweets **7** Quote Tweets **511** Likes



Figure 1: Don't do this.



Jake M. Grumbach

@JakeMGrumbach



I finally found it in real life: the consultant who runs OLS in Excel and calls it machine learning

9:17 AM · Jan 31, 2019 · Twitter for iPhone

54 Retweets **7** Quote Tweets **511** Likes



Figure 1: Don't do this.

If you can't describe the procedure's “learning”, it may not be “machine learning”.



Jake M. Grumbach

@JakeMGrumbach



I finally found it in real life: the consultant who runs OLS in Excel and calls it machine learning

9:17 AM · Jan 31, 2019 · Twitter for iPhone

54 Retweets **7** Quote Tweets **511** Likes



Figure 1: Don't do this.

If you can't describe the procedure's “learning”, it may not be “machine learning”.

There should probably be some testing/training, regularization,

...

Modeling Helper Functions

modelr Helper Functions

```
data(sim1)
```

```
lm_out <- lm(y ~ x, data = sim1)
```

```
tidy(lm_out)
```

```
## # A tibble: 2 x 5
```

##	term	estimate	std.error	statistic	p.value
##	<chr>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	(Intercept)	4.22	0.869	4.86	4.09e- 5
## 2	x	2.05	0.140	14.7	1.17e-14

modelr Helper Functions

```
data(sim1)
```

```
lm_out <- lm(y ~ x, data = sim1)
```

```
tidy(lm_out)
```

```
## # A tibble: 2 x 5
```

##	term	estimate	std.error	statistic	p.value
##	<chr>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	(Intercept)	4.22	0.869	4.86	4.09e- 5
## 2	x	2.05	0.140	14.7	1.17e-14

```
glance(lm_out)
```

```
## # A tibble: 1 x 12
```

##	r.squared	adj.r.squared	sigma	statistic	p.value	df
##	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	0.885	0.880	2.20	215.	1.17e-14	1

modelr Helper Functions

Special `mutate()` functions:


modelr Helper Functions

Special mutate() functions:

```
(sim1 <- sim1 |> add_residuals(lm_out))
```

```
## # A tibble: 30 x 3
##       x     y   resid
##   <int> <dbl> <dbl>
## 1     1     1  4.20 -2.07
## 2     1     1  7.51  1.24
## 3     1     1  2.13 -4.15
## 4     2     2  8.99  0.665
## 5     2     2 10.2   1.92
## 6     2     2 11.3   2.97
## 7     3     3  7.36 -3.02
## 8     3     3 10.5   0.130
## 9     3     3 10.5   0.136
## 10    4    12.4  0.00763
## # i 20 more rows
```

```
ggplot(sim1, aes(x, resid)) + geom_point() +  
  geom_hline(yintercept = 0, linetype = 2, color = "red")
```



modelr Helper Functions

Special mutate() functions:

```
(sim1 <- sim1 |> add_predictions(lm_out))
```

```
## # A tibble: 30 x 4
##       x     y   resid  pred
##   <int> <dbl>   <dbl> <dbl>
## 1     1     1  4.20 -2.07    6.27
## 2     1     1  7.51  1.24    6.27
## 3     1     1  2.13 -4.15    6.27
## 4     2     2  8.99  0.665   8.32
## 5     2     2 10.2   1.92    8.32
## 6     2     2 11.3   2.97    8.32
## 7     3     3  7.36 -3.02   10.4
## 8     3     3 10.5   0.130   10.4
## 9     3     3 10.5   0.136   10.4
## 10    4    12.4  0.00763 12.4
## # i 20 more rows
```


modelr Helper Functions

```
lm_out2 <- lm(y ~ x - 1, data = sim1)
```


modelr Helper Functions

```
lm_out2 <- lm(y ~ x - 1, data = sim1)
```

```
coef(lm_out2)
```

```
##           x  
## 2.654508
```

```
ggplot(sim1, aes(x, y)) + geom_point() +  
  geom_abline(intercept = coef(lm_out)[1], slope = coef(lm_out)[2]) +  
  geom_abline(intercept = 0, slope = coef(lm_out2)["x"], color = "red")
```



```
glance(lm_out)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squared sigma statistic p.value    df
##   <dbl>         <dbl> <dbl>     <dbl>   <dbl> <dbl>
## 1     0.885         0.880   2.20     215. 1.17e-14     1
## # i 3 more variables: deviance <dbl>, df.residual <int>
```

```
glance(lm_out2)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squared sigma statistic p.value    df
##   <dbl>         <dbl> <dbl>     <dbl>   <dbl> <dbl>
## 1     0.970         0.969   2.94      NA      NA     NA
## # i 3 more variables: deviance <dbl>, df.residual <int>
```

```
glance(lm_out)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squared sigma statistic p.value    df
##   <dbl>         <dbl> <dbl>     <dbl>   <dbl> <dbl>
## 1     0.885         0.880   2.20     215. 1.17e-14     1
## # i 3 more variables: deviance <dbl>, df.residual <int>
```

```
glance(lm_out2)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squared sigma statistic p.value    df
##   <dbl>         <dbl> <dbl>     <dbl>   <dbl> <dbl>
## 1     0.970         0.969   2.94      NA      NA     NA
## # i 3 more variables: deviance <dbl>, df.residual <int>
```

(R^2 and predictive quality are not the same thing ...)


modelr Helper Functions

```
( sim1 <- sim1 |> spread_residuals(lm_out, lm_out2) )
```


```
## # A tibble: 30 x 6
```

##		x	y	resid	pred	lm_out	lm_out2
##		<int>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
##	1	1	4.20	-2.07	6.27	-2.07	1.55
##	2	1	7.51	1.24	6.27	1.24	4.86
##	3	1	2.13	-4.15	6.27	-4.15	-0.529
##	4	2	8.99	0.665	8.32	0.665	3.68
##	5	2	10.2	1.92	8.32	1.92	4.93
##	6	2	11.3	2.97	8.32	2.97	5.99
##	7	3	7.36	-3.02	10.4	-3.02	-0.607
##	8	3	10.5	0.130	10.4	0.130	2.54
##	9	3	10.5	0.136	10.4	0.136	2.55
##	10	4	12.4	0.00763	12.4	0.00763	1.82
##	# i	20	more	rows			

```
ggplot(sim1, aes(x, lm_out2)) + geom_point() +  
  geom_hline(yintercept = 0, linetype = 2, color = "red")
```



```
ggplot(sim1, aes(lm_out, lm_out2)) + geom_point(size = 3)
```




modelr Helper Functions

```
data(sim1)
( sim1 <- sim1 |> gather_residuals(lm_out, lm_out2) )
```

```
## # A tibble: 60 x 4
##   model      x      y    resid
##   <chr> <int> <dbl>   <dbl>
## 1 lm_out     1  4.20 -2.07
## 2 lm_out     1  7.51  1.24
## 3 lm_out     1  2.13 -4.15
## 4 lm_out     2  8.99  0.665
## 5 lm_out     2 10.2   1.92
## 6 lm_out     2 11.3   2.97
## 7 lm_out     3  7.36 -3.02
## 8 lm_out     3 10.5   0.130
## 9 lm_out     3 10.5   0.136
## 10 lm_out    4 12.4   0.00763
## # i 50 more rows
```

```
ggplot(sim1, aes(x, resid)) +  
  geom_point(aes(color = model, size = model, shape = model))
```



modelr Helper Functions

- ▶ `add_residuals()`
- ▶ `spread_residuals()`
- ▶ `gather_residuals()`
- ▶ `add_predictions()`
- ▶ `spread_predictions()`
- ▶ `gather_predictions()`

Other Helpers for Many Models: tidy()

```
ll <- list(lm_out, lm_out2)
```

```
ll |> map_df(tidy)
```

```
## # A tibble: 3 x 5
```

##	term	estimate	std.error	statistic	p.value
##	<chr>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	(Intercept)	4.22	0.869	4.86	4.09e- 5
## 2	x	2.05	0.140	14.7	1.17e-14
## 3	x	2.65	0.0865	30.7	1.15e-23

Many Models: glance()

```
ll |> map_df(glance) |> select(1:6)
```

```
## # A tibble: 2 x 6
```

##	r.squared	adj.r.squared	sigma	statistic	p.value	
##	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	0.885	0.880	2.20	215.	1.17e-14	
## 2	0.970	0.969	2.94	NA	NA	

Many Models: glance()

```
ll |> map_df(glance) |> select(1:6)
```

```
## # A tibble: 2 x 6
```

	r.squared	adj.r.squared	sigma	statistic	p.value	
	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
## 1	0.885	0.880	2.20	215.	1.17e-14	
## 2	0.970	0.969	2.94	NA	NA	

```
ll |> map_df(glance) |> select(7:12)
```

```
## # A tibble: 2 x 6
```

	logLik	AIC	BIC	deviance	df.residual	nobs
	<dbl>	<dbl>	<dbl>	<dbl>	<int>	<int>
## 1	-65.2	136.	141.	136.	28	30
## 2	-74.4	153.	156.	250.	29	30

Example: `mtcars`

Machine Learning Steps

1. Feature engineering

Machine Learning Steps

1. Feature engineering: collect/create the data

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection: algorithms decide predictors to include

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection: algorithms decide predictors to include
4. Model estimation

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection: algorithms decide predictors to include
4. Model estimation: find the slopes (e.g.)

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection: algorithms decide predictors to include
4. Model estimation: find the slopes (e.g.)
5. Validation + testing

Machine Learning Steps

1. Feature engineering: collect/create the data
2. Data splitting: split the data
 - ▶ Training. (80%? further split (“cross-validation”)?)
 - ▶ Validation. (for hyperparams; can be small (?))
 - ▶ Testing. (20%?)
3. Feature selection: algorithms decide predictors to include
4. Model estimation: find the slopes (e.g.)
5. Validation + testing: evaluate preds from trained models using new data

tidymodels Example

```
library(tidymodels)
data_split <- initial_split(mtcars, prop = 2/3)

df_train <- training(data_split)
df_test <- testing(data_split)
```

tidymodels Example

```
library(tidymodels)
data_split <- initial_split(mtcars, prop = 2/3)

df_train <- training(data_split)
df_test <- testing(data_split)
```

```
dim(df_train)
```

```
## [1] 21 11
```

```
dim(df_test)
```

```
## [1] 11 11
```

tidymodels Example

```
lm_fit <- linear_reg() |> fit(mpg ~ ., data = df_train)
lm_fit
```

```
## parsnip model object
```

```
##
```

```
##
```

```
## Call:
```

```
## stats::lm(formula = mpg ~ ., data = data)
```

```
##
```

```
## Coefficients:
```

## (Intercept)	cyl	disp	hp
## -127.13656	3.24904	0.01493	0.06491
## qsec	vs	am	gear
## 4.21793	-3.09021	NA	10.66257

tidymodels Example

```
out_preds <- bind_cols(df_test |> select(mpg),  
                        predict(lm_fit, new_data = df_test)  
                        rename(lm = .pred))
```

out_preds

##	mpg	lm
## Mazda RX4	21.0	17.68862
## Mazda RX4 Wag	21.0	18.87465
## Hornet 4 Drive	21.4	18.42586
## Hornet Sportabout	18.7	19.98952
## Merc 240D	24.4	21.63137
## Merc 230	22.8	37.74679
## Merc 280C	17.8	22.20879
## Toyota Corona	21.5	19.32277
## Porsche 914-2	26.0	33.08862
## Ford Pantera L	15.8	39.18207
## Maserati Bora	15.0	24.66780

tidymodels Example

Next, predict with *random forest* algorithm.

tidymodels Example

Next, predict with *random forest* algorithm.

Ensemble learning algorithms:

- ▶ Boosting: models build on prior models

tidymodels Example

Next, predict with *random forest* algorithm.

Ensemble learning algorithms:

- ▶ Boosting: models build on prior models

tidymodels Example

Next, predict with *random forest* algorithm.

Ensemble learning algorithms:

- ▶ Boosting: models build on prior models \rightsquigarrow pick feature, predict, upweight mispredicted data, Do several times and combine.
- ▶ Bagging: (random select units, model) \rightarrow many times. No building.

tidymodels Example

Next, predict with *random forest* algorithm.

Ensemble learning algorithms:

- ▶ Boosting: models build on prior models \rightsquigarrow pick feature, predict, upweight mispredicted data, Do several times and combine.
- ▶ Bagging: (random select units, model) \rightarrow many times. No building.

tidymodels Example

Next, predict with *random forest* algorithm.

Ensemble learning algorithms:

- ▶ Boosting: models build on prior models \rightsquigarrow pick feature, predict, upweight mispredicted data, Do several times and combine.
- ▶ Bagging: (random select units, model) \rightarrow many times. No building.

Random Forests are bagging algorithms.

tidymodels Example

```
rf_fit <- rand_forest(mode = "regression") |>  
  fit(mpg ~ ., data = df_train)  
rf_fit
```

```
## parsnip model object
```

```
##
```

```
## Ranger result
```

```
##
```

```
## Call:
```

```
##   ranger::ranger(x = maybe_data_frame(x), y = y, num.thre
```

```
##
```

```
## Type:                                Regression
```

```
## Number of trees:                      500
```

```
## Sample size:                          21
```

```
## Number of independent variables:      10
```

```
## Mtry:                                  3
```

```
## Target node size:                     5
```

```
## Variable importance mode:             none
```

tidymodels Example

`parsnip::rand_forest()` uses ranger engine

tidymodels Example

`parsnip::rand_forest()` uses ranger engine

There is also “Spark”.

tidymodels Example

```
out_preds <- bind_cols(out_preds,  
                        predict(rf_fit, new_data = df_test)  
                        rename(rf = .pred))
```

```
out_preds
```

##	mpg	lm	rf
## Mazda RX4	21.0	17.68862	20.45133
## Mazda RX4 Wag	21.0	18.87465	20.36097
## Hornet 4 Drive	21.4	18.42586	18.54591
## Hornet Sportabout	18.7	19.98952	16.77318
## Merc 240D	24.4	21.63137	21.83636
## Merc 230	22.8	37.74679	21.47683
## Merc 280C	17.8	22.20879	19.54339
## Toyota Corona	21.5	19.32277	22.28518
## Porsche 914-2	26.0	33.08862	25.05484
## Ford Pantera L	15.8	39.18207	17.33194
## Maserati Bora	15.0	24.66780	16.16053

tidymodels Example


```
out_preds_long <- out_preds |>  
  pivot_longer(cols = c(lm, rf),  
               names_to = "model",  
               values_to = "prediction")
```

```
out_preds_long
```

```
## # A tibble: 22 x 3  
##       mpg model prediction  
##   <dbl> <chr>      <dbl>  
## 1   21    lm        17.7  
## 2   21    rf        20.5  
## 3   21    lm        18.9  
## 4   21    rf        20.4  
## 5  21.4   lm        18.4  
## 6  21.4   rf        18.5  
## 7  18.7   lm        20.0  
## 8  18.7   rf        16.8
```

tidymodels Example

```
ggplot(out_preds_long, aes(mpg, prediction)) +  
  geom_point(aes(color = model), size = 3) +  
  geom_abline(slope = 1, intercept = 0)
```



tidymodels Example

Evaluate:

```
out_preds |> metrics(truth = mpg, estimate = lm) |>
  rename(lm = .estimate) |>
  left_join(out_preds |>
    metrics(truth = mpg, estimate = rf) |>
    rename(rf = .estimate))
```

```
## Joining with 'by = join_by(.metric, .estimator)'
```

```
## # A tibble: 3 x 4
```

	.metric	.estimator	lm	rf
	<chr>	<chr>	<dbl>	<dbl>
## 1	rmse	standard	9.40	1.63
## 2	rsq	standard	0.000476	0.783
## 3	mae	standard	6.74	1.46

Example: Social Pressure Experiment (recipes)

Data Splitting

```
social <- read_csv("https://raw.githubusercontent.com/l  
  
soc_split <- initial_split(social)  
soc_train <- training(soc_split)  
soc_test <- testing(soc_split)
```

Data Splitting

```
social <- read_csv("https://raw.githubusercontent.com/l  
  
soc_split <- initial_split(social)  
soc_train <- training(soc_split)  
soc_test <- testing(soc_split)
```

```
dim(soc_train)
```

```
## [1] 229399      6
```

```
dim(soc_test)
```

```
## [1] 76467      6
```

Feature Engineering

```
social_recip <- recipe(primary2006 ~ ., data = soc_train)

social_recip
```

Feature Engineering

```
summary(social_recip)
```

```
## # A tibble: 6 x 4
##   variable      type      role      source
##   <chr>        <list>   <chr>    <chr>
## 1 sex          <chr [3]> predictor original
## 2 yearofbirth  <chr [2]> predictor original
## 3 primary2004 <chr [2]> predictor original
## 4 messages     <chr [3]> predictor original
## 5 hhsize       <chr [2]> predictor original
## 6 primary2006 <chr [2]> outcome  original
```


Feature Engineering

```
social_recip <- social_recip |>  
  step_mutate(age = 2006 - yearofbirth) |>  
  step_dummy(all_nominal(), -all_outcomes())
```

```
social_recip
```

```
##
```

```
## -- Recipe -----
```

```
##
```

```
## -- Inputs
```

```
## Number of variables by role
```

```
## outcome: 1
```

```
## predictor: 5
```

```
##
```

```
## -- Operations
```

```
## * Variable mutation for: 2006 - yearofbirth
```

```
## * Dummy variables from: all_nominal(), -all_outcomes()
```

Feature Engineering

```
social_recip <- social_recip |>  
  step_zv(all_predictors())
```

```
social_recip
```

```
##
```

```
## -- Recipe -----
```

```
##
```

```
## -- Inputs
```

```
## Number of variables by role
```

```
## outcome: 1
```

```
## predictor: 5
```

```
##
```

```
## -- Operations
```

```
## * Variable mutation for: 2006 - yearofbirth
```

```
## * Dummy variables from: all_nominal(), -all_outcomes()
```

```
## * Zero variance filter on: all_predictors()
```

Feature Engineering

```
social_recip <- social_recip |>  
  step_center(all_predictors(), -primary2004)
```

```
social_recip
```

```
##
```

```
## -- Recipe -----
```

```
##
```

```
## -- Inputs
```

```
## Number of variables by role
```

```
## outcome: 1
```

```
## predictor: 5
```

```
##
```

```
## -- Operations
```

```
## * Variable mutation for: 2006 - yearofbirth
```

```
## * Dummy variables from: all_nominal(), -all_outcomes()
```

```
## * Zero variance filter on: all_predictors()
```

```
## * Centering for: all_predictors(), -primary2004
```

Feature Engineering

```
social_recip <- social_recip |>  
  step_interact(terms = ~  
    age:all_predictors() +  
    primary2004:all_predictors()  
  )
```

Feature Engineering

Recipe complete. Time to prep and bake.

Feature Engineering

Recipe complete. Time to prep and bake.

```
social_recipe |>  
  prep()
```

```
##
```

```
## -- Recipe -----
```

```
##
```

```
## -- Inputs
```

```
## Number of variables by role
```

```
## outcome:    1
```

```
## predictor:  5
```

```
##
```

```
## Training information
```

```
soc_train_processed <- social_recip |>
  prep() |>
  bake(new_data = NULL)
```

```
soc_train_processed
```

```
## # A tibble: 229,399 x 22
```

```
##   yearofbirth primary2004 hhsz primary2006 age se
```

```
##           <dbl>         <dbl> <dbl>         <dbl> <dbl>
```

```
## 1      -19.2              0 -0.184              0 19.2
```

```
## 2      -8.21              1 -0.184              1  8.21
```

```
## 3       19.8              1 -0.184              1 -19.8
```

```
## 4      -6.21              0 -0.184              1  6.21
```

```
## 5       3.79              0 -0.184              1 -3.79
```

```
## 6      11.8              0 -1.18              0 -11.8
```

```
## 7       0.793            0 -0.184              0 -0.793
```

```
## 8       4.79              1  0.816              1 -4.79
```

```
## 9       7.79              0 -0.184              1 -7.79
```

```
## 10      -1.21            1 -0.184              0  1.21
```

```
## # i 229,399 more rows
```

```
names(soc_train_processed)
```

```
## [1] "yearofbirth" "primary2004"
## [3] "hhsize" "primary2006"
## [5] "age" "sex_male"
## [7] "messages_Control" "messages_Hawthorne"
## [9] "messages_Neighbors" "age_x_yearofbirth"
## [11] "age_x_primary2004" "age_x_hhsize"
## [13] "age_x_sex_male" "age_x_messages"
## [15] "age_x_messages_Hawthorne" "age_x_messages_Neighbors"
## [17] "yearofbirth_x_primary2004" "primary2004_x_yearofbirth"
## [19] "primary2004_x_sex_male" "primary2004_x_messages"
## [21] "primary2004_x_messages_Hawthorne" "primary2004_x_messages_Neighbors"
```

```
soc_test_processed <- social_recip |>
  prep() |>
  bake(new_data = soc_test)
```

```
soc_test_processed
```

```
## # A tibble: 76,467 x 22
```

```
##   yearofbirth primary2004 hhszize primary2006   age sex
```

```
##           <dbl>         <dbl>   <dbl>         <dbl>   <dbl>
```

```
## 1         -15.2             0 -0.184             0  15.2
```

```
## 2          11.8             0 -0.184             0 -11.8
```

```
## 3          10.8             0 -0.184             0 -10.8
```

```
## 4           4.79             1 -0.184             1  -4.79
```

```
## 5         -13.2             0 -1.18              1  13.2
```

```
## 6         -17.2             0 -1.18              1  17.2
```

```
## 7          -2.21             0  1.82              0   2.21
```

```
## 8          -7.21             1 -0.184             0   7.21
```

```
## 9           6.79             0 -0.184             0  -6.79
```

```
## 10          2.79             0 -1.18              0  -2.79
```

```
## # i 76,467 more rows
```

Regularization Methods: LASSO, ridge regression, elastic nets

Feature Selection

- ▶ Wrappers: pick subset of covars, train on data (estimate model), test on hold-out, score predictions. Keep best-scoring subset.

Feature Selection

- ▶ Wrappers: pick subset of covars, train on data (estimate model), test on hold-out, score predictions. Keep best-scoring subset.
- ▶ Filters: correlate covars with outcome. Keep strongest.

Feature Selection

- ▶ Wrappers: pick subset of covars, train on data (estimate model), test on hold-out, score predictions. Keep best-scoring subset.
- ▶ Filters: correlate covars with outcome. Keep strongest.
- ▶ Embeds: select features and estimate model at same time. Penalize using more predictors.

Embedded Regularization Methods

OLS reminder

Minimize SSR:

$$\arg \min_{\beta} \sum_{i=1}^n (y_i - \hat{y}_i)^2$$
$$\arg \min_{\beta} \sum_{i=1}^n \left(y_i - \mathbf{X} \hat{\beta} \right)^2$$

Embedded Regularization Methods

L1 regularization: the LASSO (Least Absolute Shrinkage and Selection Operator)

$$\arg \min_{\beta} \left[\sum_{i=1}^n \left(y_i - \mathbf{X} \hat{\beta} \right)^2 + \lambda \sum_{j=1}^k |\hat{\beta}_j| \right]$$

Embedded Regularization Methods

L1 regularization: the LASSO (Least Absolute Shrinkage and Selection Operator)

$$\arg \min_{\beta} \left[\sum_{i=1}^n \left(y_i - \mathbf{X}\hat{\beta} \right)^2 + \lambda \sum_{j=1}^k |\hat{\beta}_j| \right]$$

L2 regularization: Ridge regression

$$\arg \min_{\beta} \left[\sum_{i=1}^n \left(y_i - \mathbf{X}\hat{\beta} \right)^2 + \lambda \sum_{j=1}^k \hat{\beta}_j^2 \right]$$

Embedded Regularization Methods

Mix L1 and L2: Elastic net

$$\arg \min_{\beta} \left(\frac{\sum_{i=1}^n (y_i - \mathbf{X}\hat{\beta})^2}{2n} + \lambda \left[\alpha \sum_{j=1}^k |\hat{\beta}_j| + \frac{1-\alpha}{2} \sum_{j=1}^k \hat{\beta}_j^2 \right] \right)$$

Embedded Regularization Methods

Mix L1 and L2: Elastic net

$$\arg \min_{\beta} \left(\frac{\sum_{i=1}^n (y_i - \mathbf{X}\hat{\beta})^2}{2n} + \lambda \left[\alpha \sum_{j=1}^k |\hat{\beta}_j| + \frac{1-\alpha}{2} \sum_{j=1}^k \hat{\beta}_j^2 \right] \right)$$

Regularized trees, ...

R packages for Regularization, etc.

- ▶ `glmnet`

- ▶ `caret`

See also `tidymodels`, `parsnip`, ...

References

Breiman, Leo. 2001. “Statistical Modeling: The Two Cultures (with comments and a rejoinder by the author).” *Statistical Science* 16 (3): 199–231.
<https://doi.org/10.1214/ss/1009213726>.