

M3-L1 Problem 2 (5 points)

```
import numpy as np
import matplotlib.pyplot as plt

def plot_data(data, c, title="",
xlabel="$x_1$", ylabel="$x_2$", classes=["", ""], alpha=1):
    N = len(c)
    colors = ['royalblue', 'crimson']
    symbols = ['o', 's']

    plt.figure(figsize=(5,5), dpi=120)

    for i in range(2):
        x = data[:,0][c==i]
        y = data[:,1][c==i]

    plt.scatter(x,y,color=colors[i],marker=symbols[i],edgecolor="black",li
newwidths=0.4,label=classes[i],alpha=alpha)

    plt.legend(loc="upper right")
    plt.xlabel(xlabel)
    plt.ylabel(ylabel)
    ax = plt.gca()
    ax.set_xticklabels([])
    ax.set_yticklabels([])
    plt.xlim([-0.05,1.05])
    plt.ylim([-0.05,1.05])
    plt.title(title)

def plot_contour(predict, mapXY = None):
    res = 500
    vals = np.linspace(-0.05,1.05,res)
    x,y = np.meshgrid(vals,vals)
    XY = np.concatenate((x.reshape(-1,1),y.reshape(-1,1)),axis=1)
    if mapXY is not None:
        XY = mapXY(XY)
    contour = predict(XY).reshape(res, res)
    plt.contour(x, y, contour)
```

Generate Dataset

(Don't edit this code.)

```
def get_line_dataset():
    np.random.seed(4)
```

```

x = np.random.rand(90)
y = np.random.rand(90)

h = 1/.9*x + 1/0.9*y - 1


d = 0.1
x1, y1 = x[h<-d], y[h<-d]
x2, y2 = x[np.abs(h)<d], y[np.abs(h)<d]
x3, y3 = x[h>d], y[h>d]

c1 = np.ones_like(x1)
c2 = (np.random.rand(len(x2)) > 0.5).astype(int)
c3 = np.zeros_like(x3)
xs = np.concatenate([x1,x2,x3],0)
ys = np.concatenate([y1,y2,y3],0)
c = np.concatenate([c1,c2,c3],0)
return np.vstack([xs,ys]).T,c

data, classes = get_line_dataset()
format = dict(title="Limiting Current with Resistors in Series",
xlabel="Resistor 1", ylabel="Resistor 2", classes=["0 - Current below
limit","1 - Current overload"])

plot_data(data, classes, **format)

```



Define helper functions

First, fill in code to complete the following functions. You may use code you wrote in the previous question.

- `sigmoid(h)` to compute the sigmoid of an input `h`
- (Given) `transform(data, w)` to add a column of ones to `data` and then multiply by the 3-element vector `w`
- (Given) `loss(data, y, w)` to compute the logistic regression loss function:

$$L(x, y, w) = \sum_{i=1}^n -y^{(i)} \cdot \ln(g(w'x^{(i)})) - (1 - y^{(i)}) \cdot \ln(1 - g(w'x^{(i)}))$$

- `gradloss(data, y, w)` to compute the gradient of the loss function with respect to `w`:

$$\frac{\partial L}{\partial w_j} = \sum_{i=1}^n (g(w'x^{(i)}) - y^{(i)}) x_j^{(i)}$$

```
def sigmoid(h):
    # YOUR CODE GOES HERE
    sigmoid_h = 1/(1+np.exp(-h))
    return sigmoid_h

def transform(data, w):
    xs = data[:,0]
    ys = data[:,1]
```

```

ones = np.ones_like(xs)
h = w[0]*ones + w[1]*xs + w[2]*ys
return h

def loss(data, y, w):
    wt_x = transform(data,w)
    J1 = -np.log(sigmoid(wt_x)) * y
    J2 = -np.log(1 - sigmoid(wt_x)) * (1-y)
    L = np.sum(J1 + J2)
    return L

def gradloss(data, y, w):
    # YOUR CODE GOES HERE
    wt_x = transform(data,w)
    xj = np.vstack([np.ones_like(data[:,0]), data[:,0], data[:,1]])
    grad_L = np.sum((sigmoid(wt_x) - y) * xj, axis=1)
    return grad_L

```

Gradient Descent

Now you'll write a gradient descent loop. Given a number of iterations and a step size, continually update w to minimize the loss function. Use the `gradloss` function you wrote to compute a gradient, then move w by `stepsize` in the direction opposite the gradient. Return the optimized w .

```

def grad_desc(data, y, w0=np.array([0,0,0]), iterations=100,
stepsize=0.1):
    # YOUR CODE GOES HERE
    w = w0
    for i in range(iterations):
        w = w - stepsize * gradloss(data, y, w)
    return w

```

Test your classifier

Run these cells to find the optimal w , compute the accuracy on the training data, and plot a decision boundary.

```

w = grad_desc(data, classes)
preds = np.round(sigmoid(transform(data, w))).astype(int)
accuracy = np.sum(preds == classes) / len(classes) * 100
print("      w = ", w)
print("True Classes: ", classes.astype(int))
print(" Predictions: ", preds)
print("  Accuracy: ", accuracy, r"%")

w = [ 7.99449326 -8.54560847 -9.92653181]
True Classes: [1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0 0 1 1 0

```

```
predict = lambda data: np.round(sigmoid(transform(data, w)))
plot_data(data, classes, **format)
plot_contour(predict)
plt.show()
```

