

GeeksforGeeks

A computer science portal for geeks

[COURSES](#)[Login](#)[HIRE WITH US](#)

dup() and
dup2() Linux
system call

dup() and
dup2() Linux
system call

Check if
given
Preorder,
Inorder and
Postorder
traversals
are of same
tree | Set 2

Difference
between
pointer to an
array and
array of
pointers

Count
substrings
that contain
all vowels |
SET 2



C program to
sort an array
using
pointers

Basic Code
Optimizations
in C

dot (.)
operator in
C/C++

Features and
Use of
Pointers in
C/C++

How can we
use Comma
operator in
place of curly
braces?

OpenMP |
Hello World
program

Difference
between
while and do-
while loop in
C, C++, Java

Sum of an
array using
MPI

__builtin_inf()
functions of



GCC
compiler

C Program to
count the
Number of
Characters in
a File

time.h
header file in
C with
Examples

scanf("%
[^\n]s", str)
Vs gets(str)
in C with
Examples

AKTU
(UPTU)
Previous
Year Solved
Papers | C
Programming

Constants vs
Variables in
C language

Analyzing
BufferOverflow
with GDB

C program to
Insert an
element in
an Array

Types of



Literals in
C/C++ with
Examples

Conditional
or Ternary
Operator (?:)
in C/C++

Difference
between C
and C#

time.h
localtime()
function in C
with
Examples

asctime()
and
asctime_s()
functions in
C with
Examples


return
statement in
C/C++ with
Examples

size of char
datatype and
char array in
C

Arrow
operator -> in
C/C++ with
Examples



Logical Not !
operator in C
with
Examples



dup() and dup2() Linux system call

dup()

The dup() system call creates a copy of a file descriptor.





- It uses the lowest-numbered unused descriptor for the new descriptor.
- If the copy is successfully created, then the original and copy file descriptors may be used interchangeably.
- They both refer to the same open file description and thus share file offset and file status flags.

Syntax:

```
int dup(int oldfd);
```

oldfd: old file descriptor whose copy is to be created.





```
// CPP program to illustrate dup()
#include<stdio.h>
#include <unistd.h>
#include <fcntl.h>

int main()
{
    // open() returns a file descriptor file_desc to a
    // the file "dup.txt" here"

    int file_desc = open("dup.txt", O_WRONLY | O_APPEND);

    if(file_desc < 0)
        printf("Error opening the file\n");

    // dup() will create the copy of file_desc as the copy_desc
    // then both can be used interchangeably.

    int copy_desc = dup(file_desc);

    // write() will write the given string into the file
    // referred by the file descriptors

    write(copy_desc,"This will be output to the file named dup.txt\n",
    write(file_desc,"This will also be output to the file named dup.tx

    return 0;
}
```

Note that this program will not run in the online compiler as it includes opening a file and writing on it.

Explanation: The open() returns a file descriptor file_desc to the file named "dup.txt". file_desc can be used to do some file operation with file "dup.txt". After using the dup() system call, a copy of file_desc is created copy_desc. This copy can also be used to do some file operation with the same file "dup.txt". After two write operations one with file_desc and another with copy_desc, same file is edited i.e. "dup.txt".


Before running the code, Let The file "dup.txt" before the write operation be as shown below:





A screenshot of a text editor window. The title bar shows 'Open' and 'Save' buttons. The text area contains the line 'Hi i am the file "dup.txt"'. The status bar at the bottom indicates 'Loading file "/home/mik/Desktop/dup.txt'...', 'Plain Text', 'Tab Width: 8', 'Ln 1, Col 27', and 'INS'.

After running the C program shown above, the file “dup.txt” is as shown below:



A screenshot of a text editor window. The title bar shows 'Open' and 'Save' buttons. The text area contains three lines: 'Hi i am the file "dup.txt"', 'This will be output to the file named dup.txt', and 'This will also be output to the file named dup.txt'. The status bar at the bottom indicates 'Plain Text', 'Tab Width: 8', 'Ln 1, Col 27', and 'INS'.

dup2()

The dup2() system call is similar to dup() but the basic difference between them is that instead of using the lowest-numbered unused file descriptor, it uses the descriptor number specified by the user.

Syntax:



```
int dup2(int oldfd, int newfd);
```


oldfd: old file descriptor

newfd new file descriptor which is used by dup2() to create a copy.

Important points:

- Include the header file unistd.h for using dup() and dup2() system call.
- If the descriptor newfd was previously open, it is silently closed before being reused.
- If oldfd is not a valid file descriptor, then the call fails, and newfd is not closed.
- If oldfd is a valid file descriptor, and newfd has the same value as oldfd, then dup2() does nothing, and returns newfd.

A tricky use of dup2() system call: As in dup2(), in place of newfd any file descriptor can be put. Below is a C implementation in which the file descriptor of Standard output (stdout) is used. This will lead all the printf() statements to be written in the file referred by the old file descriptor.



```
// CPP program to illustrate dup2()
#include<stdlib.h>
#include<unistd.h>
#include<stdio.h>
#include<fcntl.h>

int main()
{
    int file_desc = open("tricky.txt",O_WRONLY | O_APPEND);

    // here the newfd is the file descriptor of stdout (i.e. 1)
    dup2(file_desc, 1) ;


    // All the printf statements will be written in the file
    // "tricky.txt"
    printf("I will be printed in the file tricky.txt\n");

    return 0;
}
```

This can be seen in the figure shown below:


Let The file "tricky.txt" before the dup2() operation be as shown below:





A screenshot of a text editor window. The title bar shows 'Open' and 'Save' buttons. The text area contains the line: `Hi i am the file "tricky.txt"`. The status bar at the bottom indicates 'Saving file "/home/mik/Desktop/tricky.txt"...', 'Plain Text', 'Tab Width: 8', 'Ln 1, Col 30', and 'INS'.

After running the C program shown above, the file "tricky.txt" is as shown below:



A screenshot of a text editor window, similar to the one above. The title bar shows 'Open' and 'Save' buttons. The text area contains two lines: `Hi i am the file "tricky.txt"` and `I will be printed in the file tricky.txt`. The status bar at the bottom indicates 'Plain Text', 'Tab Width: 8', 'Ln 1, Col 30', and 'INS'.

Reference: [dup\(2\) – Linux man page](#)

This article is contributed by **MAZHAR IMAM KHAN**. If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Recommended Posts:

[pipe\(\) System call](#)

[Accept system call](#)

[Wait System Call in C](#)

[Difference between Call by Value and Call by Reference](#)

[What is Linux System Administration?](#)

[Groups in Linux System Administration](#)

[proc file system in Linux](#)

[Users in Linux System Administration](#)

[SAR command in Linux to monitor system performance](#)

[Linux Operating System | CLI \(Command Line Interface\) and GUI \(Graphic User Interface\)](#)

[A C/C++ Function Call Puzzle](#)

[Can we call an undeclared function in C++?](#)

[Is it possible to call constructor and destructor explicitly?](#)

[Difference between CALL and JUMP instructions](#)

[Linux Virtualization : Linux Containers \(lxc\)](#)

Article Tags : [C](#) [Linux-Unix](#) [system-programming](#)

Practice Tags : [C](#)



1

3.6



☐ To-do ☐ Done

Based on 11 vote(s)

[Feedback/ Suggest Improvement](#)[Add Notes](#)[Improve Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

PRACTICE

Courses
Company-wise
Topic-wise
How to begin?

CONTRIBUTE

Write an Article
Write Interview
Experience
Internships
Videos

@geeksforgeeks, Some rights reserved

