

Compilers Principles Lab5 Report

Language Feature Extension

Yurun Yuan

CS, USTC

January 21, 2022

Outline

- 1 Type System Extension
 - Pointers and Arrays
 - Structures
- 2 Operator Extension
 - Context Free Grammar of Expressions
 - Operations on Structures
- 3 Classes and Templates
 - Non-Static Member Functions
 - Operator Overloading
 - Class Templates

Outline

- 1 Type System Extension
 - Pointers and Arrays
 - Structures
- 2 Operator Extension
 - Context Free Grammar of Expressions
 - Operations on Structures
- 3 Classes and Templates
 - Non-Static Member Functions
 - Operator Overloading
 - Class Templates

Declarations of Variables

- Pointers

```
int *ptr;
```

- Function

```
int func(int );
```

- Arrays

```
int array [42];
```

- Structures

```
struct S {...};
```

```
struct S s;
```

```
struct S {...} s;
```

```
struct {...} anonymous;
```

Declaration Grammar

Declaration grammar

declaration \rightarrow type-specifier declarator ;

Example

type-specifier

int

* a[2] ;

declarator

Declaration Grammar

Declaration grammar

declaration \rightarrow type-specifier declarator ;

- Pointer declarators
`int * ptr ;`
- Function declarators
`int func(float) ;`
- Array declarators
`int array[42] ;`

Crux: declarators can get mixed up

Example

```
int (* a [2])( int );
```

Nested declarators	Type expression
(* a [2])(int)	int
* a [2]	int → int
a [2]	pointer(int → int)
a	array(2, pointer(int → int))

Trial 1: a naive solution

Example

```
int (* a [2])( int );
```



declarator	→	* declarator	<i>Pointer declarator</i>
		declarator (type, ...)	<i>Function declarator</i>
		declarator [int]	<i>Array declarator</i>
		(declarator)	
		ID	

Trial 1: a naive solution

Example

```
int (* a [2])( int );
```

Problem: ambiguity



Trial 2: eliminating ambiguity

- Parentheses and identifiers

$$\begin{array}{l} \text{factor} \rightarrow \mathbf{ID} \\ \quad \quad | \text{ (decl)} \end{array}$$

- Function calls and array subscripting

$$\begin{array}{l} \text{decl-1} \rightarrow \text{decl-1}(\text{type}, \dots) \\ \quad \quad | \text{ decl-1}[\mathbf{int}] \\ \quad \quad | \text{ factor} \end{array}$$

- Dereference


$$\begin{array}{l} \text{decl} \rightarrow * \text{ decl} \\ \quad \quad | \text{ decl-1} \end{array}$$

Preced	Operation
0	Parenthesis ()
1	Call () subscript []
2	Dereference *

Trial 2: eliminating ambiguity

Example

```
int * array [2] ;
```



- Parentheses and identifiers

$$\text{factor} \rightarrow \mathbf{ID}$$
$$\quad \quad \quad | \quad (\text{ decl })$$

- Function calls and array subscripting

$$\text{decl-1} \rightarrow \text{decl-1}(\text{type}, \dots)$$
$$\quad \quad \quad | \quad \text{decl-1}[\mathbf{int}]$$
$$\quad \quad \quad | \quad \text{factor}$$

- Dereference

$$\text{decl} \rightarrow * \text{ decl}$$
$$\quad \quad \quad | \quad \text{decl-1}$$

Declarations of Structures

- Structure definition
struct S {...};
- Variable definition
struct S s;
- Structure and variable definition
struct S {...} s;
- Anonymous structure
struct {...} anonymous;

Extension of the declaration grammar

Declaration grammar

declaration \rightarrow type-specifier declarator ;

Declaration	Type specifier	Declarator
struct S { ... } ;	struct S { ... }	\emptyset
struct S s ;	struct S	s
struct S { ... } s ;	struct S { ... }	s
struct { ... } anonymous ;	struct { ... }	anonymous

Extension of the declaration grammar

Declaration grammar

declaration \rightarrow type-specifier declarator ;

type-specifier \rightarrow ...
| struct-definition
| **struct ID**

struct-definition \rightarrow **struct ID**{definitions}
| **struct**{definitions}

declarator \rightarrow ...
| ϵ

Self reference

Example

A naive implementation of the node of a forwarding linked list

```
struct list_node{  
    int elem;  
    struct list_node* next;  
};
```

The identifier `struct list_node` is visible within the definition of the structure, although `struct list_node` is an incomplete type.

Self reference

Example

A naive implementation of the node of a forwarding linked list

```
struct list_node{  
    int elem;  
    struct list_node* next;  
};
```

To render the identifier `struct list_node` available, construct an empty structure before parsing the body of the structure definition, and complete the type after the definition parsing is done.

Outline

- 1 Type System Extension
 - Pointers and Arrays
 - Structures
- 2 **Operator Extension**
 - Context Free Grammar of Expressions
 - Operations on Structures
- 3 Classes and Templates
 - Non-Static Member Functions
 - Operator Overloading
 - Class Templates

Supported operators

- Arithmetic operators
+, -, *, /
- Relational operators
>, <, >=, <=, ==, !=
- Assignment operator
=
- Array subscript
array[index]
- Pointer dereference
* ptr
- Address of
& lvalue
- Member access
var.member
- Function call
callable (params)

Precedence and CFG

0 Parenthesis ()

$\text{expr-0} \rightarrow$ **ID**
| **Integer-literal**
| **Float-literal**
| (expr)

1 Function call, array subscript, member access

$\text{expr-1} \rightarrow \text{expr-1 (args)}$
| expr-1 [expr]
| expr-1 . ID
| expr-0

Precedence and CFG

- ② Dereference, address of

$$\begin{aligned} \text{expr-2} &\rightarrow * \text{expr-2} \\ &| \& \text{expr-2} \\ &| \text{expr-1} \end{aligned}$$

- ③ Multiplication, division

$$\begin{aligned} \text{expr-3} &\rightarrow \text{expr-3} \mathbf{MulOp} \text{expr-2} \\ &| \text{expr-2} \end{aligned}$$

- ④ Addition subtraction

$$\begin{aligned} \text{expr-4} &\rightarrow \text{expr-4} \mathbf{AddOp} \text{expr-3} \\ &| \text{expr-3} \end{aligned}$$

Precedence and CFG

5 Relational operations

$$\begin{array}{l} \text{expr-5} \rightarrow \text{expr-5} \textbf{RelOp} \text{expr-4} \\ \quad \quad \quad | \text{expr-4} \end{array}$$

6 Assignment

$$\begin{array}{l} \text{expr} \rightarrow \text{expr-5} = \text{expr} \\ \quad \quad \quad | \text{expr-5} \end{array}$$

Note

The assignment operator is right associated, so the production is $\text{expr} \rightarrow \text{expr-5} = \text{expr}$ instead of $\text{expr} \rightarrow \text{expr} = \text{expr-5}$.

Problems with operations on structures

- Assignment to structures
struct S s = t;
- Structures as parameters
void func(**struct** S){...};
- Structures as return values
struct S func () {...};

Assignment to structures

- Source code

```
struct S
{
    int member1;
    float member2;
};

s = t;
```

- Transformed code

```
struct S{
    int member1;
    float member2;
};

s.member1 = t.member1;
s.member2 = t.member2;
```

Structures as parameters

- Source code

```
void func(struct S s)
{
    ...
}

int main()
{
    func(t);
}
```

- Transformed code

```
void func(struct S *ptr)
{
    struct S s = *ptr;
}

int main()
{
    func(&t);
}
```


Structures as return values

- Source code

```
struct S func()  
{  
    ...  
    return s;  
}  
  
int main()  
{  
    func();  
}
```

- Transformed code

```
void func(struct S* ret_ptr)  
{  
    ...  
    *ret_ptr = ret_value;  
}  
  
int main() {  
    struct S ret_value;  
    func(&ret_value);  
}
```

Outline

- 1 Type System Extension
 - Pointers and Arrays
 - Structures
- 2 Operator Extension
 - Context Free Grammar of Expressions
 - Operations on Structures
- 3 Classes and Templates
 - Non-Static Member Functions
 - Operator Overloading
 - Class Templates

Functions declared within a structure

Example

```
struct S
{
    ...
    void func(){}
};
```

```
int main()
{
    struct S s;
    s.func();
}
```

Transformation of member functions

- Source code

```
struct S
{
    ...
    void func(){}
};

int main()
{
    struct S s;
    s.func();
}
```

- Transformed code

```
struct S
{
    ...
};
void S::func(struct S* this){}

int main()
{
    struct S s;
    S::func(&s);
}
```

Overload an operator

```
struct S {  
    struct S operator+(struct S rhs)  
    {...}  
};  
  
int main()  
{  
    struct S s;  
    struct S t;  
    ...  
    s + t; // S::operator+ is called  
}
```

Transform the overloading function

- Source code

```
struct S
{
    S operator+(S)
    {...}
};
```

```
int main() {
    struct S s;
    struct S t;
    ...
    s + t;
}
```

- Transformed code

```
void S::operator+(
    struct S* ret_ptr,
    struct S* this
    struct S* rhs_ptr){
    struct S rhs = *rhs_ptr;
    ...
    *ret_ptr = ret_value;
}

int main(){
    struct S s; struct S t;
    ...
    struct S ret_value;
    S::operator+(&ret_value, &s, &t);
}
```

Generic programming

Example

```
template<typename T>
struct stack{
    T top();
    void push(T);
};
```

```
int main()
{
    stack<int> a;
    stack<string> b;
    a.push(42);
    b.push("42");
}
```

CFG for class templates

template-definition \rightarrow **template** < **typename ID**, ...>
struct-definition

type-specifier \rightarrow ...
| **typename ID**
| **struct ID** <declaration,...>


Note

Due to the limitation of CFG, in the specification of a class template, the keyword *typename* is required before a template parameter.


Translation process of a class template

```
template<typename T>
struct S{
    typename T a;
};


int main(){
    struct S<int> x;
}
```



Translation process of a class template




Translation process of a class template




- Record the pointer of node template **S** in AST, do not analyse subtrees.

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<int>$ does not exist. Map parameter T to int , analyse class template

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to int , analyse class template
- **Construct structure $S<\text{int}>$**

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to int , analyse class template
- Construct structure $S<\text{int}>$

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to int , analyse class template
- Construct structure $S<\text{int}>$
- **Use mapping to replace T with int**

Translation process of a class template




- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to int , analyse class template
- Construct structure $S<\text{int}>$
- Use mapping to replace T with int

Translation process of a class template



- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to **int**, analyse class template
- Construct structure $S<\text{int}>$
- Use mapping to replace T with **int**
- $S<\text{int}>$ now is a complete type

Translation process of a class template



- Record the pointer of node template S in AST, do not analyse subtrees.
- $S<\text{int}>$ does not exist. Map parameter T to int , analyse class template
- Construct structure $S<\text{int}>$
- Use mapping to replace T with int
- $S<\text{int}>$ now is a complete type
- **Declare a variable of type $S<\text{int}>$**

Thank You.