

Compilers Principle Lab5: *Language Features Extension* Report

BY 袁玉润 PB19111692

摘要

基于Lab1-Lab4, 我在本次实验中增加了 **cminusf** 的语言特性, 主要包括:

1. 类型拓展

增加了丰富的指针、数组类型, 支持结构体。

2. 运算符拓展

除基本的算数运算和关系运算外, 增加下标运算、调用运算、取地址运算、解引运算、成员访问运算。

3. 类

支持部分类的特性, 包括成员函数, 算数运算符重载和类模板。

在本报告中, 我将展示上述内容的实现方法和实现效果。

1 新增语言特性及实现方法

1.1 类型拓展

1.1.1 指针与数组

定义. *Declaration grammar*

$$\text{var-declaration} \rightarrow \text{type-specifier declarator ;}$$

例. `int *a;` 中 `int` 为 type-specifier, `*a` 为 declarator.

1. type specifier

$$\text{type-specifier} \rightarrow \text{int} \mid \text{float}$$

2. declarator

Declarator 分为以下3种:

a. Pointer declarator

`int *a;` 中 `*a` 即 pointer declarator.

b. Function declarator

`int (*p)(int);` 中 `(*p)(int)` 即 function declarator.

c. Array declarator

`int a[32];` 中 `a[32]` 即 array declarator.

各种 declarator 间可以嵌套, 得到更加丰富的类型:

Trial 1:

$$\begin{aligned} \text{declarator} \rightarrow & * \text{declarator} \\ & \mid \text{declarator} (\text{params}) \\ & \mid \text{declarator} [\text{int}] \\ & \mid (\text{declarator}) \end{aligned}$$

Problem: Ambiguity

```
int *ambiguous[42]
// Can be interpreted as either of the following
int (*ptr)[42];
int*(array[42]);
```

Solution: Precedence

根据*和[]的运算优先级修改CFG，消除二义性。

表格. Declarator CFG

Precedence	Description	Context Free Grammar
0		factor \rightarrow ID (declarator)
1	Function declarator Array declarator	declarator-1 \rightarrow declarator-1 (params) declarator-1 [int] factor
2	Pointer declarator	declarator \rightarrow * declarator declarator-1

例. An array of function pointers.

```
int (* func_table[2])(int, int)
```

type-specifier	int
declarator	(* func_table[2])(int, int)

各层Declarators如下:

Declarators	Type
(* func_table[2])(int, int)	int
(* func_table[2])	int \times int \rightarrow int
func_table[2]	pointer(int \times int \rightarrow int)
func_table	array(2, pointer(int \times int \rightarrow int))

1.1.2 结构体

例. 结构体及结构体类型变量定义语法的多样性，使得结构体的实现看起来十分困难。

```
// Struct definitions with no variables declared
struct S
{
    ...
};

// Struct definitions with a variable declared
struct T
{
    ...
} t;

// Define a variable with struct type
struct S s;

// Anonymous structs
struct
{
    ...
};
```

```

    ...
} anonymous;

// Nested structs
struct U
{
    struct Nested
    {
        ...
    } n;
};

```

根据观察和调研，可知：

Struct definitions *are* type specifiers.

declarators may be omitted if the type-specifier is a struct definition.

例.

Description	整数	结构体定义+变量声明	结构体定义	变量声明
Declaration	int a;	struct S{...} s;	struct S{...};	struct S s;
Type specifier	int	struct S{...}	struct S{...}	struct S
Declarator	a	s	empty	s

修改文法如下：

```

type-specifier → int | float
               | struct-definition
               | struct ID
struct-definition → struct ID { definitions }
                 | struct { definitions }
declarator → ...
           | ε

```

1.2 运算拓展

支持如下运算：

1. Arithmetic operations
2. Relational operations
3. Assignment
4. Array subscript
array[subscript]
5. Pointer dereference
*ptr
6. Address of
&rval
7. Member access
inst.mem

8. Function call

callable(params)

1.2.1 表达式CFG

根据运算优先级消除二义性，得到以下文法：

表格. Expression CFG

Precedence	Operator	Description	Context Free Grammar
0			$\text{expr-0} \rightarrow \text{ID}$ $\quad \quad \quad \text{Integer-literal}$ $\quad \quad \quad \text{Float-literal}$ $\quad \quad \quad (\text{expr})$
1	() [] .	Function call Array subscripting Member access	$\text{expr-1} \rightarrow \text{expr-1} (\text{args})$ $\quad \quad \quad \text{expr-1} [\text{expr}]$ $\quad \quad \quad \text{expr-1} . \text{ID}$ $\quad \quad \quad \text{expr-0}$
2	* &	Dereference Address of	$\text{expr-2} \rightarrow * \text{expr-2}$ $\quad \quad \quad \& \text{expr-2}$ $\quad \quad \quad \text{expr-1}$
3	* /	Multiplication, division	$\text{expr-3} \rightarrow \text{expr-3} \text{ MulOp } \text{expr-2}$ $\quad \quad \quad \text{expr-2}$
4	+ -	Addition, subtraction	$\text{expr-4} \rightarrow \text{expr-4} \text{ AddOp } \text{expr-3}$ $\quad \quad \quad \text{expr-3}$
5	> ≥ == ≠ < ≤	Relational operators	$\text{expr-5} \rightarrow \text{expr-5} \text{ RelOp } \text{expr-4}$ $\quad \quad \quad \text{expr-4}$
6	=	Assignment	$\text{expr} \rightarrow \text{expr-5} \text{ Assign } \text{expr}$ $\quad \quad \quad \text{expr-5}$

1.2.2 结构体相关的运算

支持结构体这样的复合类型后，一些对scalar type的运算需要拓展，以支持结构体类型的运算元。最显著的变化便是，由于许多结构体类型的变量无法储存在单一寄存器中，结构体的赋值和传递需要特别的操作。

Assignment to struct-type variables 通过对成员逐个赋值的方式实现了结构体变量的默认赋值操作。

例. 考虑如下定义的结构体S:

```
struct S
{
    int member1;
    float member2;
};
```

对struct S类型的变量s的赋值操作将会被翻译为:

cminusr	Translated representation
s=t	$\text{s.member1} = \text{t.member1};$ $\text{s.member2} = \text{t.member2};$

Struct-type parameters 当函数调用时参数为结构体类型时，传递结构体变量的指针，并由callee复制指针指向的结构体变量。

例. 考虑如下情形

cminusf	Translated representation
<pre>void func(struct S s) { ... } int main() { func(t); ... }</pre>	<pre>void func(struct S *ptr) { struct S s; s = *ptr; ... } int main() { func(&t); }</pre>

Struct-type return value 当函数返回值为结构体类型时，由caller开辟返回值存放空间，并将指向这块空间的指针作为参数传递至callee

例. 考虑如下情形

cminusf	Translated representation
<pre>struct S func() { ... return s; } int main() { func(); }</pre>	<pre>void func(struct S* ret_ptr) { ... *ret_ptr = ret_value; } int main() { struct S ret_value; func(&ret_value); }</pre>

1.3 部分类的特性

1.3.1 Member functions (Non-static)

在参数列表首位添加this指针参数，将成员函数翻译为普通函数。

例.

cminusf	Translated representation
<pre>struct S { ... void member_func(){} }; int main() { struct S s; s.member_func(); }</pre>	<pre>struct S { ... }; void S.member_func(struct S* this){} int main() { struct S s; S.member_func(&s); }</pre>

Problem: 若按顺序对结构体定义中的成员变量和成员函数的定义遍历，则在某函数定义后的成员变量对成员函数不可见。

例.

```
struct S
{
    void mem_func(); // 此处并不知道struct S有成员a
    int a;
}
```

Solution: 首先遍历结构体中所有定义，将成员函数与成员变量分离开，在得到完整的结构体成员变量定义后再处理成员函数。

1.3.2 Arithmetic Operator Overloading

识别关键字operator，将重载操作的函数记录于表中，在需要时调用此函数。

例.

cminusf	Translated representation
<pre>struct S { ... // Overload operator '+' struct S operator+(struct S rhs) {...} }; int main() { struct S s; struct S t; ... s + t; // Call 'S::operator+' }</pre>	<pre>struct S{...}; void S.operator+(struct S* ret_ptr, struct S* this struct S* rhs_ptr) { struct S rhs; rhs = *rhs_ptr; ... *ret_ptr = ret_value; } int main() { struct S s; struct S t; ... struct S ret_value; S.operator+(&ret_value, &s, &t); }</pre>

1.3.3 Class Templates

注记. 由于CFG的限制，我的实现中的语法与C++中并不完全兼容，具体表现在：在类模板中使用模板参时，需要在参数名前使用typename关键字。具体可见4.1。


Overview

实现类模板的大体思路是：当访问到AST中类模板定义的节点时，记录此节点的地址。后续过程中如需对模板实例化，则使用类模板参数重新访问类模板对应节点，并构建相应结构体、成员函数。

例.

```
template<typename T>
struct Demo{
    ...
};

int main(){
    struct Demo<int> int_demo;
}
```



在访问节点template时，并不访问节点 `class template struct Demo`，而是只记录下此节点的位置。

在访问 `var-definition struct Demo<int> int_demo;` 时，使用模板参int访问节点 `class template struct Demo`，此过程中会产生 `struct Demo<int>` 的实例。

Modification of CFG

```

class-template-declaration → template <typename ID, typename ID...>
type-specifier → int | float
                  | struct-definition
                  | struct ID
                  | class-template-type
                  | typename ID
class-template-type → struct ID <type-specifier,type-specifier...>

```

Modification of AST visitors

类型等价判断. 当首次遇到 `struct Demo<int>` 时，编译器会生成结构体 `struct.Demo.int`. 在之后的过程中遇到 `struct Demo<int>` 时，编译器应当识别出此类型，而非构建新的结构体。

在我的实现中，使用类模板名和模板参数的值为键，记录已生成的结构体。

2 Demos

The source code can be found at `CMINUS/Reports/5-bonus/demos/complex_num_cal.cminus`.

I wrote a complex nubmer calculator to exhibit all the extended language features mentioned above. It may seem a little verbose because I am trying to exert all the features my compiler supports. The program has following components:

Struct `complex_num`. A struct representing a complex number, which simply contains 2 floats as real component and imaginary component.

This struct has several member functions and overloads 4 arithmetic operators, that is, addition, subtraction, multiplication and division.

The prototype of the struct is shown as follows (not in `cminusr` syntax):

```
struct complex_num{
    float real, imaginary;
    complex_num operator+(complex_num);
    complex_num operator-(complex_num);
    complex_num operator*(complex_num);
    complex_num operator/(complex_num);
};
```

Functions performing arithmetic operations for complex number. 4 functions that take 2 complex numbers's addresses as parameters and calculate plus(function `plus`), subtraction(function `subtract`), multiplication(function `multiply`) and division(function `divide`) respectively. For example, the function `plus` is defined as:

```
struct complex_num plus(struct complex_num *lhs, struct complex_num *rhs)
{
    return *lhs + *rhs;
}
```

An array `function_table`. An array containing all 4 functions mentioned above, i.e., `function_table = {plus,subtract,multiply,divide}`.

Function `get_function`. It takes an operator as input and returns a function pointer in the function table that performs the corresponding operation. For example, `get_function('+')` would return the first element in the `function_table`, i.e. the function pointer `plus`.

A class template `stack`. The template has one template parameter `T`, which is the type of the element in the stack. The template has several member functions relevant to stack data structure. The compact prototype is as follows:

```
template<typename T>
struct stack{
    T *memory; // To store the elements in stack
    int
    void init();// Constructor
    void drop();// Destructor

    void push(T elem);
    T top();
    T pop();
};
```

The `main` function. To implement the calculator, I used 2 stacks:

1. one for the operands, whose type is `struct stack<struct complex_num>`, and
2. one for the operators, whose type is `struct stack<int>`, containing operators like `+, -, *, /, (` and `)`.

To parse an algebraic expression like `1i * 2 * (3 + 4i)`, the program would push the operands and operators into stack respectively, and do the calculation at the right time.

3 实现时的阻碍

实现上述特性时遇到许多耗时耗力的工作，主要的困难来自以下几点：

1. Lab1-Lab3中代码的大规模重新设计及重写

因拓展点较多，原先的结构无法支持增加的语言特性，故对词法分析、语法分析、AST的设计及构建、IR的翻译部分均有较大的删改。

2. LightIR对一些特性支持的缺失

需自行修改LightIR使之支持结构体类型。

此外，LightIR中只能对函数实施调用操作，但在IR中允许对函数指针实施调用。

4 Unsolved Problems

4.1 Omitting Keyword **struct** when Referring to a Struct Type

在C++中，指代类类型时可忽略**struct**或**class**关键字，如

```
struct S{};
int func()
{
    S s;
}
```

但使用CFG似乎很难区分以下两种情况：

变量声明	函数调用
S (s);	func(s);

因此在我的实现中要求类型名前使用**struct**关键字。

同样的问题也出现在类模板内。在C++中使用类模板参数时可直接以参数名表示，例如：

```
template<typename T>
class Demo{
    T mem;
};
```

在我的实现中，基于上述原因，要求用户在参数名前使用**typename**关键字，如：

```
template<typename T>
class Demo{
    // 'typename' is compulsory in my cminusf
    typename T mem;
};
```

4.2 Recursive Type

链表节点的常见实现如下：

```
struct Node{
    T elem;
    Node* next;
};
```

在Node节点未完整定义(但已声明)的情况下，可使用Node*类型。

我的实现中未考虑此情况。