SCANIQ LLC

Resonant Biofabrication & Embryonic Spectral Intelligence

A friend-readable concept summary combining continuous SDF/voxel engineering, silk-based chiral structures, terahertz resonators, and AI-assisted developmental sensing

Core fusion: ScanIQ uses continuous signed-distance fields and voxel mathematics to turn millimeter-scale silk fibers and material domains into tightly controlled submillimeter geometry - then links that geometry to chiral/terahertz response and biological sensing data through machine learning.

Concept document - not a clinical protocol

Prepared from our ScanIQ discussion | September 8, 2026

1. The idea in plain English

The concept is to build a platform that can **design, manufacture, sense, and learn from resonant biological interfaces**. ScanIQ would represent both structure and material distribution as continuous mathematical fields rather than only as triangle meshes. That makes it possible to control not just the outer shape of a device, but also local orientation, chirality, porosity, dielectric regions, conductive paths, and silk-fiber organization at progressively smaller scales.

For the embryo research branch, the first objective is passive measurement, not stimulation. Opposed resonant structures above and below a culture region could interrogate changes in dielectric behavior, impedance, phase, resonance frequency, bandwidth and Q factor as an embryo develops. Imaging and environmental data would be synchronized with those signals. AI would then search for a developmental spectral fingerprint: a trajectory through multiple measurements rather than a single supposed "magic frequency."

2. How the technologies fuse

ScanIQ computational engineering	Resonant bio-material interface
Continuous SDF geometry defines surfaces without being limited to a coarse polygon mesh.	Silk fibroin can act as a tunable dielectric/biomaterial platform and has already been used with THz metamaterial sensing.
Voxel/material fields can encode local composition, orientation, density, chirality and gradients.	Chiral and Möbius-inspired resonators introduce topology and polarization-sensitive modes that ordinary rings do not necessarily support.
AI can connect simulation, toolpath generation, optical metrology and sensor feedback.	Embryo/oocyte electrical spectroscopy has already shown that developmental or physiological state can alter measurable impedance signatures.
Field-native slicing can translate optimized geometry directly into graded or multi-material deposition paths.	The research question is whether the manufactured resonator/material geometry can improve sensitivity, selectivity and repeatability of passive developmental sensing.

3. Proposed ScanIQ architecture

SCAN / MODEL	SDF + VOXEL FIELDS	CHIRAL / MOBIUS OPTIMIZATION	FIELD-NATIVE TOOLPATH	PASSIVE SENSING	AI DIGITAL PHENOTYPE

geometry + material --> predicted EM response --> manufactured structure --> measured response --> learning loop

4. Why continuous SDF and voxel mathematics matter here

Submillimeter organization without redesigning the entire CAD model

A field representation can describe fine geometric features and material transitions mathematically, allowing the same design logic to scale from millimeter fibers toward smaller resonant features as the fabrication process permits.

Geometry and material become one computational object

Instead of storing only the boundary of a part, ScanIQ can associate each spatial location with material fraction, orientation, conductivity, dielectric behavior, porosity or another state variable.

Chirality becomes programmable

Right-handed and left-handed domains, twists, helices and Möbius-like transitions can be generated as parameterized field operations and optimized against electromagnetic simulations or measured spectra.

Manufacturing feedback becomes part of the model

Microscope or camera measurements of printed features can be converted back into the digital field, letting AI learn the difference between intended geometry and as-built geometry.

The same kernel can serve both THz materials and biological fixtures

The manufacturing mathematics does not need to know whether it is designing a photonic metamaterial, a resonator carrier or a biological scaffold; the physics objectives and constraints change, while the field-native representation remains common.

5. The silk / chiral / terahertz branch

Silk is useful here because it is not simply a structural fiber. Silk fibroin has optical, dielectric, mechanical and biointerface properties that make it interesting for photonic and sensing devices. Prior work has already combined silk fibroin films with terahertz metamaterial resonators and observed resonance shifts as the material environment changed. Separately, chiral textile and metasurface structures have demonstrated strong polarization-dependent THz behavior.

ScanIQ contribution: use field-native design to organize silk-based or silk-composite material into controlled chiral domains, then learn a geometry-to-spectrum relationship. Instead of "print a shape and test it," the loop becomes "predict -> print -> measure -> reconstruct -> learn -> redesign."

6. The embryonic spectral-intelligence branch

Electrical impedance spectroscopy has already been used to detect measurable changes in mammalian embryo and oocyte properties. A 2024 bovine-embryo study reported a change in differential real impedance near 1.49 MHz that correlated with increasing embryo cell mass. In 2026, frequency-resolved microfluidic impedance phenotyping of porcine oocytes measured responses up to 30 MHz and distinguished fresh from severely freeze-thaw-injured oocytes.

That suggests a realistic research target: build a multimodal developmental fingerprint that combines imaging with electrical and resonant measurements. The AI would learn normal trajectories, stage transitions and deviations associated with developmental arrest or reduced competence, without assuming in advance that one frequency controls growth.

Signal channel	What the AI may learn from it
Resonant frequency shift	Changes in effective dielectric loading or geometry around the sensing region.
Q factor / bandwidth	Changes in loss, damping or coupling - useful only when interpreted with environmental controls.
Complex impedance / phase	Membrane, cytoplasmic and conductive changes across frequency.
Time-lapse morphology	Cleavage timing, cell count, compaction, blastocyst expansion and visible anomalies.
Environmental telemetry	Temperature, pH, medium condition and instrument drift so the model does not confuse the incubator with the embryo.
Temporal derivatives	Whether a variable is merely different or is changing at an abnormal rate.

7. The AI target: a developmental digital phenotype

The machine-learning target should be a trajectory through a multidimensional state space, not a single scalar score. At each time point, the model can combine morphology, impedance, resonance, phase, Q factor, environmental variables and process history. Over many labeled observations, ScanIQ can learn which trajectories cluster with normal development and which begin to diverge before a visible anomaly appears.

Best research framing: "detect the changing electromechanical fingerprint of development" rather than "find the frequency that makes an embryo grow."

8. Meiosis and mitosis as a separate spectral atlas

A useful sub-program would map how electrical and resonant signatures change across cell-cycle state. Meiosis should be studied primarily in gametes/oocyte maturation; post-fertilization embryonic cleavage is mitotic. Keeping those datasets separate will help the AI distinguish universal cell-division signatures from embryo-stage-specific signals.

9. A staged research path

Stage 1 - Materials calibration

Print or fabricate known resonator geometries and silk/silk-composite domains. Measure dimensional accuracy, dielectric response and spectral repeatability.

Stage 2 - Geometry-to-spectrum learning

Use ScanIQ to vary chirality, topology, thickness, orientation and local material distribution, then train surrogate models that predict THz or RF response from the field representation.

Stage 3 - Passive biological sensing

Evaluate whether the resonator platform can detect repeatable changes in non-human model systems without intentionally stimulating development.

Stage 4 - Multimodal AI

Fuse spectroscopy, resonance, imaging and environmental telemetry into developmental-state and anomaly models.

Stage 5 - Outcome validation

Test whether early spectral deviations are statistically associated with later developmental outcomes under proper reproductive-research oversight.

Future branch - Controlled perturbation

Only after passive sensing and exposure safety are characterized should any intentional EM or acoustic stimulation be studied as a separate hypothesis.

10. What is established vs. what ScanIQ would be testing

Already demonstrated in published research	ScanIQ research hypothesis / integration
SDF/implicit methods can represent geometry and continuously varying material distributions for additive manufacturing.	Use one field-native kernel to co-design resonator geometry, material chirality and manufacturing paths.
Silk fibroin has useful dielectric/photonic properties and has been integrated with THz metamaterial sensors.	Organize silk or silk-composite domains into AI-optimized chiral / Möbius-inspired resonant structures.
Chiral THz structures can produce polarization-selective response; Möbius resonators can support unusual fractional/topological modes.	Test whether those modes improve sensitivity to small local dielectric changes in a biological sensing geometry.
Embryo and oocyte impedance measurements can vary with developmental or physiological state.	Combine impedance, resonator shifts, imaging and environmental telemetry into a developmental digital phenotype.
AI can learn from multimodal time-series data.	Close the loop so measured biology and as-built resonator performance directly drive the next geometry/material iteration.

11. Why this could matter to ScanIQ

This project is a good demonstration of the broader ScanIQ thesis: the same computational engine can move from scanned reality to continuous geometry, physics, manufacturing, sensing and back again. In this case the "part" is not only a mechanical component. It is a spatially programmed material system whose electromagnetic behavior becomes part of the design objective.

- Field-native geometry and material organization become a common language across manufacturing and sensing.
- Terahertz/chiral materials provide a high-value test bed for microstructured geometry-to-function optimization.
- Embryonic sensing provides a demanding multimodal application where subtle physical changes must be separated from environmental noise.
- The feedback loop creates defensible engineering data: intended field -> manufactured structure -> measured spectrum -> learned correction.
- The concept can remain modular: the resonator/material platform can be developed independently of reproductive applications, reducing technical and regulatory coupling.

12. Responsible-development boundary

The immediate research case is sensing and characterization. This document does not assume that electromagnetic or acoustic exposure improves embryo viability or growth rate. Any work involving embryos, oocytes or reproductive outcomes should use appropriate institutional, veterinary and/or reproductive-research oversight, with exposure characterization and controls. Claims of growth enhancement should only follow reproducible evidence.

13. Potential invention / IP themes

- Field-native co-design of geometry and spatial material distribution for chiral or topological resonators.
- AI optimization that links SDF/voxel design variables directly to measured RF/THz response and as-built metrology.
- Opposed or distributed resonator architectures for passive dielectric/impedance monitoring of biological development.
- Multimodal developmental digital phenotyping from resonance, impedance, imaging and environmental time-series data.
- Closed-loop manufacturing in which sensed device performance and biological measurement quality feed back into geometry, material and toolpath optimization.

Selected research references

1. Uzzaman, M.A., Rahman, M.A., Ohta, A. "Bovine Embryo Development Monitoring Using Differential Electrical Impedance Spectroscopy." IEEE EMBC (2024). DOI: 10.1109/EMBC53108.2024.10782213.
2. "Cell-by-cell dielectric and mechanical phenotyping of oocytes." Sensing and Bio-Sensing Research 53 (2026), 101079. DOI: 10.1016/j.sbsr.2026.101079.
3. Wade, C. et al. "OpenVCAD: An open source volumetric multi-material geometry compiler." Additive Manufacturing 79 (2024), 103912. DOI: 10.1016/j.addma.2023.103912.
4. Wade, C., Beck, D., MacCurdy, R. "Implicit toolpath generation for functionally graded additive manufacturing via gradient-informed slicing." Additive Manufacturing 112 (2025), 104963. DOI: 10.1016/j.addma.2025.104963.
5. Panda, B., Ahuja, R., Singh, K.P. "Advances in understanding silk materials and its nano-photonic applications." Nano Energy 134 (2025), 110540. DOI: 10.1016/j.nanoen.2024.110540.
6. Kim, H.S. et al. "Humidity sensing using THz metamaterial with silk protein fibroin." Optics Express 26 (2018), 33575-33581. DOI: 10.1364/OE.26.033575.
7. Wang, P. et al. "Terahertz Chiral Metamaterials Enabled by Textile Manufacturing." Advanced Materials 34 (2022), 2110590. DOI: 10.1002/adma.202110590.
8. Hamilton, J.K., Hooper, I.R., Lawrence, C.R. "Absorption modes of Mobius strip resonators." Scientific Reports 11 (2021), 9045. DOI: 10.1038/s41598-021-88280-x.
9. Chen, Y. et al. "Topological resonances in a Mobius ring resonator." Communications Physics 6 (2023), 84. DOI: 10.1038/s42005-023-01205-0.
10. Wang, B. et al. "Sustainable Materials Enabled Terahertz Functional Devices." Nano-Micro Letters 17 (2025), 212. DOI: 10.1007/s40820-025-01732-1.

ScanIQ concept summary - prepared for internal research, collaborator discussion, and early technical framing.