NPTEL MOOC, JAN-FEB 2015 Week 2, Module 5

DESIGNAND ANALYSIS OF ALGORITHMS

Merge Sort

MADHAVAN MUKUND, CHENNAI MATHEMATICAL INSTITUTE http://www.cmi.ac.in/~madhavan

O(n²) sorting algorithms


- * Selection sort and insertion sort are both O(n²)
- * O(n²) sorting is infeasible for n over 100000

A different strategy?

- * Divide array in two equal parts
- * Separately sort left and right half
- * Combine the two sorted halves to get the full array sorted

Combining sorted lists

- * Given two sorted lists A and B, combine into a sorted list C
 - * Compare first element of A and B
 - * Move it into C
 - * Repeat until all elements in A and B are over
- * Merging A and B



- * Sort A[0] to A[n/2-1]
- * Sort A[n/2] to A[n-1]
- * Merge sorted halves into B[0..n-1]
- * How do we sort the halves?
 - * Recursively, using the same strategy!

43 32 22 78 63 57 91 13

43 32 22 78

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

32 43 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

32 43 22 78 63 57 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

32 43 22 78 57 63 91 13

43 32 22 78 63 57 91 13

43 32 22 78 63 57 91 13

32 43 22 78 57 63 13 91

 43
 32
 22
 78
 63
 57
 91
 13

43 32 22 78 63 57 91 13

22 32 43 78 63 57 91 13

32 43 22 78 57 63 13 91

43 32 22 78 63 57 91 13

22 32 43 78 13 57 63 91

32 43 22 78 57 63 13 91

13 22 32 43 57 63 78 91

22 32 43 78 13 57 63 91

32 43 22 78 57 63 13 91

43 | 32 | 22 | 78 | 63 | 57 | 91 | 13

Divide and conquer

- * Break up problem into disjoint parts
- * Solve each part separately
- * Combine the solutions efficiently

Combine two sorted lists A and B into C

- * If A is empty, copy B into C
- * If B is empty, copy A into C
- * Otherwise, compare first element of A and B and move the smaller of the two into C
- * Repeat until all elements in A and B have been moved

Merging

```
function Merge(A, m, B, n, C)
  // Merge A[0..m-1], B[0..n-1] into C[0..m+n-1]
  i = 0; j = 0; k = 0;
  // Current positions in A,B,C respectively
  while (k < m+n)
  // Case 0: One of the two lists is empty
     if (i==m) \{j++; k++;\}
     if (j==n) {i++; k++;}
  // Case 1: Move head of A into C
     if (A[i] \le B[j]) \{ C[k] = B[j]; j++; k++; \}
  // Case 2: Move head of B into C
     if (A[i] > B[j]) \{C[k] = B[j]; j++; k++;\}
```

To sort A[0..n-1] into B[0..n-1]

- * If n is 1, nothing to be done
- * Otherwise
 - * Sort A[0..n/2-1] into L (left)
 - * Sort A[n/2..n-1] into R (right)
 - * Merge L and R into B

```
function MergeSort(A, left, right, B)
  // Sort the segment A[left..right-1] into B
  if (right - left == 1) // Base case
     B[0] = A[left]
  if (right - left > 1) // Recursive call
     mid = (left+right)/2
     MergeSort(A, left, mid, L)
     MergeSort(A, mid, right, R)
     Merge(L, mid-left, R, right-mid, B)
```