



Java Lambda Expressions

[< Previous](#)[Next >](#)

Java Lambda Expressions

Lambda Expressions were added in Java 8.

A lambda expression is a short block of code which takes in parameters and returns a value. Lambda expressions are similar to methods, but they do not need a name and they can be implemented right in the body of a method.

Syntax

The simplest lambda expression contains a single parameter and an expression:

```
parameter -> expression
```

To use more than one parameter, wrap them in parentheses:

```
(parameter1, parameter2) -> expression
```

Expressions are limited. They have to immediately return a value, and they cannot contain variables, assignments or statements such as `if` or `for`. In order to do more complex operations, a code block can be used with curly braces. If the lambda expression needs to return a value, then the code block should have a `return` statement.

```
(parameter1, parameter2) -> { code block }
```

ADVERTISEMENT

Using Lambda Expressions

Lambda expressions are usually passed as parameters to a function:

Example

Use a lambda expression in the `ArrayList`'s `forEach()` method to print every item in the list:

```
import java.util.ArrayList;
```

```
public class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> numbers = new ArrayList<Integer>();  
        numbers.add(5);  
        numbers.add(9);  
        numbers.add(8);  
        numbers.add(1);  
        numbers.forEach( (n) -> { System.out.println(n); } );  
    }  
}
```

Try it Yourself »

Lambda expressions can be stored in variables if the variable's type is an interface which has only one method. The lambda expression should have the same number of parameters and the same return type as that method. Java has many of these kinds of interfaces built in, such as the `Consumer` interface (found in the `java.util` package) used by lists.

Example

Use Java's `Consumer` interface to store a lambda expression in a variable:

```
import java.util.ArrayList;  
import java.util.function.Consumer;  
  
public class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> numbers = new ArrayList<Integer>();  
        numbers.add(5);  
        numbers.add(9);  
        numbers.add(8);  
        numbers.add(1);  
        Consumer<Integer> method = (n) -> { System.out.println(n); };  
        numbers.forEach( method );  
    }  
}
```

Try it Yourself »

To use a lambda expression in a method, the method should have a parameter with a single-method interface as its type. Calling the interface's method will run the lambda expression:

Example

Create a method which takes a lambda expression as a parameter:

```
interface StringFunction {
    String run(String str);
}

public class Main {
    public static void main(String[] args) {
        StringFunction exclaim = (s) -> s + "!";
        StringFunction ask = (s) -> s + "?";
        printFormatted("Hello", exclaim);
        printFormatted("Hello", ask);
    }
    public static void printFormatted(String str, StringFunction format) {
        String result = format.run(str);
        System.out.println(result);
    }
}
```


Try it Yourself »

[< Previous](#)[Next >](#)

ADVERTISEMENT

NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



Get certified
by completing
a Java
course today!



Get started

CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT



[Report Error](#)

[Spaces](#)

[Pro](#)

[Buy Certificate](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)

[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant

full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

