



# Java Modifiers

[< Previous](#)[Next >](#)

## Modifiers

By now, you are quite familiar with the `public` keyword that appears in almost all of our examples:

```
public class Main
```

The `public` keyword is an **access modifier**, meaning that it is used to set the access level for classes, attributes, methods and constructors.

We divide modifiers into two groups:

- **Access Modifiers** - controls the access level
- **Non-Access Modifiers** - do not control access level, but provides other functionality

## Access Modifiers

For **classes**, you can use either `public` or *default*:

Modifier	Description	Try it
<b>public</b>	The class is accessible by any other class	<a href="#">Try it »</a>
<b>default</b>	The class is only accessible by classes in the same package. This is used when you don't specify a modifier. You will learn more about packages in the <a href="#">Packages chapter</a>	<a href="#">Try it »</a>

For **attributes, methods and constructors**, you can use the one of the following:

Modifier	Description	Try it
<b>public</b>	The code is accessible for all classes	<a href="#">Try it »</a>
<b>private</b>	The code is only accessible within the declared class	<a href="#">Try it »</a>
<b>default</b>	The code is only accessible in the same package. This is used when you don't specify a modifier. You will learn more about packages in the <a href="#">Packages chapter</a>	<a href="#">Try it »</a>
<b>protected</b>	The code is accessible in the same package and <b>subclasses</b> . You will learn more about subclasses and superclasses in the <a href="#">Inheritance chapter</a>	<a href="#">Try it »</a>

## Non-Access Modifiers

For **classes**, you can use either **final** or **abstract** :

Modifier	Description	Try it
<b>final</b>	The class cannot be inherited by other classes (You will learn more about inheritance in the <a href="#">Inheritance chapter</a> )	<a href="#">Try it »</a>
<b>abstract</b>	The class cannot be used to create objects (To access an abstract class, it must be inherited from another class. You will learn more about inheritance and abstraction in the <a href="#">Inheritance</a> and <a href="#">Abstraction</a> chapters)	<a href="#">Try it »</a>

For **attributes and methods**, you can use the one of the following:

Modifier	Description
<b>final</b>	Attributes and methods cannot be overridden/modified
<b>static</b>	Attributes and methods belongs to the class, rather than an object
<b>abstract</b>	Can only be used in an abstract class, and can only be used on methods. The method does not have a body, for example <b>abstract void run();</b> . The body is provided by the subclass (inherited from). You will learn more about inheritance and abstraction in the <a href="#">Inheritance</a> and <a href="#">Abstraction</a> chapters
<b>transient</b>	Attributes and methods are skipped when serializing the object containing them
<b>synchronized</b>	Methods can only be accessed by one thread at a time
<b>volatile</b>	The value of an attribute is not cached thread-locally, and is always read from the "main memory"

ADVERTISEMENT



## Final

If you don't want the ability to override existing attribute values, declare attributes as **final** :

## Example

```
public class Main {  
  
    public static void main(String[] args) {  
        Main myObj = new Main();  
        myObj.x = 50; // will generate an error: cannot assign a value to a final variable  
        myObj.PI = 25; // will generate an error: cannot assign a value to a final variable  
        System.out.println(myObj.x);  
    }  
}
```

Try it Yourself »

## Static

A **static** method means that it can be accessed without creating an object of the class, unlike **public** :

## Example

An example to demonstrate the differences between **static** and **public** methods:

```
public class Main {  
    // Static method  
  
    System.out.println("Static methods can be called without creating objects");  
}  
  
// Public method  
  
System.out.println("Public methods must be called by creating objects");  
}
```

```
// Main method
public static void main(String[ ] args) {
    myStaticMethod(); // Call the static method
    // myPublicMethod(); This would output an error

    Main myObj = new Main(); // Create an object of Main
    myObj.myPublicMethod(); // Call the public method
}
}
```

Try it Yourself »

## Abstract

An **abstract** method belongs to an **abstract** class, and it does not have a body. The body is provided by the subclass:

## Example

```
// Code from filename: Main.java
// abstract class

public String fname = "John";
public int age = 24;

}

// Subclass (inherit from Main)
class Student extends Main {
    public int graduationYear = 2018;

    System.out.println("Studying all day long");
}
}

// End code from filename: Main.java
```

```
// Code from filename: Second.java
class Second {
    public static void main(String[] args) {
        // create an object of the Student class (which inherits attributes and meth
        Student myObj = new Student();

        System.out.println("Name: " + myObj.fname);
        System.out.println("Age: " + myObj.age);
        System.out.println("Graduation Year: " + myObj.graduationYear);
        myObj.study(); // call abstract method
    }
}
```

Try it Yourself »


◀ Previous

Next ▶

## ADVERTISEMENT


**NEW**

We just launched  
W3Schools videos



Explore now

## COLOR PICKER



Get certified  
by completing  
a Java  
course today!



Get started

## CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT



ADVERTISEMENT



---

[Report Error](#)

[Spaces](#)

[Pro](#)

[Buy Certificate](#)

---

## Top Tutorials

[HTML Tutorial](#)  
[CSS Tutorial](#)  
[JavaScript Tutorial](#)  
[How To Tutorial](#)  
[SQL Tutorial](#)  
[Python Tutorial](#)  
[W3.CSS Tutorial](#)  
[Bootstrap Tutorial](#)

[PHP Tutorial](#)  
[Java Tutorial](#)  
[C++ Tutorial](#)  
[jQuery Tutorial](#)

## Top References

[HTML Reference](#)  
[CSS Reference](#)  
[JavaScript Reference](#)  
[SQL Reference](#)  
[Python Reference](#)  
[W3.CSS Reference](#)  
[Bootstrap Reference](#)  
[PHP Reference](#)  
[HTML Colors](#)  
[Java Reference](#)  
[Angular Reference](#)  
[jQuery Reference](#)

## Top Examples

[HTML Examples](#)  
[CSS Examples](#)  
[JavaScript Examples](#)  
[How To Examples](#)  
[SQL Examples](#)  
[Python Examples](#)  
[W3.CSS Examples](#)  
[Bootstrap Examples](#)  
[PHP Examples](#)  
[Java Examples](#)  
[XML Examples](#)  
[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)  
[CSS Certificate](#)  
[JavaScript Certificate](#)  
[Front End Certificate](#)  
[SQL Certificate](#)  
[Python Certificate](#)  
[PHP Certificate](#)  
[jQuery Certificate](#)  
[Java Certificate](#)  
[C++ Certificate](#)  
[C# Certificate](#)  
[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant

full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

