



Menu ▼

Log in



HTML

CSS



C Pointers

[< Previous](#)[Next >](#)

Creating Pointers

You learned from the previous chapter, that we can get the **memory address** of a variable with the reference operator **&** :

Example

```
int myAge = 43; // an int variable

printf("%d", myAge); // Outputs the value of myAge (43)
printf("%p", &myAge); // Outputs the memory address of myAge (0x7ffe5367e044)
```

[Try it Yourself »](#)

In the example above, **&myAge** is also known as a **pointer**.

A **pointer** is a variable that stores the memory address of another variable as its value.

A **pointer variable points to a data type** (like **int**) of the same type, and is created with the ***** operator. The address of the variable you are working with is assigned to the pointer:

Example

```
int myAge = 43;    // An int variable
int* ptr = &myAge; // A pointer variable, with the name ptr, that stores the
                  // address of myAge

// Output the value of myAge (43)
printf("%d\n", myAge);

// Output the memory address of myAge (0x7ffe5367e044)
printf("%p\n", &myAge);

// Output the memory address of myAge with the pointer (0x7ffe5367e044)
printf("%p\n", ptr);
```

Try it Yourself »

Example explained

Create a pointer variable with the name `ptr`, that **points to** an `int` variable (`myAge`). Note that the type of the pointer has to match the type of the variable you're working with.

Use the `&` operator to store the memory address of the `myAge` variable, and assign it to the pointer.

Now, `ptr` holds the value of `myAge`'s memory address.

Dereference

In the example above, we used the pointer variable to get the memory address of a variable (used together with the `&` **reference** operator).

However, you can also get the value of the variable the pointer points to, by using the `*` operator (the **dereference** operator):

Example

```
int myAge = 43;      // Variable declaration
int* ptr = &myAge;   // Pointer declaration

// Reference: Output the memory address of myAge with the pointer
// (0x7ffe5367e044)
printf("%p\n", ptr);

// Dereference: Output the value of myAge with the pointer (43)
printf("%d\n", *ptr);
```

Try it Yourself »

Note that the `*` sign can be confusing here, as it does two different things in our code:

- When used in declaration (`int* ptr`), it creates a **pointer variable**.
- When not used in declaration, it act as a **dereference operator**.

Why Should I Learn About Pointers?

Pointers are one of the things that make C stand out from other programming languages, like Python and Java.

This chapter was just a short introduction to Pointers. They are important in C, because they give you the ability to manipulate the data in the computer's memory - this can reduce the code and improve the performance. **However**, pointers must be handled with care, since it is possible to damage data stored in other memory addresses.

Good To Know: There are three ways to declare pointer variables, but the first way is mostly used:

```
int* myNum; // Most used
int *myNum;
int * myNum;
```

C Exercises

Test Yourself With Exercises

Exercise:

Create a pointer variable called **ptr**, that points to the **int** variable myAge:

```
int myAge = 43;  
    = &myAge;
```

[Submit Answer »](#)

[Start the Exercise](#)


[◀ Previous](#)

[Next ▶](#)

ADVERTISEMENT

NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



Get certified
by completing
a course today!



Get started

CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT

[Report Error](#)

[Spaces](#)

[Pro](#)

[Get Certified](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)

XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

