



Java ArrayList

[< Previous](#)[Next >](#)

Java ArrayList

The `ArrayList` class is a resizable array, which can be found in the `java.util` package.

The difference between a built-in array and an `ArrayList` in Java, is that the size of an array cannot be modified (if you want to add or remove elements to/from an array, you have to create a new one). While elements can be added and removed from an `ArrayList` whenever you want. The syntax is also slightly different:

Example

Create an `ArrayList` object called **`cars`** that will store strings:

```
import java.util.ArrayList; // import the ArrayList class

ArrayList<String> cars = new ArrayList<String>(); // Create an ArrayList object
```

If you don't know what a package is, read our [Java Packages Tutorial](#).

Add Items

The `ArrayList` class has many useful methods. For example, to add elements to the `ArrayList`, use the `add()` method:

Example

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> cars = new ArrayList<String>();
        cars.add("Volvo");
        cars.add("BMW");
        cars.add("Ford");
        cars.add("Mazda");
        System.out.println(cars);
    }
}
```

Try it Yourself »

Access an Item

To access an element in the `ArrayList`, use the `get()` method and refer to the index number:

Example

```
cars.get(0);
```

[Try it Yourself »](#)

Remember: Array indexes start with 0: [0] is the first element. [1] is the second element, etc.

ADVERTISEMENT

Change an Item

To modify an element, use the `set()` method and refer to the index number:

Example

```
cars.set(0, "Opel");
```

[Try it Yourself »](#)

Remove an Item

To remove an element, use the `remove()` method and refer to the index number:

Example

```
cars.remove(0);
```

Try it Yourself »

To remove all the elements in the `ArrayList`, use the `clear()` method:

Example

```
cars.clear();
```

Try it Yourself »

ArrayList Size

To find out how many elements an `ArrayList` have, use the `size` method:

Example

```
cars.size();
```

Try it Yourself »

Loop Through an ArrayList

Loop through the elements of an `ArrayList` with a `for` loop, and use the `size()` method to specify how many times the loop should run:

Example

```
public class Main {  
    public static void main(String[] args) {  
        ArrayList<String> cars = new ArrayList<String>();  
        cars.add("Volvo");  
        cars.add("BMW");  
        cars.add("Ford");  
        cars.add("Mazda");  
        for (int i = 0; i < cars.size(); i++) {  
            System.out.println(cars.get(i));  
        }  
    }  
}
```

Try it Yourself »

You can also loop through an `ArrayList` with the **for-each** loop:

Example

```
public class Main {  
    public static void main(String[] args) {  
        ArrayList<String> cars = new ArrayList<String>();  
        cars.add("Volvo");  
        cars.add("BMW");  
        cars.add("Ford");  
        cars.add("Mazda");  
        for (String i : cars) {  
            System.out.println(i);  
        }  
    }  
}
```

```
}  
}
```

Try it Yourself »

Other Types

Elements in an ArrayList are actually objects. In the examples above, we created elements (objects) of type "String". Remember that a String in Java is an object (not a primitive type). To use other types, such as int, you must specify an equivalent wrapper class: **Integer**. For other primitive types, use: **Boolean** for boolean, **Character** for char, **Double** for double, etc:

Example

Create an **ArrayList** to store numbers (add elements of type **Integer**):

```
import java.util.ArrayList;  
  
public class Main {  
    public static void main(String[] args) {  
        ArrayList<Integer> myNumbers = new ArrayList<Integer>();  
        myNumbers.add(10);  
        myNumbers.add(15);  
        myNumbers.add(20);  
        myNumbers.add(25);  
        for (int i : myNumbers) {  
            System.out.println(i);  
        }  
    }  
}
```

Try it Yourself »

Sort an ArrayList

Another useful class in the `java.util` package is the `Collections` class, which include the `sort()` method for sorting lists alphabetically or numerically:

Example

Sort an ArrayList of Strings:

```
import java.util.ArrayList;
import java.util.Collections; // Import the Collections class

public class Main {
    public static void main(String[] args) {
        ArrayList<String> cars = new ArrayList<String>();
        cars.add("Volvo");
        cars.add("BMW");
        cars.add("Ford");
        cars.add("Mazda");
        Collections.sort(cars); // Sort cars
        for (String i : cars) {
            System.out.println(i);
        }
    }
}
```

Try it Yourself »

Example

Sort an ArrayList of Integers:

```
import java.util.ArrayList;
import java.util.Collections; // Import the Collections class

public class Main {
    public static void main(String[] args) {
```

```
ArrayList<Integer> myNumbers = new ArrayList<Integer>();  
myNumbers.add(33);  
myNumbers.add(15);  
myNumbers.add(20);  
myNumbers.add(34);  
myNumbers.add(8);  
myNumbers.add(12);  
  
Collections.sort(myNumbers); // Sort myNumbers  
  
for (int i : myNumbers) {  
    System.out.println(i);  
}  
}  
}
```

Try it Yourself »


◀ Previous

Next ▶

ADVERTISEMENT

NEW

We just launched
W3Schools videos



[Explore now](#)

COLOR PICKER



Get certified
by completing
a Java
course today!



[Get started](#)

CODE GAME



Play Game

ADVERTISEMENT

ADVERTISEMENT

ADVERTISEMENT



Report Error

Spaces

Pro

Buy Certificate

Top Tutorials

[HTML Tutorial](#)

[CSS Tutorial](#)

[JavaScript Tutorial](#)

- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial
- C++ Tutorial
- jQuery Tutorial

Top References

- HTML Reference
- CSS Reference
- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- Java Reference
- Angular Reference
- jQuery Reference

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- Java Examples
- XML Examples
- jQuery Examples

Get Certified

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- Front End Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- jQuery Certificate
- Java Certificate
- C++ Certificate
- C# Certificate
- XML Certificate

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

