



Java If ... Else

[< Previous](#)[Next >](#)

Java Conditions and If Statements

Java supports the usual logical conditions from mathematics:

- Less than: `a < b`
- Less than or equal to: `a <= b`
- Greater than: `a > b`
- Greater than or equal to: `a >= b`
- Equal to: `a == b`
- Not Equal to: `a != b`

You can use these conditions to perform different actions for different decisions.

Java has the following conditional statements:

- Use `if` to specify a block of code to be executed, if a specified condition is true
- Use `else` to specify a block of code to be executed, if the same condition is false
- Use `else if` to specify a new condition to test, if the first condition is false
- Use `switch` to specify many alternative blocks of code to be executed

The if Statement

Use the **if** statement to specify a block of Java code to be executed if a condition is **true**.

Syntax

```
if (condition) {  
    // block of code to be executed if the condition is true  
}
```

Note that **if** is in lowercase letters. Uppercase letters (If or IF) will generate an error.

In the example below, we test two values to find out if 20 is greater than 18. If the condition is **true**, print some text:

Example

```
if (20 > 18) {  
    System.out.println("20 is greater than 18");  
}
```

Try it Yourself »

We can also test variables:

Example

```
int x = 20;  
int y = 18;  
if (x > y) {  
    System.out.println("x is greater than y");  
}
```

Try it Yourself »

Example explained

In the example above we use two variables, **x** and **y**, to test whether x is greater than y (using the **>** operator). As x is 20, and y is 18, and we know that 20 is greater than 18, we print to the screen that "x is greater than y".

ADVERTISEMENT

The else Statement

Use the **else** statement to specify a block of code to be executed if the condition is **false**.

Syntax

```
if (condition) {  
    // block of code to be executed if the condition is true  
} else {  
    // block of code to be executed if the condition is false  
}
```

Example

```
int time = 20;
if (time < 18) {
    System.out.println("Good day.");

    System.out.println("Good evening.");
}
// Outputs "Good evening."
```

Try it Yourself »

Example explained

In the example above, time (20) is greater than 18, so the condition is **false**. Because of this, we move on to the **else** condition and print to the screen "Good evening". If the time was less than 18, the program would print "Good day".

The else if Statement

Use the **else if** statement to specify a new condition if the first condition is **false**.

Syntax

```
if (condition1) {
    // block of code to be executed if condition1 is true
} else if (condition2) {
    // block of code to be executed if the condition1 is false and condition2 is t
} else {
    // block of code to be executed if the condition1 is false and condition2 is f
}
```

Example

```
int time = 22;
if (time < 10) {
    System.out.println("Good morning.");

    System.out.println("Good day.");
} else {
    System.out.println("Good evening.");
}
// Outputs "Good evening."
```

Try it Yourself »

Example explained

In the example above, time (22) is greater than 10, so the **first condition** is **false**. The next condition, in the **else if** statement, is also **false**, so we move on to the **else** condition since **condition1** and **condition2** is both **false** - and print to the screen "Good evening".

However, if the time was 14, our program would print "Good day."

Test Yourself With Exercises

Exercise:

Print "Hello World" if **x** is greater than **y**.

```
int x = 50;
int y = 10;
(x > y) {
```

```
System.out.println("Hello World");  
}
```

[Submit Answer »](#)

[Start the Exercise](#)

[◀ Previous](#)


[Next ▶](#)

ADVERTISEMENT



NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



Get certified
by completing
a Java
course today!




Get started

CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT



[Report Error](#)

[Spaces](#)

[Pro](#)

[Buy Certificate](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)

[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant

full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

