



Log in





HTML

CSS







Java Wrapper Classes

Previous

Next >

Java Wrapper Classes

Wrapper classes provide a way to use primitive data types (int, boolean, etc..) as objects.

The table below shows the primitive type and the equivalent wrapper class:

Primitive Data Type	Wrapper Class
byte	Byte
short	Short
int	Integer
long	Long
float	Float
double	Double
boolean	Boolean
char	Character

Sometimes you must use wrapper classes, for example when working with Collection objects, such as ArrayList, where primitive types cannot be used (the list can only store objects):

Example

```
ArrayList<int> myNumbers = new ArrayList<int>(); // Invalid

ArrayList<Integer> myNumbers = new ArrayList<Integer>(); // Valid

Try it Yourself »
```

Creating Wrapper Objects

To create a wrapper object, use the wrapper class instead of the primitive type. To get the value, you can just print the object:

Example

```
public class Main {
  public static void main(String[] args) {
    Integer myInt = 5;
    Double myDouble = 5.99;
    Character myChar = 'A';
    System.out.println(myInt);
    System.out.println(myDouble);
    System.out.println(myChar);
  }
}
```

Try it Yourself »

ADVERTISEMENT

Since you're now working with objects, you can use certain methods to get information about the specific object.

For example, the following methods are used to get the value associated with the corresponding wrapper object: intValue(), byteValue(), shortValue(), longValue(), floatValue(), doubleValue(), charValue(), booleanValue().

This example will output the same result as the example above:

Example

```
public class Main {
  public static void main(String[] args) {
    Integer myInt = 5;
    Double myDouble = 5.99;
    Character myChar = 'A';
    System.out.println(myInt.intValue());
    System.out.println(myDouble.doubleValue());
    System.out.println(myChar.charValue());
}
```

Try it Yourself »

Another useful method is the toString() method, which is used to convert wrapper objects to strings.

In the following example, we convert an Integer to a String, and use the length()
method of the String class to output the length of the "string":

Example

```
public class Main {
  public static void main(String[] args) {
    Integer myInt = 100;
    String myString = myInt.toString();
    System.out.println(myString.length());
  }
}
```

Try it Yourself »

< Previous</pre>

Next >

ADVERTISEMENT

NEW

We just launched W3Schools videos



Explore now

COLOR PICKER





Get certified by completing a Java course today!



Get started

CODE GAME



Play Game

ADVERTISEMENT

ADVERTISEMENT

ADVERTISEMENT

Report Error

Spaces

Pro

Buy Certificate

Top Tutorials

HTML Tutorial CSS Tutorial JavaScript Tutorial How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
Angular Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.

