



# Java Numbers

[< Previous](#)[Next >](#)

## Numbers

Primitive number types are divided into two groups:

**Integer types** stores whole numbers, positive or negative (such as 123 or -456), without decimals. Valid types are `byte`, `short`, `int` and `long`. Which type you should use, depends on the numeric value.

**Floating point types** represents numbers with a fractional part, containing one or more decimals. There are two types: `float` and `double`.

Even though there are many numeric types in Java, the most used for numbers are `int` (for whole numbers) and `double` (for floating point numbers). However, we will describe them all as you continue to read.

## Integer Types

### Byte

The **byte** data type can store whole numbers from -128 to 127. This can be used instead of **int** or other integer types to save memory when you are certain that the value will be within -128 and 127:

## Example

```
byte myNum = 100;  
System.out.println(myNum);
```

Try it Yourself »

## Short

The **short** data type can store whole numbers from -32768 to 32767:

## Example

```
short myNum = 5000;  
System.out.println(myNum);
```

Try it Yourself »

## Int

The **int** data type can store whole numbers from -2147483648 to 2147483647. In general, and in our tutorial, the **int** data type is the preferred data type when we create variables with a numeric value.

## Example

```
int myNum = 100000;  
System.out.println(myNum);
```

Try it Yourself »

## Long

The **long** data type can store whole numbers from -9223372036854775808 to 9223372036854775807. This is used when int is not large enough to store the value. Note that you should end the value with an "L":

## Example

```
long myNum = 15000000000L;  
System.out.println(myNum);
```

Try it Yourself »

---

## Floating Point Types

You should use a floating point type whenever you need a number with a decimal, such as 9.99 or 3.14515.

The **float** and **double** data types can store fractional numbers. Note that you should end the value with an "f" for floats and "d" for doubles:

## Float Example

```
float myNum = 5.75f;  
System.out.println(myNum);
```

Try it Yourself »

## Double Example

```
double myNum = 19.99d;  
System.out.println(myNum);
```

Try it Yourself »

Use `float` or `double` ?

The **precision** of a floating point value indicates how many digits the value can have after the decimal point. The precision of `float` is only six or seven decimal digits, while `double` variables have a precision of about 15 digits. Therefore it is safer to use `double` for most calculations.

## Scientific Numbers

A floating point number can also be a scientific number with an "e" to indicate the power of 10:

## Example

```
float f1 = 35e3f;  
double d1 = 12E4d;  
System.out.println(f1);  
System.out.println(d1);
```

Try it Yourself »

---


< Previous

Next >

## ADVERTISEMENT

NEW

We just launched  
W3Schools videos

[Explore now](#)

## COLOR PICKER



Get certified  
by completing  
a Java  
course today!



Get started

## CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT

[Report Error](#)[Spaces](#)[Pro](#)[Buy Certificate](#)

---

## Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

## Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

## Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)



[XML Examples](#)  
[jQuery Examples](#)

## Get Certified

[HTML Certificate](#)  
[CSS Certificate](#)  
[JavaScript Certificate](#)  
[Front End Certificate](#)  
[SQL Certificate](#)  
[Python Certificate](#)  
[PHP Certificate](#)  
[jQuery Certificate](#)  
[Java Certificate](#)  
[C++ Certificate](#)  
[C# Certificate](#)  
[XML Certificate](#)

---

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.  
W3Schools is Powered by W3.CSS.

