



Java Class Methods

[< Previous](#)[Next >](#)

Java Class Methods

You learned from the [Java Methods](#) chapter that methods are declared within a class, and that they are used to perform certain actions:

Example

Create a method named `myMethod()` in Main:

```
public class Main {  
  
    System.out.println("Hello World!");  
}  
}
```

`myMethod()` prints a text (the action), when it is **called**. To call a method, write the method's name followed by two parentheses **()** and a semicolon;

Example

Inside `main` , call `myMethod()` :

```
public class Main {  
    static void myMethod() {  
        System.out.println("Hello World!");  
    }  
  
    public static void main(String[] args) {  
  
    }  
}  
  
// Outputs "Hello World!"
```

Try it Yourself »

Static vs. Non-Static

You will often see Java programs that have either `static` or `public` attributes and methods.

In the example above, we created a `static` method, which means that it can be accessed without creating an object of the class, unlike `public` , which can only be accessed by objects:

Example

An example to demonstrate the differences between `static` and `public methods`:

```
public class Main {  
    // Static method  
  
    System.out.println("Static methods can be called without creating objects");  
}  
  
// Public method
```

```
    System.out.println("Public methods must be called by creating objects");
}

// Main method
public static void main(String[] args) {
    myStaticMethod(); // Call the static method
    // myPublicMethod(); This would compile an error

    Main myObj = new Main(); // Create an object of Main
    myObj.myPublicMethod(); // Call the public method on the object
}
}
```

Try it Yourself »

Note: You will learn more about these keywords (called modifiers) in the [Java Modifiers](#) chapter.

Access Methods With an Object

Example

Create a Car object named `myCar` . Call the `fullThrottle()` and `speed()` methods on the `myCar` object, and run the program:

```
// Create a Main class
public class Main {

    // Create a fullThrottle() method
    public void fullThrottle() {
        System.out.println("The car is going as fast as it can!");
    }

    // Create a speed() method and add a parameter
```

```
public void speed(int maxSpeed) {  
    System.out.println("Max speed is: " + maxSpeed);  
}  
  
// Inside main, call the methods on the myCar object  
public static void main(String[] args) {  
    Main myCar = new Main();    // Create a myCar object  
    myCar.fullThrottle();        // Call the fullThrottle() method  
    myCar.speed(200);            // Call the speed() method  
}  
}  
  
// The car is going as fast as it can!  
// Max speed is: 200
```

Try it Yourself »

Example explained

- 1) We created a custom `Main` class with the `class` keyword.
- 2) We created the `fullThrottle()` and `speed()` methods in the `Main` class.
- 3) The `fullThrottle()` method and the `speed()` method will print out some text, when they are called.
- 4) The `speed()` method accepts an `int` parameter called `maxSpeed` - we will use this in **8**).
- 5) In order to use the `Main` class and its methods, we need to create an **object** of the `Main` Class.
- 6) Then, go to the `main()` method, which you know by now is a built-in Java method that runs your program (any code inside main is executed).
- 7) By using the `new` keyword we created an object with the name `myCar` .
- 8) Then, we call the `fullThrottle()` and `speed()` methods on the `myCar` object, and run the program using the name of the object (`myCar`), followed by a dot (`.`), followed by the name of the method (`fullThrottle();` and `speed(200);`). Notice that we add an `int` parameter of **200** inside the `speed()` method.

Remember that..

The dot (`.`) is used to access the object's attributes and methods.

To call a method in Java, write the method name followed by a set of parentheses (`()`), followed by a semicolon (`;`).

A class must have a matching filename (`Main` and `Main.java`).

ADVERTISEMENT

Using Multiple Classes

Like we specified in the [Classes chapter](#), it is a good practice to create an object of a class and access it in another class.

Remember that the name of the java file should match the class name. In this example, we have created two files in the same directory:

- `Main.java`
- `Second.java`

`Main.java`

```
public class Main {  
    public void fullThrottle() {  
        System.out.println("The car is going as fast as it can!");  
    }  
  
    public void speed(int maxSpeed) {  
        System.out.println("Max speed is: " + maxSpeed);  
    }  
}
```

Second.java

```
class Second {  
    public static void main(String[] args) {  
        Main myCar = new Main();    // Create a myCar object  
        myCar.fullThrottle();        // Call the fullThrottle() method  
        myCar.speed(200);            // Call the speed() method  
    }  
}
```

When both files have been compiled:

```
C:\Users\Your Name>javac Main.java  
C:\Users\Your Name>javac Second.java
```

Run the Second.java file:

```
C:\Users\Your Name>java Second
```

And the output will be:

The car is going as fast as it can!

Max speed is: 200

Try it Yourself »


◀ Previous

Next ▶

ADVERTISEMENT

NEW

We just launched
W3Schools videos



Explore now

COLOR PICKER



Get certified
by completing
a Java
course today!



Get started

CODE GAME



Play Game

ADVERTISEMENT



ADVERTISEMENT

ADVERTISEMENT



[Report Error](#)

[Spaces](#)

[Pro](#)

[Buy Certificate](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)

[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) | [ABOUT](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant

full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2022 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

