RICH SOLAR | NOVA™ Series Inverters

NOVA SUPERCHARGER 2K / 3K
INVERTER CHARGER

NOVA SUPERCHARGER 2K

NOVA SUPERCHARGER 3K

Efficient & Full Protection

91% power conversion efficiency for longer runtimes.

Comprehensive safeguards against overload, short-circuit, overheating, and adjustable low-voltage cutoff (10.5V–12.8V), meeting UL and FCC safety standards.

Clean & Reliable Power

Pure sine wave output (<5% THD) delivers 2000–3000W of stable AC power—safe for sensitive electronics, medical devices, and inductive loads like motors.

Smart Monitoring & Instant Switching

Multi-function LCD and status LEDs provide real-time system information and error codes.

Built-in transfer switch enables seamless grid-to-battery changeover in under 20ms, ensuring uninterrupted power for critical loads.

Versatile & Durable Design

Compatible with 12V deep-cycle, $LiFePO_4$ (with BMS), and AGM batteries, with battery recovery capability and supports fast charging. Built to marine-grade standards—corrosion-resistant, vibration-proof, and ABYC-compliant, with optional drip shield.

Intertek FC CE RoHS

© 2025 RICH SOLAR ALL RIGHTS RESERVED

SPECIFICATIONS

Model	RS-V2P12C	RS-V3P12C
Product Name	**NOVA SUPERCHARGER 2K**	**NOVA SUPERCHARGER 3K**
Rated Power	2000W	3000W
Surge Power (5s)	4000W	6000W
Nominal Voltage (Input/Output)	120VAC	
Input Voltage Range	100~130VAC	
Input Frequency	50/60Hz (Selectable)	
Output Voltage Regulation	120VAC ±5% (Battery Mode)	
Output Frequency	50Hz or 60Hz (±1%)	
Peak Efficiency	91%	
Transfer Time	<20ms	
Line Mode Indicator	Solid green AC LED	
Battery Mode Indicator	Solid green BATT LED	
Warning (Output Active) Indicator	Flashing red Fault LED+audible alarm	
Fault (No Output) Indicator	Solid red Fault LED	
Humidity	5%~95% RH (Non-Condensing)	
Operating Temperature	-40°F to +160°F, with output derated above 122°F	
Certifications	UL458, FCC Part 15 Subpart B (Class B)	
Battery Nominal DC Voltage	12VDC	
Battery Operating Voltage Range	LBCO–18.0VDC	
Battery Charger Current	5~80A (Selectable)	5~150A (Selectable)
Dimensions	15.4 × 12.0 × 4.1 in	15.4 × 12.0 × 4.8 in
Weight	16.5 lb	18.5 lb

SPECIFICATIONS INCLUDED IN THIS DATASHEET ARE SUBJECT TO CHANGE WITHOUT NOTICE.