

# Supplementary File for

## “TPAM: A Simulation-Based Model for Quantitatively Analyzing Parameter Adaptation Methods”

**ACM Reference format:**

. 2016. Supplementary File for  
“TPAM: A Simulation-Based Model for Quantitatively Analyzing Parameter  
Adaptation Methods”. In *Proceedings of ACM Conference, Washington, DC,  
USA, July 2017 (Conference’17)*, 8 pages.  
DOI: 10.1145/nnnnnnn.nnnnnnn

---

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

*Conference’17, Washington, DC, USA*

© 2016 Copyright held by the owner/author(s). 978-x-xxxx-xxxx-x/YY/MM...\$15.00  
DOI: 10.1145/nnnnnnn.nnnnnnn

---

**Algorithm S.1:** Parameter Adaptation Method in jDE (PAM-jDE)

---

```

1  $t \leftarrow 1$ , initialize  $P^t = \{\mathbf{x}^{1,t}, \dots, \mathbf{x}^{N,t}\}$  randomly;
2  $F_{i,t} \leftarrow 0.5$ ,  $C_{i,t} \leftarrow 0.9$ ,  $i \in \{1, \dots, N\}$ ;
3 while The termination criteria are not met do
4   for  $i \in \{1, \dots, N\}$  do
5     if  $\text{rand}[0, 1] \leq \tau_F$  then
6        $F'_{i,t} \leftarrow \text{rand}[0.1, 1]$ ;
7     else
8        $F'_{i,t} \leftarrow F_{i,t}$ ;
9     if  $\text{rand}[0, 1] \leq \tau_C$  then
10       $C'_{i,t} \leftarrow \text{rand}[0, 1]$ ;
11    else
12       $C'_{i,t} \leftarrow C_{i,t}$ ;
13    Generate the mutant vector  $\mathbf{v}^{i,t}$  using an arbitrary mutation strategy with  $F'_{i,t}$ ;
14    Generate the trial vector  $\mathbf{u}^{i,t}$  by crossing  $\mathbf{x}^{i,t}$  and  $\mathbf{v}^{i,t}$  using an arbitrary crossover method with  $C'_{i,t}$ ;
15   for  $i \in \{1, \dots, N\}$  do
16     if  $f(\mathbf{u}^{i,t}) \leq f(\mathbf{x}^{i,t})$  then
17        $\mathbf{x}^{i,t+1} \leftarrow \mathbf{u}^{i,t}$ ,  $F_{i,t+1} \leftarrow F'_{i,t}$ ,  $C_{i,t+1} \leftarrow C'_{i,t}$ ;
18     else
19        $\mathbf{x}^{i,t+1} \leftarrow \mathbf{x}^{i,t}$ ,  $F_{i,t+1} \leftarrow F_{i,t}$ ,  $C_{i,t+1} \leftarrow C_{i,t}$ ;
20    $t \leftarrow t + 1$ ;

```

---

**Algorithm S.2:** Parameter Adaptation Method in EPSDE (PAM-EPSDE)

---

```

1  $t \leftarrow 1$ , initialize  $P^t = \{\mathbf{x}^{1,t}, \dots, \mathbf{x}^{N,t}\}$  randomly;
2  $F\text{-pool} = \{0.4, 0.5, 0.6, 0.7, 0.8, 0.9\}$ ;
3  $C\text{-pool} = \{0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9\}$ ;
4 For each individual  $\mathbf{x}^{i,t}$ , assign the  $F_{i,t}$  and  $C_{i,t}$  values randomly from each pool;
5 while The termination criteria are not met do
6   for  $i \in \{1, \dots, N\}$  do
7     Generate the mutant vector  $\mathbf{v}^{i,t}$  using an arbitrary mutation strategy with  $F'_{i,t}$ ;
8     Generate the trial vector  $\mathbf{u}^{i,t}$  by crossing  $\mathbf{x}^{i,t}$  and  $\mathbf{v}^{i,t}$  using an arbitrary crossover method with  $C'_{i,t}$ ;
9   for  $i \in \{1, \dots, N\}$  do
10    if  $f(\mathbf{u}^{i,t}) \leq f(\mathbf{x}^{i,t})$  then
11       $\mathbf{x}^{i,t+1} \leftarrow \mathbf{u}^{i,t}$ ,  $F_{i,t+1} \leftarrow F_{i,t}$ ,  $C_{i,t+1} \leftarrow C_{i,t}$ ;
12    else
13       $\mathbf{x}^{i,t+1} \leftarrow \mathbf{x}^{i,t}$ ;
14      For  $\mathbf{x}^{i,t+1}$ , reassign the  $F_{i,t+1}$  and  $C_{i,t+1}$  values randomly from each pool;
15    $t \leftarrow t + 1$ ;

```

---

**Algorithm S.3:** Parameter Adaptation Method in JADE (PAM-JADE)

---

```

1  $t \leftarrow 1$ , initialize  $P^t = \{\mathbf{x}^{1,t}, \dots, \mathbf{x}^{N,t}\}$  randomly;
2  $\mu_F \leftarrow 0.5$ ,  $\mu_C \leftarrow 0.5$ ;
3 while The termination criteria are not met do
4    $S^F \leftarrow \emptyset$ ,  $S^C \leftarrow \emptyset$ ;
5   for  $i \in \{1, \dots, N\}$  do
6      $F_{i,t} \leftarrow \text{randc}(\mu_F, 0.1)$ ;
7      $C_{i,t} \leftarrow \text{randn}(\mu_C, 0.1)$ ;
8     Generate the mutant vector  $\mathbf{v}^{i,t}$  using an arbitrary mutation strategy with  $F'_{i,t}$ ;
9     Generate the trial vector  $\mathbf{u}^{i,t}$  by crossing  $\mathbf{x}^{i,t}$  and  $\mathbf{v}^{i,t}$  using an arbitrary crossover method with  $C'_{i,t}$ ;
10    for  $i \in \{1, \dots, N\}$  do
11      if  $f(\mathbf{u}^{i,t}) \leq f(\mathbf{x}^{i,t})$  then
12         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{u}^{i,t}$ ,  $S^F \leftarrow S^F \cup \{F_{i,t}\}$ ,  $S^C \leftarrow S^C \cup \{C_{i,t}\}$ ;
13      else
14         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{x}^{i,t}$ ;
15    if  $S^F, S^C \neq \emptyset$  then
16       $\mu_F \leftarrow (1 - c) \cdot \mu_F + c \cdot \text{mean}_L(S^F)$ ;
17       $\mu_C \leftarrow (1 - c) \cdot \mu_C + c \cdot \text{mean}_A(S^C)$ ;
18    $t \leftarrow t + 1$ ;

```

---

**Algorithm S.4:** Parameter Adaptation Method in MDE (PAM-MDE)

---

```

1  $t \leftarrow 1$ , initialize  $P^t = \{\mathbf{x}^{1,t}, \dots, \mathbf{x}^{N,t}\}$  randomly;
2  $\mu_F \leftarrow 0.5$ ,  $\mu_C \leftarrow 0.5$ ;
3 while The termination criteria are not met do
4    $S^F \leftarrow \emptyset$ ,  $S^C \leftarrow \emptyset$ ;
5   for  $i \in \{1, \dots, N\}$  do
6      $F_{i,t} \leftarrow \text{randc}(\mu_F, 0.1)$ ;
7      $C_{i,t} \leftarrow \text{randn}(\mu_C, 0.1)$ ;
8     Generate the mutant vector  $\mathbf{v}^{i,t}$  using an arbitrary mutation strategy with  $F'_{i,t}$ ;
9     Generate the trial vector  $\mathbf{u}^{i,t}$  by crossing  $\mathbf{x}^{i,t}$  and  $\mathbf{v}^{i,t}$  using an arbitrary crossover method with  $C'_{i,t}$ ;
10    for  $i \in \{1, \dots, N\}$  do
11      if  $f(\mathbf{u}^{i,t}) \leq f(\mathbf{x}^{i,t})$  then
12         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{u}^{i,t}$ ,  $S^F \leftarrow S^F \cup \{F_{i,t}\}$ ,  $S^C \leftarrow S^C \cup \{C_{i,t}\}$ ;
13      else
14         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{x}^{i,t}$ ;
15    if  $S^F, S^C \neq \emptyset$  then
16       $c_F \leftarrow \text{rand}(0.0, 0.2]$ ,  $c_C \leftarrow \text{rand}(0.0, 0.1]$ ;
17       $\mu_F \leftarrow (1 - c_F) \cdot \mu_F + c_F \cdot \text{mean}_P(S^F)$ ;
18       $\mu_C \leftarrow (1 - c_C) \cdot \mu_C + c_C \cdot \text{mean}_P(S^C)$ ;
19     $t \leftarrow t + 1$ ;

```

---

**Algorithm S.5:** Parameter Adaptation Method in SHADE (PAM-SHADE)


---

```


1  $t \leftarrow 1$ , initialize  $P^t = \{\mathbf{x}^{1,t}, \dots, \mathbf{x}^{N,t}\}$  randomly;
2 Set all values in  $M^F = (M_1^F, \dots, M_H^F)$ ,  $M^C = (M_1^C, \dots, M_H^C)$  to 0.5;
3  $k \leftarrow 1$ ;
4 while The termination criteria are not met do
5    $S^F \leftarrow \emptyset$ ,  $S^C \leftarrow \emptyset$ ;
6   for  $i \in \{1, \dots, N\}$  do
7     Select the memory index  $r_{i,t}$  from  $\{1, \dots, H\}$  randomly;
8      $F_{i,t} \leftarrow \text{randc}(M_{r_{i,t}}^F, 0.1)$ ;
9      $C_{i,t} \leftarrow \text{randn}(M_{r_{i,t}}^C, 0.1)$ ;
10    Generate the mutant vector  $\mathbf{v}^{i,t}$  using an arbitrary mutation strategy with  $F'_{i,t}$ ;
11    Generate the trial vector  $\mathbf{u}^{i,t}$  by crossing  $\mathbf{x}^{i,t}$  and  $\mathbf{v}^{i,t}$  using an arbitrary crossover method with  $C'_{i,t}$ ;
12    for  $i \in \{1, \dots, N\}$  do
13      if  $f(\mathbf{u}^{i,t}) \leq f(\mathbf{x}^{i,t})$  then
14         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{u}^{i,t}$ ,  $S^F \leftarrow S^F \cup \{F_{i,t}\}$ ,  $S^C \leftarrow S^C \cup \{C_{i,t}\}$ ;
15      else
16         $\mathbf{x}^{i,t+1} \leftarrow \mathbf{x}^{i,t}$ ;
17    if  $S^F, S^C \neq \emptyset$  then
18       $M_k^F \leftarrow \text{mean}_L(S^F)$ ;
19       $M_k^C \leftarrow \text{mean}_L(S^C)$ ;
20       $k \leftarrow (k \text{ modulo } H) + 1$ ;
21     $t \leftarrow t + 1$ ;

```

---



**Figure S.1:** Behavior of the meta-parameters ( $\mu$  and  $M$ ) of PAM-JADE and PAM-SHADE on the same  $g^{\text{ran}}$  instance ( $p_a^{\max} = 0.1$ ). For PAM-SHADE, we plot all elements in  $M$ . Data of a single run with the median  $r^{\text{succ}}$  value out of the 101 runs are shown.



**Figure S2: Comparisons of the five PAMs with four mutation strategies (rand/1, rand/2, best/1, and best/2) and binomial crossover on the BBOB benchmarks ( $D \in \{2, 3, 5, 10, 20\}$ ). These figures show the bootstrapped Empirical Cumulative Distribution Function (ECDF) of the number of function evaluations (FEvals) divided by dimension for 50 targets in  $10^{[8...2]}$  for all functions (higher is better). For details of the ECDF, see a manual of COCO software (<http://coco.gforge.inria.fr/>).**





Figure S.3: Comparisons of the five PAMs with four mutation strategies (current-to-rand/1, current-to-best/1, current-to-pbest/1, and rand-to-pbest/1) and binomial crossover on the BBOB benchmarks ( $D \in \{2, 3, 5, 10, 20\}$ ). These figures show the bootstrapped Empirical Cumulative Distribution Function (ECDF) of the number of function evaluations (FEvals) divided by dimension for 50 targets in  $10^{[-8..2]}$  for all functions (higher is better). For details of the ECDF, see a manual of COCO software (<http://coco.gforge.inria.fr>).



**Figure S4:** Comparisons of the five PAMs with four mutation strategies (rand/1, rand/2, best/1, and best/2) and shuffled exponential crossover on the BBOB benchmarks ( $D \in \{2, 3, 5, 10, 20\}$ ). These figures show the bootstrapped Empirical Cumulative Distribution Function (ECDF) of the number of function evaluations (FEvals) divided by dimension for 50 targets in  $10^{[-8..2]}$  for all functions (higher is better). For details of the ECDF, see a manual of COCO software (<http://coco.gforge.inria.fr>).




Figure S5: Comparisons of the five PAMs with four mutation strategies (current-to-rand/1, current-to-best/1, current-to-best/10, and shuffled exponential crossover on the BBOB benchmarks ( $D \in \{2, 3, 5, 10, 20\}$ )). These figures show the bootstrapped Empirical Cumulative Distribution Function (ECDF) of the number of function evaluations (FEvals) divided by dimension for 50 targets in  $10^{[-8..2]}$  for all functions (higher is better). For details of the ECDF, see a manual of COCO software (<http://coco.gforge.inria.fr/>).