

SAVE TIME! RESERVE Online and Pickup In-store



Search Over +100,000 Products

My Vehicle | 2005 Toyota Camry (LE)

[Change Vehicle](#)

[Browse Parts](#)

[Find a Store](#)



How to boost your car battery?

If your car battery is dead or too weak to start the engine, you can use jumper cables and another vehicle's battery to boost your car. Here's a step-by-step guide on how to boost your car battery:

1. Find a booster vehicle:



Search Over +100,000 Products

My Vehicle | 2005 Toyota Camry (LE)



2. Identify the positive and negative terminals:

Identify the positive (+) and negative (-) terminals on both batteries. They are usually marked with red (+) and black (-) covers or symbols.

3. Connect the jumper cables:

- Connect one end of the red (positive) cable to the positive terminal of the dead battery.
- Connect the other end of the red (positive) cable to the positive terminal of the booster vehicle's battery.
- Connect one end of the black (negative) cable to the negative terminal of the booster vehicle's battery.





Search Over +100,000 Products

My Vehicle | 2005 Toyota Camry (LE)

6. Start your car:

Attempt to start your car's engine. If it doesn't start initially, wait a couple more minutes before trying again.



7. Disconnect in reverse order:

Once your car starts, carefully disconnect the jumper cables in reverse order:

- Disconnect the black (negative) cable from your car's grounding point.
- Disconnect the black (negative) cable from the booster vehicle's negative terminal.
- Disconnect the red (positive) cable from both batteries, starting with the booster vehicle's positive terminal.
- Disconnect the red (positive) cable from your car's positive terminal.

8. Let your engine run:



Search Over +100,000 Products

My Vehicle | 2005 Toyota Camry (LE)

Connect the positive red clamp to the positive terminal of the battery, and the negative black clamp to the negative terminal. A warning light will indicate if you have accidentally connected the clamps in reverse. A safety feature that booster cables don't have. Once this connection is established, move the switch to the ON position to energize your clamps.

3. Step 3 – Start your vehicle:

Try starting your vehicle. If it doesn't start right away, wait a minute before trying again. This will protect the booster pack and your car starter from overheating.

4. Step 4 – Remove the clamps:

Once the engine is running again, remove the negative black cable first and then the positive red cable. Don't forget to recharge your booster pack so it is ready whenever you need it again.

Remember, boosting a car battery can be potentially hazardous if not done correctly. Always follow these instructions carefully and exercise caution during the process. If you're unsure or uncomfortable with jump-starting a car yourself, consider seeking assistance from a professional or roadside service provider.

PartSource has you covered with a wide selection of booster packs & cables. Find them here:

Booster Packs & Cables