

Rest of Chapter 9 slides


- ▶ **Case study:**

- Core i7/Linux memory system (on your own)


Intel Core i7 Memory System

Processor package

Core x4



End-to-end Core i7 Address Translation (fig. 9.22)



Core i7 Level 1-3 Page Table Entries

63	62	52	51	12	11	9	8	7	6	5	4	3	2	1	0
XD	Unused	Page table physical base address				Unused	G	PS		A	CD	WT	U/S	R/W	P=1
Available for OS (page table location on disk)															P=0

Each entry references a 4K child page table. Significant fields:

P: Child page table present in physical memory (1) or not (0).

R/W: Read-only or read-write access access permission for all reachable pages.

U/S: user or supervisor (kernel) mode access permission for all reachable pages.

WT: Write-through or write-back cache policy for the child page table.

A: Reference bit (set by MMU on reads and writes, cleared by software) ([accessed](#))

PS: Page size either 4 KB or 4 MB (defined for Level 1 PTEs only).

Page table physical base address: 40 most significant bits of physical page table address (forces page tables to be 4KB aligned)

XD: Disable or enable instruction fetches from all pages reachable from this PTE.

Core i7 Level 4 Page Table Entries

63	62	52	51	12	11	9	8	7	6	5	4	3	2	1	0
XD	Unused	Page physical base address				Unused	G		D	A	CD	WT	U/S	R/W	P=1
Available for OS (page location on disk)															P=0

Each entry references a 4K child page. Significant fields:

P: Child page is present in memory (1) or not (0)

R/W: Read-only or read-write access permission for child page

U/S: User or supervisor mode access

WT: Write-through or write-back cache policy for this page


A: Reference bit (set by MMU on reads and writes, cleared by software)

D: Dirty bit (set by MMU on writes, cleared by software)


Page physical base address: 40 most significant bits of physical page address
(forces pages to be 4KB aligned)

XD: Disable or enable instruction fetches from this page.

Core i7 Page Table Translation




Cute Trick for Speeding Up L1 Access




► Observation

- Bits that determine CI identical in virtual and physical address
- Can index into cache while address translation taking place
- Generally we hit in TLB, so PPN bits (CT bits) available next
- “Virtually indexed, physically tagged”
- Cache carefully sized to make this possible


Virtual Address Space of a Linux Process



Linux Organizes VM as Collection of “Areas” (p.830)



Linux Page Fault Handling



Segmentation fault:
accessing a non-existing page

Normal page fault (miss)

Protection exception:
e.g., violating permission by
writing to a read-only page (Linux
reports as Segmentation fault)