

Multilingual Room Matching with Fuzzy Logic and XGBoost

Ryoji – Room Match ML API Project

April 2025

Contents

1 Introduction	1	– README.md <i>Instructions and architecture overview</i>
2 Project Structure and API Setup	1	– requirements.txt <i>Dependencies</i>
3 Methodology	1	– app.py <i>Flask server for POST API</i>
3.1 Input Format	1	– matcher.py <i>Core logic: fuzzy matching, ML inference</i>
3.2 Candidate Matching Strategy	2	– models/ <i>Includes:</i>
3.3 Model Training	2	* model.pkl (XGBoost model)
3.4 Multilingual Handling	2	* lid.176.bin (fastText language model)
4 Results	2	– sample_request.json <i>Example POST input</i>
5 Sample Output	2	– test_post.py <i>Simple test script</i>
6 Figures	3	– notebooks/room_match_dev.ipynb <i>EDA and training</i>
7 Limitations and Future Work	3	– report.pdf <i>Technical report summarizing the matching system and evaluation results</i>
7.1 Deployment Notes	3	
7.2 LLM Potential	3	

1 Introduction

This project builds a multilingual machine learning API for matching hotel room listings, inspired by Cupid's Room Match API. The system accepts POST requests with structured room data from both suppliers and a reference catalog, and returns probabilistic room match predictions. It supports mixed-language inputs (e.g., English, Arabic, Korean) and uses fuzzy logic, language detection, and machine learning classification.

2 Project Structure and API Setup

- Room_Match/ (project root)

Running the API:

1. `pip install -r requirements.txt`
2. `FLASK_APP=app.py flask run --host=0.0.0.0 --port=5050`
3. Send a test request:

```
curl -X POST http://127.0.0.1:5050/room_match \
-H 'Content-Type: application/json' \
-d @sample_request.json
```

4. Or run `python test_post.py`

3 Methodology

3.1 Input Format

The input to the API is a JSON object with supplier and reference rooms:

```
{
  "inputCatalog": [
    {
      "supplierId": "nuitee",
      "supplierRoomInfo": [
        {"supplierRoomId": "2", "supplierRoomName": "Classic Room - Olympic Queen Bed - ROOM ONLY"}
      ]
    }
  ],
  "referenceCatalog": [
    {
      "propertyId": "5122906",
      "propertyName": "Pestana Park Avenue",
      "referenceRoomInfo": [
        {"roomId": "512290602", "roomName": "Classic Room"},
        {"roomId": "512290608", "roomName": "Classic Room - Disability Access"}
      ]
    }
  ]
}
```

3.2 Candidate Matching Strategy

1. ID Filtering:

- Supplier IDs are checked against reference room_id, lp_id, core_room_id, etc.

2. Fuzzy Matching:

- Normalize strings (lowercase, remove accents/punctuation)
- Compute similarity using `rapidfuzz.partial_ratio`

3. Language Detection:

- Uses `fastText` model to annotate room names for language context

4. Feature Extraction:

- lp_id_match, hotel_id_match, room_id_match, fuzzy_score

3.3 Model Training

- Label = 1 if fuzzy score ≥ 0.85 AND ID match
- Model: XGBoost classifier
- Tuning: Optuna
- Metrics: F1, AUC, Confusion Matrix

3.4 Multilingual Handling

- `fastText` supports 100+ languages.

- Can detect Arabic, Korean, Japanese, etc. — but only the dominant language.
- Mixed-language strings may produce partial results.
- Example: **Deluxe Room** (デラックスルーム) may be detected as Japanese or English depending on structure.

Limitation: `fastText` cannot detect or translate multiple languages in one string. It returns only the dominant language.

Recommendation: Use `SentenceTransformer` (MiniLM-L12-v2) with GPU for better cross-lingual semantic understanding.

4 Results

- **F1-score:** 99.6%
- **ROC AUC:** High
- **Confusion Matrix:** Few false positives/negatives

5 Sample Output

```
{
  "supplierRoomId": "2",
  "supplierRoomName": "Classic Room - Olympic Queen Bed",
  "refRoomId": "512290602",
  "refRoomName": "Classic Room",
  "fuzzy_score": 1.0,
  "match_score": 0.9991,
  "lang_supplier": "en",
}
```

```
"lang_ref": "en"  
}
```

6 Figures

Figure 1: Confusion Matrix

Figure 2: ROC AUC Curve

Figure 3: XGBoost Feature Importance

7 Limitations and Future Work

- Only one supplier — needs extension to multiple.
- Current model uses only name-based features.
- Future versions should add:
 - Room view, floor, amenities
 - Descriptions and full metadata

7.1 Deployment Notes

- Docker for reproducibility
- CI/CD with Jenkins or GitHub Actions
- Hosting via FastAPI or TorchServe

7.2 LLM Potential

- Fine-tuning MiniLM-L12-v2 with LoRA
- Use of RAG + embeddings for richer room description grounding
- Large LLMs for summarization and inference