

FRONT VIEW – SIDE A

1:20



VIEW FROM WALL

1:20




= WALL DRILLING

CABLE EXIT: ~230 V cable 1.5 m through plate Ø11 into wall, on axis, 95 mm from top of sign. PSU on plate, under leg covers.


FRONT VIEW – SIDE B

1:20 (mirrored)




SECTION A–A

1:15



TOP VIEW


1:20




32 screws: 12 per side of band, into PVC edge

ASSEMBLY – EXPLODED VIEW

not to scale; face A + PVC 4 – body 2 + frame 1 + LED 7 – PVC 6 + face B; inside white






3D VIEW – SIDE A

ILLUSTRATIVE – NOT TO SCALE

3D VIEW – SIDE B

ILLUSTRATIVE – NOT TO SCALE

DETAIL B – SECTION TOP / BOTTOM 1:3



screws 8 (D3.2) through band into PVC edge; band welded to frame

BILL OF MATERIALS

POS	PART	MATERIAL	FINISH	QTY (PERIMETER / AREA)
1	Frame □40x40x2 (cut list – sheet 2)	Alu EN AW-6060	white (inside)	2 x 1544 + 384 + 304 = 3776 mm
1B	Legs □40x40x2, through rear vert.	Alu, welded to frame	NCS S 8010-R90B	2 x 143 mm
1A	Mounting plate 140x470x5, 4 x Ø8 + Ø11	Alu, welded to legs	NCS S 8010-R90B	1 pc.
2	Body band 1.5 x 100, inside white	Alu, folded, welded to frame	RAL 9010 out	1547 x 467: 4028 mm
3	Face A (glass)	3 mm opal white plexiglass	–	1550 x 470 = 0.73 m²
4	PVC edge 3 x 15 (face A)	PVC, glued to face	white	4016 mm
5	Face B (glass, mirror)	3 mm opal white plexiglass	–	1550 x 470 = 0.73 m²
6	PVC edge 3 x 15 (face B)	PVC, glued to face	white	4016 mm
7	LED + PSU (on 1A)	LED / PSU	–	38 pcs. + 1 PSU
8	Tapping screw, D3.2 holes	A2	–	32 pcs. (into PVC edge)
9	Logo, sides A + B	3M 100-54	–	2 pcs., 1086 x 246 mm
10	Leg cover A + B, 2 x Ø3.2 top (DXF)	Alu 2, ribs 10 notched	NCS S 8010-R90B	2 pcs., 96.5 x 388 x 25

MAIN DATA

Product	double-sided lightbox, projecting
Size (glass)	1550 x 470 x 106 mm
Sides	A + B: logo 1086 x 246 (9)
From wall	1655 mm (body 109.5)
Fixing	1 plate 140x470, 4 x Ø8, 109 x 344
LED / PSU	38 x LED, PSU
Finish	legs + plates NCS S 8010-R90B
Cable	~230V 1.5 m via plate Ø11
Qty	1 pcs.
Weight (calc.)	≈ 12.1 kg / pcs, excl. PSU

REVISIONS

ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED

REV	DESCRIPTION	DATE	BY
A	First issue	2026-10-15	

CLIENT

BN Skilte A/S / danbolig Hornbæk

TITLE

DB-0001 DOUBLE-SIDED LIGHTBOX 1550 x 470, PROJECTING


ORDER NO.	FILE / DRAWING NO.
ALT0000_00.00_RS	PO 3295 / DB-0001

SCALE	FORMAT	REV.	PROJECTION
1:20 / 1:15	A3	A	

DATE		
2026-10-15	1 pcs.	Sheet 1 / 3

FRAME (1) – SIDE VIEW

1:8 (from side A, welded)



□40x40x2: 3776 mm, welded, ground
LED 38 pcs., 76.5 mm, light to both faces

FRAME – END VIEW (FROM WALL)

1:8 (mounting plate 1A)





plate t = 5, 4 x ⌀8, welded to legs 1B (dashed); cable ⌀11 on axis



FRAME – ISOMETRIC

not to scale

LED (7)	
Module	LED
Mounting	top + bottom members
Qty / pitch	38 pcs., 76.5 mm
PSU	PSU, on plate 1A under covers

BILL OF MATERIALS

POS	PART	MATERIAL	FINISH	QTY (PERIMETER / AREA)
1.1	Top member □40x40x2	Alu EN AW-6060	white	1 x 1544 mm
1.2	Bottom member □40x40x2	Alu EN AW-6060	white	1 x 1544 mm
1.3	Front vertical □40x40x2	Alu EN AW-6060	white	1 x 384 mm
1.4	Rear vertical □40x40x2, between legs	Alu EN AW-6060	white	1 x 304 mm
1B	Leg □40x40x2, through rear vert.	Alu EN AW-6060	NCS S 8010-R90B	2 x 143 mm
1A	Mounting plate 140x470x5	Alu	NCS S 8010-R90B	1 pc., 4 x ⌀8 + ⌀11
7	LED	LED	-	38 pcs.
7A	PSU on plate 1A, under covers	PSU	-	1 pc.
7B	Cable ~230 V from PSU, out via plate			1.5 m

MAIN DATA	
Frame outer	1544 x 464 mm
Profile	□40x40x2 Alu, centre of depth
Legs	□40x40x2 through rear vert., gap 101.5
Leg axes	344 mm (from glass edge 63)
Joints	welded (TIG), ground
Body	band 1547 x 467, welded to frame
Cable	~230V 1.5 m: PSU on 1A -> ⌀11
Finish	legs + plates NCS S 8010-R90B
Qty	1 set

REVISIONS — ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED

REV	DESCRIPTION	DATE	BY
A	First issue	2026-10-15	

CLIENT: BN Skilte A/S / danbolig Hornbæk

TITLE: DB-0001 DOUBLE-SIDED LIGHTBOX 1550 x 470, PROJECTING – FRAME (CAD)

ORDER NO.: **ALT0000_00.00_RS**

FILE / DRAWING NO.: PO 3295 / DB-0001


SCALE: 1:8 / 1:8 | FORMAT: A3 | REV. A | PROJECTION

DATE: 2026-10-15 | 1 pcs. | Sheet 2 / 3



FRONT VIEW

SCALE 1:10




SIDE VIEW (RIGHT)

SCALE 1:10

Power / PSU / cable exits:

– – – 12V cable 1.5 m from each letter, exits on one line (9 pcs., small parts – exit in the part)



REAR VIEW (MIRRORED)

SCALE 1:10 | true view from the back


FRONT PAINTED IN 2 LAYERS:
1st layer WHITE (base), 2nd layer BLACK (top coat); gold leaf – by client



3D VIEW

ILLUSTRATIVE – NOT TO SCALE

PROFILE P10 – THREADED RODS TO FACADE



Alu 1.5 back recessed (rim 5); LED groove 8 x ; rod M

BILL OF MATERIALS (per 1 pcs.)

POS	PART	MATERIAL	FINISH	QTY (PERIMETER / AREA)
1	Letter block (LED groove from back, DXF)	Acrylic 30 mm white (opal)	front white+black	10.12 m / 0.27 m²
2	LED strip in groove	LED 12V	–	
3	Letter back (recessed into block)	Alu 1.5 mm	–	0.27 m²
4	Threaded rod welded to back –> facade	M? (?)	–	30 pcs.
5	Paper mounting template 1:1	paper	–	1 pc.
6	Trafo box	12V	–	1 pc.

MAIN DATA

Quantity	1 pcs.
Overall size	1800 x 406
Profile	P10 block letters 30 mm
Depth	30
Front	painted white, then black
Gold leaf	by client (BN)
Sides	unpainted, illuminated
Illumination	LED 12V
Power	12V per letter + trafo box
Fixing	threaded rods + paper template
Mounting	separate letters, no frame
Weight (calc.)	≈ 11 kg / pcs, excl. PSU

REVISIONS ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED

REV	DESCRIPTION	DATE	BY
A	First issue	2026-10-15	

CLIENT
BN Skilte A/S / danbolig Hornbæk

TITLE
DB-0002 danbolig 1800 x 352 – P10 letters, threaded rods to facade

ORDER NO.
ALT0000_00.00_RS

FILE / DRAWING NO.
PO 3295 / DB-0002

SCALE
1:10 / 1:10

FORMAT
A3

REV. A

PROJECTION

DATE
2026-10-15

1 pcs.

Sheet 3 / 3