

FRONT VIEW – SIDE A

1:12



VIEW FROM WALL


1:12



= WALL DRILLING; - - - tray seam


FRONT VIEW – SIDE B

1:12 (mirrored)




SECTION A-A


1:8



ASSEMBLY – EXPLODED VIEW

not to scale; tray A – insert 4 – base 6 + nuts – frame + LED – base 7 – insert 5 – tray B; inside white





3D VIEW – SIDE A


ILLUSTRATIVE – NOT TO SCALE

3D VIEW – SIDE B

ILLUSTRATIVE – NOT TO SCALE


TOP VIEW

1:12



screws 10: 12 pcs. ⌀3.2, top + bottom flanges, 7 from seam

DETAIL B – SECTION TOP / GLASS / BOTTOM 1:4



gap 0.7; insert GLUED to base; studs welded inside, 15 from glass

BILL OF MATERIALS

POS	PART	MATERIAL	FINISH	QTY (PERIMETER / AREA)
1	Frame + legs □30x30x2, in box white	Alu, welded		2 x 689 + 2 x 534 mm
1A	Mounting plate 66x67x8, ⌀10	Alu, welded to leg		2 pcs.
2	Front A, folded 600x600x40, in white	Alu 2 mm		1 pc.
3	Back B, folded 600x600x40, in white	Alu 2 mm		1 pc.
4	Insert A 10 mm, GLUED to base	Plexi opal white	-	1 pc. 0.027 m²
5	Insert B 10 mm, GLUED to base	Plexi opal white	-	1 pc. 0.027 m²
6	Base A 3 mm, 12 x ⌀8 (DXF)	Plexi opal white	-	1 pc. 0.064 m²
7	Base B 3 mm, 12 x ⌀8 (DXF)	Plexi opal white	-	1 pc. 0.064 m²
8	LED + PSU	LED / PSU	-	14 pcs. + 1 PSU
9	Stud (welded to Alu) + nut		-	24 pcs.
10	Screw, ⌀3.2 holes in flanges	A2	-	12 pcs.

MAIN DATA

Product	P10_lightbox_doublesided
Size	600 x 600 x 80 (+ 2 x 8)
From wall	100 mm (legs 92 + plate 8)
Body	Alu 2, 2 trays A + B, inside white
Glass	3+10 mm, cut-out + 0.7
Frame	□30x30x2 white, legs
LED / PSU	14 x LED, PSU
Qty	
Weight (calc.)	≈ 7.4 kg / pcs, excl. PSU

REVISIONS

REV	DESCRIPTION	DATE	BY
A	First issue	2026-10-13	

CLIENT

TEST

TITLE

P10_lightbox_doublesided 600x600x80 – push-through (etalon)

ORDER NO.

ALT0000_00.00_RS

FILE / DRAWING NO.

TEST P10_lightbox_doublesided

SCALE (DIM. mm)

1:5 / 1:2 / 1:1

FORMAT

A3

REV. A

PROJECTION


DATE

2026-10-13

Sheet 1 / 2

FRAME (1) – SIDE VIEW

1:8 (from side A, welded)



□30x30x2: legs 2 x 689, verticals 2 x 534
welded, ground; LED 14 pcs., 76 mm

FRAME – END VIEW (FROM WALL)

1:8 (mounting plate 1A)





plate t = 8, 2 x ⌀10, welded to legs; legs dashed; holes – PLATE 1A




FRAME – ISOMETRIC

not to scale

PLATE 1A

1:4



t = 8, ⌀10, welded to leg (2 pcs.), hole centred

LED (8)	
Module	LED
Mounting	top + bottom members
Qty / pitch	14 pcs., 76.3 mm
PSU	PSU, place:

BILL OF MATERIALS

POS	PART	MATERIAL	FINISH	QTY (PERIMETER / AREA)
1.1	Top member + leg □30x30x2	Alu EN AW-6060		1 x 689 mm
1.2	Bottom member + leg □30x30x2	Alu EN AW-6060		1 x 689 mm
1.3	Vertical □30x30x2	Alu EN AW-6060	white	2 x 534 mm
1A	Mounting plate 66x67x8, 1 x ⌀10	Alu		2 pc.
	Frame profile total			2446 mm (+ cut allowance)
8	LED	LED	–	14 pcs.
8A	PSU	PSU	–	1 pc.
8B	Cable 2 x 0.75 (LED -> PSU)			length:

MAIN DATA	
Frame outer	594 x 594 mm
Profile	□30x30x2 Alu, centre of depth
Legs	members extended +92 out of body
Plate	66 x 67 x 8
Joints	welded (TIG), ground
Finish	legs + plate ; frame white
Qty	? set

REVISIONS

REV	DESCRIPTION	DATE	BY
A	First issue	2026-10-13	

CLIENT
TEST

TITLE
P10_lightbox_doublesided 600x600x80 – push-through (etalon) – FRAME (CAD)

ORDER NO.	FILE / DRAWING NO.
ALT0000_00.00_RS	TEST P10_lightbox_doublesided

SCALE (DIM. mm)	FORMAT	REV.	PROJECTION
1:8 / 1:4	A3	A	

DATE
2026-10-13

Sheet 2 / 2