

An introduction to R

Scott Powers and Ryan Wang

January 23, 2014

Goal

- ▶ Serious data work requires programming (at least with the current state of tools like Excel and Tableau)
- ▶ In this tutorial, we'll work through the basics of R by analyzing the set of box scores from the '12-'13 NBA season
- ▶ Among other things, we will:
 1. Identify the top scorers in that season
 2. Understand how statistics vary over the course of a season
 3. Determine the relationship between scoring and rebounding
 4. Build a model for predicting this year's top scorers

The help function

- ▶ R is a very well-documented language
- ▶ A crucial function is `help`, as it allows you to access that documentation
- ▶ It can be accessed by `help(function)` or `?function` for short e.g. type `?help` to learn more about the help function
- ▶ Google is also a great resource and usually links to either stackoverflow or the R mailing list

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics

Visualizing data

Linear regression

Data frames

Let's start by reading in some real-life data

```
> setwd('~/.GitHub/data-mining-intersession/day1')
> nba <- read.csv('box_2012to2013.csv'
+               , stringsAsFactors=F)
> class(nba)

[1] "data.frame"
```

In R terminology, data typically comes in the form of a *data.frame* (try ?data.frame). Data frames are essentially matrices that can store non-numeric values, and are very similar to spreadsheets.

Data frames cont.

This is essentially the same as what you would see if you opened the .csv file in MS Excel

```
> nba[1:5,1:5]
```

	game_id	pid	player	pos	team
1	400277721	4270	Trevor Booker	PF	Washington Wizards
2	400277721	2426	Trevor Ariza	SF	Washington Wizards
3	400277721	2399	Emeka Okafor	C	Washington Wizards
4	400277721	4010	A.J. Price	PG	Washington Wizards
5	400277721	6580	Bradley Beal	SG	Washington Wizards

Columns correspond to *variables* e.g. column 5 indicates the number of minutes played. Rows correspond to *observations* e.g. row 1 corresponds to Trevor Booker's line on the box score.

Data frames cont.

This data frame contains 31,375 rows (observations) and 19 columns (variables)

```
> nrow(nba)
```

```
[1] 31351
```

```
> ncol(nba)
```

```
[1] 19
```

```
> dim(nba)
```

```
[1] 31351    19
```

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics

Visualizing data

Linear regression

Accessing elements of the data

Specific elements of the data can be accessed with [row, column] coordinates

```
> nba[1:2,1:2]
```

```
  game_id  pid  
1 400277721 4270  
2 400277721 2426
```

```
> nba[1,1]
```

```
[1] 400277721
```

```
> nba[2,1]
```

```
[1] 400277721
```

We'll discuss subsetting data frames more in-depth after we have seen how vectors (and specifically sequences) work.

Vectors

The fundamental unit of computation in R is the vector.
Create a vector by combining values with the "c" function (see ?vector and ?c):

```
> c(1,2,3,4,5)
```

```
[1] 1 2 3 4 5
```

```
> c('a','b','c','d','e')
```

```
[1] "a" "b" "c" "d" "e"
```

Vectors cont.

Assign a value, which includes vectors, to a name using the "<-" operator (see ?assignOps)

```
> v1 <- c(1,2,3,4,5)
```

```
> v1
```

```
[1] 1 2 3 4 5
```

```
> v1[1]
```

```
[1] 1
```

The first element of v1 is 1, and the second element is 2. Note that unlike most programming languages, indexing starts at 1.

Vectors cont.

Most functions involving vectors operate element-wise. Calling a function like `?sum` or `?mean` on a vector will collapse it:

```
> v1 + 3
```

```
[1] 4 5 6 7 8
```

```
> v1 + v1
```

```
[1] 2 4 6 8 10
```

```
> sqrt(v1)
```

```
[1] 1.000000 1.414214 1.732051 2.000000 2.236068
```

```
> sum(v1^2)
```

```
[1] 55
```

Vectors cont.

The ":" operator (see ?colon) creates a sequence, which is also a vector

```
> x <- 1:5
```

```
> x
```

```
[1] 1 2 3 4 5
```

```
> x[1]
```

```
[1] 1
```

Vectors cont.

Boolean values are TRUE and FALSE, or T and F for short (see ?logical)

```
> TRUE & FALSE
```

```
[1] FALSE
```

```
> !(T & F)
```

```
[1] TRUE
```

It is easy to create boolean vectors by writing conditions. This will come in handy soon.

```
> 1:5 > 2
```

```
[1] FALSE FALSE  TRUE  TRUE  TRUE
```

Exercises

1. Create a vector of the even numbers between 1 and 50
2. What happens if you use `?sum` on a vector of boolean values?
3. What would happen if you ran `nba[,]`?
4. Explore R's built-in constants by reading the documentation (type `?Constants`)

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics

Visualizing data

Linear regression

Accessing elements of the data cont.

Now that we know about sequences, see that the data frame is subsetted by passing a vector of row and/or column indices

```
> nba[1:5,1:5] # rows 1 to 5, columns 1 to 5
```

	game_id	pid	player	pos	team
1	400277721	4270	Trevor Booker	PF	Washington Wizards
2	400277721	2426	Trevor Ariza	SF	Washington Wizards
3	400277721	2399	Emeka Okafor	C	Washington Wizards
4	400277721	4010	A.J. Price	PG	Washington Wizards
5	400277721	6580	Bradley Beal	SG	Washington Wizards

```
> nba[1:5,] # would give rows 1 to 5, all columns
```

You can access all the entries along a particular dimension by leaving the slot blank.

Accessing elements of the data cont.

A neat feature of data frames is that columns are named.
Access specific columns with the "\$" operator (see ?Extract)

```
> names(nba)[1:5]
[1] "game_id" "pid"      "player"  "pos"      "team"
> nba$pid[1:5]
[1] 4270 2426 2399 4010 6580
> nba[1:5, 'pid'] # alternatively...
[1] 4270 2426 2399 4010 6580
```

Exploring the data

Using boolean vectors, we can subset the data to look at specific players' statistics

```
> lbj <- nba[nba$player == "LeBron James",]  
> basic <- c('player', 'min', 'pts', 'reb')  
> lbj[1:5, basic]
```

	player	min	pts	reb
40	LeBron James	29	26	10
464	LeBron James	37	23	7
735	LeBron James	39	20	9
1097	LeBron James	30	23	11
1406	LeBron James	30	20	12

Under the hood, the boolean vector is being translated into a vector of indices for the TRUE entries. This can be accomplished explicitly by using the `?which` function on a boolean vector.

Exploring the data cont.

It's not enough to know only the dimensions of the data frame, which tell us the number of box scores. We might need to know things such as: how many players were active?

```
> v1 <- c('a','a','b','d')
> unique(v1)

[1] "a" "b" "d"

> length(unique(v1))

[1] 3

> length(unique(nba$pid)) # number of players active

[1] 476
```

The `?unique` function returns the unique values that appear in the inputted vector. The `?length` function returns its length.

Exercises!

1. Examine the nba dataset with ?View. What does it contain?
2. What is the difference between the 'pid' and 'player' columns (besides that one is a number)?
3. What set of variables is an identifier for the dataset (i.e. there are 31,351 unique combinations)? In other words, what is the level of the dataset?
4. Create a subset of the data that contains entries for all point guards (PG). What are its dimensions?
5. How many total games were played in the '12-'13 season? Is it what you would expect (hint: 30 teams play 82 games each)?
6. What is the average number of minutes played? Points scored? (Try ?mean)

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics

Visualizing data

Linear regression

Total points scored

We now have some basic tools for exploring and manipulating data. We can use them to answer question such as: how many points did LeBron James score in the '12-'13 season?

```
> sum(lbj$pts)
```

```
[1] 2036
```

```
> sum(nba$pts[nba$player=='LeBron James'])
```

```
[1] 2036
```

Check this against ESPN's records http://espn.go.com/nba/player/stats/_/id/1966/lebron-james.

Points per game (PPG)

Let's try answering more substantive questions such as: Who had the highest PPG? First we need to remove games in which a player did not play.

```
> nba <- nba[nba$min>0,]
```

Next, we want to repeatedly do the following:

```
> pid <- 9  
> tmp <- nba[nba$pid==pid,]  
> mean(tmp$pts)  
[1] 10.92405
```

Player 9 corresponds to Ray Allen.

Mini-Exercises!

1. How would you check that pid 9 corresponds to Ray Allen?
2. How would you check the player name for any given pid?
3. (Optional) Write a "for loop" to calculate points per game for every player
 - 3.1 Review the documentation of the "for" command (?Control)
 - 3.2 Create a vector of the unique players that appeared
 - 3.3 Looping over this vector, repeatedly calculate the mean
 - 3.4 (Challenge) You could store the calculated means by initializing an empty vector with ?rep e.g. `ppg <- rep(NA, n)` where n is the number of entries

Points per game (PPG) cont.

We could literally repeat the averaging process with a loop. But since this is so common in data work, R has fast functions for this type of thing.

```
> ppg <- aggregate(x=nba$pts,  
+                  by=list(pid=nba$pid),  
+                  FUN=mean)  
> max(ppg$x) # highest ppg is 28.6  
[1] 28.65672
```

What's going on here? The vector `nba$pts` is first split into subsets according to `nba$pid`. Then the `?mean` function is being applied to each subset. This idea is known as *split-apply-combine* and is similar to *map-reduce* (which is a big buzzword in big data).

Points per game (PPG) cont.

We can also use Hadley Wickham's very popular `plyr` package to do the same thing.

```
> # install.packages('plyr')
> require(plyr)
> ppg2 <- ddply(nba, .(pid), summarize,
+               ppg = mean(pts))
> ppg2[1,]

  pid      ppg
1   9 10.92405
```

The structure of this command is exactly the same as with `aggregate`. See the documentation (`?ddply` and `?plyr`).

Points per game (PPG) cont.

We can identify this player by figuring out the index of the maximum value, and looking it up in `nba`.

```
> idx <- which.max(ppg$x)
> pid <- ppg$pid[idx]
> pid

[1] 1975

> nba$player[nba$pid==pid][1]

[1] "Carmelo Anthony"
```

Points per game (PPG) cont.

What if we want to know the top 5 scorers? The top N scorers? Luckily there is a better way than manually looking everyone up... First, we'll create a new dataset that maps pid to player name.

```
> plyrs <- unique(nba[,c('pid', 'player')])  
> plyrs[1:5,]
```

	pid	player
1	4270	Trevor Booker
2	2426	Trevor Ariza
3	2399	Emeka Okafor
4	4010	A.J. Price
5	6580	Bradley Beal

This is a lookup table of sorts. We can always consult it to figure out the player name corresponding to a pid. Can we always do the reverse?

Points per game (PPG) cont.

Next, let's try merging two datasets. We'll combine our *ppg* dataset with the *pid*->*player* mapping so we don't have to lookup names separately anymore.

```
> ppg <- merge(ppg, plyrs, by='pid')  
> ppg[1:5,]
```

	pid	x	player
1	9	10.924051	Ray Allen
2	25	12.386667	Metta World Peace
3	63	8.363636	Chauncey Billups
4	91	7.194444	Elton Brand
5	110	27.346154	Kobe Bryant

Think about how you would do this by hand. For each *pid* in *ppg*, you'd look it up in *plyrs* and find the associated player name. Then you'd come back to *ppg* and record the name you found. This is also known as joining.

Points per game (PPG) cont.

The last thing to do is sort ppg. We'll use the `?order` function to sort by `ppg$x`.

```
> order_ppg <- order(ppg$x, decreasing=T)
> order_ppg[1:5] # vector of indices
```

```
[1] 79 201 5 78 278
```

```
> ppg <- ppg[order_ppg,]
> ppg[1:5,]
```

	pid	x	player
79	1975	28.65672	Carmelo Anthony
201	3202	28.14815	Kevin Durant
5	110	27.34615	Kobe Bryant
78	1966	26.78947	LeBron James
278	3992	25.93590	James Harden

Exercises

1. Calculate rebounds, assists, and blocks per game (reb, ast, blk). Who are the top players in each category?
2. (Challenge) Calculate all per-game stats with a single command
3. Which team scored the most points per game?

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics


Visualizing data

Linear regression

Histograms

We know a bit about PPG for the top players. What does the distribution look like?


```
> hist(ppg$x)
```



PPG over the season

Another interesting question is how much does PPG vary over the course of the season? We'll plot the time series with `?plot`.

```
> lbj <- subset(nba, player=='LeBron James')  
> lbj_ppg <- cumsum(lbj$pts)/1:length(lbj$pts)  
> plot(lbj_ppg, type='l')
```




Time series are very common in applications within finance.

PPG over the season cont.

How did LeBron compare to Kevin Durant? We can overlay plots with the `?lines` function

```
> kd <- subset(nba, player=='Kevin Durant')  
> kd_ppg <- cumsum(kd$pts)/1:length(kd$pts)  
> plot(lbj_ppg, type='l', ylim=c(20,30))  
> lines(kd_ppg, type='l', col='red')
```



Note that we're sidestepping the fact that they might not have played the same number of games.

PPG over the season cont.

What if we wanted to compare any given players? Minor segue: we will need to know how to define functions.

Functions are defined with the 'function' keyword and can be assigned to names.

```
> square <- function(x) { return(x^2) } # minor segue on  
> square(2)
```

```
[1] 4
```

```
> square(1:5)
```

```
[1] 1 4 9 16 25
```

```
> sum2 <- function(x, y) { return(x+y) }  
> sum2(1,2)
```

```
[1] 3
```

PPG over the season cont.

Let's define a custom function that will allow us to make rolling calculations for any given player.

```
> roll_calc <- function(x) {  
+   ppg <- cumsum(x$pts) / 1:length(x$pts)  
+   return(ppg)  
+ }  
> kd_ppg2 <- roll_calc(subset(nba, pid==3202))  
> kd_ppg2[1:5]  
  
[1] 23.00000 23.00000 22.66667 20.75000 21.40000
```

The roll_calc function takes in a subset of nba and returns a vector.

PPG over the season cont.

Now let's use the `dlply` function to apply `roll_calc` for each player. See documentation in `?dlply`. This returns a list of vectors.


```
> ppg_roll <- dlply(nba, .(pid), roll_calc)
> ppg_roll[[1]][1:5] # access by index
[1] 19.00000 12.00000 15.66667 15.50000 14.20000
> ppg_roll[['9']][1:5] # access by key
[1] 19.00000 12.00000 15.66667 15.50000 14.20000
```

Experiment with `ppg_roll` to better understand how lists work. Also see `?list`. Lists in R are very similar to dictionaries in Python.

PPG over the season cont.

Compare LeBron to Durant to Kobe:

```
> plot(ppg_roll[['1966']], type='l', ylim=c(20,32))  
>   # LeBron  
> lines(ppg_roll[['3202']], type='l', col='red')  
>   # Durant  
> lines(ppg_roll[['110']], type='l', col='blue')  
>   # Kobe
```



Relationship between scoring and rebounding

Let's switch gears a bit. We'll now consider the relationship between scoring and rebounding. First let's get all these stats in one place.


```
> stats <- c('min','reb','ast','stl','blk','tos','pts')
> pg <- aggregate(nba[,stats],list(pid=nba$pid),mean)
> pg <- merge(pg, plyrs, by='pid')
> pg[1:5,1:5]
```

	pid	min	reb	ast	stl
1	9	25.73418	2.746835	1.7088608	0.8481013
2	25	33.74667	4.960000	1.4933333	1.6266667
3	63	19.00000	1.454545	2.2272727	0.5454545
4	91	21.25000	5.972222	0.9722222	0.6944444
5	110	38.69231	5.551282	6.0128205	1.3589744

Relationship between scoring and rebounding cont.

Next, let's look at a scatter plot of scoring (Y axis) versus rebounding (X axis). There seems to be a positive relationship

```
> plot(y=pg$pts, x=pg$reb)
```



Exercises

1. Plot a histogram of rebounds per game. What does it tell you?
2. What is an issue with our rolling calculation? (Hint: How many games has each player played?)
3. (Challenge) Fix the issue above. (Hint: You may need to ask me for a supplementary dataset, as game_ids are not exactly ordered by time)
4. There is a positive relationship between points and rebounds per game. Does this mean better scorers are also better rebounders? Why or why not?
5. What is a drawback of per-game statistics? (Hint: Try scatter plots against minutes played)
6. Calculate points and rebounds per 48 minutes. What does this relationship tell you?

Outline

A look at the data

R Basics

Exploring the data

Scoring statistics


Visualizing data

Linear regression

Scoring and minutes

Let's further explore the relationship between scoring and rebounding. The point of Exercise 5 was that per-game statistics are highly dependent on minutes played.

```
> plot(pg$pts~pg$min)
```



Scoring and minutes cont.

We can quantify the relationship between scoring and minutes using linear regression, implemented with the `lm` function (for linear model).

```
> m1 <- lm(pts~min, data=pg)
> m1
```

Call:

```
lm(formula = pts ~ min, data = pg)
```

Coefficients:


(Intercept)	min
-2.6043	0.5206

Try `summary(m1)` for an assessment of how well the model fits the data. This is the type of thing you would learn about in an intro stats course.

Scoring and minutes cont.

The idea of linear regression is essentially to fit a line through the scatter plot of Y on X.

```
> plot(pg$pts~pg$min)
> abline(m1, col='red')
```



Scoring and minutes cont.

How do we interpret this model?

```
> m1
```

Call:

```
lm(formula = pts ~ min, data = pg)
```

Coefficients:

(Intercept)	min
-2.6043	0.5206

Since it's a line, the model is defined by two parameters - slope and intercept. The slope can be interpreted as follows: for the average player, each additional minute per game results in an additional 0.5 points per game.

Scoring and rebounding

What does the scoring/rebounding relationship look like after we account for minutes played?

```
> m2 <- lm(pts~reb+min, data=pg)
> summary(m2)
```

Call:

```
lm(formula = pts ~ reb + min, data = pg)
```

Residuals:

Min	1Q	Median	3Q	Max
-7.2248	-1.4160	0.0465	1.3873	11.9978

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	-2.60479	0.25688	-10.140	<2e-16 ***
reb	-0.05420	0.05713	-0.949	0.343
min	0.53006	0.01516	34.965	<2e-16 ***

Scoring and minutes cont.

Linear regression supplies us with a method for making predictions. See `?predict.lm`

```
> fake_player <- list(min=20.0)
> predict(m1, newdata=fake_player)
```

1

7.807913

In particular, $\hat{pts} = 0.52 * min - 2.60$ where \hat{pts} is our prediction. So we would predict that a player who played 20 minutes per game would score 7.8 points per game. Admittedly, this is not a great model. But it's a start.

Exercises

1. Rank the top scorers by points per 48 minutes
 - 1.1 How does this ranking compare to the points per game ranking?
 - 1.2 What additional considerations must you make to get at scoring ability?
2. (Challenge) Create a regression model for predicting a player's scoring in terms of ppg
 - 2.1 Read in and prepare data from the '11-'12 season
 - 2.2 Fit a model that predicts '12-'13 ppg from '11-'12 statistics
 - 2.3 Evaluate the model's performance on '13-'14 (so far)