

# API DOCUMENTATION

## SoftifyBD

### Basic Information

SMS Server IP: 118.67.213.114

HTTP port: 3775    HTTPS port: 3770

Domain: portal.khudebarta.com

**Note: please check API key, Secret key and other parameters while configuring API link.**

### 1. SEND-RECEIVE SMS

Using this API, The Server can act as Origin and send sms to its own copy, or act as termination and receive sms.

Receive SM Request API:

#### **Parameters:**

| Parameter | Value   | Required |
|-----------|---|----------|
| apikey    | apikey provided by termination                | √        |
| secretkey | secretkey provided by termination             | √        |
| Content   | JSON formatted array of sms. Described bellow | √        |

#### **Request endpoint:**

- To send data as JSON object (supports multiple sms with single request)

<http://118.67.213.114:3775/send>

- To send data through simple parameters

<http://118.67.213.114:3775/sendtext>

#### **Sample request:**

##### **1. without hash request**

- [a. \[http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465&content=\\[{\]\(http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465&content=\[{\)](http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465&content=[{)

[{"callerID":"8801847","toUser":"452621,568468","messageContent":"abcd"}, {"callerID":"9101847","toUser":"912621,918468","messageContent":"abcd"}\]](#)

- b. <http://118.67.213.114:3775/sendtext?apikey=5d2a&secretkey=465&callerID=8801847&toUser=452621&messageContent=abcd>

## 2. with hash request

- a. [http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465&content=\[{"callerID":"8801847","toUser":"452621,568468","messageContent":"abcd"},{"callerID":"9101847","toUser":"912621,918468","messageContent":"abcd"}\]&hash=dsfasdasfsdf](http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465&content=[{)
- b. <http://118.67.213.114:3775/sendtext?apikey=5d2a&secretkey=465&callerID=8801847&toUser=452621&messageContent=abcd&hash=asdfsadds>

### **content parameter explained:**

There are 3 parameters for every content

1. callerID – Senders cell/identifying number
2. toUser – Semicolon separated receivers numbers.
3. messageContent – SMS content.

For example –

- a. `&callerID=8801847&toUser=452621&messageContent=abcd`
- b. data structured as json object for supporting multi sms with one request

```
[{
  "callerID":"8801847",
  "toUser":"452621;568468",
  "messageContent":"abcdef"
},
{
  "callerID":"9101847",
  "toUser":"912621;918468",
  "messageContent":"Hi"
}]
```

### **Response:**

#### **Example:**

```
{"Status":"0","Text":"ACCEPTE","Message_ID":"444"}
```

### **API Response Status:**

| Case                            | Response   |
|---------------------------------|--|
| If user not provided/Deleted    | {"Status": "109", "Text": "REJECTD", "Message_ID": ""}         |
| If wrong password/ not provided | {"Status": "108", "Text": "REJECTD", "Message_ID": ""}         |
| If content not provided         | {"Status": "114", "Text": "REJECTD", "Message_ID": ""}         |
| if internal server error occurs | {"Status": "101", "Text": "REJECTD", "Message_ID": ""}         |
| If request successful           | {"Status": "0", "Text": "Acceptd", "Message_ID": "message_id"} |
| If request failed               | {"Status": "1", "Text": "REJECTD", "Message_ID": ""}           |
| If TPS limit exceed             | {"Status": "137", "Text": "REJECTD", "Message_ID": ""}         |

### **Send SM Request:**

While sending sms from this server, the URL should contain two parts, the “request” part (**base URL**) should look like this

- a. for json structure

<http://118.67.213.114:3775/send?apikey=5d2a&secretkey=465>

and the “query” part (**query URL**) look like this

[&content=\[{"callerID": "REPLACE\\_FROM", "toUser": "REPLACE\\_TO", "messageContent": "REPLACE\\_MESSAGE"}\]](#)

- b. for simple request

<http://118.67.213.114:3775/sendtext?apikey=5d2a&secretkey=465>

and the “query” part (**query URL**) look like this

[&callerID=REPLACE\\_FROM&toUser=REPLACE\\_TO&messageContent=REPLACE\\_MESSAGE](#)

where

| Key             | meaning      |
|-----------------|--------------|
| REPLACE_FROM    | callers ID   |
| REPLACE_TO      | receivers ID |
| REPLACE_MESSAGE | message text |

### **Parsing Response from Termination**

#### **Response:**

Termination will send response after receiving an sms. Origination have to save response pattern for each termination as “Response Text”. The format of the response after receiving sms should be

explained in the “submit” part of the “Response Text” field of an http terminating client. This data has to be provided while adding the terminating client at the billing section of the origination.

```
{
  "submit": {
    "format": "json",
    "status": "Text",
    "successStatus": "ACCEPTE",
    "deliveryStatus": "DELIVRD",
    "messageId": "Message_ID",
    "fieldSeparator": "",
    "pairSeparator": ""
  },
  "deliver": {
    "format": "json",
    "status": "Text",
    "successStatus": "DELIVRD",
    "failedStatus": ["REJECTD"],
    "messageId": "Message_ID",
    "fieldSeparator": "",
    "pairSeparator": ""
  }
}
```

#### **Explanation of Response Text:**

| Key            | Meaning  |
|----------------|--|
| format         | format of the response   |
| status         | keyword in the response which contains the status text   |
| successStatus  | status text for accepted sms   |
| deliveryStatus | status text for accepted sms in case the terminating provider doesn't provide any delivery data. in this case 'successStatus' field should be blank. |

|                |  |
|----------------|--|
| messageld      | the id provided by this termination..  |
| fieldSeparator | character to separate parameters in case of the response in 'Text' format      |
| pairSeparator  | character to separate key-value pairs in case of the response in 'Text' format |

### **Example:**

1. If the response of a termination is in **json** format and the response is like this

```
{"Status":"0","Text":"ACCEPTD","Message_ID":"444"}
```

then the "Response Text" for that termination should look like this

```
{ "submit": { "format": "json", "status": "Text", "successStatus": "ACCEPTD", "deliveryStatus": "",  
"messageld": "Message_ID", "fieldSeparator": "", "pairSeparator": "" }, "deliver": { "format":  
"json", "status": "Text", "successStatus": "DELIVRD", "failedStatus": ["REJECTD"], "messageld": "Mess  
age_ID", "fieldSeparator": "", "pairSeparator": "" } }
```

2. If the response of a termination is in **json** format and the response is like this

```
{"Status":"0","Text":"DELIVRD","Message_ID":"444"}
```

then the "Response Text" for that termination should look like this

```
{ "submit": { "format": "json", "status": "Text", "successStatus": "", "deliveryStatus": "DELIVRD",  
"messageld": "Message_ID", "fieldSeparator": "", "pairSeparator": "" }, "deliver": { "format":  
"json", "status": "Text", "successStatus": "DELIVRD", "failedStatus": ["REJECTD"], "messageld": "Mess  
age_ID", "fieldSeparator": "", "pairSeparator": "" } }
```

- 3.

### **sample API Response:**

```
{  
  
  "Status":"0",  
  
  "Text":"ACCEPTD",  
  
  "Message_ID":"777"  
  
}
```

Next two APIs are for asking/providing SMS Status after sending/receiving SMS. A termination can provide the origin with "delivery URL", then it's up to the origination to ask for status. or the Origination can provide the termination with

“delivery URL”, then it’s up to the termination to inform the origination the sms status. This server implements both of this features So that it’s possible to connect with any of these servers.

## 2. ASK SMS STATUS

If the Termination provides “delivery URL”, then it’s up to the origination to do query on the termination for status receipt after sending the sms.

Using this API Origin asks SMS delivery receipt from this server. This “delivery URL” have to be added while creating Terminating HTTP client. server must provide the origination with **apikey** and **secretkey** for validating the query.

### Query the server for status

#### **Parameters:**

| Parameter | Value                             | Required |
|-----------|-----------------------------------|----------|
| apikey    | apikey provided by termination    | √        |
| secretkey | secretkey provided by termination | √        |
| messageid | id provided by the termination    | √        |

#### **Request format for this server:**

1. for single message ID

[http://118.67.213.114:3775/getstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageid=REPLACE\\_ID](http://118.67.213.114:3775/getstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageid=REPLACE_ID)

2. for multiple message ID

[http://118.67.213.114:3775/getmultistatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageids=REPLACE\\_ID](http://118.67.213.114:3775/getmultistatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageids=REPLACE_ID)

#### **example:**

1. for single message ID

<http://118.67.213.114:3775/getstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageid=7777>

2. for multiple message ID

<http://118.67.213.114:3775/getmultistatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&messageids=7777,7778,7779>

**Response:**

**Example:**

1. for single message ID

```
{"Status":"0","Text":"DELIVRD","Message_ID":"7777","Delivery Time":"1581330747547"}
```

2. for multiple message ID

```
[{"Status":"0","Text":"DELIVRD","Message_ID":"7777","Delivery Time":"1581330747547"}, {"Status":"0","Text":"DELIVRD","Message_ID":"7778","Delivery Time":"1581330747547"}, {"Status":"0","Text":"DELIVRD","Message_ID":"7779","Delivery Time":"1581330747547"}]
```

**API Response Status:**

| Case   | Response                             |
|--|--------------------------------------|
| If api key isn't provided  | {"Status": "109", "Text": "REJECTD"} |
| If wrong password/ not provided  | {"Status": "108", "Text": "REJECTD"} |
| If message id isn't provided   | {"Status": "114", "Text": "REJECTD"} |
| If message id isn't valid or query has been done already for the same id | {"Status": "114", "Text": "REJECTD"} |
| if internal server error occurs  | {"Status": "101", "Text": "REJECTD"} |
| if Authorization failed  | {"Status": "-42", "Text": "REJECTD"} |
| If request failed  | {"Status": "1", "Text": "REJECTD"}   |
| If request pending   | {"Status": "2", "Text": "PENDING"}   |
| If request sent  | {"Status": "4", "Text": "SENT"}      |
| If sms request successful  | {"Status": "0", "Text": "DELIVRD"}   |

**Response as Termination:**

**Response:**

Termination will send a response after receiving an query. Origination has to save response pattern for each termination as "Response Text". The format of the response after receiving sms should be explained in the "deliver" part of the "Response Text" field of an http terminating client. This data have to be provided while adding the terminating client at the billing section of the origination.

response format should be explained in "Response Text" fields "deliver" part in http terminating client



```

{
  "submit": {
    "format": "json",
    "status": "Text",
    "successStatus": "ACCEPTE",
    "deliveryStatus": "DELIVRD",
    "messageId": "Message_ID",
    "fieldSeparator": "",
    "pairSeparator": ""
  },
  "deliver": {
    "format": "json",
    "status": "Text",
    "successStatus": "DELIVRD",
    "failedStatus": ["REJECTD"],
    "messageId": "Message_ID",
    "fieldSeparator": "",
    "pairSeparator": ""
  }
}

```

### **Explanation of Response Text:**

| Key            | Meaning  |
|----------------|--|
| format         | format of the response   |
| status         | keyword in the response which contains the status text                         |
| successStatus  | status text for accepted sms   |
| failedStatus   | array of status text for rejected sms  |
| messageId      | the id provided by this termination  |
| fieldSeparator | character to separate parameters in case of the response in 'Text' format      |
| pairSeparator  | character to separate key-value pairs in case of the response in 'Text' format |

### **Example:**

If the response of a termination is in **json** format and the response is like this

```
{"Status":"0","Text":"DELIVRD","Message_ID":"444"}
```

then the "Response Text" for that termination should look like this

```
{ "submit": { "format": "json", "status": "Text", "successStatus": "ACCEPTD", "deliveryStatus": "", "messageId":  
"Message_ID", "fieldSeparator": "", "pairSeparator": "" }, "deliver": { "format": "json", "status": "Text",  
"successStatus": "DELIVRD", "failedStatus": ["REJECTD"], "messageId": "Message_ID", "fieldSeparator":  
"", "pairSeparator": "" } }
```

**sample API Response:**

```
{  
    "Status":"0",  
    "Text":"DELIVRD",  
    "Message_ID":"777"  
}
```

### 3.SEND SMS STATUS

If the Origination provides “**delivery URL**” ,then it’s up to the Termination to inform the Origination the status receipt after receiving, processing and sending the sms to the targeted clients.

Using this API server sends SMS delivery receipt to the Origination. This “**delivery URL**” has to be provided while creating Originating HTTP clients in the billing section for Origination .

#### Sending status to the origin

##### 1. using GET Method

**delivery url format of origination as set in web:**

[http://abc.com/submitstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&status=REPLACE\\_STATUS&text=REPLACE\\_TEXT&messageid=REPLACE\\_ID](http://abc.com/submitstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2&status=REPLACE_STATUS&text=REPLACE_TEXT&messageid=REPLACE_ID)

Valid delivery url will be created by replacing the following parts of the given url with appropriate data -

| Key            | meaning     |
|----------------|-------------|
| REPLACE_STATUS | status code |
| REPLACE_TEXT   | status text |
| REPLACE_ID     | message id  |

#### Formation or Response Text in Origin:

then the “Response Text” for that termination should look like this

```
{"submit":{"format":"json","status":"Text","successStatus":"ACCEPTD","deliveryStatus":"","messageId":"Message_ID","fieldSeparator":"","pairSeparator":""}, "deliver": { "format":"","status":"text", "successStatus":"DELIVRD", "failedStatus":["REJECTD"], "messageId":"message","fieldSeparator":"","pairSeparator":"" } }
```

## 2. using POST Method

**delivery url format of origination as set in web:**

<http://abc.com/submitstatus?apikey=5d2a5cebf00d66bb65f30b5a81c882e4&secretkey=46586ec2>

parameters= Status:value, Message\_ID:value, Text:value

example: Status:0, Message\_ID:775000, Text:DELIVRD

**Formation or Response Text in Origin:**

if the termination submits the values as post parameters, then the "Response Text" for that termination should look like this

```
{"submit":{"format":"json","status":"Text","successStatus":"ACCEPTD","deliveryStatus":"","messageId":"Message_ID","fieldSeparator":"","pairSeparator":"","deliver":{"format":"","status":"Text","successStatus":"DELIVRD","failedStatus":["REJECTD"],"messageId":"Message_ID","fieldSeparator":"","pairSeparator":""}}
```

Valid delivery data will contain following types of data -

| Status                 | Key in GET Method | meaning    |
|------------------------|-------------------|------------|
| Successfully delivered | REPLACE_STATUS    | 0          |
|                        | REPLACE_TEXT      | DELIVRD    |
|                        | REPLACE_ID        | message id |
| Failed to deliver      | REPLACE_STATUS    | 1          |
|                        | REPLACE_TEXT      | REJECTD    |
|                        | REPLACE_ID        | message id |
| Authorization Failed   | REPLACE_STATUS    | -42        |
|                        | REPLACE_TEXT      | REJECTD    |
|                        | REPLACE_ID        | message id |

Response as origin from server

**Response Example:**

```
{"Status":"0","Text":"SUCCESS","Message_ID":"444"}
```

**API Response Status:**

| Case | Response |
|------|----------|
|------|----------|

|  |                                      |
|--|--------------------------------------|
| If user not provided/Deleted                   | {"Status": "109", "Text": "REJECTD"} |
| If wrong password/ not provided                | {"Status": "108", "Text": "REJECTD"} |
| If content not provided                        | {"Status": "114", "Text": "REJECTD"} |
| If status doesn't match with configured status | {"Status": "137", "Text": "REJECTD"} |
| if internal server error occurs                | {"Status": "101", "Text": "REJECTD"} |
| If request successful                          | {"Status": "0", "Text": "SUCCESS"}   |
| If request failed                              | {"Status": "1", "Text": "REJECTD"}   |