

CHANGELOG

7.3

- Add `RunProcessMessage::fromShellCommandline()` to instantiate a `Process` via the `fromShellCommandline` method

7.1

- Add `Process::setIgnoredSignals()` to disable signal propagation to the child process

6.4

- Add `PhpSubprocess` to handle PHP subprocesses that take over the configuration from their parent
- Add `RunProcessMessage` and `RunProcessMessageHandler`

5.2.0

- added `Process::setOptions()` to set `Process` specific options
- added option `create_new_console` to allow a subprocess to continue to run after the main script exited, both on Linux and on Windows

5.1.0

- added `Process::getStartTime()` to retrieve the start time of the process as float

5.0.0

- removed `Process::inheritEnvironmentVariables()`
- removed `PhpProcess::setPhpBinary()`
- `Process` must be instantiated with a command array, use `Process::fromShellCommandline()` when the command should be parsed by the shell
- removed `Process::setCommandLine()`

4.4.0

- deprecated `Process::inheritEnvironmentVariables()`: env variables are always inherited.
- added `Process::getLastOutputTime()` method

4.2.0

- added the `Process::fromShellCommandline()` to run commands in a shell wrapper

- deprecated passing a command as string when creating a `Process` instance
- deprecated the `Process::setCommandline()` and the `PhpProcess::setPhpBinary()` methods
- added the `Process::waitUntil()` method to wait for the process only for a specific output, then continue the normal execution of your application

4.1.0

- added the `Process::isTtySupported()` method that allows to check for TTY support
- made `PhpExecutableFinder` look for the `PHP_BINARY` env var when searching the php binary
- added the `ProcessSignaledException` class to properly catch signaled process errors

4.0.0

- environment variables will always be inherited
- added a second array `$env = []` argument to the `start()`, `run()`, `mustRun()`, and `restart()` methods of the `Process` class
- added a second array `$env = []` argument to the `start()` method of the `PhpProcess` class
- the `ProcessUtils::escapeArgument()` method has been removed
- the `areEnvironmentVariablesInherited()`, `getOptions()`, and `setOptions()` methods of the `Process` class have been removed
- support for passing `proc_open()` options has been removed
- removed the `ProcessBuilder` class, use the `Process` class instead
- removed the `getEnhanceWindowsCompatibility()` and `setEnhanceWindowsCompatibility()` methods of the `Process` class
- passing a not existing working directory to the constructor of the `Symfony\Component\Process\Process` class is not supported anymore

3.4.0

- deprecated the `ProcessBuilder` class
- deprecated calling `Process::start()` without setting a valid working directory beforehand (via `setWorkingDirectory()` or constructor)

3.3.0

- added command line arrays in the `Process` class
- added `$env` argument to `Process::start()`, `run()`, `mustRun()` and `restart()` methods
- deprecated the `ProcessUtils::escapeArgument()` method
- deprecated not inheriting environment variables
- deprecated configuring `proc_open()` options

- deprecated configuring enhanced Windows compatibility
- deprecated configuring enhanced sigchild compatibility

2.5.0

- added support for PTY mode
- added the convenience method “mustRun”
- deprecation: `Process::setStdin()` is deprecated in favor of `Process::setInput()`
- deprecation: `Process::getStdin()` is deprecated in favor of `Process::getInput()`
- deprecation: `Process::setInput()` and `ProcessBuilder::setInput()` do not accept non-scalar types

2.4.0

- added the ability to define an idle timeout

2.3.0

- added `ProcessUtils::escapeArgument()` to fix the bug in `escapeshellarg()` function on Windows
- added `Process::signal()`
- added `Process::getPid()`
- added support for a TTY mode

2.2.0

- added `ProcessBuilder::setArguments()` to reset the arguments on a builder
- added a way to retrieve the standard and error output incrementally
- added `Process::restart()`

2.1.0

- added support for non-blocking processes (`start()`, `wait()`, `isRunning()`, `stop()`)
- enhanced Windows compatibility
- added `Process::getExitCodeText()` that returns a string representation for the exit code returned by the process
- added `ProcessBuilder`