

# CHANGELOG

## 7.3

- Add `TreeHelper` and `TreeStyle` to display tree-like structures
- Add `SymfonyStyle::createTree()`
- Add support for invocable commands and add `#[Argument]` and `#[Option]` attributes to define input arguments and options
- Deprecate not declaring the parameter type in callable commands defined through `setCode` method
- Add support for help definition via `AsCommand` attribute
- Deprecate methods `Command::getDefaultName()` and `Command::getDefaultDescription()` in favor of the `#[AsCommand]` attribute
- Add support for Markdown format in `Table`
- Add support for `LockableTrait` in invocable commands
- Deprecate returning a non-integer value from a `\Closure` function set via `Command::setCode()`
- Mark `#[AsCommand]` attribute as `@final`
- Add support for `SignalableCommandInterface` with invocable commands

## 7.2

- Add support for `FORCE_COLOR` environment variable
- Add `verbosity` argument to `mustRun` process helper method
- [BC BREAK] Add silent verbosity (`--silent/SHELL_VERBOSITY=-2`) to suppress all output, including errors
- Add `OutputInterface::isSilent()`, `Output::isSilent()`, `OutputStyle::isSilent()` methods
- Add a configurable finished indicator to the progress indicator to show that the progress is finished
- Add ability to schedule alarm signals and a `ConsoleAlarmEvent`

## 7.1

- Add `ArgvInput::getRawTokens()`

## 7.0

- Add method `__toString()` to `InputInterface`
- Remove `Command::$defaultName` and `Command::$defaultDescription`, use the `AsCommand` attribute instead
- Require explicit argument when calling `*Command::setApplication()`, `*FormatterStyle::setForeground/setBackground()`, `Helper::setHelpSet()`, `Input*::setDefault()` and `Question::setAutocompleterCallback/setValidator()`
- Remove `StringInput::REGEX_STRING`

## 6.4

- Add `SignalMap` to map signal value to its name
- Multi-line text in vertical tables is aligned properly
- The application can also catch errors with `Application::setCatchErrors(true)`
- Add `RunCommandMessage` and `RunCommandMessageHandler`
- Dispatch `ConsoleTerminateEvent` after an exit on signal handling and add `ConsoleTerminateEvent::getInterruptingSignal()`

## 6.3

- Add support for choosing exit code while handling signal, or to not exit at all
- Add `ProgressBar::setPlaceholderFormatter` to set a placeholder attached to a instance, instead of being global.
- Add `ReStructuredTextDescriptor`

## 6.2

- Improve truecolor terminal detection in some cases
- Add support for 256 color terminals (conversion from `Ansi24` to `Ansi8` if terminal is capable of it)
- Deprecate calling `*Command::setApplication()`, `*FormatterStyle::setForeground/setBackground()`, `Helper::setHelperSet()`, `Input*::setDefault()`, `Question::setAutocompleterCallback/setValidate()` any arguments
- Change the signature of `OutputFormatterStyleInterface::setForeground/setBackground()` to `setForeground/setBackground(?string)`
- Change the signature of `HelperInterface::setHelperSet()` to `setHelperSet(?HelperSet)`

## 6.1

- Add support to display table vertically when calling `setVertical()`
- Add method `__toString()` to `InputInterface`
- Added `OutputWrapper` to prevent truncated URL in `SymfonyStyle::createBlock`.
- Deprecate `Command::$defaultName` and `Command::$defaultDescription`, use the `AsCommand` attribute instead
- Add suggested values for arguments and options in input definition, for input completion
- Add `$resumeAt` parameter to `ProgressBar#start()`, so that one can easily ‘resume’ progress on longer tasks, and still get accurate `getEstimate()` and `getRemaining()` results.

## 6.0

- `Command::setHidden()` has a default value (`true`) for `$hidden` parameter and is final

- Remove `Helper::strlen()`, use `Helper::width()` instead
- Remove `Helper::strlenWithoutDecoration()`, use `Helper::removeDecoration()` instead
- `AddConsoleCommandPass` can not be configured anymore
- Remove `HelperSet::setCommand()` and `getCommand()` without replacement

## 5.4

- Add `TesterTrait::assertCommandIsSuccessful()` to test command
- Deprecate `HelperSet::setCommand()` and `getCommand()` without replacement

## 5.3

- Add `GithubActionReporter` to render annotations in a Github Action
- Add `InputOption::VALUE_NEGATABLE` flag to handle `--foo/--no-foo` options
- Add the `Command::$defaultDescription` static property and the `description` attribute on the `console.command` tag to allow the `list` command to instantiate commands lazily
- Add option `--short` to the `list` command
- Add support for bright colors
- Add `#[AsCommand]` attribute for declaring commands on PHP 8
- Add `Helper::width()` and `Helper::length()`
- The `--ansi` and `--no-ansi` options now default to `null`.

## 5.2.0

- Added `SingleCommandApplication::setAutoExit()` to allow testing via `CommandTester`
- added support for multiline responses to questions through `Question::setMultiline()` and `Question::isMultiline()`
- Added `SignalRegistry` class to stack signals handlers
- Added support for signals:
  - Added `Application::getSignalRegistry()` and `Application::setSignalsToDispatchEvent()` methods
  - Added `SignalableCommandInterface` interface
- Added `TableCellStyle` class to customize table cell
- Removed `php` prefix invocation from help messages.

## 5.1.0

- `Command::setHidden()` is final since Symfony 5.1
- Add `SingleCommandApplication`
- Add `Cursor` class

### 5.0.0

- removed support for finding hidden commands using an abbreviation, use the full name instead
- removed `TableStyle::setCrossingChar()` method in favor of `TableStyle::setDefaultCrossingChar()`
- removed `TableStyle::setHorizontalBorderChar()` method in favor of `TableStyle::setDefaultCrossingChars()`
- removed `TableStyle::getHorizontalBorderChar()` method in favor of `TableStyle::getBorderChars()`
- removed `TableStyle::setVerticalBorderChar()` method in favor of `TableStyle::setVerticalBorderChars()`
- removed `TableStyle::getVerticalBorderChar()` method in favor of `TableStyle::getBorderChars()`
- removed support for returning null from `Command::execute()`, return 0 instead
- `ProcessHelper::run()` accepts only `array|Symfony\Component\Process\Process` for its command argument
- `Application::setDispatcher` accepts only `Symfony\Contracts\EventDispatcher\EventDispatcherInterface` for its dispatcher argument
- renamed `Application::renderException()` and `Application::doRenderException()` to `renderThrowable()` and `doRenderThrowable()` respectively.

### 4.4.0

- deprecated finding hidden commands using an abbreviation, use the full name instead
- added `Question::setTrimmable` default to true to allow the answer to be trimmed
- added method `minSecondsBetweenRedraws()` and `maxSecondsBetweenRedraws()` on `ProgressBar`
- `Application` implements `ResetInterface`
- marked all dispatched event classes as `@final`
- added support for displaying table horizontally
- deprecated returning null from `Command::execute()`, return 0 instead
- Deprecated the `Application::renderException()` and `Application::doRenderException()` methods, use `renderThrowable()` and `doRenderThrowable()` instead.
- added support for the `NO_COLOR` env var (<https://no-color.org/>)

### 4.3.0

- added support for hyperlinks
- added `ProgressBar::iterate()` method that simplify updating the progress bar when iterating
- added `Question::setAutocompleterCallback()` to provide a callback function that dynamically generates suggestions as the user types

#### 4.2.0

- allowed passing commands as `[$process, 'ENV_VAR' => 'value']` to `ProcessHelper::run()` to pass environment variables
- deprecated passing a command as a string to `ProcessHelper::run()`, pass it the command as an array of its arguments instead
- made the `ProcessHelper` class final
- added `WrappableOutputFormatterInterface::formatAndWrap()` (implemented in `OutputFormatter`)
- added `capture_stderr_separately` option to `CommandTester::execute()`

#### 4.1.0

- added option to run suggested command if command is not found and only 1 alternative is available
- added option to modify console output and print multiple modifiable sections
- added support for iterable messages in output `write` and `writeln` methods

#### 4.0.0

- `OutputFormatter` throws an exception when unknown options are used
- removed `QuestionHelper::setInputStream()/getInputStream()`
- removed `Application::getTerminalWidth()/getTerminalHeight()` and `Application::setTerminalDimensions()/getTerminalDimensions()`
- removed `ConsoleExceptionEvent`
- removed `ConsoleEvents::EXCEPTION`

#### 3.4.0

- added `SHELL_VERBOSITY` env var to control verbosity
- added `CommandLoaderInterface`, `FactoryCommandLoader` and `PSR-11 ContainerCommandLoader` for commands lazy-loading
- added a case-insensitive command name matching fallback
- added static `Command::$defaultName/getDefaultName()`, allowing for commands to be registered at compile time in the application command loader. Setting the `$defaultName` property avoids the need for filling the `command` attribute on the `console.command` tag when using `AddConsoleCommandPass`.

#### 3.3.0

- added `ExceptionListener`
- added `AddConsoleCommandPass` (originally in `FrameworkBundle`)
- [BC BREAK] `Input::getOption()` no longer returns the default value for options with value optional explicitly passed empty
- added `console.error` event to catch exceptions thrown by other listeners

- deprecated `console.exception` event in favor of `console.error`
- added ability to handle `CommandNotFoundException` through the `console.error` event
- deprecated default validation in `SymfonyQuestionHelper::ask`

### 3.2.0

- added `setInputs()` method to `CommandTester` for ease testing of commands expecting inputs
- added `setStream()` and `getStream()` methods to `Input` (implement `StreamableInputInterface`)
- added `StreamableInputInterface`
- added `LockableTrait`

### 3.1.0

- added `truncate` method to `FormatterHelper`
- added `setColumnWidth(s)` method to `Table`

### 2.8.3

- remove readline support from the question helper as it caused issues

### 2.8.0

- use readline for user input in the question helper when available to allow the use of arrow keys

### 2.6.0

- added a `Process` helper
- added a `DebugFormatter` helper

### 2.5.0

- deprecated the `dialog` helper (use the question helper instead)
- deprecated `TableHelper` in favor of `Table`
- deprecated `ProgressHelper` in favor of `ProgressBar`
- added `ConsoleLogger`
- added a question helper
- added a way to set the process name of a command
- added a way to set a default command instead of `ListCommand`

### 2.4.0

- added a way to force terminal dimensions
- added a convenient method to detect verbosity level

- [BC BREAK] made descriptors use output instead of returning a string

### 2.3.0

- added multiselect support to the select dialog helper
- added Table Helper for tabular data rendering
- added support for events in `Application`
- added a way to normalize EOLs in `ApplicationTester::getDisplay()` and `CommandTester::getDisplay()`
- added a way to set the progress bar progress via the `setCurrent` method
- added support for multiple InputOption shortcuts, written as `'-a|-b|-c'`
- added two additional verbosity levels, `VERBOSITY_VERY_VERBOSE` and `VERBOSITY_DEBUG`

### 2.2.0

- added support for colorization on Windows via ConEmu
- add a method to Dialog Helper to ask for a question and hide the response
- added support for interactive selections in console (`DialogHelper::select()`)
- added support for autocompletion as you type in Dialog Helper

### 2.1.0

- added `ConsoleOutputInterface`
- added the possibility to disable a command (`Command::isEnabled()`)
- added suggestions when a command does not exist
- added a `--raw` option to the list command
- added support for `STDERR` in the console output class (errors are now sent to `STDERR`)
- made the defaults (helper set, commands, input definition) in `Application` more easily customizable
- added support for the shell even if `readline` is not available
- added support for process isolation in Symfony shell via `--process-isolation` switch
- added support for `--`, which disables options parsing after that point (tokens will be parsed as arguments)