

phpunit/php-timer



Utility class for timing things, factored out of PHPUnit into a stand-alone component.

Installation

You can add this library as a local, per-project dependency to your project using Composer:

```
composer require phpunit/php-timer
```

If you only need this library during development, for instance to run your project's test suite, then you should add it as a development-time dependency:

```
composer require --dev phpunit/php-timer
```

Usage

Basic Timing

```
require __DIR__ . '/vendor/autoload.php';

use SebastianBergmann\Timer\Timer;

$timer = new Timer;

$timer->start();

foreach (\range(0, 100000) as $i) {
    // ...
}

$duration = $timer->stop();

var_dump(get_class($duration));
var_dump($duration->asString());
var_dump($duration->asSeconds());
var_dump($duration->asMilliseconds());
var_dump($duration->asMicroseconds());
var_dump($duration->asNanoseconds());
```

The code above yields the output below:

```
string(32) "SebastianBergmann\Timer\Duration"
string(9) "00:00.002"
float(0.002851062)
```

```
float(2.851062)
float(2851.062)
int(2851062)
```

Resource Consumption

Explicit duration

```
require __DIR__ . '/vendor/autoload.php';

use SebastianBergmann\Timer\ResourceUsageFormatter;
use SebastianBergmann\Timer\Timer;

$timer = new Timer;
$timer->start();

foreach (\range(0, 100000) as $i) {
    // ...
}

print (new ResourceUsageFormatter)->resourceUsage($timer->stop());
```

The code above yields the output below:

Time: 00:00.002, Memory: 6.00 MB

Duration since PHP Startup (using unreliable \$_SERVER['REQUEST_TIME_FLOAT'])

```
require __DIR__ . '/vendor/autoload.php';

use SebastianBergmann\Timer\ResourceUsageFormatter;

foreach (\range(0, 100000) as $i) {
    // ...
}

print (new ResourceUsageFormatter)->resourceUsageSinceStartOfRequest();
```

The code above yields the output below:

Time: 00:00.002, Memory: 6.00 MB