

Department I - C Plus Plus

Modern and Lucid C++ Advanced
for Professional Programmers

Week 13 – Hourglass Interfaces

Prof. Peter Sommerlad / Thomas Corbat
Rapperswil, 16.05.2019
FS2019



Hourglass Interfaces


based on Stefanus DuToit "Hourglass Interfaces" talk at CppCon 2016

<https://www.youtube.com/watch?v=PVYdHDm0q6Y>



- **DLL APIs work best (and cross-platform compatible) with C only**
 - We ignore the Windows burden of providing DLL-export and DLL-import syntax
- **C++ can provide C-compatible function interfaces using extern "C" in front of a declaration**
- **C-APIs are error-prone and can be tedious to use**
- **C++ exceptions do not pass nicely across a C-API**
- **Foreign language bindings (e.g. for Python etc) often expect C-APIs**
- **API - Application Programming Interface**
 - If stable, you do not need to change your code, if something changes
- **ABI - Application Binary Interface**
 - If stable, you can use and share DLLs/shared libraries without recompilation
- **Not universally applicable, but very common**


- **Shape of an hourglass**




- **Let's add some functionality to our Wizard**

- `doMagic()` – still casts a spell ("wootsh") or uses a potion ("zapp")
- `learnSpell()` – learns a new spell (by name)
- `maxAndStorePotion()` – creates a potion and puts it to the inventory
- `getName()` – function to make Java programmers happy, otherwise there wouldn't be a "getX" function

```
struct Wizard {  
    Wizard(std::string name = "Rincewind")  
        : name{name}, wand{} {  
    }  
    char const * doMagic(std::string const & wish);  
    void learnSpell(std::string const & newspell);  
    void mixAndStorePotion(std::string const & potion);  
    char const * getName() const {  
        return name.c_str();  
    }  
};
```



- **Testing a wizard provides the same view a client has**



```
using wizard_client::Wizard;

void canCreateDefaultWizard() {
    Wizard const magician{};
    ASSERT_EQUAL("Rincewind", magician.getName());
}


void canCreateWizardWithName() {
    Wizard const magician{ "Petrosilius Zwackelmann" };
    ASSERT_EQUAL("Petrosilius Zwackelmann", magician.getName());
}

void wizardLearnsSpellAndCanRecall() {
    Wizard magician{};
    magician.learnSpell("Expelliarmus");
    ASSERT_EQUAL("wootsh", magician.doMagic("Expelliarmus"));
}

void wizardMixesPotionAndCanApply() {
    Wizard magician{};
    magician.mixAndStorePotion("Polyjuice Potion");
    ASSERT_EQUAL("zapp", magician.doMagic("Polyjuice Potion"));
}

void unknownMagicFails() {
    Wizard magician{};
    ASSERT_THROWS(magician.doMagic("Expecto Patronum!"), std::runtime_error);
}
```

- **Abstract data types can be represented by pointers**
 - Ultimate abstract pointer `void *`
- **Member functions map to functions taking the abstract data type pointer as first argument**
- **Requires Factory and Disposal functions to manage object lifetime**
- **Strings can only be represented by `char *`**
 - Need to know who will be responsible for memory
 - Make sure not to return pointers to temporary objects!
- **Exceptions do not work across a C API**



- **A Wizard can only be accessed through a pointer (const and non-const)**
 - Construction and destruction through functions
- **An error pointer stores messages of exceptions**
 - Functions that may fail need an error pointer parameter for reporting exceptions
 - Errors need to be cleaned up when not used anymore
- **Member functions take a Wizard (pointer) as first parameter**

Wizard.h

```
typedef struct Wizard * wizard;
typedef struct Wizard const * cwizard;
wizard createWizard(char const * name,
                   error_t * out_error);
void disposeWizard(wizard toDispose);

typedef struct Error * error_t;
char const * error_message(error_t error);
void error_dispose(error_t error);

char const *doMagic(wizard w,
                   char const * wish,
                   error_t *out_error);
void learnSpell(wizard w,
               char const * spell);
void mixAndStorePotion(wizard w,
                     char const * potion);
char const *wizardName(cwizard w);
```


- **Functions, but not templates or variadic**
 - No overloading in C!
- **C primitive types (char, int, double, void)**
- **Pointers, including function pointers**
- **Forward-declared structs**
 - Pointers to those are opaque types!
 - Are used for abstract data types
- **Enums (unscoped - without class or base type!)**
- **If using from C must embrace it with extern "C" when compiling it with C++**
 - Otherwise names do not match, because of mangling

Wizard.h

```
#ifdef __cplusplus
extern "C" {
#endif

typedef struct Wizard * wizard;
typedef struct Wizard const * cwizard;
wizard createWizard(char const * name,
                    error_t * out_error);
void disposeWizard(wizard toDispose);

// ...
// Comments are ok too, as the preprocessor
// eliminates them anyway

#ifdef __cplusplus
}
#endif
```

- **Wizard class must be implemented**
- **To allow full C++ including templates, we need to use a "trampoline" class**
 - It wraps the actual Wizard implementation

Wizard.cpp

```
extern "C" {  
struct Wizard { // C linkage trampoline  
    Wizard(char const * name)  
        : wiz{name} {  
    }  
    unseen::Wizard wiz;  
};
```

WizardHidden.h

```
namespace unseen {  
struct Wizard {  
    // ...  
    Wizard(std::string name = "Rincewind")  
        : name{name}, wand{} {  
    }  
    char const * doMagic(std::string const & wish);  
    void learnSpell(std::string const & newspell);  
    void mixAndStorePotion(std::string const & potion);  
    char const * getName() const {  
        return name.c_str();  
    }  
};  
}
```

Note: The Hairpoll example of Stefanus Du Toit has non-standard code in the trampoline

- Remember the 5 ways to deal with errors!
- You can't use references in C API, must use pointers to pointers
- In case of an error, allocate error value on the heap
 - You must provide a disposal function to clean up
- You can use C++ types internally (std::string)
- It is safe to return the char const *
 - because caller owns the object providing the memory

Wizard.h

```
typedef struct Error * error_t;
char const * error_message(error_t error);
void error_dispose(error_t error);

wizard createWizard(char const * name,
                    error_t * out_error);
```

Wizard.cpp

```
extern "C" {
struct Error {
    std::string message;
};

const char * error_message(error_t error) {
    return error->message.c_str();
}

void error_dispose(error_t error) {
    delete error;
}
}
```


- **Call the function body and catch exceptions**
- **Map them to an Error object**
- **Set the pointer pointed to by out_error**
 - Use pointer to pointer as reference to pointer
 - Passed out_error must not be nullptr!

Wizard.cpp

```
template<typename Fn>
bool translateExceptions(error_t * out_error, Fn && fn)
try {
    fn();
    return true;
} catch (const std::exception& e) {
    *out_error = new Error{e.what()};
    return false;
} catch (...) {
    *out_error = new Error{"Unknown internal error"};
    return false;
}


wizard createWizard(const char * name,
                    error_t * out_error) {
    wizard result = nullptr;
    translateExceptions(out_error, [&] {
        result = new Wizard{name};
    });
    return result;
}
```

- **Client-side C++ usage requires mapping error codes back to exceptions**
 - Unfortunately exception type doesn't map through
 - But can use a generic standard exception
 - `std::runtime_error`, keep the message
 - Dedicated RAI class for disposal
- **Temporary object with throwing destructor**
 - Strange but possible
 - Automatic type conversion passes the address of its guts (opaque)
 - Tricky, take care you don't leak when creating the object!

WizardClient.h

```
struct ErrorRAII {
    ErrorRAII(error_t error) : opaque {error} {}
    ~ErrorRAII() {
        if (opaque) {
            error_dispose(opaque);
        }
    }
    error_t opaque;
};

struct ThrowOnError {
    ThrowOnError() = default;
    ~ThrowOnError() noexcept(false) {
        if (error.opaque) {
            throw std::runtime_error{error_message(error.opaque)};
        }
    }
    operator error_t*() {
        return &error.opaque;
    }
private:
    ErrorRAII error{nullptr};
};
```



WizardClient.h

```
struct ThrowOnError {
    ThrowOnError() = default;
    ~ThrowOnError() noexcept(false) {
        if (error.opaque) {
            throw std::runtime_error{error_message(error.opaque)};
        }
    }
    operator error_t*() {
        return &error.opaque;
    }
private:
    ErrorRAII error{nullptr};
};

struct Wizard {
    Wizard(std::string const & who = "Rincewind")
        : wiz {createWizard(who.c_str(), ThrowOnError{})} {
    }
    // C linkage trampoline
};
```


- **Here the complete view of the client side Wizard class**
- **Calls "C" functions from global namespace**
 - Namespace prefix needed for synonyms to member functions
- **Header-only**
 - Inline functions delegating
- **Need to take care of passed and returned Pointers, esp. char ***
 - Do not pass/return dangling pointers!

WizardClient.h

```
struct Wizard {
    Wizard(std::string const & who = "Rincewind")
        : wiz {createWizard(who.c_str(), ThrowOnError{})} {}
    ~Wizard() {
        disposeWizard(wiz);
    }
    std::string doMagic(std::string const & wish) {
        return ::doMagic(wiz, wish.c_str(), ThrowOnError{});
    }
    void learnSpell(std::string const & spell) {
        ::learnSpell(wiz, spell.c_str());
    }
    void mixAndStorePotion(std::string const & potion) {
        ::mixAndStorePotion(wiz, potion.c_str());
    }
    char const * getName() const {
        return wizardName(wiz);
    }
private:
    Wizard(Wizard const &) = delete;
    Wizard & operator=(Wizard const &) = delete;
    wizard wiz;
};
```

- **With the Gnu compiler (and clang I presume)**

- -fvisibility=hidden
 - Can be added to suppress exporting symbols
 - Must mark exported ABI functions with default visibility

- **Visibility refers to dynamic library/object file export of symbols**

- Windows: `__declspec(dllexport)`
- See also hairpoll demo project
<https://youtu.be/PVYdHDm0q6Y>
- For more on gcc visibility (expert-level knowledge):
see <https://gcc.gnu.org/wiki/Visibility>

WizardClient.h

```
#define WIZARD_EXPORT_DLL
        __attribute__((visibility ("default")))

WIZARD_EXPORT_DLL
char const * error_message(error_t error);
WIZARD_EXPORT_DLL
void error_dispose(error_t error);

WIZARD_EXPORT_DLL
wizard createWizard(char const * name,
                   error_t *out_error);

WIZARD_EXPORT_DLL
void disposeWizard(wizard toDispose);

WIZARD_EXPORT_DLL
char const * doMagic(wizard w,
                    char const * wish,
                    error_t *out_error);

WIZARD_EXPORT_DLL
void learnSpell(wizard w, char const *spell);
WIZARD_EXPORT_DLL
void mixAndStorePotion(wizard w, char const *potion);
WIZARD_EXPORT_DLL
char const * wizardName(cwizard w);
```

- **Library API and ABI design can be tricky for third party users**
 - Only really a problem if not in-house or all open source
 - Even with open source libraries, re-compiles can be a burden
 - There are just too many compiler options
 - Plus DLL versioning
- **API stability can be important**
 - PIMPL idiom helps with avoiding client re-compiles (but should be considered a legacy)
 - Not easily applicable with heavily templated code -> that often is header-only
- **ABI stability is even more important when delivering DLLs/shared libraries**
 - Only relevant when not header-only
 - “C” linkage safe, but crippling - Hourglass-Interfaces allow shielding C++ clients from the crippled ABI
 - Still easy to make mistakes (which we always tried to avoid)