

Literature Review

Salome Bachmann

March 12, 2026



Overview of literature review

- Literature review of 13 papers
- Main topics: crack propagation in snow, snow modeling, modeling in more general sense (introduction to different modeling methods used)
- Modeling methods: Material Point Method (MPM) and Discrete Element Method (DEM)

Motivation

- Understanding the different modeling methods and their limitation is important for thesis to understand which methods are suited for what
- Understanding how cracks propagate and which factors influence them is important for risk assessment
- Understanding which factors lead to supershear crack propagation is also important for risk assessment

Modeling Methods

- Two main methods used: MPM and DEM
- DEM described by Cundall and Strack, 1979, material of disks & spheres, contact forces and resulting displacements calculated
- MPM where material is discretized in points with Eulerian background mesh to calculate stresses at points and time-dependent equations, for example in Gaume et al., 2018
- MPM is more favorable for slope-scale simulations because of modelling of grain contacts
- Other models for snow such as SNOWPACK (Bartelt & Lehning, 2002) and CROCUS (Brun et al., 1992) model snowpack response to external factors

Avalanche Release - General Crack Propagation

- All papers agree on avalanche formation by loading - weak layer failure
- Some papers discuss anticrack propagation (closure of cracks formed) like eg Gaume et al., 2018
- Others state shear cracks to be the main failure mode
- Bergfeld et al., 2025 combine the two main hypotheses: anticrack early in avalanche propagation, shearing later

Factors influencing crack propagation

- Slope angle: higher slope angle generally increases crack speed and can trigger transition from sub-Rayleigh to supershear; it can also reduce the critical crack length needed for release (Bobillier et al., 2024; Gaume et al., 2017; Trottet et al., 2022)
- Slab stiffness (elastic modulus): stiffer slabs lead to lower normalized crack speed in some DEM results, but it tends to increase critical crack length (more crack growth needed before release) (Bobillier et al., 2024; Gaume et al., 2017)
- Weak layer strength & elastic modulus: higher weak-layer elastic modulus can increase crack speed; stronger weak layers generally require more energy/longer cracks for release (Bobillier et al., 2024; Gaume et al., 2015; Gaume et al., 2017)

Factors influencing crack propagation (continued)

- Slab density: higher slab density is associated with faster propagation in some models, while also reducing critical crack length for release (Gaume et al., 2015; Gaume et al., 2017)
- Slab thickness: thicker slabs can increase propagation speed in DEM studies; in critical-crack formulations, greater slab thickness lowers critical crack length (Gaume et al., 2015; Gaume et al., 2017)
- Weak layer thickness: thinner weak layers can lead to faster crack propagation and lower critical crack length for release (Gaume et al., 2015; Gaume et al., 2017)
- Snow structure and loading rate: sintering and lower loading rates can lead to more stable snowpacks, which means higher critical crack lengths (Mulak & Gaume, 2019)

Deformation stages

- After loading, multiple stages of deformation
- loading response by an elastic regime, a drop in pressure and shear stress, volumetric collapse of the weak layer and lastly dense packing (Gaume et al., 2018)
- Slab bending induced by weak layer collapse at bottom of snowpack (Bergfeld et al., 2025)
- Deformation because of slab tension at top of snow (Bergfeld et al., 2025)

Crack propagation direction

- Direction of crack propagation dependent on simulation scale (Trottet et al., 2022)
- Small-scale: propagation upslope (remote triggering), because collapse depth for bending limited by weak layer collapse (Trottet et al., 2022)
- Large-scale: downslope, because propagation speed can increase because of slab tension (Trottet et al., 2022)

Bibliography



Bartelt, P., & Lehning, M. (2002). A physical SNOWPACK model for the Swiss avalanche warning: Part I: Numerical model. *Cold Regions Science and Technology*, 35(3), 123–145. [https://doi.org/10.1016/S0165-232X\(02\)00074-5](https://doi.org/10.1016/S0165-232X(02)00074-5)



Bergfeld, B., Gaume, J., Bobillier, G., Pellet, A., Schweizer, J., & van Herwijnen, A. (2025). Signatures of the sub-Rayleigh to supershear fracture transition in snow avalanche experiments. *Nature Communications*, 16(1), 11153. <https://doi.org/10.1038/s41467-025-65825-6>



Bobillier, G., Bergfeld, B., Dual, J., Gaume, J., van Herwijnen, A., & Schweizer, J. (2024). Numerical investigation of crack propagation regimes in snow fracture experiments. *Granular Matter*, 26(3), 58. <https://doi.org/10.1007/s10035-024-01423-5>



Brun, E., David, P., Sudul, M., & Brunot, G. (1992). A numerical model to simulate snow-cover stratigraphy for operational avalanche forecasting. *Journal of Glaciology*, 38(128), 13–22. <https://doi.org/10.3189/S0022143000009552>



Cundall, P. A., & Strack, O. D. L. (1979). A discrete numerical model for granular assemblies. *Géotechnique*, 29(1), 47–65.



Salome Bachmann
Master Student
sbachmann@student.ethz.ch

ETH Zurich
D-EAPS