

From Particles to Waves

Towards Coupling Dynamic
Snow Modelling and Spectral
Elements to Detect
Avalanche Breakoff in DAS
Data

Salome Bachmann

August 14, 2026



Overview

- Created 3 different models and 2 scenarios for crack propagation in snow using SALVUS
- Two pure spectral element (SE) models, one combined with data from material point method (MPM) simulations
- **Goal:** Couple dynamic snow modelling with SE to model crack propagation in snow

Nomenclature & Abbreviations

- **SE, FE, FEM**: Spectral elements, Finite Element (Method), done in SALVUS
- **MPM**: Material Point Method Numerical Modeling
- **PST**: Propagation Saw Test
- **F-k**: Frequency-Wavenumber Plot
- **DAS**: Distributed Acoustic Sensing (Fibre-Optics)
- **STF**: Source-time function (the wavelet fired by SALVUS)

Why model crack propagation in snow? - Relevance

- 22 fatalities by avalanche in Switzerland every year (**LongtermStatistics**)
- Avalanches are danger for human life but also infrastructure (**schweizerSnowAvalancheFormation2003**)
- Understanding processes associated with avalanches important
- Avalanche release because of loading, leading to crack propagation in a weak layer (**gaumeSnowFractureRelation2017a**)

Relevance

- Crack propagation at different speeds: sub-Rayleigh (below vs of material) and Supershear (above vs) (**trottetTransitionSubRayleighAnticrack2022**), transition between two regimes possible (**bergfeldSignaturesSubRayleighSupershear2025**)
- Fast crack propagation → critical crack length for release (**gaumeModelingCrackPropagation2015**) is reached faster
- Distributed Acoustic Sensing (DAS) already used to monitor avalanches in Switzerland (**paitzPhenomenologyAvalancheRecordings2023**; **edmeFiberopticDetectionSnow2023**) and Norway (**turquetAutomatedSnowAvalanche2024**)
- No knowledge if crack propagation associated with breakoff can be seen in DAS data

Research Questions

- What FE modelling framework is required to simulate DAS measurements of crack propagation in snow, and what are the key assumptions and limitations?
- What physical phenomena are observed in a two-layer model with a simple STF and how do they differ for sub-Rayleigh versus Supershear crack propagation?
- To what extent do the results change if source wavelets from a MPM simulation of a PST are injected?
- How could the phenomena observed be used to distinguish crack propagation regimes in real-world DAS data and aid in detecting snow slab avalanche breakoff?

Simple Model I




Figure: Two-layer model setup in SALVUS. Colors show materials, material types and properties in legend. Source line extent in red.

Simple Model II

- Set up to test custom STF in SALVUS, see physical effects on output
- Sources spaced over 240m in 10cm intervals
- 20Hz central frequency Ricker wavelet
- Source Wavelet in xx (1), xy (1) and yy (-1) direction
- Time delay of wavelet calculated based on propagation speed: sub-Rayleigh speed is $0.6v_s$, Supershear $1.6v_s$ (**trottetTransitionSubRayleighAnticrack2022**)

MPM-Guided Model I




Figure: Five-layer model setup in SALVUS. Colors show materials, material types and properties in legend. Source line extent in red.

MPM-Guided Model II

- Source-time functions obtained from MPM-simulation of PST by **trottetTransitionSubRayleighAnticrack2022**
- Source Wavelet in all three directions, but irregular and different for every source point

Results

- SALVUS Output: Displacement field u
- $\frac{\partial u_i}{\partial t} \rightarrow$ velocity in x and y
- $\frac{\partial u_i}{\partial j} \rightarrow$ strain in x and y ϵ
- $\frac{\partial^2 u_i}{\partial t \partial t} \rightarrow$ strain rate $\dot{\epsilon}$
- Simulation of DAS data from ϵ , $\dot{\epsilon}$ using Pyber Gauge length class by **noeFrontiersFullwaveformSeismology2025**, gauge length according to **turquetAutomatedSnowAvalanche2024**
- Spate-time plots of strain, strain rate and velocity at different receiver depths
- Frequency-wavenumber plots with theoretical speeds and dispersion curves
- Animations of velocity wavefields

Simple Sub-Rayleigh: Strain and Strain Rate I




Figure: Horizontal Strain and strain rate for sub-Rayleigh crack propagation in simple two-layer model. Plotted at crack depth (2.625m) and at the snow bottom (2.25m). Gauge length is 10.4m.

Simple Sub-Rayleigh: Strain and Strain Rate II

- Two-wavefront structure
- Main (thicker) wavefront: slope corresponds to prescribed rupture speed
- Second wavefront: coming only from first source
- Wavefront is emitted by all sources but they interfere (**madariagaDynamicsExpandingCircular1976**), as shown by wider source spacing
- Slope of line close to p-wave speed in medium: S0 wave bounded by plate wave speed limit (**roseWavesPlates2014**)
- S0/P-wave precursor observed in field data by **herwijnenSeismicSensorArray2011**
- Oscillatory behavior of both wavefronts (polarity flip at adjacent timesteps)
- At rupture arrest (270m): v-shaped arrest signature: bidirectional, at fastest speed in medium (**freundDynamicFractureMechanics1998**)
- Significant weakening of amplitude between two depths

Simple Supershear: Strain and Strain Rate I




Figure: Horizontal Strain and strain rate for Supershear crack propagation in simple two-layer model. Plotted at crack depth (2.625m) and at the snow bottom (2.25m). Gauge length is 10.4m.

Simple Supershear: Strain and Strain Rate II

- One wavefront, contrary to sub-Rayleigh
- Slope corresponds to rupture speed (within 1m/s of v_p and S_0)
- Dispersion and broadening of main wavefront (**kAkiRichards19801981**)
- Oscillatory wavefront
- At $x=270\text{m}$, unidirectional fan-like arrest front: rupture outruns v_s , so arrest energy is only propagated forward (**madariagaHighfrequencyRadiationCrack1977**)
- S_0 precursor can be seen in traces
- Supershear larger amplitude compared to sub-Rayleigh

MPM-Guided: Strain and Strain Rate I




Figure: Horizontal Strain and strain rate for MPM-guided model. Plotted at crack depth (0.525) and at the snow bottom (0.3m). Gauge length is 10.4m.

MPM-Guided: Strain and Strain Rate II

- One two main wavefronts observed
- Crack extent from 75m to 125m: sub-Rayleigh speed from front
- Positive wedge in crack area: extends until rupture arrest, then jumps to same thickness as negative front → quasi-static offset
- Backward-propagating front and forward after crack arrest: close to v_p/S_0 from slope
- Second, weaker wavefront: at onset but also arrest: same arrest structure as sub-Rayleigh
- Oscillatory wavefronts

Quasi-Static Offset

- Static field represents permanent deformation after sources have fired
(**zhuNoteDynamicStatic2002**; **archambeauGeneralTheoryElastodynamic1968**)
- MPM STFS are not symmetric: contrary to Ricker wavelets, they do not integrate to 0 over time
→ net displacement of material (**zhuNoteDynamicStatic2002**; **kAkiRichards19801981**)
- Cumulative integral of MPM STFs is negative: collapse of the weak layer, as observed by
(**heierliAnticracksNewTheory2003**; **heierliAnticrackNucleationTriggering2008**;
gaumeDynamicAnticrackPropagation2018; **trottetTransitionSubRayleighAnticrack2022**)
- All components of MPM STF (directionality) indicate mixed-mode anticrack instead of pure opening or shearing (mode I, II or III)

Simple model: Lamb Wave Identification I

- Polarity oscillation in all plots: indicative of Lamb waves
- Plotting dispersion curves over f-k spectra: energy is concentrated at symmetric (S0) and antisymmetric (A0) mode
- Antisymmetric mode gets excited preferentially when source is applied normal to midplane of material (**lambWavesElasticPlate1917**; **roseWavesPlates2014**; **achenbachWavePropagationElastic2012**), so in this case yy
- Confirmed by animations of wavefield:

Simple model: Lamb Wave Identification II




Figure: Animation still for Sub-Rayleigh V_x




Figure: Lamb wave modes intensity, taken from **cartaLambWavesDiscrete2023**

MPM-Guided Model: Lamb Wave Identification I

- Like in simple model: oscillatory wavefronts $\rightarrow$ A0 mode




Figure: Animation still for MPM V_x

MPM-Guided Model: Lamb Wave Identification II

- F-k plots also show concentration of energy around A0 and S0 dispersion curves
- Polarity reversal around slab midplane in animation indicative of A0


Summary of Results & Discussion I

- S0 Precursor observed in all Strain & Strain Rate Plots, as well as in traces
- Main wavfront in all cases is A0 $\rightarrow$ source normal to slab midplane
- Different rupture arrest structures depending on propagation speed
- Quasi-static wavefield for sources that do not integrate to 0 over time
- Weakening of amplitude only in simple case $\rightarrow$ also thicker slab

Implications for DAS field data I

- Identification of rupture speed via number of wavefronts & arrest structure
- Precursors in sub-Rayleigh: S0 and Quasi-Static offset
- Consistent with observations by **herwijnenSeismicSensorArray2011**
- Structures identified as being geometry-independet
- Signals identified as being larger than instrument noise of Silixa iDAS used by **paitzPhenomenologyAvalancheRecordings2023**
- Supershear signals larger in amplitude: possibly false conclusions if transition happens
- Identification flowchart:

Implications for DAS field data II



Implications for DAS field data III

Figure: Graphical Representation to Identify Different Signatures in DAS

Outlook

- Add topography to models
- Verify Supershear effects for more complex STFs as well
- Inhomogenous, multi-layered snowpack
- Transitional propagation regimes
- Comparison to field data → amplitude of signals compared to noise
- 3D model


Answer to Research Questions - Conclusions

- **What physical phenomena are observed in a two-layer model with a simple STF and how do they differ for sub-Rayleigh versus Supershear crack propagation?** Rupture-arrest signatures depending on propagation speed, S0 precursor, A0 main wavefront for both propagation regimes. Changes in amplitude
- **To what extent do the results change if source wavelets from a MPM simulation of a propagation saw test (PST) are injected?** Verification of sub-Rayleigh S0 precursor, A0 mode excitation, changes because appearance of quasi-static offset
- **How could the phenomena observed be used to distinguish crack propagation regimes in real-world DAS data and aid in detecting snow slab avalanche breakoff?** Precursors (S0 and quasi-static offset) used as "early" warning, identification of propagation speed using arrest structures, possibility of identifying transitions by number of wavefronts

Questions?

Bibliography I

MPM STF Workflow



Simple model velocity plots I




Figure: Simple model Sub-Rayleigh velocity plots. Crack depth on left side, snow bottom on right. v_y at top, v_x at bottom. Velocity derived from displacement.

Simple model velocity plots II




Figure: Simple model Supershear velocity plots. Crack depth on left side, snow bottom on right. v_y at top, v_x at bottom. Velocity derived from displacement.

MPM velocity plots








Figure: MPM-guided model velocity plots. Crack depth on left side, snow bottom on right. v_y at top, v_x at bottom. Velocity derived from displacement.

Simple model F-k plots and dispersion curves



MPM F-k plots



MPM STF cumulative Integral




Figure: Cumulative integral over time of all MPM STF components



Salome Bachmann
Master Student
sbachmann@student.ethz.ch

ETH Zurich
D-EAPS

Temporary page!

$\text{\LaTeX}$ was unable to guess the total number of pages correctly. As there was some unprocessed data should have been added to the final page this extra page has been added to receive it.
If you rerun the document (without altering it) this surplus page will go away, because $\text{\LaTeX}$ now knows how many pages to expect for this document.