scaNMAP

Local Web-Based Vulnerability Scanner Tool -- Documentation

1. **Project Overview**

scaNMAP is a locally-hosted, web-based graphical interface for the Nmap Security Scanner. It allows users to perform network reconnaissance, reveal various threat levels based on criteria, view active hosts, and inspect open ports directly from their web browser.

Unlike traditional web applications, this project is designed exclusively for local execution, allowing it to leverage elevated system privileges (such as root & administrator access) required for advanced Nmap functionalities like OS detection and SYN stealth scanning.

2. **System Architecture**

The application follows a simple, monolithic client-server architecture tailored for a localhost environment:

- Backend: Python with Flask. Handles API requests, session management, and spawns asynchronous threads for running scans.
- Scanner Core: python-nmap module acting as a wrapper around the system's native Nmap binary.
- Frontend: Single-page HTML application utilizing Vanilla JavaScript (ES6) and inline CSS for dynamic rendering without relying on heavy frameworks.
- Database: SQLite3 for persistent storage of user credentials and historical scan logs.

3. **Prerequisites & Installation**

3.1.**System Requirements**

- Python 3.7 or higher
- Nmap installed on the host system system-wide.

3.2.**Setup Instructions**

1. Ensure `nmap` is installed and accessible in your system's PATH.
2. Create a project directory (e.g., `mkdir scaNMAP && cd scaNMAP`).
3. Create a virtual environment: `python -m venv venv`
4. Activate the virtual environment.
5. Install dependencies: `pip install Flask python-nmap werkzeug`

6. Save the backend code as `app.py` and frontend code as `templates/index.html`.

4. **Usage & Execution**

Because advanced scans require raw socket access, the Flask application must be run with elevated privileges.
Important: On Linux/macOS, run using sudo: `sudo python app.py`. On Windows, open your Command Prompt or PowerShell as an Administrator before executing python app.py.

Once running, open a web browser and navigate to http://127.0.0.1:5000.

5. **Features**

- **Inline Authentication**: Multi-user support with secure password hashing using Werkzeug.
- **Asynchronous Scanning**: Scans run in a background thread, preventing browser timeouts and keeping the UI responsive.
- **Scan Profiles**: Includes pre-configured Nmap arguments (Stealth, Intense, Ping Sweep, Vulnerability Scripts).
- **Persistent History**: All completed and failed scans are logged to SQLite and can be recalled by clicking on them in the history sidebar.
- **PDF Exports**: Any scan, whether currently executed or available in history, can be exported in PDF format.
- **Risk Assessment**: Any open ports found are matched against a hardcoded dictionary of risk levels, which are displayed alongside with the scan results.

6. **Database Schema**

The application initializes a local SQLite database (`zenmap_local.db`) with two primary tables:

Table: users

Column	Type	Description
id	INTEGER	Primary Key (Auto-increment)
username	TEXT	Unique user identifier
password_hash	TEXT	Securely hashed password

Table: scans

Column	Type	Description
id	TEXT	Primary Key (UUID string)
username	TEXT	Foreign Key linking to users table
target	TEXT	The IP or hostname scanned
arguments	TEXT	The Nmap flags used (e.g., -sS -O)
status	TEXT	'running', 'completed', or 'failed'
results	TEXT	JSON string of parsed Nmap output

7. **API Endpoints Reference**


Authentication

- `POST /api/auth` — Accepts JSON `{"username", "password", "action"}` where action is 'login' or 'register'.
- `POST /api/logout` — Clears the current user session.
- `GET /api/user` — Returns the currently logged-in username.


Scanning & History

- `POST /api/scan` — Starts a new background scan. Requires authentication. Accepts `{"target", "type"}`. Returns a scan_id.
- `GET /api/scan/<scan_id>` — Polls the status of an ongoing scan. Returns 'running' or the full results if 'completed'.
- `GET /api/history` — Fetches all historical scans associated with the logged-in user, ordered by most recent.

8. **MVP Screenshots**




Home page




Scan history can be viewed once securely logged in (not visible to other users)




Four types of scan procedures are provided



Scans cannot be run without being logged in



Completed scan results are displayed (i)



Completed scan results are displayed (ii)