

No.	Time	Source	Destination	Protocol	Length	Info
363	9.863243200	192.168.0.123	104.21.4.210	HTTP	457	GET / HTTP/1.1
373	10.391051000	104.21.4.210	192.168.0.123	HTTP	60	HTTP/1.1 200 OK (text/html)
375	10.477105800	192.168.0.123	104.21.4.210	HTTP	396	GET /css/style.css HTTP/1.1
380	10.483934500	192.168.0.123	104.21.4.210	HTTP	379	GET /js/theme.js HTTP/1.1
382	10.510605100	104.21.4.210	192.168.0.123	TCP	147	[TCP Previous segment not captured] 80 → 50262 [PSH, ACK] Seq=1441 Ack=326 Win=131072 Len=93Continuation
386	10.511000000	104.21.4.210	192.168.0.123	HTTP	832	Continuation
387	10.511106900	104.21.4.210	192.168.0.123	HTTP	60	Continuation
389	10.988329400	104.21.4.210	192.168.0.123	TCP	131	[TCP Previous segment not captured] 80 → 50261 [PSH, ACK] Seq=6649 Ack=746 Win=131072 Len=77Continuation
393	10.988588100	104.21.4.210	192.168.0.123	HTTP	1494	Continuation
394	10.988791700	104.21.4.210	192.168.0.123	HTTP	1494	Continuation
396	10.988769100	104.21.4.210	192.168.0.123	HTTP	527	Continuation
397	10.988776700	104.21.4.210	192.168.0.123	HTTP	60	Continuation
399	11.113326400	192.168.0.123	104.21.4.210	HTTP	440	GET /favicon.svg HTTP/1.1
405	11.124129600	104.21.4.210	192.168.0.123	HTTP/X_	60	HTTP/1.1 200 OK

After filtering “http”, this is the result I got.

Http request :

```

Frame 375: Packet, 396 bytes on wire (3168 bits), 396 bytes captured (3168 bits) on interface \Device\NPF_{485D37F9-1814-4C48-929C-EC867E3CA8CA}, id 0
Section number: 1
  Interface id: 0 (\Device\NPF_{485D37F9-1814-4C48-929C-EC867E3CA8CA})
  Encapsulation type: Ethernet (1)
  Arrival Time: Jul 19, 2026 21:52:06.160459700 Bangladesh Standard Time
  UTC Arrival Time: Jul 19, 2026 15:52:06.160459700 UTC
  Epoch Arrival Time: 1784476326.160459700
  [Time shift for this packet: 0.000000000 seconds]
  [Time delta from previous captured frame: 85.203900 milliseconds]
  [Time delta from previous displayed frame: 613.862600 milliseconds]
  [Time since reference or first frame: 10.477105800 seconds]
  Frame Number: 375
  Frame Length: 396 bytes (3168 bits)
  Capture Length: 396 bytes (3168 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:tcp:http]
  Character encoding: ASCII (0)
  [Coloring Rule Name: HTTP]
  [Coloring Rule String: http || tcp.port == 80 || http2]

```

Here the frame number is 375 and frame size is 396 bytes. It is encoded in ASCII.

Epoch Arrival Time: 1784476326.160459700

```

Ethernet II, Src: ASUSTekCOMPU_23:e4:98 (18:31:bf:23:e4:98), Dst: TPLink_77:0c:3c (20:23:51:77:0c:3c)
  Destination: TPLink_77:0c:3c (20:23:51:77:0c:3c)
  Source: ASUSTekCOMPU_23:e4:98 (18:31:bf:23:e4:98)
  Type: IPv4 (0x0800)
  [Stream index: 0]

```

Source mac: 18:31:bf:23:e4:98

Destination mac: 20:23:51:77:0c:3c

It is an Internet Protocol version 4 packet.

```

Internet Protocol Version 4, Src: 192.168.0.123, Dst: 104.21.4.210
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
  Total Length: 382
  Identification: 0x8971 (35185)
  010. .... = Flags: 0x2, Don't fragment
  ...0 0000 0000 0000 = Fragment Offset: 0
  Time to Live: 128
  Protocol: TCP (6)
  Header Checksum: 0x41fe [validation disabled]
  [Header checksum status: Unverified]
  Source Address: 192.168.0.123
  Destination Address: 104.21.4.210
  [Stream index: 12]

```

Source ip: 192.168.0.123

Destination ip: 104.21.4.210

The packet is carrying a TCP segment. The TTL (Time to Live) is set to 128, meaning it will be dropped if it passes through 128 routers without reaching its destination.

```
Transmission Control Protocol, Src Port: 50261, Dst Port: 80, Seq: 404, Ack: 5209, Len: 342
  Source Port: 50261
  Destination Port: 80
  [Stream index: 6]
  [Stream Packet Number: 14]
  ▸ [Conversation completeness: Incomplete, DATA (15)]
  [TCP Segment Len: 342]
  Sequence Number: 404      (relative sequence number)
  Sequence Number (raw): 2496502802
  [Next Sequence Number: 746      (relative sequence number)]
  Acknowledgment Number: 5209      (relative ack number)
  Acknowledgment number (raw): 4233952152
  0101 .... = Header Length: 20 bytes (5)
  ▸ Flags: 0x018 (PSH, ACK)
  Window: 514
  [Calculated window size: 131584]
  [Window size scaling factor: 256]
  Checksum: 0xe82a [unverified]
  [Checksum Status: Unverified]
  Urgent Pointer: 0
  ▸ [Timestamps]
  ▸ [SEQ/ACK analysis]
  [Client Contiguous Streams: 1]
  [Server Contiguous Streams: 1]
  TCP payload (342 bytes)
```

Source Port: 50261

Destination Port: 80

The packet is carrying 342 bytes of actual application data [TCP Segment Len: 342]

The push flag (PSH) and acknowledgement flag (ACK) are set.

```
Hypertext Transfer Protocol
  ▸ GET /css/style.css HTTP/1.1\r\n
  Host: httpforever.com\r\n
  Connection: keep-alive\r\n
  User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/150.0.0.0 Safari/537.36\r\n
  Accept: text/css,*/*;q=0.1\r\n
  Sec-GPC: 1\r\n
  Accept-Language: en-US,en;q=0.9\r\n
  Referer: http://httpforever.com/\r\n
  Accept-Encoding: gzip, deflate\r\n
  \r\n
  [Full request URI: http://httpforever.com/css/style.css]
```

Request Type: HTTP GET request

Requested Resource: a stylesheet located at /css/style.css

host website: httpforever.com

Persistent Connection

Http response:

```

Frame 405: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \Device\NPF_{485D37F9-1814-4C48-929C-EC867E3CA8CA}, id 0
Section number: 1
  Interface id: 0 (\Device\NPF_{485D37F9-1814-4C48-929C-EC867E3CA8CA})
  Encapsulation type: Ethernet (1)
  Arrival Time: Jul 19, 2026 21:52:06.807483500 Bangladesh Standard Time
  UTC Arrival Time: Jul 19, 2026 15:52:06.807483500 UTC
  Epoch Arrival Time: 1784476326.807483500
  [Time shift for this packet: 0.000000000 seconds]
  [Time delta from previous captured frame: 500 nanoseconds]
  [Time delta from previous displayed frame: 732.278600 milliseconds]
  [Time since reference or first frame: 11.124129600 seconds]
  Frame Number: 405
  Frame Length: 60 bytes (480 bits)
  Capture Length: 60 bytes (480 bits)
  [Frame is marked: False]
  [Frame is ignored: False]
  [Protocols in frame: eth:ethertype:ip:tcp:http:xml]
  Character encoding: ASCII (0)
  [Coloring Rule Name: HTTP]
  [Coloring Rule String: http || tcp.port == 80 || http2]

```

The frame number is 403 and size is 60 bytes, encoded in ASCII.

Epoch Arrival Time: 1784476326.807483500

```

Ethernet II, Src: TPLink_77:0c:3c (20:23:51:77:0c:3c), Dst: ASUSTekCOMPU_23:e4:98 (18:31:bf:23:e4:98)
  Destination: ASUSTekCOMPU_23:e4:98 (18:31:bf:23:e4:98)
  Source: TPLink_77:0c:3c (20:23:51:77:0c:3c)
  Type: IPv4 (0x0800)
  [Stream index: 0]
  Padding: 00

```

Source mac: 20:23:51:77:0c:3c

Destination mac: 18:31:bf:23:e4:98

It is an Internet Protocol version 4 packet.

```

Internet Protocol Version 4, Src: 104.21.4.210, Dst: 192.168.0.123
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  Differentiated Services Field: 0x04 (DSCP: LE, ECN: Not-ECT)
  Total Length: 45
  Identification: 0x1ea8 (7848)
  010. .... = Flags: 0x2, Don't fragment
  ...0 0000 0000 0000 = Fragment Offset: 0
  Time to Live: 58
  Protocol: TCP (6)
  Header Checksum: 0xf414 [validation disabled]
  [Header checksum status: Unverified]
  Source Address: 104.21.4.210
  Destination Address: 192.168.0.123
  [Stream index: 12]

```

Source ip: 104.21.4.210

Destination ip: 192.168.0.123

The packet is carrying a TCP segment. The TTL (Time to Live) is set to 58, meaning it will be dropped if it passes through 58 routers without reaching its destination.

```

Transmission Control Protocol, Src Port: 80, Dst Port: 50261, Seq: 11907, Ack: 1132, Len: 5
  Source Port: 80
  Destination Port: 50261
  [Stream index: 6]
  [Stream Packet Number: 32]
  ▸ [Conversation completeness: Incomplete, DATA (15)]
  [TCP Segment Len: 5]
  Sequence Number: 11907      (relative sequence number)
  Sequence Number (raw): 4233958850
  [Next Sequence Number: 11912      (relative sequence number)]
  Acknowledgment Number: 1132      (relative ack number)
  Acknowledgment number (raw): 2496503530
  0101 .... = Header Length: 20 bytes (5)
  ▸ Flags: 0x018 (PSH, ACK)
  Window: 16
  [Calculated window size: 131072]
  [Window size scaling factor: 8192]
  Checksum: 0x3315 [unverified]
  [Checksum Status: Unverified]
  Urgent Pointer: 0
  ▸ [Timestamps]
  ▸ [SEQ/ACK analysis]
  [Client Contiguous Streams: 1]
  [Server Contiguous Streams: 1]
  TCP payload (5 bytes)
  TCP segment data (5 bytes)

```

Source Port: 80

Destination Port: 50261

The packet is carrying 5 bytes of actual application data [TCP Segment Len: 5]

The push flag (PSH) and acknowledgement flag (ACK) are set.

```

[4 Reassembled TCP Segments (1828 bytes): #401(1440), #402(84), #404(299), #405(5)]
[Frame: 401, payload: 0-1439 (1440 bytes)]
[Frame: 402, payload: 1440-1523 (84 bytes)]
[Frame: 404, payload: 1524-1822 (299 bytes)]
[Frame: 405, payload: 1823-1827 (5 bytes)]
[Segment count: 4]
[Reassembled TCP length: 1828]
[Reassembled TCP Data [...]: 485454502f312e3120323030204f4b0d0a446174653a2053756e2c203139204a756c20323032362031353a35323a303620474d540d0a436f6e74656e7...]

```

The complete, reassembled data payload is 1828 bytes in length. It took 4 distinct frames (Frames 401, 402, 404, and 405) to transmit the entire message.


```

Hypertext Transfer Protocol, has 2 chunks (including last chunk)
> HTTP/1.1 200 OK\r\n
Date: Sun, 19 Jul 2026 15:52:06 GMT\r\n
Content-Type: image/svg+xml\r\n
Transfer-Encoding: chunked\r\n
Connection: keep-alive\r\n
Server: cloudflare\r\n
Last-Modified: Wed, 01 Jul 2026 19:39:16 GMT\r\n
cf-cache-status: HIT\r\n
Referrer-Policy: strict-origin-when-cross-origin\r\n
X-Content-Type-Options: nosniff\r\n
X-Frame-Options: DENY\r\n
X-Permitted-Cross-Domain-Policies: none\r\n
X-XSS-Protection: 0\r\n
Cross-Origin-Resource-Policy: same-origin\r\n
[...] Permissions-Policy: accelerometer=(), autoplay=(), camera=(), display-capture=(), encrypted-media=(), fullscreen=(), gamepad=(), geolocation=(), g
[...] Content-Security-Policy: default-src 'none'; script-src 'self' 'report-sha256' 'report-sample'; style-src 'self'; img-src 'self'; base-uri 'none';
Reporting-Endpoints: default="https://scotthelme.report-uri.com/a/d/g"\r\n
Report-To: {"group":"default","max_age":31536000,"endpoints":[{"url":"https://scotthelme.report-uri.com/a/d/g"}],"include_subdomains":true}\r\n
NEL: {"report_to":"default","max_age":31536000,"include_subdomains":true}\r\n
Age: 3337\r\n
Cache-Control: max-age=3600\r\n
etag: W/"6a456ce4-1af"\r\n
Content-Encoding: gzip\r\n
CF-RAY: a1dae4325e318139-CGP\r\n
\r\n
[Request in frame: 399]
[Time since request: 10.803200 milliseconds]
[Request URI: /favicon.svg]
[Full request URI: http://httpforever.com/favicon.svg]
> HTTP chunked response
Content-encoded entity body (gzip): 292 bytes -> 431 bytes
File Data: 431 bytes

```

HTTP/1.1 200 OK\r\n status indicates the server successfully received, understood, and accepted the client's request. The payload was compressed using gzip to save bandwidth and is being delivered in segments [Transfer-Encoding: chunked\r\n]

The server is delivering an SVG image file



Here it confirms that this specific XML code is being used to render an SVG image.