Why regressing a policy onto measured-residual ILC steps converges on the real system where model-based guided policy search does not

DistILC: formal analysis (draft, 2026-10-13)

Abstract

We analyse the update at the core of DistILC: a goal-conditioned policy network is regressed, trial after trial, onto one damped Gauss–Newton (Levenberg–Marquardt) iterative-learning-control (ILC) correction whose *error* is measured on the real system and whose *Jacobian* comes from an approximate (nominal) model, evaluated along the measured trajectory with the network's own feedback. We make every space and regularity assumption explicit and prove: (i) every fixed point of the update is a zero of the *real* error, whatever the size of the model error (Proposition 4); (ii) local linear convergence to such a zero, and almost-sure convergence under zero-mean trial noise with Robbins–Monro steps, under a single *positivity* condition coupling the true sensitivity, the network's tangent kernel and the model's damped pseudo-inverse (Theorems 8 and 9); (iii) checkable sufficient conditions for positivity, including a small-gain bound and arbitrary multiplicative mismatch (Lemma 6). We contrast this with guided policy search (GPS): with the nominal model, GPS's fixed points carry the model's zeroth-order residual as an irreducible real error (Proposition 11); with dynamics fitted from real samples, GPS is unbiased only once the local fits are identifiable, which needs at least $n+m+1$ rollouts per condition and iteration (Proposition 13); and with a nominal prior in place of identifiable fits, any *cost-side* regularization (control cost, entropy) turns the approximate-gradient fixed point into a biased one, whereas *step-side* damping does not (Proposition 14). A first-order statement of cross-goal transfer answers when correcting the flown goals corrects unflown ones (Proposition 15). Section 10 lists the criticisms we expect and what the analysis does and does not answer.

Contents

1 Setting, spaces and standing assumptions **2**
- 1.1 Spaces . . . 2
- 1.2 Systems . . . 2
- 1.3 Regularity . . . 3
- 1.4 Sensitivities . . . 3

2 The DistILC update **4**

3 Fixed points are zeros of the real error **4**

4 Convergence **5**

5 Guided policy search: where it fails and where it does not **7**
- 5.1 GPS with the nominal model . . . 7
- 5.2 GPS with dynamics fitted from real samples . . . 7
- 5.3 GPS with a nominal prior and too few samples: the cost-regularization bias . . . 8
- 5.4 Summary of the comparison . . . 8

6 Does correcting the flown goals correct the others? **8**

7 The simulation stage **9**

8 Mode cells: certifying and enforcing Assumption A(b) **10**

9 Domain randomization, for comparison **12**

10 Anticipated criticisms **13**

1 Setting, spaces and standing assumptions

Throughout, all vector spaces are finite-dimensional real vector spaces; "norm" means the norm induced by the stated inner product; linear maps between such spaces are identified with matrices in fixed bases; $\|\cdot\|$ on linear maps is the induced operator norm. For a linear map M on an inner-product space $(\mathcal{E}, \langle\cdot,\cdot\rangle_W)$ we write $\mathrm{sym}_W(M) := \frac{1}{2}(M + M^\star)$, with $M^\star = W^{-1}M^\top W$ the W-adjoint, and $\mathrm{sym}_W(M) \succeq \mu I$ means $\langle e, Me\rangle_W \geq \mu\|e\|_W^2$ for all $e \in \mathcal{E}$.

1.1 Spaces

(S1) **Time.** A trial has a fixed finite horizon of $T \in \mathbb{N}$ control periods, $t = 0, \ldots, T-1$.

(S2) **State, action, observation, goal.** The state space $\mathcal{X} \subseteq \mathbb{R}^n$ is open; the action space is $U = [-1, 1]^m \subset \mathbb{R}^m$ (normalized, compact, convex); the observation space is $\mathcal{O} \subseteq \mathbb{R}^{n_o}$ with a measurable observation map $h : \mathcal{X} \times \mathcal{G} \to \mathcal{O}$, C^1 in x; the goal space $\mathcal{G} \subset \mathbb{R}^d$ is compact. The method updates the policy at a finite set of *trained goals* $\mathcal{G}_{\mathrm{tr}} = \{g_1, \ldots, g_N\} \subset \mathcal{G}$.

(S3) **Trial input space.** $\mathcal{V} := \mathbb{R}^{Tm}$, sequences $v = (v_0, \ldots, v_{T-1})$ of additive action perturbations, with the Euclidean inner product. Stacked over trained goals: $\mathcal{V}^N$ with the product inner product.

(S4) **Error space.** Each period produces q error rows $c(x_t, g) \in \mathbb{R}^q$ (*task errors*: in the pogo-stick instance the ballistic apex predictor minus $h^\star$ and the speed minus $v^\star$, active in flight); $\mathcal{E} := \mathbb{R}^{Tq}$ with the weighted inner product $\langle a, b\rangle_W = a^\top W b$, $W \succ 0$ (the inverse squared error scales). Stacked: $\mathcal{E}^N$, block-diagonal weight. We let $\mathcal{E}_g \subseteq \mathcal{E}$ denote the subspace of rows that are active along the trial (masked rows are identically zero and are removed); all statements about $\mathcal{E}$ refer to $\mathcal{E}_g$.

(S5) **Parameter space.** $\Theta = \mathbb{R}^p$ with the Euclidean inner product; the policy is a map $\pi : \Theta \times \mathcal{O} \times \mathcal{G} \to \mathbb{R}^m$, $(\theta, o, g) \mapsto \pi_\theta(o, g)$, followed by the clip onto U.

(S6) **Probability.** A probability space $(\Omega, \mathcal{F}, P)$ with a filtration $(\mathcal{F}_k)_{k\geq 0}$, $\mathcal{F}_k$ the σ-algebra generated by all trials up to iteration k; per-trial noise ξ_k takes values in a measurable space $(\Xi, \mathcal{B})$; all maps composed with noise below are jointly measurable.

1.2 Systems

(D1) **Real system.** $x_{t+1} = f(x_t, u_t)$ with $f : \mathcal{X} \times U \to \mathcal{X}$ (noise enters through measurement and initial state, see (N1)). It may be *hybrid*: f is the period map of a piecewise-smooth flow with guards (touchdown/liftoff).

(D2) **Nominal model.** $\widehat{f} : \mathcal{X} \times U \to \mathcal{X}$, differentiable along the trajectories used (in the pogo instance: the same SLIP equations without leg damping, at a coarser step).

(D3) **Closed loop and the additive input.** For policy θ, goal g and $v \in \mathcal{V}$, the trial from x_0^g is $u_t = \mathrm{clip}_U(\pi_\theta(h(x_t, g), g) + v_t)$, $x_{t+1} = f(x_t, u_t)$. The trial map is

$$E_g : \Theta \times \mathcal{V} \to \mathcal{E}, \qquad E_g(\theta, v) = (c(x_t, g))_{t=0}^{T-1}, \qquad e_g(\theta) := E_g(\theta, 0).$$

$\widehat{E}_g$ is defined in the same way with $\widehat{f}$.

1.3 Regularity

Assumption A (Smoothness in a neighbourhood)**.** There is an open set $\mathcal{N} \subseteq \Theta$ such that for every $g \in \mathcal{G}_{\mathrm{tr}}$ and $\theta \in \mathcal{N}$:

(a) *(interior actions)* the clip is inactive along the trial (actions in the interior of U);

(b) *(fixed, transversal mode sequence)* the hybrid trial visits the same sequence of modes for all $\theta \in \mathcal{N}$, and every guard crossing is transversal (the guard's normal derivative along the flow is non-zero), so that event times are C^1 functions of the state by the implicit function theorem and the trial map is C^1 (saltation matrices included in its derivative);

(c) *(Lipschitz derivative)* $\theta \mapsto D_\theta e_g(\theta)$ is Lipschitz on $\mathcal{N}$ with constant L_2, and π is C^2 in (θ, o) with bounded second derivatives on $\mathcal{N} \times h(\mathcal{X}, \mathcal{G})$.

Assumption A(b) is the hybrid-systems price: across a change of the mode sequence (a missed touchdown, a grazing contact) the trial map is not differentiable and no first-order argument applies; $\mathcal{N}$ must lie inside one mode-sequence cell. Saturation (a) is similar: on an active clip the sensitivity to that action is zero.

1.4 Sensitivities

Definition 1 (True and nominal closed-loop sensitivities)**.** Along the trial of (θ, g) with states x_t, actions u_t, let $A_t = \partial_x f$, $B_t = \partial_u f$ (with saltation at events), $C_t = \partial_x c(x_t, g)$, and the policy feedback $K_t = \partial_o \pi_\theta \, \partial_x h$. The true closed-loop sensitivity $G_g(\theta) = \partial_v E_g(\theta, 0) \in L(\mathcal{V}, \mathcal{E})$ has blocks

$$G[t, j] = C_t \, \Phi^{\mathrm{cl}}(t, j+1) \, B_j \ (j < t), \qquad G[t, j] = 0 \ (j \geq t), \qquad \Phi^{\mathrm{cl}}(t, s) = \prod_{r=s}^{t-1} (A_r + B_r K_r).$$

The *nominal* sensitivity $\widehat{G}_g(\theta)$ is the same formula with $\widehat{A}_t = \partial_x \widehat{f}$, $\widehat{B}_t = \partial_u \widehat{f}$ evaluated **at the measured real states and actions** (x_t, u_t), the same C_t and the same K_t.

Remark 2. Because $\widehat{G}$ is evaluated along the measured trajectory with the network's own measured feedback, $G - \widehat{G}$ contains *only* the derivative mismatch $(\partial f - \partial \widehat{f})$ at the same points (and, for hybrid systems, the approximation of saltation terms); it contains no state-mismatch term. The zeroth-order mismatch $f - \widehat{f}$ never enters the update: the error is measured.

Lemma 3 (Chain rule through the closed loop)**.** *Under Assumption A, define $J_g(\theta) \in L(\Theta, \mathcal{V})$ by $(J_g \delta\theta)_t = \partial_\theta \pi_\theta(o_t, g) \, \delta\theta$ along the trial. Then $D_\theta e_g(\theta) = G_g(\theta) J_g(\theta)$.*

Proof. A parameter change $\delta\theta$ changes the action at period t by $\partial_\theta \pi \, \delta\theta + K_t \delta x_t$; the first term is exactly an additive input $v_t = (J_g \delta\theta)_t$ applied to the closed loop with feedback K_t, and the second is the closed loop's own response. Linearizing the recursion $\delta x_{t+1} = (A_t + B_t K_t)\delta x_t + B_t v_t$, $\delta x_0 = 0$, and $\delta e_t = C_t \delta x_t$ gives $\delta e = G_g J_g \delta\theta$. Differentiability of each map is Assumption A. □

2 The DistILC update

ILC step (per trained goal). With damping $\lambda > 0$, gain $\beta \in (0, 1]$:

$$\Delta v_g = -\beta\, \widehat{L}_g\, e_g, \qquad \widehat{L}_g := (\widehat{G}_g^\top W \widehat{G}_g + \lambda I)^{-1} \widehat{G}_g^\top W \ \in L(\mathcal{E}, \mathcal{V}). \tag{1}$$

The damping is on the *step* (Levenberg–Marquardt), not in the objective.

Regression (one network for all goals). The targets are $y_{g,t} = \pi_{\theta_k}(o_{g,t}, g) + \Delta v_{g,t}$ at the measured observations. The network is refit, $\theta_{k+1} \approx \arg\min_\theta \sum_{g,t} \|\pi_\theta(o_{g,t}, g) - y_{g,t}\|^2 + \rho\|\theta - \theta_k\|^2$, with $\rho \geq 0$ a proximal weight (trust region, finite fitting). Stacking $J = (J_{g_1}; \ldots; J_{g_N}) \in L(\Theta, \mathcal{V}^N)$ and $\Delta v = (\Delta v_{g_i})_i$, the first-order solution of this fit is the kernel (minimum-norm, ridge) step

$$\theta_{k+1} - \theta_k = J^\top (JJ^\top + \rho I)^{-1} \Delta v + r_k, \tag{2}$$

where r_k collects the inexactness of the actual optimizer (finite Adam steps, nonlinearity of π in θ, replayed targets) and $\Theta_k := JJ^\top \in L(\mathcal{V}^N, \mathcal{V}^N)$ is the empirical neural tangent kernel on the visited (observation, goal) pairs. Define the *realized-correction operator*

$$S_k := \Theta_k(\Theta_k + \rho I)^{-1} \in L(\mathcal{V}^N, \mathcal{V}^N), \qquad 0 \preceq S_k \preceq I,$$

whose off-diagonal blocks $S_{g_i g_j}$ couple goals: the correction asked at g_j moves the policy at g_i.

Closed-loop error recursion. By Lemma 3 and Taylor's theorem,

$$e_{k+1} = e_k - \beta\, M_k\, e_k + G_k J_k r_k + R_k, \qquad M_k := G_k S_k \widehat{L}_k \in L(\mathcal{E}^N, \mathcal{E}^N), \tag{3}$$

with $G_k = \mathrm{blkdiag}(G_{g_i}(\theta_k))$, $\widehat{L}_k = \mathrm{blkdiag}(\widehat{L}_{g_i})$ and the Taylor remainder $\|R_k\|_W \leq \frac{L_2}{2}\|\theta_{k+1} - \theta_k\|^2$.

From the implementation to the analysed update. The implementation (`hw_stage.py`) differs from (1)–(2) in four ways, each mapped onto a term of the analysis. (i) *rms cap*: the step is scaled down when its rms exceeds a cap, i.e. a state-dependent gain $\beta_k \in (0, \beta]$; every statement below holds for any gain sequence in $(0, \mu/\Gamma^2]$. (ii) *replayed targets*: the network is fit to the targets of all trials so far with weights halving per iteration of age; the difference from fitting the current targets only is part of the regression error r_k (the analysed update is the no-replay limit, `--age-decay 0`, which performed the same in the pogo sweep). (iii) *finite Adam fitting* instead of the kernel step: also r_k. (iv) *rollback*: a trial worse than the last kept one restores the previous parameters and halves the cap; this is a safeguard outside the analysis (a projection onto a sublevel set of the measured cost), used in Theorem 9's localization remark. The sim stage (Section 7) uses the same update with $f = \widehat{f}$ and many lanes per iteration.

3 Fixed points are zeros of the real error

Assumption B (Realizability and rank)**.** For $\theta \in \mathcal{N}$: (a) $J(\theta)$ is surjective onto $\mathcal{V}^N$ (the network can realize any correction at the visited inputs; $\Theta_k \succ 0$); (b) each $\widehat{G}_g$ has full row rank on $\mathcal{E}_g$, i.e. $\dim \mathcal{E}_g \leq \dim \mathcal{V}$ and the model can, to first order, move every active error row.

Proposition 4 (No model bias at fixed points)**.** *Under Assumptions A–B, with exact regression ($r_k = 0$): θ is a fixed point of (1)–(2) if and only if $e_g(\theta) = 0$ for every trained goal g. This holds for every nominal model $\widehat{f}$ satisfying Assumption B(b), regardless of $\|f - \widehat{f}\|$ or $\|G - \widehat{G}\|$.*

Proof. $\theta_{k+1} = \theta_k$ iff $J^\top(\Theta + \rho I)^{-1}\Delta v = 0$. Since J is surjective, $J^\top$ is injective, and $(\Theta + \rho I)^{-1}$ is invertible, so this holds iff $\Delta v = 0$, i.e. $\widehat{L}_g e_g = 0$ for all g. $\widehat{L}_g = (\widehat{G}_g^\top W \widehat{G}_g + \lambda I)^{-1}\widehat{G}_g^\top W$ is injective on $\mathcal{E}_g$ because $W \succ 0$ and $\widehat{G}_g^\top$ is injective (full row rank of $\widehat{G}_g$). Hence $e_g = 0$. Conversely $e_g = 0$ gives $\Delta v = 0$. □

Remark 5. The statement is about the location of fixed points, not about reaching them; Section 4 gives the convergence condition. The essential mechanism: the update is linear in a *measured* residual, so the residual, not a model prediction of it, must vanish at rest. Step-side damping λ changes the path, not the fixed points.

4 Convergence

Assumption C (Positivity)**.** There are $\mu > 0$ and $\Gamma < \infty$ such that for all $\theta \in \mathcal{N}$: $\mathrm{sym}_W(M(\theta)) \succeq \mu I$ on $\mathcal{E}^N$ and $\|M(\theta)\|_W \le \Gamma$, where $M = GS\widehat{L}$ as in (3).

Positivity says that the correction the nominal model asks for, after passing through the network's realization operator S and the *true* closed loop G, reduces the measured error to first order, uniformly, and including the interference between goals (the off-diagonal blocks of S).

Lemma 6 (Sufficient conditions for positivity)**.** *Let $\widehat{G}_g^+ := \widehat{G}_g^\top(\widehat{G}_g\widehat{G}_g^\top)^{-1}$ be the right pseudo-inverse (full row rank, Assumption B(b)). With $A := W^{1/2}\widehat{G}_g$, the push-through identity gives $\widehat{L}_g = A^\top(AA^\top + \lambda I)^{-1}W^{1/2}$, hence $\widehat{L}_g \to A^\top(AA^\top)^{-1}W^{1/2} = \widehat{G}_g^+$ as $\lambda \to 0$ (the weight cancels in the limit) and $\widehat{G}_g\widehat{G}_g^+ = I$ on $\mathcal{E}_g$. Write $\Delta_g := G_g - \widehat{G}_g$.*

(i) (Small gain.) *If $S = I$ (exact realization without cross-goal interference), $\lambda \to 0$, and $\|\Delta_g\widehat{G}_g^+\|_W \le 1 - \mu'$ for all g, then $\mathrm{sym}_W(M) \succeq \mu' I$.*

(ii) (Multiplicative mismatch.) *If $S = I$, $\lambda \to 0$ and $G_g = P_g\widehat{G}_g$ with $\mathrm{sym}_W(P_g) \succeq \mu I$ (P_g any linear map on $\mathcal{E}_g$ with positive-definite symmetric part, e.g. gain, mass or actuator-scale errors of any size), then $\mathrm{sym}_W(M) \succeq \mu I$.*

(iii) (Interference.) *For general S, write $M = D + O$ with D the block-diagonal and O the off-diagonal part. If $\mathrm{sym}_W(D) \succeq \mu_D I$ and $\|O\|_W \le \omega < \mu_D$, then $\mathrm{sym}_W(M) \succeq (\mu_D - \omega)I$.*

(iv) (Continuity in λ.) *If (i) or (ii) holds with margin μ', it holds with margin $\mu' - O(\lambda/\sigma_{\min}(\widehat{G})^2)$ for $\lambda > 0$.*

Proof. (i) $G\widehat{G}^+ = (\widehat{G} + \Delta)\widehat{G}^+ = I + \Delta\widehat{G}^+$ because $\widehat{G}\widehat{G}^+ = I$ on $\mathcal{E}_g$ (full row rank); then $\langle e, (I + \Delta\widehat{G}^+)e\rangle_W \ge \|e\|_W^2 - \|\Delta\widehat{G}^+\|_W\|e\|_W^2 \ge \mu'\|e\|_W^2$. (ii) $G\widehat{G}^+ = P\widehat{G}\widehat{G}^+ = P$. (iii) $\langle e, Me\rangle_W \ge \langle e, De\rangle_W - |\langle e, Oe\rangle_W| \ge (\mu_D - \omega)\|e\|_W^2$. (iv) $\widehat{L}_g - \widehat{G}_g^+ = -\lambda A^\top(AA^\top + \lambda I)^{-1}(AA^\top)^{-1}W^{1/2}$, whose norm is at most $\lambda\|A\|\|W^{1/2}\|/\sigma_{\min}(A)^4$; compose with $\|GS\|$ bounded. □

Remark 7 (Positivity is checkable)*.* Positivity concerns the map from the measured error to the realized error change; its Rayleigh quotients are observable from consecutive trials: $\cos\angle(\widehat{G}\Delta v,\ e_{k+1} - e_k)$ (predicted vs measured change). The pogo-stick study logs this: positive in 97% of trial pairs for the nominal-sim network, median 0.88; across 125 robot runs the median cosine predicts the hardware stage's gain (Spearman 0.63); the 180-degree control ($\widehat{G} \to -\widehat{G}$) gives 0% success. A sign-wrong model is exactly the case where Assumption C fails, and the method fails, as predicted.

Theorem 8 (Local linear convergence)**.** *Let Assumptions A–C hold; let* $c_J := \sup_{\mathcal{N}} \|J^\top(\Theta+\rho I)^{-1}\|$, $c_L := \sup_{\mathcal{N}} \|\widehat{L}\|$, $c_G := \sup_{\mathcal{N}} \|GJ\|$*; suppose the regression error satisfies* $\|r_k\| \le \varepsilon_k$*. Let* $0 < \beta \le \mu/\Gamma^2$ *and* $\delta > 0$ *with* $L_2\, c_J^2 c_L^2\, \beta\, \delta \le \mu/4$*; let* $\bar{\varepsilon} := \sup_k \varepsilon_k$ *and* $\varepsilon_\Sigma := \sum_k \varepsilon_k < \infty$ *with* $c_G\bar{\varepsilon} + L_2\bar{\varepsilon}^2 \le \beta\mu\delta/4$*. If* $\theta_0 \in \mathcal{N}$*,* $\|e_0\|_W \le \delta$*, and the closed ball of radius* $R := \frac{4c_J c_L}{\mu}\big(\delta + c_G\varepsilon_\Sigma + L_2\bar{\varepsilon}\varepsilon_\Sigma\big) + \varepsilon_\Sigma$ *around* θ_0 *lies in* $\mathcal{N}$*, then*

$$\|e_{k+1}\|_W \le \Big(1 - \frac{\beta\mu}{4}\Big)\|e_k\|_W + c_G\varepsilon_k + L_2\varepsilon_k^2,$$

so $\|e_k\|_W \to 0$ *linearly if* $\varepsilon_k \equiv 0$*, and* $\limsup_k \|e_k\|_W \le \frac{4}{\beta\mu}\limsup_k(c_G\varepsilon_k + L_2\varepsilon_k^2)$ *in general.*

Proof. From (3), $\|(I-\beta M)e\|_W^2 = \|e\|_W^2 - 2\beta\langle e, Me\rangle_W + \beta^2\|Me\|_W^2 \le (1-2\beta\mu+\beta^2\Gamma^2)\|e\|_W^2 \le (1-\beta\mu)\|e\|_W^2$ for $\beta \le \mu/\Gamma^2$, and $\sqrt{1-\beta\mu} \le 1-\beta\mu/2$. The step satisfies $\|\theta_{k+1}-\theta_k\| \le \beta c_J c_L\|e_k\|_W + \varepsilon_k$, so $\|R_k\|_W \le \frac{L_2}{2}(\beta c_J c_L\|e_k\|_W + \varepsilon_k)^2 \le L_2\beta^2 c_J^2 c_L^2\|e_k\|_W^2 + L_2\varepsilon_k^2$. With $\|e_k\|_W \le \delta$ and the choice of δ, $L_2\beta^2 c_J^2 c_L^2\|e_k\|_W^2 \le \frac{\beta\mu}{4}\|e_k\|_W$. Adding $\|GJr_k\|_W \le c_G\varepsilon_k$ gives the recursion, valid as long as $\theta_k \in \mathcal{N}$ and $\|e_k\|_W \le \delta$. Invariance, by induction: if $\|e_k\|_W \le \delta$ then $\|e_{k+1}\|_W \le (1 - \frac{\beta\mu}{4})\delta + c_G\bar{\varepsilon} + L_2\bar{\varepsilon}^2 \le \delta$. Summing the recursion, $\sum_k\|e_k\|_W \le \frac{4}{\beta\mu}\big(\|e_0\|_W + c_G\varepsilon_\Sigma + L_2\bar{\varepsilon}\varepsilon_\Sigma\big)$, hence $\sum_k\|\theta_{k+1}-\theta_k\| \le \beta c_J c_L \sum_k\|e_k\|_W + \varepsilon_\Sigma \le R$: every iterate lies in the ball, inside $\mathcal{N}$, where all constants are valid. □

Noise.

(N1) The measured error is $\tilde{e}_k = e(\theta_k) + \xi_k$ with $\mathbb{E}[\xi_k \mid \mathcal{F}_k] = 0$ and $\mathbb{E}[\|\xi_k\|_W^2 \mid \mathcal{F}_k] \le \sigma^2$ (trial-to-trial noise from initial states, disturbances and sensing).

(N2) The Jacobian used in iteration k is $\mathcal{F}_k$-measurable, or its dependence on ξ_k is at most second order: $\|\mathbb{E}[(\widehat{L}(\tilde{x}_k) - \widehat{L}(x_k))\xi_k \mid \mathcal{F}_k]\|_W \le c_\xi\sigma^2$. (Our implementation evaluates $\widehat{G}$ at the measured states of the same trial; with idealized sensing in the pogo study $\xi \equiv$ start-state randomness only.)

Theorem 9 (Almost-sure convergence with Robbins–Monro gains)**.** *Let Assumptions A–C, (N1), (N2) with* $c_\xi = 0$ *hold,* $r_k = 0$*, and use gains* $\beta_k > 0$ *with* $\sum_k \beta_k = \infty$*,* $\sum_k \beta_k^2 < \infty$*,* $\beta_k \le \mu/\Gamma^2$*. On the event* $\Omega_{\mathcal{N}} := \{\theta_k \in \mathcal{N},\ \|e(\theta_k)\|_W \le \delta\ \forall k\}$*,* $e(\theta_k) \to 0$ *almost surely. If* $c_\xi > 0$*,* $\limsup_k \|e(\theta_k)\|_W = O(c_\xi\sigma^2/\mu)$ *a.s. on* $\Omega_{\mathcal{N}}$*.*

Proof. Let $V_k = \|e(\theta_k)\|_W^2$. The update uses $-\beta_k M_k\tilde{e}_k = -\beta_k M_k e_k - \beta_k M_k\xi_k$; by (N1) and $\mathcal{F}_k$-measurability of M_k, $\mathbb{E}[\langle e_k, M_k\xi_k\rangle_W \mid \mathcal{F}_k] = 0$. Expanding as in Theorem 8, $\mathbb{E}[V_{k+1} \mid \mathcal{F}_k] \le (1-\beta_k\mu)V_k + C\beta_k^2(V_k+\sigma^2)$ on $\Omega_{\mathcal{N}}$ for a constant C collecting Γ, L_2, c_J, c_L. The Robbins–Siegmund theorem gives $V_k \to V_\infty$ a.s. and $\sum_k \beta_k\mu V_k < \infty$ a.s.; since $\sum\beta_k = \infty$, $V_\infty = 0$. With $c_\xi > 0$ the conditional mean of the update carries an extra $O(\beta_k c_\xi\sigma^2)$ term, which leaves a neighbourhood of radius $O(c_\xi\sigma^2/\mu)$. □

Remark 10 (Localization). The event $\Omega_{\mathcal{N}}$ is not automatic: a noisy step can leave $\mathcal{N}$ (change the mode sequence, saturate). The implementation's rollback (a trial worse than the last kept one restores the previous network and halves the step) is a practical projection onto a safe set; it makes the iterate sequence a.s. remain in a sublevel set of the measured cost, not in $\mathcal{N}$. We state the theorem on $\Omega_{\mathcal{N}}$ and do not claim more.

5 Guided policy search: where it fails and where it does not

We take GPS in its standard form [1, 2, 3]: per trained condition (goal) a local controller p_g is optimized by a trajectory optimizer (iLQR/LQG) on a cost ℓ under a dynamics model, subject to a trust region (KL) to the current policy; the policy is regressed onto the local controllers; repeat. Three cases cover the variants relevant to sim-to-real.

5.1 GPS with the nominal model

Proposition 11 (Irreducible zeroth-order bias)**.** *Let GPS use $\widehat{f}$ for its trajectory optimization, with the task cost $\ell = \frac{1}{2}\|\widehat{E}_g\|_W^2$ (any additional cost terms only add bias). At any GPS fixed point θ_{GPS} with exact regression, the local controllers are model-optimal, $D_\theta \frac{1}{2}\|\widehat{E}_g(\theta_{\mathrm{GPS}})\|_W^2 = 0$; if the goals are feasible in the model and the model-optimal set is $\{\widehat{E}_g = 0\}$, then the real error is*

$$e_g(\theta_{\mathrm{GPS}}) = \underbrace{\widehat{E}_g(\theta_{\mathrm{GPS}})}_{=0} + \rho_g(\theta_{\mathrm{GPS}}), \qquad \rho_g := e_g - \widehat{E}_g,$$

with ρ_g the zeroth-order sim-to-real residual along the policy, so $\inf\{\|e_g(\theta)\|_W : \widehat{E}_g(\theta) = 0\} = \inf\{\|\rho_g(\theta)\|_W : \widehat{E}_g(\theta) = 0\}$, which is strictly positive whenever the residual does not vanish on the model's solution set. No number of GPS iterations reduces it; DistILC's fixed points (Proposition 4) have zero real error.

Proof. Immediate from the definitions: the GPS update depends on the real system only through the regression's input distribution, and its targets are model-optimal; the decomposition is the definition of ρ_g. □

Remark 12. This is the pogo study's zero-shot row: the nominal-sim network has 0% success on the real sticks (apex 4.5 cm low: the residual is the unmodelled leg damping), while the nominal-sim validation reports 100%.

5.2 GPS with dynamics fitted from real samples

In the unknown-dynamics variant [2], GPS fits a time-varying linear(-Gaussian) model $x_{t+1} \approx F_t[x_t; u_t; 1]$ per condition and iteration from N_s real rollouts and optimizes in that model. Because the fit includes the affine term from the real samples, the model reproduces the real trajectory to zeroth order, and with accurate first-order fits the fixed points are real optima: *this variant is unbiased*. Its cost is first-order information:

Proposition 13 (Identifiability needs $n+m+1$ rollouts per condition and iteration)**.** *For each t, the least-squares fit of $F_t \in \mathbb{R}^{n\times(n+m+1)}$ from samples $\{(x_t^i, u_t^i, x_{t+1}^i)\}_{i=1}^{N_s}$ has a unique solution iff the design matrix $Z_t = [x_t^i; u_t^i; 1]_i \in \mathbb{R}^{(n+m+1)\times N_s}$ has full row rank, which requires $N_s \geq n+m+1$ (and persistently exciting, i.e. deliberately perturbed, rollouts). For $N_s < n+m+1$, F_t is determined on the $(n+m+1-\operatorname{rank} Z_t)$-dimensional complement only by the prior/regularizer.*

Proof. Normal equations $F_t Z_t Z_t^\top = X_{t+1} Z_t^\top$ have a unique solution iff $Z_t Z_t^\top$ is invertible iff $\operatorname{rank} Z_t = n+m+1 \leq N_s$. For lower rank, any $F_t + \Delta$ with $\Delta Z_t = 0$ fits equally well. □

With N trained goals, unbiased first-order fits cost at least $N(n+m+1)$ real rollouts per iteration (the GMM prior of [2] pools across time and conditions and reduces this in practice, at the price of making the first-order model prior-dominated). DistILC uses one rollout per goal per iteration and no fitted first-order model: it takes the first-order information from the nominal model and needs only Assumption C of it.

5.3 GPS with a nominal prior and too few samples: the cost-regularization bias

With N_s below identifiability, a fitted model with a nominal prior has the measured zeroth order and an (essentially) nominal first order: its trajectory optimization then computes an approximate-Jacobian step on the measured residual, much like (1). The remaining difference is where regularization enters.

Proposition 14 (Cost-side regularization biases approximate-Jacobian fixed points; step-side damping does not)**.** *Let $\Phi(v) = \frac{1}{2}\|E(v)\|_W^2 + \frac{1}{2}v^\top Rv$, $R \succeq 0$ (control cost; entropy and KL-to-prior terms have the same effect locally), and consider any method whose fixed points satisfy the approximate stationarity $\widehat{G}^\top W E(\hat{v}) + R\hat{v} = 0$ (e.g. iLQR/DDP run to convergence in a model with the measured zeroth order and the nominal first order). Then at $\hat{v}$ the true gradient is*

$$\nabla\Phi(\hat{v}) = (G - \widehat{G})^\top W E(\hat{v}),$$

which is non-zero whenever $R\hat{v} \neq 0$, $\widehat{G}$ has full row rank and $(G - \widehat{G})^\top W$ is injective on the range of $E(\hat{v})$; so $\hat{v}$ is neither a real stationary point nor a real zero, with $\|\nabla\Phi(\hat{v})\| \leq \|G - \widehat{G}\|_W \|E(\hat{v})\|_W$ and $\|E(\hat{v})\|_W \geq \|R\hat{v}\|/\|\widehat{G}^\top W\|$. With $R = 0$ and damping only in the step (1), the fixed points are $\{E = 0\}$ (Proposition 4), the global minimizers of the real $\frac{1}{2}\|E\|_W^2$.

Proof. $\nabla\Phi = G^\top W E + Rv$; subtract the fixed-point condition. If $R\hat{v} \neq 0$ then $\widehat{G}^\top W E(\hat{v}) = -R\hat{v} \neq 0$, so $E(\hat{v}) \neq 0$ and $\|E\|_W \geq \|R\hat{v}\|/\|\widehat{G}^\top W\|$. □

This is the precise sense of the contrast with Abbeel, Quigley and Ng [4]: optimizing a utility with approximate derivatives converges to a region of size proportional to the derivative error; root-finding a measured residual with approximate derivatives converges to the root.

5.4 Summary of the comparison

method	real rollouts per goal and iteration	first-order information	real error at fixed points
GPS, nominal model	0	model	$\rho_g \neq 0$ (Prop. 11)
GPS, fitted dynamics	$\geq n + m + 1$	fitted (unbiased)	0 (if feasible, identifiable)
GPS, nominal prior, $N_s < n + m + 1$	N_s	$\approx$ model	biased if $R \neq 0$ (Prop. 14)
DistILC hardware stage	1	model, positivity only	0 (Prop. 4, Thm. 8)

"GPS fails" is therefore a statement about a regime: few real trials and a wrong model. With enough real samples to identify local dynamics, GPS does not fail; it costs at least $n + m + 1$ times more real rollouts per iteration.

6 Does correcting the flown goals correct the others?

Let $g' \notin \mathcal{G}_{\text{tr}}$ and $J_{g'}$ its policy Jacobian along its own trial. The first-order change of its error after one update is, by Lemma 3 and (2),

$$\Delta e_{g'} = -\beta\, G_{g'}\, S_{g',\text{tr}}\, \widehat{L}\, e_{\text{tr}} + O(\|\Delta\theta\|^2), \qquad S_{g',\text{tr}} := J_{g'} J^\top (JJ^\top + \rho I)^{-1}. \tag{4}$$

Proposition 15 (First-order transfer)**.** *Assume, for some $g \in \mathcal{G}_{\mathrm{tr}}$ at goal distance $d = \|g' - g\|$, within one mode-sequence cell: (T1) systematic error, $\|e_{g'} - e_g\|_W \le L_e d$; (T2) sensitivity continuity, $\|G_{g'} - G_g\| \le L_G d$; (T3) kernel coupling, $S_{g',\mathrm{tr}} = \kappa\, S_{g,\mathrm{tr}} + \Sigma$ with $\kappa > 0$ and $\|\Sigma\| \le s(d)$, $s(0) = 0$; (T4) positivity at g with margin μ_g for the row of M belonging to g. Then*

$$-\langle e_{g'}, \Delta e_{g'} \rangle_W \;\ge\; \beta\Big(\kappa\mu_g \|e_g\|_W^2 - c\,(L_e d + L_G d + s(d))\,\|e_{\mathrm{tr}}\|_W\,\|e_g\|_W\Big) - O(\beta^2),$$

so the unflown goal's error decreases to first order for $d < r^\star \propto \kappa\mu_g \|e_g\|_W / (L_e + L_G + s'(0))\,\|e_{\mathrm{tr}}\|_W^{-1}$: transfer is local, with a radius set by how fast the error, the sensitivity and the network's coupling vary with the goal.

Proof. Substitute (T1)–(T3) into the inner product

$$\langle e_{g'}, G_{g'} S_{g',\mathrm{tr}} \widehat{L} e_{\mathrm{tr}} \rangle_W,$$

expand around $\langle e_g, G_g S_{g,\mathrm{tr}} \widehat{L} e_{\mathrm{tr}} \rangle_W \ge \mu_g \|e_g\|_W^2$ (T4), and bound each cross term by Cauchy–Schwarz with the uniform bounds c_G, c_L; the constant c collects them. □

Evidence. Pogo stick, hardware stage on one goal $(0.8, 0.65)$ for 6 trials per robot, evaluated on a 7×5 goal grid over the whole box: the error ratio after/before is 0.11 at the trained goal, 0.16–0.45 within normalized distance 0.3, 0.37–0.89 at 0.5–0.73; the error decreased at all 35 goals. The main experiment's 8 test goals are all unflown; all improved. The sources of a systematic error (T1) are robot-wide (damping, mass, actuator scale), which is why transfer is broad here. Mode boundaries (e.g. a different contact sequence) violate (T2)/(T3) and give no first-order guarantee; nor does the theory guarantee anything beyond the trained goals: generalization is a property of the network and the data, not of the update.

7 The simulation stage

In simulation the "real" system is the nominal model, $G = \widehat{G}$ up to the hybrid approximation of saltation terms, and the recursion (3) has $M = GS\widehat{L}$ with $G\widehat{L} = G(G^\top W G + \lambda I)^{-1} G^\top W \succeq 0$ (a damped projector). Per lane positivity therefore holds automatically in the limit $S \to I$; what can fail is the *stacked* condition through S: lanes compete for one network (Lemma 6(iii)), and regression error r_k accumulates. We observed this: the nominal-sim stage's speed loop drifts late (the nominal-sim score cannot see it; a sim-only DR-family score can), and under domain randomization the drift starts before the DR objective is learned.

Proposition 16 (Monotone acceptance)**.** *If each update is kept only when the measured cost $\sum_{\text{lanes}} \frac{1}{2}\|e\|_W^2$ of the same lanes (same initial states, models and exploration noise) decreases, the cost of the accepted sequence on the lanes it is evaluated on is non-increasing, and an update is accepted whenever the first-order decrease $\beta\mu \sum \|e\|_W^2$ exceeds the second-order and regression terms of* (3)*, i.e. for β small enough when Assumption C holds on those lanes.*

Proof. The acceptance test is exactly the sign of the realized change of the cost; the rejection branch restores θ_k. The second statement is Theorem 8's one-step inequality summed over lanes. □

This is a guarantee on the evaluated lanes only (a fresh batch each iteration), not on the population; it removed the drift in the pogo study (speed error 0.04–0.10 m/s at iteration 60 against 0.7 m/s without it).

8 Mode cells: certifying and enforcing Assumption A(b)

Assumption A(b) asks the iterates to stay where the trial map is C^1. For hybrid systems with transversal, event-selected discontinuities the flow is *piecewise* differentiable, with a continuous piecewise-linear Bouligand derivative [8]: kinks, not jumps. The map from parameters to *sampled* trajectories and errors has two kinds of non-smoothness, which we separate.

Definition 17 (Mode signature and mode cells)**.** For a trial of (θ, g) let the *mode signature* $\sigma(\theta)$ be the ordered list of events (guard crossings: touchdown, lift-off, slip onset, a tire entering or leaving the sliding regime), each with its type and the control period in which it occurs, together with the actuator-saturation pattern (the periods and channels at a clip) and the fall flag. Its *topological part* σ^{top} keeps only the ordered types and the fall flag. The *piece* of θ is $P_\sigma = \{\theta' : \sigma(\theta') = \sigma(\theta)\}$ and its *mode cell* is $C_\sigma = \{\theta' : \sigma^{\mathrm{top}}(\theta') = \sigma^{\mathrm{top}}(\theta)\} \supseteq P_\sigma$.

Within a piece the sampled trial map is C^1 (Assumption A(b),(c) hold piecewise). Crossing between pieces of one cell (an event moving into the neighbouring control period, an action reaching its clip) is a kink; the analysis of Section 4 extends to it if positivity holds for every limiting Jacobian of the adjacent pieces (the Clarke generalized Jacobian), as in semismooth Newton methods. Crossing between cells (an event appears or disappears, a fall) is in general a jump of the error and lies outside every first-order argument.

Lemma 18 (Margin certificate)**.** *Let $\theta \in P_\sigma$. Suppose that on the closure of P_σ (i) each event time $\tau_i(\theta')$ is Lipschitz with constant L_τ (by the implicit function theorem, $L_\tau \le \sup\|\nabla h_i\|\|\partial_\theta x\|/|\dot h_i|$ under transversality), and (ii) every* inactive *guard value $\gamma_j(\theta')$ (a guard function along the trajectory where it does not cross, e.g. foot clearance during flight, leg force during stance, the distance of an action to its clip, a tire's distance to the sliding limit) is Lipschitz with constant L_γ. Define the margins*

$$m_\tau(\theta) := \min_i \operatorname{dist}\big(\tau_i(\theta), \{0, \Delta t, 2\Delta t, \dots, T\Delta t\}\big), \qquad m_\gamma(\theta) := \min_j |\gamma_j(\theta)|.$$

Then the ball $B\big(\theta, r(\theta)\big)$, $r(\theta) := \min\{m_\tau/L_\tau,\ m_\gamma/L_\gamma\}$, is contained in P_σ.

Proof. Let $\theta' \in B(\theta, r)$ and suppose $\theta' \notin P_\sigma$. On the segment from θ to θ' let $\theta^\star$ be the first point not in P_σ (it exists: P_σ is relatively open along the segment by continuity of the event times and guard values, and its complement is closed). At $\theta^\star$ the signature changes, so either an event time reaches a control-period boundary, which needs $|\tau_i(\theta^\star) - \tau_i(\theta)| \ge m_\tau$, hence $\|\theta^\star - \theta\| \ge m_\tau/L_\tau \ge r$; or an inactive guard reaches zero (an event appears, a clip activates), which needs $|\gamma_j(\theta^\star) - \gamma_j(\theta)| \ge m_\gamma$, hence $\|\theta^\star - \theta\| \ge m_\gamma/L_\gamma \ge r$; or an event disappears, which happens only through its guard becoming inactive, i.e. through an event time leaving the horizon (the first case, with the boundaries 0 and $T\Delta t$) or a transversality loss, excluded by (i). Every case contradicts $\|\theta^\star - \theta\| < r$. The Lipschitz bounds apply on the segment up to $\theta^\star$, which lies in the closure of P_σ. □

Corollary 19 (Certified steps)**.** *If every update satisfies $\|\theta_{k+1} - \theta_k\| < r(\theta_k)$, all iterates lie in one piece, where Theorem 8 applies with $\mathcal{N} = P_\sigma$ (if its other hypotheses hold there).*

The certificate needs L_τ and L_γ *of the real system*, which are unknown. They can be estimated from consecutive trial pairs (measured change of event times and guard values per parameter change), or bounded from the nominal model and an assumed mismatch. Either way the certificate has the same epistemic status as positivity: an assumption checkable from data, not a guarantee from the model.

Proposition 20 (Mode-consistent acceptance)**.** *Suppose the algorithm keeps an update only if the next trial's topological signature equals that of the last kept trial at every flown goal (and rolls back otherwise). Then every kept iterate lies in the mode cell of the first one. Theorem 8, with the semismooth extension above, applies to the kept sequence if (a) a zero of the real error exists in the interior of that cell, (b) positivity holds for all limiting Jacobians in the cell, and (c) the steps can be shrunk until accepted (the rollback's halving).*

Proof. The cell is defined by a measured quantity; the acceptance rule makes the kept sequence remain in it by construction. Within the cell the trial map is piecewise C^1 with finitely many pieces (finitely many event-to-period assignments and clip patterns), continuous across pieces [8]; the contraction argument of Theorem 8 holds with any element of the generalized Jacobian under (b). Halving the step makes it eventually smaller than the certified radius of Lemma 18, so (c) holds whenever the current iterate is in the cell's interior. □

What remains an assumption is (a): that the solution lies inside the cell and can be reached without crossing. Nothing local certifies it in advance; after convergence the margins at the limit can be checked.

How often do our domains cross? Measured on the hardware stages from the mode signatures (consecutive trials of a robot at the same goal; events compared on their common prefix, so that an event moving past the end of the trial window is not counted as a mode change):

domain	topological change (cell)	piece change (kink) and margins
pogo stick	**0%** (nominal and DR networks, 108 pairs each); mode-consistent acceptance never fires and costs nothing	96–98%: an event moves to the neighbouring 10 ms period almost every iteration (median event margin 1–3% of a period)
quadruped	push-off 61–65% (stance-foot contact flicker ≥ 6 ms), landing 47–57% (bounces), fall outcome 7–11%; 80–88% of jumps touch down before the landing sample N	94–98%; torque saturation in 11% of push-off samples
car	tire regimes (front/rear axle sliding) 53% (a slide appears or vanishes in a corner); no crashes in the recorded arms	100% with actuator clips: the steering is at ± 0.34 rad 51% of the time and toggles ∼46 times per 2-lap trial; the axles slide 78–86% of the time, only 5–7% of periods within 10% of the sliding limit

So the three domains sit at different places relative to the theory. The pogo stick's hardware stage stays in one mode cell and crosses kinks constantly, exactly the piecewise-differentiable regime of this section. The car and the quadruped cross cells in about half of their iterations, and their convergence rests on positivity holding for the averaged or saturated Jacobians actually used (finite differences through soft contact; Fiala forces in full slide, whose lateral sensitivity to slip angle is zero), not on the local analysis. This is a statement about the scope of the theory, made with measured numbers, not a claim that the theory covers them.

How other work handles discontinuities.

- *Assume differentiability almost everywhere, treat discontinuities heuristically.* Deep off-policy ILC [7], the closest relative of DistILC, assumes the simulator and reward "differentiable in most regions" and handles non-smooth dynamics by skipping or clipping the gradient update on such transitions and by hinge losses on the value-gradient terms; there is no mode identification and no convergence statement.
- *Fix the mode sequence by design*: hybrid zero dynamics [14] plans the contact sequence and stabilizes the motion along it; early or late impacts are disturbances. Our quadruped's prescribed push-off schedule is of this kind.
- *Model the jump*: saltation matrices give the first-order effect of an event [8, 9]; hybrid iLQR adds a reference extension for mode mismatch [9]; sensitivity analysis of trajectories with state-triggered jumps and *reference spreading* (overlapping ante- and post-impact references) keep tracking errors meaningful when impact times shift [12, 13]. Our straight-through saltation terms (pogo stick) are a crude instance; the arc-length-indexed errors of the car are the analogue of time reparameterization.
- *Smooth the contact*: first-order gradients are biased near discontinuities, and zeroth-order (RL-style) estimators amount to randomized smoothing [10]; stochastic and analytic smoothing are equivalent on simple systems and enable planning through contact [11]; soft-contact simulators (MuJoCo) are smooth by construction [15]. Our quadruped's finite-difference Jacobians through soft contact are an implicit smoothing of this kind.
- *Fit local models that span modes*: GPS under unknown dynamics fits time-varying linear-Gaussian dynamics with a Gaussian-mixture prior (soft piecewise-linear dynamics) and bounds each update by a KL trust region so that the local fit stays valid [2]: mode locality enforced through the step size, not identified. In the pogo study, fitting local dynamics from real samples that straddle different event timings gives Jacobians with median positivity cosine 0.15–0.21 and 0–9% success at up to 192 trials per robot, against 0.9 and 80–87% for the nominal model's derivative at 24–48 trials.

None of these certifies, during learning on the real system, that the iterates stay in one mode cell; Lemma 18 and Proposition 20 make that a measured and enforced condition, at the price of an estimated Lipschitz constant and of stalling, rather than converging, when the solution lies across a boundary.

9 Domain randomization, for comparison

Let $\xi \sim \nu$ index the randomized family and $L(\theta;\xi)$ the task loss. DR's SGD converges (under the usual conditions) to stationary points of $\bar{L}(\theta) = \mathbb{E}_\nu L(\theta;\xi)$. If reality is $\xi^\star$, the real loss at DR's optimum is $L(\theta_{\mathrm{DR}};\xi^\star)$, which is small only if (C1) $\xi^\star$ lies where ν has mass and (C2) the compromise optimum $\arg\min \bar{L}$ is near $\arg\min L(\cdot;\xi^\star)$ (no conflicting family members, or a policy that can identify ξ from observations). Neither (C1) nor (C2) is checkable from simulation alone; positivity is checkable from a few real trial pairs. The two are not nested: reality can lie outside every family while positivity holds (Lemma 6(ii) with a large gain error), and a wide family can contain reality while the nominal Jacobian points more than 90° off. They are complementary: DR is a choice of warm start, the ILC update is a convergence mechanism; the pogo study's best arm is the DR policy followed by the ILC hardware stage (94–96%).

10 Anticipated criticisms

1. **"This is ILC / Abbeel et al. 2006 / GPS with a prior."** The per-goal step (1) is approximate-model ILC; we do not claim it. What is analysed here is its use as the regression target of one goal-conditioned feedback network shared across goals (operator S, Sections 2, 6), the role of the network's own feedback in the sensitivity (Definition 1), and the fixed-point contrast with cost-optimizing methods (Proposition 14). With a nominal prior and too few samples, GPS becomes a close relative; the difference is then the regularization (cost-side vs step-side) and the use of one step per trial instead of a converged local optimization.

2. **"Positivity is an unverifiable assumption."** It is a condition on observables: predicted vs measured error changes over consecutive trials. Lemma 6 gives model-error conditions (small gain; multiplicative mismatch of any size). Empirically it holds in 97% of pogo trial pairs and predicts the gain; the flipped-Jacobian control fails as predicted.

3. **"Only local."** Yes: Theorems 8–9 are local, on a neighbourhood $\mathcal{N}$ inside one mode-sequence cell. A warm start in the basin (the simulation stage, or a DR policy) is part of the method.

4. **"Hybrid systems are not differentiable."** Assumption A(b) restricts the analysis to a fixed transversal mode sequence, where the trial map is C^1 with saltation terms. The implementation's straight-through saltation terms are an approximation of G, i.e. part of $G - \widehat{G}$, covered by positivity; mode-sequence changes are outside the theory.

5. **"The network cannot realize the targets."** Captured by $S \neq I$ (cross-goal coupling) and the regression error r_k (Theorem 8's $O(\varepsilon)$ neighbourhood). Realizability (Assumption B(a)) is an over-parameterization assumption on the visited inputs; it can fail with conflicting targets (one observation, two goals asking for opposite corrections), which is the interference term of Lemma 6(iii).

6. **"Guarantees only on the trained goals."** Correct. Proposition 15 is a first-order, conditional statement; generalization to unflown goals is empirical (Section 6).

7. **"What if a goal is infeasible on the real system?"** Then $\{e_g = 0\} = \emptyset$ and Proposition 4 says there is no fixed point at that goal; any limit satisfies only $\widehat{L}e = 0$ in the damped sense, which is *not* the real least-squares stationarity $G^\top W e = 0$: our iteration is biased for infeasible goals, as Proposition 14 shows for cost-optimizers. The implementation's stall guard and fallback ladders handle infeasible goals heuristically.

8. **"More error rows than inputs."** Then $\widehat{G}$ cannot have full row rank and zero error is generically unreachable; the theory requires $\dim \mathcal{E}_g \leq \dim \mathcal{V}$ (Assumption B(b)). In the pogo instance $q = m = 2$ and half the rows are masked in stance.

9. **"Noise in the Jacobian correlates with noise in the error."** (N2) with $c_\xi > 0$; the bias is second order in the noise level (Theorem 9). Averaging repeated trials or evaluating $\widehat{G}$ on the previous trial removes it.

10. **"Step sizes are tuned."** The theory prescribes $\beta \leq \mu/\Gamma^2$; the full Gauss–Newton step ($\beta = 1$, small λ) was chosen on validation goals in the pogo study. Too large a step leaves the region of Theorem 8; the rollback guards against it.

11. **"The sensitivity uses the policy's own feedback, which changes."** Yes: M depends on θ through K and S. A fragile network can lose positivity (observed: a DR network on the heavy pogo stick, median cosine < 0, no gain). Assumption C is uniform on $\mathcal{N}$ for this reason.

12. **"The comparison to GPS is not empirical."** Propositions 11–14 are structural. The nominal-model case is measured (zero-shot row); a fitted-dynamics GPS arm at equal real budget is the missing experiment.

13. **"DR wins zero-shot."** When its family covers reality it can (PPO+DR 77% vs 0% for the nominal-sim network on the pogo sticks, whose damping lies inside the DR family). The claim is not dominance; it is that the ILC update converges on the real system under a different, checkable assumption, and that it composes with DR.

14. **"Finite horizon, finite trials."** The theorems are asymptotic in the iteration count at fixed horizon T; at 24 trials the pogo study is in the transient regime, where the linear rate of Theorem 8 is the relevant statement.

Assumption index

(S1)–(S6)	finite horizon; open state set, compact convex action set, compact goal set; trial input space $\mathbb{R}^{Tm}$ (Euclidean); error space $\mathbb{R}^{Tq}$ with $W \succ 0$ (active rows only); parameter space $\mathbb{R}^p$; filtered probability space, measurable noise.
(D1)–(D3)	real (possibly hybrid) dynamics, nominal model, closed-loop trial map with an additive input.
A	interior actions; fixed transversal mode sequence on $\mathcal{N}$; Lipschitz $D_\theta e$; C^2 policy.
B	realizability (J surjective on the visited inputs); full row rank of $\widehat{G}_g$ ($\dim \mathcal{E}_g \le \dim \mathcal{V}$).
C	positivity: $\mathrm{sym}_W(GS\widehat{L}) \succeq \mu I$, $\|GS\widehat{L}\| \le \Gamma$ on $\mathcal{N}$, cross-goal interference included.
(N1)–(N2)	zero-mean, bounded-variance trial noise; Jacobian independent of the current noise (or second-order).
Thm. 8	small initial error, step $\beta \le \mu/\Gamma^2$, iterates stay in $\mathcal{N}$, regression error ε_k.
Thm. 9	Robbins–Monro gains; on the event that the iterates stay in $\mathcal{N}$.
Prop. 15	(T1)–(T4): systematic error, sensitivity continuity, kernel coupling, positivity at a flown goal; same mode-sequence cell.

References

[1] S. Levine and V. Koltun. Guided policy search. ICML, 2013.

[2] S. Levine and P. Abbeel. Learning neural network policies with guided policy search under unknown dynamics. NeurIPS, 2014.

[3] W. Montgomery and S. Levine. Guided policy search via approximate mirror descent. NeurIPS, 2016. [verify]

[4] P. Abbeel, M. Quigley and A. Y. Ng. Using inaccurate models in reinforcement learning. ICML, 2006.

[5] H. Robbins and D. Siegmund. A convergence theorem for non negative almost supermartingales and some applications. Optimizing Methods in Statistics, 1971.

[6] H. J. Kushner and G. G. Yin. Stochastic Approximation and Recursive Algorithms and Applications. Springer, 2003.

[7] S. Gurumurthy, J. Z. Kolter and Z. Manchester. Deep off-policy iterative learning control. Learning for Dynamics and Control (L4DC), PMLR 211, 2023.

[8] S. A. Burden, S. S. Sastry, D. E. Koditschek and S. Revzen. Event-selected vector field discontinuities yield piecewise-differentiable flows. SIAM J. Applied Dynamical Systems 15(2):1227–1267, 2016.

[9] N. J. Kong, G. Council and A. M. Johnson. iLQR for piecewise-smooth hybrid dynamical systems. IEEE CDC, 2021 (arXiv 2103.14584).

[10] H. J. T. Suh, M. Simchowitz, K. Zhang and R. Tedrake. Do differentiable simulators give better policy gradients? ICML, PMLR 162, 2022.

[11] T. Pang, H. J. T. Suh, L. Yang and R. Tedrake. Global planning for contact-rich manipulation via local smoothing of quasi-dynamic contact models. IEEE Trans. Robotics, 2023.

[12] A. Saccon, N. van de Wouw and H. Nijmeijer. Sensitivity analysis of hybrid systems with state jumps with application to trajectory tracking. IEEE CDC, 2014.

[13] M. Rijnen, A. Saccon and H. Nijmeijer. Reference spreading: tracking performance for impact trajectories of a 1DoF setup. IEEE Trans. Control Systems Technology 28(3):1124–1131, 2020. [verify]

[14] E. R. Westervelt, J. W. Grizzle, C. Chevallereau, J. H. Choi and B. Morris. Feedback Control of Dynamic Bipedal Robot Locomotion. CRC Press, 2007. [verify]

[15] E. Todorov. Convex and analytically-invertible dynamics with contacts and constraints: theory and implementation in MuJoCo. IEEE ICRA, 2014. [verify]