

Group C - No-Tool Experiment Tasks

You will perform the tasks with the python file (notool-c.py) which contains the solution to a regression problem, predicting housing prices in California. This has been done using SK-Learn. You will perform the following instructions and tasks where you will alter certain data such as hyperparameter and dataset features, and run the regression using two different supervised learning algorithms: Linear_regression and Random Forest Regressor algorithms.

1) You are required to track the following assets/data using the way you see best:

- The datasets and features used for each run
- Relevant parameters and hyper-parameters are used in each run.
- The model generated in each run
- The evaluation metrics obtained from generated model

Experimenting with algorithm 1 (Linear Regression)

Carry out several experiment runs using different sets of dataset features and learning parameters as described below. Execute the python script to train and evaluate the model.

1. **Run 1:** Use the default dataset features and parameter values and execute the python scripts:

```
$ python notool-c.py
```

2. **Run 2:** Change the normalize parameter to False and execute the script again:

```
$ python notool-c.py
```

3. **Run 3:** In the California dataset we have a total of 8 features::

```
Attribute Information:
- MedInc      median income in block
- HouseAge    median house age in block
- AveRooms    average number of rooms
- AveBedrms   average number of bedrooms
- Population  block population
- AveOccup    average house occupancy
- Latitude    house block latitude
- Longitude   house block longitude
```

Now we will train the model with 3 features: 'MedInc', 'HouseAge', 'AveBedrms'. Uncomment line 24.

Run the file again: `$ python notool-c.py`

4. **Run 4:** We have used 80% (0.20) of the dataset as a training set. Change the `test_size` to 70% (0.30) That's in `split_param`, for a change.

```
# Splitting the data and setting test_size
split_param = {'test_size': 0.20, 'random_state': 28750}

X_train, X_test, y_train, y_test = train_test_split(data, y, **split_param)
```

Run the script again: `$ python notool-c.py`

5. **Run 5:** We will now use other features to train the model. Change the 'MedInc' to "AveRooms". Also, set the "normalize" parameter to True

Run the file again: `$ python notool-c.py`

6. **Run 6:** Use all features from the dataset to train the model. Do this by commenting out line 24

Run the file again: `$ python notool-c.py`

7. **Run 7:** Add 'Latitude' to the features in line 24. And uncomment line 24 again.

Run the file again: `$ python notool-c.py`

Experimenting with algorithm 2 (RFR)

We have carried out a series of runs using the Linear Regression algorithm, and now we will use the RFR algorithm. This will give us different results compared to the previous algorithm.

1. **Run 8:** Comment out the Linear regression model with (#), and uncomment the RandomForestRegressor, as shown below:

```
model = RandomForestRegressor(**parameters)
#model = LinearRegression(normalize=True)
```

Run the file again: `$ python notool-c.py`

2. **Run 9:** The parameter we are using for the RFR is in line 32, uncomment it.

```
# The parameters for Random Forest Regressor
parameters = {'n_estimators': 50, 'max_depth': 5, 'min_samples_split': 6, 'ccp_alpha'=0.1}
```

Run the script again: `$ python notool-c.py`

3. **Run 10:** To avoid overfitting we will change the `ccp_alpha`. Change the `ccp_alpha` variable to 0.01

Run the script again: `$ python notool-c.py`

4. **Run 11:** Now we will add more features to train the model. Add '**Population**' in feature selection. This is how it should look:

```
df = df[['AveRooms', 'HouseAge', 'AveBedrms', 'Latitude', 'Population']]
```

Run the script again: `$ python notool-c.py`

5. **Run 12:** Let's try to improve the model. The default value of `max_features` is `None`. Add the following to the parameter dictionary in line 42:

`'max_features': 'log2'`

Run the file again: `$ python notool-c.py`

6. **Run 13:** Change the `test_size` back to 0.20.

Run the file again: `$ python notool-c.py`

***Now return to the experiment's questionnaire**