



Uncertainty Estimation for Natural Language Processing. Text Generation Tasks

Artem Vazhentsev

PhD Student at Skoltech,
Junior Research Scientist at AIRI



Contents

1. Background
2. Baselines for Uncertainty Estimation of LLMs
3. SOTA for Uncertainty Estimation of LLMs
4. Applications of Uncertainty Estimation
5. Conclusion

1



Background

Problem Statement (1)

ChatGPT:



How many letters are there in the word "nineteen"?



There are nine letters in the word "nineteen."



No, there are 12 letters in the word "nineteen."



You are correct. I apologize for the mistake. There are indeed 12 letters in the word "nineteen." My mistake was due to a misunderstanding of the question. When you asked how many letters were in the word "nineteen," I interpreted that to mean the number of letters in the word when it is written in numerical form, which is nine. However, when the word is written out in full, as a written word, there are indeed 12 letters. Again, I apologize for the mistake.



Are you sure there are 12 letters in the word "nineteen"?



Try again

Problem Statement (2)

ChatGPT:

What is the language with the highest number of total speakers in the world that is not an official language of the United States?



The language with the highest number of total speakers (native + non-native) that is **not** an official language of the United States is **Hindi**.

Problem Statement (3)

DeepL Translator

English (detected) ▾



↔ Russian ▾






Automatic ▾

Glossary

The following is a list of the most important information about the situation in the world, and it is important to note that this is the first time that a person is in the world. ✕

Примечание.

Problem Statement (4)

A

Tell me about prof. Alexander Panchenko



Professor Alexander Panchenko is a well-known researcher in the field of natural language processing (NLP) and computational linguistics. He is currently a Full Professor of Computational Linguistics at the University of Hamburg, Germany, where he leads the Language Technology Group.



Prof. Panchenko's research interests include NLP, machine learning, and information retrieval. His research focuses on developing algorithms and models for solving challenging NLP problems, such as word sense disambiguation, sentiment analysis, and semantic similarity. He is particularly interested in the use of deep learning techniques for NLP applications.

Prof. Panchenko has published extensively in leading NLP and computational linguistics conferences and journals, including ACL, EMNLP, COLING, and TACL. He has also served as a program committee member and reviewer for many of these conferences.

In addition to his research, Prof. Panchenko is active in promoting and supporting the NLP community. He has organized several workshops and tutorials on NLP and machine learning, and has served as a reviewer for many NLP-related journals and conferences. He is also the editor-in-chief of the Natural Language Processing journal, which is published by Springer.

Overall, Prof. Alexander Panchenko is a respected and accomplished researcher in the field of NLP and computational linguistics, and his work has made important contributions to the field.

Problem Statement (5)

InstructGPT (text-davinci-003):

Tell me about prof. Alexander Panchenko



AI:

Professor Alexander Panchenko is a well-known AI researcher and professor of the Department of Computer Science at the University of Saskatchewan. He has a long history of teaching and research in artificial intelligence, robotics, and intelligent systems. He has published numerous books and articles on these topics and is an active member of the AI community. Professor Panchenko is renowned for his deep understanding of AI technologies and techniques, which he uses to develop solutions to challenging problems. As an educator, he is highly respected for his lectures and seminars, which are consistently rated as "must attend" events by his students. Professor Panchenko is considered a leader in the field of artificial intelligence.

Human:|

Problem Statement (6)

There are **infinite number of possible answers** and decisions are generally based sampling and inference algorithms such as beam search

Question: What is the capital of Russia?

Correct answers:

- Moscow
- The capital is Moscow
- It's Moscow
- Moscow, Russia

Incorrect answers:

- Saint Petersburg
- Berlin
- Vladivostov
- Siberia

Problem Statement (7)

Conditional dependency between generated tokens:




Metrics

Prediction Rejection Ratio (PRR) metric measures the correctness of the ranking of generations based on uncertainty relative to a specified quality metric

$$PRR = \frac{AUC_{\text{unc}} - AUC_{\text{rnd}}}{AUC_{\text{oracle}} - AUC_{\text{rnd}}}$$

The choice of the generation quality measure depends on the task, e.g. Accuracy, ROUGE, AlignScore , or COMET.



2

Baselines for Uncertainty Estimation of LLMs

Sequence Probability

For a given:

- x – input sequence (prompt)
- y – generated sequence of length L
- θ – model parameters

We can compute:

$$P(y \mid x, \theta) = \prod_{l=1}^L P(y_l \mid y_{<l}, x, \theta)$$

$$U_{\text{Perplexity}}(x) = \exp\left\{-\frac{1}{L} \log P(y \mid x)\right\}$$

$$U_{\text{MSP}}(y \mid x, \theta) = 1 - P(y \mid x, \theta)$$

- Probability of the generated sequence

- Perplexity or Normalized Sequence Probability (NSP)


- Maximum Sequence Probability (MSP)

Density-Based Methods (1)

Mahalanobis distance (**MD**) is a generalization of the Euclidean distance, which takes into account the spreading of instances in the training set along various directions in a feature space:

$$U^{\text{MD}}(\mathbf{x}, l) = (h_l(\mathbf{x}) - \mu)^T \Sigma^{-1} (h_l(\mathbf{x}) - \mu)$$


where $h_l(\mathbf{x})$ is a hidden representation of instance \mathbf{x} from the layer l , Σ is the empirical covariance matrix, and μ is a centroid of the training data.



Density-Based Methods (2)

Relative Mahalanobis distance (RMD) is a modification of MD that takes into account a background contrastive MD score $U_0^{\text{MD}}(\mathbf{x}, l)$:

$$U^{\text{RMD}}(\mathbf{x}, l) = U^{\text{MD}}(\mathbf{x}, l) - U_0^{\text{MD}}(\mathbf{x}, l)$$



Density-Based Methods (3)

PE – product of expectations (ensemble-based UEs)




Figure 1: Average ROC curves in various configurations on the NMT task for the selected UE methods. The first dataset in the title represents the ID dataset, the second is the OOD dataset.

While achieving state-of-the-art performance in OOD detection for sequence-to-sequence models, the performance is low for selective generation using LLMs

Reflexive (white-box)

$U_{p(True)} = 1 - P(True | x, y)$ – the probability of the token “True”, given the input prompt:

```
Question: Who was the third president of the United States?  
Here are some brainstormed ideas: James Monroe  
Thomas Jefferson  
John Adams  
Thomas Jefferson  
George Washington  
Possible Answer: James Monroe  
Is the possible answer:  
  (A) True  
  (B) False  
The possible answer is:
```

Reflexive (black-box)

Idea: ask the LLM to self-assess its confidence level after the response generation

Verb. 1S top-1 Provide your best guess and the probability that it is correct (0.0 to 1.0) for the following question. Give ONLY the guess and probability, no other words or explanation. For example:\n\nGuess: <most likely guess, as short as possible; not a complete sentence, just the guess!>\n\nProbability: <the probability between 0.0 and 1.0 that your guess is correct, without any extra commentary whatsoever; just the probability!>\n\nThe question is: \${THE_QUESTION}


Sampling-based Methods

For a given:

- x – input sequence (prompt)
- θ – model parameters

We can compute:

- $y_1, y_2 \dots y_N$ – N sequences generated via multinomial sampling or beam search



Lexical Similarity

Compute average lexical similarity between the generated answers:

$$\text{D-Lex-Sim} = \frac{1}{C} \sum_{i=1}^{|\mathbb{H}|} \sum_{j=1}^{|\mathbb{H}|} \text{sim}(h_i, h_j)$$

sim – is a sentence similarity measure, e.g. ROUGE, BLUE, or BERTScore

Variants of Predicted Entropy

Monte-Carlo estimation of the predicted entropy (PE) for N samples:

$$1. \quad U_{PE}(x) = - \int P(y|x) \log P(y|x) dy = \mathbb{E}_{y \sim P(y|x)} [-\log P(y|x)] \approx -\frac{1}{N} \sum_{i=1}^N \log P(y_i|x)$$

To ensure balanced contributions to the overall uncertainty from sequences of different lengths, we can employ a length-normalized version of PE:

$$\bar{P}(y|x) = \exp \left(\frac{1}{L} \sum_{l=1}^L \log P(y_l|x) \right)$$

$$2. \quad U_{LN-PE}(x) = - \int \bar{P}(y|x) \log \bar{P}(y|x) dy = \mathbb{E}_{y \sim \bar{P}(y|x)} [-\log \bar{P}(y|x)] \approx -\frac{1}{N} \sum_{i=1}^N \log \bar{P}(y_i|x)$$

3

SOTA for Uncertainty Estimation of LLMs

Semantic Entropy (1)

Problem of PE: semantic equivalence of different answers

(a) Scenario 1: No semantic equivalence			(b) Scenario 2: Some semantic equivalence		
Answer s	Likelihood $p(s x)$	Semantic likelihood $\sum_{s \in c} p(s x)$	Answer s	Likelihood $p(s x)$	Semantic likelihood $\sum_{s \in c} p(s x)$
Paris	0.5	0.5	Paris	0.5	0.9
Rome	0.4	0.4	It's Paris	0.4	
London	0.1	0.1	London	0.1	0.1
Entropy	0.94	0.94	Entropy	0.94	0.33

Semantic Entropy (2)


Idea: Group the answers into clusters based on their meaning, and calculate the predictive entropy within each cluster:

$$SE(x) = - \sum_c p(c | x) \log p(c | x) = - \sum_c \left(\left(\sum_{\mathbf{s} \in c} p(\mathbf{s} | x) \right) \log \left[\sum_{\mathbf{s} \in c} p(\mathbf{s} | x) \right] \right)$$


Finally, Semantic Entropy can be computed as:

$$SE(x) \approx -|C|^{-1} \sum_{i=1}^{|C|} \log p(C_i | x)$$

Comparison



(a)



(b)


Shifting Attention to Relevance (SAR) (1)

Token relevance:

$$R_T(z_i, s, x) = 1 - |g(x \cup s, x \cup s \setminus \{z_i\})|$$

Token-shifted probability:

$$U_{\text{TokenSAR}}(x) = - \sum_{l=1}^L \tilde{R}_T(y_l, y, x) \log P(y_l | y_{<l}, x)$$



Shifting Attention to Relevance (SAR) (2)

Sentence relevance:
$$R_S(s_i, S, \mathbf{x}) = \sum_{j=1, j \neq i} g(s_i, s_j) p(s_j | \mathbf{x})$$

Sentence SAR:
$$U_{\text{SentSAR}}(\mathbf{x}) = -\frac{1}{K} \sum_{k=1}^K \log \left(P(\mathbf{y}^{(k)} | \mathbf{x}) + \frac{1}{t} R_S(\mathbf{y}^{(k)}, \mathbf{x}) \right)$$

Combining SentenceSAR and TokenSAR results in a new method SAR by replacing the generative probability with token-shifted probability:

$$P'(\mathbf{y} | \mathbf{x}) = \exp\{-\text{TokenSAR}(\mathbf{y}, \mathbf{x})\}$$

Black-box Methods

1. Construct a matrix S representing similarities between responses based on some semantic similarity measure, e.g. NLI entailment score
2. Compute uncertainty by analyzing the similarity matrix:
 - a) Lexical Similarity
 - b) Sum of Eigenvalues of the Graph Laplacian: $U_{EigV} = \sum_{k=1}^K \max(0, 1 - \lambda_k)$
 - c) Degree Matrix: $U_{Deg} = 1 - \text{trace}(D)/K^2$
 - d) Eccentricity: $U_{Ecc} = \|\tilde{\mathbf{v}}_1^T, \dots, \tilde{\mathbf{v}}_K^T\|_2$

$$L = I - D^{-\frac{1}{2}} S D^{-\frac{1}{2}} \quad \text{- Laplacian Matrix}$$

$$D_{ii} = \sum_{j=1}^K S_{ij} \quad \text{- Degree Matrix}$$

$$\mathbf{u}_1, \dots, \mathbf{u}_K \in \mathbb{R}^K \quad \text{- eigenvectors of } L; \quad \mathbf{v}_j = [u_{1,j}, \dots, u_{K,j}] \quad \text{- "informative" embedding for } s_j$$

Claim Conditioned Probability (CCP)

Sentence:

She attended the School of Design, where she earned a Bachelor of Fine Arts Degree in painting.

AAAAAAAA AA AAAA AAAA AAAAAA AA AAAAAAAAAA

Fact: She earned a Bachelor of Fine Arts Degree in painting.

She attended the School of Design, where she earned a Bachelor of Fine Arts Degree in ...

painting 49%

art 3%

acting 7%

sculpture 2%

1977 39%

NLI(Bachelor of Fine Arts Degree in painting, Bachelor of Fine Arts Degree in painting) = entail

NLI(Bachelor of Fine Arts Degree in painting, Bachelor of Fine Arts Degree in art) = entail

NLI(Bachelor of Fine Arts Degree in painting, Bachelor of Fine Arts Degree in acting) = contra

NLI(Bachelor of Fine Arts Degree in painting, Bachelor of Fine Arts Degree in sculpture) = contra

NLI(Bachelor of Fine Arts Degree in painting, Bachelor of Fine Arts Degree in 1977) = neutral

top-K words


$$\text{CCP}_{\text{word}}(\text{painting}) = (\text{P}(\text{painting}) + \text{P}(\text{art})) / (\text{P}(\text{painting}) + \text{P}(\text{art}) + \text{P}(\text{acting}) + \text{P}(\text{sculpture})) \\ = 0.52 / 0.61 = 0.85$$

$$\text{CCP}_{\text{word}}(\text{of}) = \text{CCP}_{\text{word}}(\text{in}) = 1 \quad (\text{functional words})$$

$$\text{CCP}_{\text{claim}}(\text{She earned a Bachelor of Fine Arts Degree in painting.}) = \\ -(\text{CCP}_{\text{word}}(\text{Bachelor}) * \text{CCP}_{\text{word}}(\text{of}) * \text{CCP}_{\text{word}}(\text{Fine}) * \text{CCP}_{\text{word}}(\text{Arts}) * \\ \text{CCP}_{\text{word}}(\text{Degree}) * \text{CCP}_{\text{word}}(\text{in}) * \text{CCP}_{\text{word}}(\text{painting}))$$


Overall Comparison

Mean PRR aggregated over all QA tasks (CoQA, TriviaQA, GSM8k, and MMLU)



Overall Comparison (2)

Mean PRR aggregated over all selective generation tasks (ATS and NMT)



Supervised Methods (1)

Idea: train a supplement model to predict the level of uncertainty of the model

$$U_{\text{supervised}}(\mathbf{x}) = f(h(\mathbf{x}))$$

SAPLMA is a one of the pioneering supervised methods. This approach employs a multi-layer perceptron (MLP) with four layers, trained on the hidden states of the LLM to serve as f .

Supervised Methods (2)


Several works aim to enhance the performance of the SAPLMA method:

1. MIND (explores embedding selection and optimizes the training configuration)
2. Sheeps (incorporating a trainable attention layer to re-weight token embeddings)

$$p(y_i = 1 \mid u, x_{\leq i}) = \sigma(\mathbf{w}^\top \bar{\mathbf{h}}_i)$$
$$\bar{\mathbf{h}}_i = \sum_{j=1}^i \alpha_{i,j} \mathbf{h}_j, \quad \alpha_{i,j} = \frac{\exp(\mathbf{q}^\top \mathbf{h}_j)}{\sum_{k=1}^i \exp(\mathbf{q}^\top \mathbf{h}_k)}$$

3. Factoscope (combines multiple DL models trained on diverse features extracted from LLMs, e.g. activations, distances between embeddings of the top-K predicted tokens, ranks of predicted tokens)

Supervised Methods (3)




1. Extract **token-level embeddings** from each decoder layer of the LLM
2. Select a **subset of token embeddings** from high-quality LLM responses
3. Compute MD or RMD for each token at every layer
4. **Aggregate token-level scores** by averaging across the generated sequence
5. **Apply PCA** to enhance robustness
6. **Add the sequence probability** as an additional feature
7. Train a **linear regression** model on the extracted features to predict uncertainty score


Supervised Methods (4)

Idea: extract features from the attention matrices

- LookBack Lens



- Trainable Attention-based Dependency (TAD)



[Lookback Lens: Detecting and Mitigating Contextual Hallucinations in Large Language Models Using Only Attention Maps](#) (Chuang et al., EMNLP 2024)

[Unconditional Truthfulness: Learning Conditional Dependency for Uncertainty Quantification of Large Language Models](#) (Vazhentsev et al., 2024)

Supervised Methods (5)

Overall comparison:

UQ Method	SamSum	CNN	WMT19	TruthfulQA	CoQA	SciQ	TriviaQA	MMLU	GSM8k	Mean	Mean
	AlignScore	AlignScore	Comet	AlignScore	AlignScore	AlignScore	AlignScore	Acc.	Acc.	PRR	Rank
MSP	.370	.061	.588	.187	.527	.614	.772	.771	.425	.479	7.00
Perplexity	.008	-.036	.480	.171	.517	.178	.779	.756	.225	.342	12.33
CCP	.266	.031	.432	.102	.448	.450	.769	.678	.482	.406	12.56
Simple Focus	.308	.066	.578	.178	.543	.583	.770	.755	.436	.469	7.56
Focus	.110	-.040	.494	.198	.446	.528	.721	.721	.419	.400	12.44
Lexical Similarity Rouge-L	.077	.071	.458	-.002	.453	.453	.751	.587	.544	.377	13.33
EigenScore	.134	.085	.368	-.144	.456	.452	.701	.473	.355	.320	15.44
EVL NLI Score entail.	.143	.089	.373	.035	.469	.464	.750	.606	.486	.380	12.22
Ecc. NLI Score entail.	.073	.047	.393	-.020	.487	.478	.742	.609	.512	.369	13.56
DegMat NLI Score entail.	.147	.090	.381	.034	.427	.466	.762	.465	.514	.365	12.67
Semantic Entropy	.181	.078	.521	-.039	.490	.473	.744	.673	.546	.407	10.78
SAR	.107	.087	.491	.069	.496	.472	.781	.690	.545	.415	9.33
LUQ	.104	.114	.261	.140	.411	.430	.755	.503	.451	.352	13.89
Factoscope	.090	.063	.088	-.093	-.056	.480	.289	.542	.084	.165	17.22
SAPLMA	.318	.019	.600	.375	-.005	.535	.601	.535	.604	.398	11.00
MIND	.292	.098	.608	.511	.345	.524	.528	.782	.702	.488	7.78
Sheeps	.304	.080	.638	.397	.358	.439	.551	.733	.756	.473	9.78
LookBackLens	.475	.194	.672	.481	.465	.666	.685	.750	.712	.567	4.89
SATRMD+MSP	.413	.113	.544	.412	.524	.670	.771	.749	.607	.534	4.56
TAD	.462	.219	.643	.575	.555	.641	.773	.812	.769	.605	1.67

Supervised Methods (6)

Training dataset is constructed by using 300 samples from the training datasets from each of the eleven other datasets, except the target dataset.

UQ Method	CNN	WMT19	MedQUAD	CoQA	SciQ	MMLU	GSM8k	Mean
	AlignScore	Comet	AlignScore	AlignScore	AlignScore	Acc.	Acc.	PRR
MSP	.157	.569	.356	.450	.582	.444	.380	.420
Factoscope	.023	.131	.166	.007	.129	-.022	-.082	.050
SAPLMA	.021	-.003	.137	.012	.151	-.034	.073	.051
MIND	.048	.258	.095	.171	.222	.415	.335	.220
Sheeps	-.021	.059	.044	.201	.364	.624	.348	.231
LookBackLens	-.032	.069	.061	.111	.331	.224	.261	.147
SATRMD+MSP	.135	.399	.242	.271	.001	.582	.333	.280
TAD	.003	.192	.336	.461	.601	.489	.391	.353

All supervised methods show a significant performance drop in out-of-domain settings

4

Applications of Uncertainty Estimation

Selective Generation

Sequence-level

This is LM-Polygraph demo: it augments LLM responses with confidence scores, helping you determine the reliability of the LLM's answer. Choose a model and an uncertainty estimation method first.

Consider dinosaurs came from space to Earth for help. How to cure them from pneumonia (write short answer)?

GPT-3.5-turbo
tokens-level: None
sequence-level: Lexical Similarity

To cure dinosaurs from pneumonia, the following steps can be taken:

1. Isolate affected dinosaurs to prevent the spread of the infection.
2. Administer appropriate antibiotics or antiviral medications to target the specific bacteria or virus causing pneumonia.
3. Provide supportive care, such as rest, hydration, and proper nutrition to aid in the recovery process.
4. Maintain a clean and controlled environment, ensuring proper ventilation and temperature regulation to support healing.
5. Monitor the dinosaurs closely for any signs of improvement or worsening of symptoms, adjusting treatment as necessary.
6. Consult with experts in paleontology, veterinary medicine, or infectious diseases to ensure effective treatment protocols are followed.
7. Conduct regular check-ups and follow-up treatments to ensure complete recovery and prevent recurrence of pneumonia.

Confidence: 86%

Consider there is a human looking for help. How to cure him from pneumonia (write short answer)?

GPT-3.5-turbo
tokens-level: None
sequence-level: Lexical Similarity

To cure a person suffering from pneumonia, it is important to seek medical attention promptly. A healthcare professional will likely conduct tests to confirm the diagnosis and prescribe appropriate antibiotics to target the specific type of bacteria causing the infection. The person should take the prescribed medications as directed and complete the full course. Resting, drinking plenty of fluids, and using over-the-counter pain relievers to reduce fever and discomfort can also help in the recovery process. Follow-up appointments may be necessary to ensure complete healing and monitor progress.

Confidence: 67%

Translate into French language: I want a small cup of coffee

GPT-3.5-turbo
tokens-level: None
sequence-level: Lexical Similarity

Je veux une petite tasse de café.

Confidence: 100%

Translate into Wizzaggian language: I want a small cup of coffee

GPT-3.5-turbo
tokens-level: None
sequence-level: Lexical Similarity

I swan izjarröp t'vittel karvat.

Confidence: 0%

Enter your OpenAI API key:

GPT-3.5-turbo Lexical Similarity

Fact-checking

Claim-level



Tell me a bio of Madonna.



Madonna is an American singer, songwriter, actress, and businesswoman. She was born on August 16, 1958, in Bay City, Michigan, and is best known for her provocative image and music. Madonna has sold over 300 million records worldwide, making her one of the best-selling music artists of all time. She has won numerous awards, including 20 Grammy Awards, a Golden Globe Award, and an Emmy Award. Madonna is also known for her philanthropic work and her activism on various social issues.

5

Conclusion

Takeaways

- Uncertainty estimation is a crucial component of LLM-based systems
- Sampling-based methods demonstrate strong performance for the long text generation tasks but underperform compared to the MSP baseline for the short text generation
- Supervised methods achieve state-of-the-art results for in-domain but experience a significant drop in performance when applied to out-of-domain
- Attention matrices provide valuable information into the truthfulness of generations
- Not all methods are applicable for claim-level UE
- Good starting point with implementations of many UE methods for LLMs
<https://github.com/INemo/lm-polygraph>



vazhentsev@airi.net
<https://t.me/artemvazh>

Artificial Intelligence Research Institute

airi.net



[airi_research_institute](https://t.me/airi_research_institute)



[AIRI Institute](https://vk.com/AIRI_Institute)



[AIRI Institute](https://www.youtube.com/AIRI_Institute)



[AIRI_inst](https://twitter.com/AIRI_inst)



[artificial-intelligence-research-institute](https://www.linkedin.com/company/artificial-intelligence-research-institute)