



# Spring Boot 3

Mar - Apr 2023

# What is RESTful API?

- RESTful API is an interface that two computer systems use to exchange information securely over the internet.
- RESTful APIs support this information exchange because they follow secure, reliable, and efficient software communication standards.

# What is an API?

- An application programming interface (API) defines the rules that you must follow to communicate with other software systems.
- Developers expose or create APIs so that other applications can communicate with their applications programmatically.



# Web API

- You can think of a web API as a **gateway** between **clients** and **resources** on the web.
- **Clients** are users who want to access information from the web. The client can be a person or a software system that uses the API.
- **Resources** are the information that different applications provide to their clients.
  - Resources can be images, videos, text, numbers, or any type of data. The machine that gives the resource to the client is also called the server.
  - Organizations use APIs to share resources and provide web services while maintaining security, control, and authentication.
  - In addition, APIs help them to determine which clients get access to specific internal resources.

# What is REST?

- Representational State Transfer (REST) is a software architecture that imposes conditions on how an API should work.
- REST was initially created as a guideline to manage communication on a complex network like the internet.
- You can use REST-based architecture to support high-performing and reliable communication at scale.
- APIs that follow the REST architectural style are called REST APIs.
- Web services that implement REST architecture are called RESTful web services.
- The term RESTful API generally refers to RESTful web APIs. However, you can use the terms REST API and RESTful API interchangeably.

# Principles of the REST

- Uniform interface
- Statelessness
- Layered system
- Cache ability



# Uniform interface

- The uniform interface is fundamental to the design of any RESTful webservice. It indicates that the server transfers information in a standard format.
- Uniform interface imposes four architectural constraints:
  1. Requests should identify resources. They do so by using a uniform resource identifier.
  2. Clients have enough information in the resource representation to modify or delete the resource if they want to. The server meets this condition by sending metadata that describes the resource further.
  3. Clients receive information about how to process the representation further. The server achieves this by sending self-descriptive messages that contain metadata about how the client can best use them.
  4. Clients receive information about all other related resources they need to complete a task. The server achieves this by sending hyperlinks in the representation so that clients can dynamically discover more resources.

# Statelessness

- In REST architecture, statelessness refers to a communication method in which the server completes every client request independently of all previous requests.
- Clients can request resources in any order, and every request is stateless or isolated from other requests.
- This REST API design constraint implies that the server can completely understand and fulfill the request every time.



# Layered system

- In a layered system architecture, the client can connect to other authorized intermediaries between the client and server, and it will still receive responses from the server.
- Servers can also pass on requests to other servers.
- You can design your RESTful web service to run on several servers with multiple layers such as security, application, and business logic, working together to fulfill client requests.
- These layers remain invisible to the client.

# Cache ability

- RESTful web services support caching, which is the process of storing some responses on the client or on an intermediary to improve server response time.
- For example, suppose that you visit a website that has common header and footer images on every page. Every time you visit a new website page, the server must resend the same images. To avoid this, the client caches or stores these images after the first response and then uses the images directly from the cache.
- RESTful web services control caching by using API responses that define themselves as cacheable or noncacheable.




# What are the benefits of RESTful APIs?

- Scalability
  - optimizes client-server interactions
  - Statelessness
- Flexibility
  - client-server separation
  - They simplify and decouple various server components so that each part can evolve independently.
  - Platform or technology changes at the server application do not affect the client application.
- Independence
  - Independent of the technology used.
  - Various programming languages without affecting the API design
  - Change the underlying technology, Without affecting the communication



# How do RESTful APIs work?



# What does the RESTful API client request contain?

- Unique resource identifier
- Method
  - GET / POST / PUT / DELETE
- HTTP headers
- Data
  - Request body
- Parameters
  - Path parameters
  - Query parameters
  - Cookie parameters

# What are RESTful API authentication methods?

- Basic authentication
- Bearer authentication
- API keys
- OAuth




# What does the RESTful API server response contain?


- Status line
  - 2XX codes indicate success
  - 4XX and 5XX codes indicate errors.
  - 3XX codes indicate URL redirection
- Message body
- Headers

# Interceptor

- authentication
- authorization
- logging
- customizing




# Web Filter






# SpringDoc-OpenApi V2.0.2



# Springdoc-openapi Demos



The image shows a Swagger UI interface for an OpenAPI definition. At the top, the Swagger logo is on the left, and a search bar contains the text `/openapi.json` with an **Explore** button on the right. Below the header, the title **OpenAPI definition** is displayed with version tags `v0` and `OA 3.0`. A link `/openapi.json` is shown below the title. The main section is titled **pet** with a dropdown arrow. It lists eight API endpoints, each with a colored button indicating the HTTP method and a description:

- GET** `/v3/pet/{petId}` Find pet by ID
- POST** `/v3/pet/{petId}` Updates a pet in the store with form data
- DELETE** `/v3/pet/{petId}` Deletes a pet
- GET** `/v3/pet/findByTags` Finds Pets by tags
- GET** `/v3/pet/findByStatus` Finds Pets by status
- PUT** `/v3/pet` Update an existing pet
- POST** `/v3/pet` Add a new pet to the store
- POST** `/v3/pet/{petId}/uploadImage` uploads an image