Zone Plate tilt simulation

Sajid Ali¹

¹Applied Physics Northwestern Univ

8 Aug 2018

Multislice

Multislice basics

Zone plates

Introduction
Tilt tolerance
Implementation details
Results

Multislice Multislice basics

Zone plates

Introduction


Tilt tolerance

Implementation details

Results

What is multislice

- Method to calculate x-ray wave propagation through arbitrary discrete objects ¹
- Involves breaking up the object into multiple "slices" and alternate propagation between the slice and refraction at the slice.



Number of slices.

- ▶ Li et al² showed that by increasing the number of slices, the mulsitlice method gives identical results to CWT with the advantage that it can work with arbitrary structures on a discretized grid.
- It was empirically shown that the step size to achieve this is

$$\Delta z = \frac{\epsilon_2}{\epsilon_1^2} \frac{\Delta x^2}{\lambda}$$

(Δx is the pixel size, λ is the wavelength and ϵ_1 , ϵ_2 are \approx 0.1.)

► Thus, we need more slices at lower energy.

Multislice

Multislice basics

Zone plates

Introduction

Tilt tolerance Implementation details Results

Need for multislice simulation

- Advances in nanofabrication processes have led to fabrication of zone plates with high aspect ratios³. As the thickness of zone plates increases and the outermost zone width decreases, aspect ratios as high as 500:1 have been achieved⁴.
- ► These high aspect ratios have made the zone plates very sensitive to tilt alignment errors while also making them behave like volume gratings⁵.
- This makes previous results that calculate tilt tolerance that assume zone plates to be thin optical elements invalid and require new calculations for the same.



³[CS14],[JVCP⁺07]

^{4[}LWD+17]

⁵[MS92],[Sch97]

Multislice

Multislice basics

Zone plates

Introduction

Tilt tolerance

Implementation details

Results

Previous results

- Myers⁶ and Young⁷ had calculated the tilt tolerance using optical path lenghts. Jacobsen et al⁸ took the depth of focus limits into account
- ▶ Jacobsen et al. ⁹ approached the problem by relating the tilt angle to a factor of depth of focus.



As stated earlier, these results don't take into account the thickness of the zone plates.


```
<sup>6</sup>[Mye51]

<sup>7</sup>[You72]

<sup>8</sup>[ NAA+0
```

⁸[JWA⁺91] ⁹[eaed]

Previous results



Multislice

Multislice basics

Zone plates

Introduction


Tilt tolerance

Implementation details

Results


Partial filling

- ▶ Pixel sizes are chosen to be no larger than 0.25 times the outermost zone width to ensure adequate sampling.
- Partial filling is done to avoid jagged edges.



Simulating tilt

- To simulate tilt, the phase of the incoming plane wave is modified instead of laboriously tilting the zone plate in three dimensions.
- ▶ A plane wave input that is perfectly aligned with the zone plate would correspond to a grid where all the values are set to 1



Results

Multislice

Multislice basics

Zone plates

Introduction


Tilt tolerance

Implementation details

Results


Dependance on number of zones

➤ Zone plate focal profiles along axis of tilt. Both zone plates are 8 microns thick but the one on the left has 200 zones and the one on the right has 500.



Dependance on thickness

Zone plate focal profiles along axis of tilt. Both have 200 zones while the one of the left is 0.5 microns thick and the one on the right is 10 microns thick.



Summary

- Zone plate tilt tolerance depends on thickness of zone plate.
- Need better models to quantify tilt tolerance of zone plates.
- Multislice allows us to predict this.
- Future
 - ► SRW integration ?

Acknowledgements

- Chris Jacobsen XSD, APS.
- Kenan Li SLAC National Accelerator Laboratory.
- Michael Wojcik XSD, APS.

- [CS14] Chieh Chang and Anne Sakdinawat. Ultra-high aspect ratio high-resolution nanofabrication for hard x-ray diffractive optics. *Nature Communications*, 5:4243 EP –, Jun 2014. Article.
- [eaed] C. Jacobsen et al. X-ray microscopy. to be published.
- [JVCP+07] K. Jefimovs, J. Vila-Comamala, T. Pilvi, J. Raabe, M. Ritala, and C. David. Zone-doubling technique to produce ultrahigh-resolution x-ray optics. *Phys. Rev. Lett.*, 99:264801, Dec 2007.
- [JWA⁺91] C. Jacobsen, S. Williams, E. Anderson, M.T. Browne, C.J. Buckley, D. Kern, J. Kirz, M. Rivers, and X. Zhang. Diffraction-limited imaging in a scanning transmission x-ray microscope. *Optics Communications*, 86(3):351 364, 1991.

References II

- [LJ15] Kenan Li and Chris Jacobsen. Rapid calculation of paraxial wave propagation for cylindrically symmetric optics. *Journal of the Optical Society of America A*, 32(11):2074, 2015.
- [LWD+17] Kenan Li, Michael J. Wojcik, Ralu Divan, Leonidas E. Ocola, Bing Shi, Daniel Rosenmann, and Chris Jacobsen. Fabrication of hard x-ray zone plates with high aspect ratio using metal-assisted chemical etching. Journal of Vacuum Science & Technology B, Nanotechnology and Microelectronics: Materials, Processing, Measurement, and Phenomena, 35(6):06G901, 2017.
 - [LWJ17] Kenan Li, Michael J Wojcik, and Chris Jacobsen. Multislice does it all: calculating the performance of nanofocusing x-ray optics. *Optics Express*, 25(3):185–194, 2017.

References III

- [MS92] Jörg Maser and Günter Schmahl. Coupled wave description of the diffraction by zone plates with high aspect ratios. *Optics Communications*, 89(2-4):355–362, 1992.
- [Mye51] Ora E. Myers. Studies of Transmission Zone Plates. American Journal of Physics, 19(6):359, 1951.
- [Sch97] G. Schneider. Zone plates with high efficiency in high orders of diffraction described by dynamical theory. Applied Physics Letters, 71(16):2242–2244, 1997.
- [You72] M Young. Zone Plates and Their Aberrations. *Journal of the Optical Society of America*, 62(8):972–976, 1972.