



# MARKOV2: ALGORITHMS



Kernel mathematically expresses algorithmic moves:

► Conversely, given a set of instructions for generating  $X' \in \mathbb{X}$  to  $X \in \mathbb{X}$ , there exists a kernel  $K$  such that (1) holds

- A kernel  $K$  provides instructions to move samples  $X \in \mathbb{X}$  to  $X' \in \mathbb{X}$

$$X' \sim K(X, dx') \quad (1)$$

Both representations are important!

► Kernels allow us to formally study the correctness and mathematical properties of a given algorithm



► Instructions (i.e. pseudo-code) provide implementation details and analyse algorithmic complexity.

► Define  $\mu \otimes K \in \mathcal{P}(X \times X)$  as the joint law  $X \sim \mu$  and  $X' \sim K(X, dx')$

$$\mu \otimes K(dx, dx') = \mu(dx)K(x, dx')$$

# MARKOV KERNELS V2: ALGORITHMS

6

- ▶ Kernels mathematically express algorithmic moves:

- ▶ A kernel  $K$  provides instructions to move samples  $X \in \mathbb{X}$  to  $X' \in \mathbb{X}$

$$X' \sim K(X, dx') \tag{1}$$

- ▶ Conversely, given a set of instructions for generating  $X' \in \mathbb{X}$  to  $X \in \mathbb{X}$ , there exists a kernel  $K$  such that (1) holds

- ▶ Both representations are important!

- ▶ Kernels allow us to formally study the correctness and mathematical properties of a given algorithm
  - ▶ Instructions (i.e. pseudo-code) provide implementation details and analyse algorithmic complexity.

- ▶ Define  $\mu \otimes K \in \mathcal{P}(\mathbb{X} \times \mathbb{X})$  as the joint law  $X \sim \mu$  and  $X' \sim K(X, dx')$

$$\mu \otimes K(dx, dx') = \mu(dx)K(x, dx')$$

# EXAMPLES: