


# **Object Detection**

## **Lecture 10.3 - Introduction to deep learning (CNN)**

Idar Dyrdal

# Deep Learning


- Computational models composed of multiple processing layers (non-linear transformations)
- Used to learn representations of data with multiple levels of abstraction:
  - Learning a hierarchy of feature extractors
  - Each level in the hierarchy extracts features from the output of the previous layer (pixels  $\rightarrow$  classes)
- Deep learning has dramatically improved state-of-the-art in:
  - Speech and character recognition
  - Visual object detection and recognition
- Convolutional neural nets for processing of images, video, speech and signals (time series) in general
- Recurrent neural nets for processing of sequential data (speech, text).



# Deep Learning for Object Recognition




Millions of images




Millions of parameters

Thousands of classes


# Traditional supervised learning




# Deep learning



# Semi-supervised learning



Labeled samples and (trained) linear decision boundary



Labeled and unlabeled samples and non-linear decision boundary

# Artificial Neural Network (ANN)

## Used in Machine Learning and Pattern Recognition:


- Regression
- Classification
- Clustering
- ...

## Applications:

- Speech recognition
- Recognition of handwritten text
- Image classification
- ...



## Network types:

- Feed-forward neural networks
- Recurrent neural networks (RNN)
- ...



Feed-forward ANN (non-linear classifier)

# Mark 1 Perceptron (Rosenblatt, 1957-59)



(Cornell Aeronautical Laboratory)



# Activation functions

- Sigmoid (logistic function):

$$f(x) = \frac{1}{1 + e^{-x}}$$


- Hyperbolic tangent:

$$f(x) = \tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}}$$

- Rectified linear unit (ReLU):


$$f(x) = \max(x, 0)$$

Biological neuron:



(Quasar Jarosz, English Wikipedia)

# Feed-forward neural network



$$y_l = f(z_l)$$

$$z_l = \sum_{k \in H_2} w_{kl} x_k$$


$$y_k = f(z_k)$$

$$z_k = \sum_{j \in H_1} w_{jk} x_j$$

$$y_j = f(z_j)$$

$$z_j = \sum_{i \in \text{Input}} w_{ij} x_i$$

# Back-propagation




# Convolutional Neural Network (CNN)

## Used in Machine Vision and Image Analysis:

- Speech Recognition
- Image Recognition
- Video Recognition
- Image Segmentation
- ...



## Convolutional neural network:

- Multi-layer feed-forward ANN
- Combinations of *convolutional* and fully connected layers
- Convolutional layers with *local* connectivity
- *Shared* weights across spatial positions
- Local or global pooling layers



(A. Karpathy)

# Typical CNN



Learned features


(Aphex34)

# Convolutional neural net




Input image


(credit: S. Lazebnik)



# Convolutional neural net




(credit: S. Lazebnik)






# Convolutional neural net

## Rectified Linear Unit (ReLU)




(credit: S. Lazebnik)






# Convolutional neural net




Max-pooling: a non-linear down-sampling

Provide *translation invariance*


(credit: S. Lazebnik)



# Convolutional neural net




Feature Maps




Feature Maps  
After Contrast  
Normalization

(credit: S. Lazebnik)




# Convolutional neural net



Feature maps after contrast normalization

(credit: S. Lazebnik)




# Example - Caffe Demos

The [Caffe](#) neural network library makes implementing state-of-the-art computer vision systems easy.

## Classification

[Click for a Quick Example](#)



Maximally accurate

Maximally specific

Egyptian cat

0.32645

tabby

0.16689

tiger cat

0.10922

Persian cat

0.06203

Siamese cat

0.05992

CNN took 0.112 seconds.

<http://demo.caffe.berkeleyvision.org>

# Caffe Demos

The [Caffe](#) neural network library makes implementing state-of-the-art computer vision systems easy.

## Classification

[Click for a Quick Example](#)



Maximally accurate

Maximally specific

macaw

0.99985

lorikeet

0.00008

crane

0.00002

vulture

0.00002

flamingo

0.00002

CNN took 0.067 seconds.

# Caffe Demos

The [Caffe](#) neural network library makes implementing state-of-the-art computer vision systems easy.

## Classification

[Click for a Quick Example](#)



Maximally accurate

Maximally specific

suspension bridge

0.20551

lakeside

0.16864

pier

0.12692

alp

0.05951

radio telescope

0.04751

CNN took 0.254 seconds.

# Example - Semantic Segmentation (SegNet)




<http://mi.eng.cam.ac.uk/projects/segnet/>

# Summary

## Topics covered:

- Deep learning
- Artificial neural networks
- Convolutional neural networks



## More information:

- Szeliski, chapter 14
- Yann LeCun ,Yoshua Bengio & Geoffrey Hinton, “Deep learning”, Nature, Vol 521, 28. May 2015.
- Shaohuai Shi, Qiang Wang, Pengfei Xu, Xiaowen Chu, “Benchmarking State-of-the-Art Deep Learning Software Tools”, 2017 (<https://arxiv.org/pdf/1608.07249.pdf>)

## Software:

- Caffe (<http://caffe.berkeleyvision.org>)
- TensorFlow (<https://www.tensorflow.org/>)
- MatConvNet (<http://www.vlfeat.org/matconvnet>)