

Babynames II: patterns of popularity

2024-09-02

```
stopifnot(  
  require(patchwork),  
  require(httr),  
  require(glue),  
  require(ineq),  
  require(here),  
  require/slider),  
  require(tidyverse),  
  require(gtools)  
)  
  
# old_theme <- theme_set(theme_minimal())
```

- **L3 MIASHS**
- [Université Paris Cité](#)
- Année 2024-2025
- [Course Homepage](#)

- [Moodle](#)



! Objectives

Setup

```
path_data <- 'DATA'  
fname <- 'nat2021_csv.zip'  
fpath <- here(path_data, fname)  
  
if (!file.exists(fpath)){  
  url <- "https://www.insee.fr/fr/statistiques/fichier/2540004/nat2021_csv.zip"  
  download.file(url, fpath, mode="wb")  
}  
  
df_fr <- readr::read_csv2(fpath)
```

```

if (!require("babynames")){
  install.packages("babynames")
  stopifnot(require("babynames"), "Couldn't install and load package 'babynames'")
}

```

```

lkp <- list(year="annais",
  sex="sexe",
  name="preusuel",
  n="nombre")

```

```

births_fr_path <- here(path_data, 't35.fr.xls')
births_fr_url <- 'https://www.ined.fr/fichier/s_rubrique/168/t35.fr.xls'

```

```

if (!file.exists(births_fr_path)) {
  download.file(births_fr_url, births_fr_path)
}

```

```

births_fr <- readxl::read_excel(births_fr_path, skip = 3)

```

```

births_fr <- births_fr[-1, ]
names(births_fr)[1] <- "year"

```

```

births_fr <- births_fr |>
  mutate(year=as.integer(year)) |>
  drop_na()

```

```

babynames <- babynames |>
  mutate(country='us') |>
  mutate(sex=as_factor(sex))

```

```

births_us <- births

```

```

df <- bind_rows(babynames, df_fr)

```

```

df <- df |>
  filter(year > 1947) |>
  drop_na() |>
  filter(name!='_PRENOMS_RARES')

```

```

df <- df |>
  group_by(year, sex, country) |>
  arrange(desc(n), .by_group=T) |>
  mutate(rnk=row_number(),
    rrnk=rnk/n(),
    cprop=cumsum(prop)) |>
  ungroup()


```

```
min_maj <- function(cprop, rrnk){  
  1- rrnk[findInterval(.5, cprop)]  
}
```

```
last_dec <- function(cprop, rrnk) {  
  cprop[findInterval(.1, rrnk)]  
}
```


```
ineq_idx_fns <- list(  
  gini=Gini,  
  atkinson=Atkinson,  
  ent=entropy,  
  theil=Theil)  
  
ineq_idxes <- df |>  
  summarize(  
    across(n, .fns=ineq_idx_fns),  
    n_alker=min_maj(cprop, rrnk),  
    n_last_dec=last_dec(cprop, rrnk),  
    .by= c(year, sex, country),  
  ) |>  
  pivot_longer(  
    cols=starts_with("n"),  
    names_to="index_name",  
    values_to="index")
```

```
ineq_idxes |>  
  ggplot() +  
  aes(x=year, y=index, color=sex) +  
  geom_line() +  
  facet_grid(rows=vars(index_name), cols=vars(country), scales="free_y")
```




```
df <- df |>
  group_by(country, sex, name) |>
  mutate(best_rnk=min(rnk)) |>
  ungroup()

(
  df |>
  filter(rrnk<.9, round(10000*rrnk)%10==1) |>
  ggplot() +
    aes(x=1-rrnk, y=1-cprop, color=sex, frame=year) +
    geom_point(size=.2) +
    coord_fixed() +
    facet_wrap(~ country)
) |>
  plotly::ggplotly()
```



```
(
df |>
  filter(rnk <=10, year %% 30 ==0) |>
  ggplot() +
  aes(x=rnk, y=prop, frame=year, fill=sex) +
  geom_col(position="dodge") +
#   coord_flip() +
  facet_grid(cols=vars(country),
             rows=vars(year),
             scales="free"))
```



```
# |> plotly::ggplotly()
```

```
df_fr <- df_fr |>
  rename(!!!lkp) |>
  mutate(country='fr') |>
  mutate(sex=as_factor(sex)) |>
  mutate(sex=fct_recode(sex, "M"="1", "F"="2")) |>
  mutate(sex=fct_relevel(sex, "F", "M")) |>
  mutate(year=ifelse(year=="XXXX", NA, year)) |>
  mutate(year=as.integer(year)) |>
  group_by(year,sex) |>
  mutate(prop=n/sum(n)) |>
  ungroup() |>
  select(year, sex, name, n, prop, country)
```

①

U+0128

```
extract_pattern <- \(x)
  str_c((as.character(lkp[as.character(x[x!=0 & !is.na(x)])]))), collapse="")
```

```
df <- df |>
  group_by(country,sex, name) |>
  arrange(year) |>
  mutate(sprop=slide_dbl(pmax(prop, 1e-4), mean, .before=2, .after =2)) |>
  ungroup()
```

```
df_patterns <- df |>
  group_by(country,sex, name) |>
  arrange(year) |>
  mutate(change=log(sprop)) |>
```

```
mutate(change=sign(change-lag(change, default = change[1]))) |>
summarise(change_pattern=extract_pattern(change), .groups = "drop") |>
arrange(country,sex, change_pattern)
```

```
df_patterns |>
  filter(name %in% c('JULES', 'KEVIN', 'STÉPHANE', 'ARTHUR', 'MICHEL', 'EMILE'), sex=='M')
```

A tibble: 6 x 4

	country	sex	name	change_pattern
	<chr>	<fct>	<chr>	<chr>
1	fr	M	KEVIN	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~
2	fr	M	ARTHUR	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~
3	fr	M	JULES	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~
4	fr	M	EMILE	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~
5	fr	M	MICHEL	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~
6	fr	M	STÉPHANE	NULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNULLNU~

```
df |>
  filter(name %in% c('STÉPHANE', 'KEVIN', 'ENZO'), sex=='M') |>
  ggplot() +
  aes(x=year) +
  geom_point(aes(y=prop, shape=name), color="blue", alpha=.5, size=.2) +
  geom_line(aes(y=sprop, linetype=name), color="red", linewidth=.2) +
  scale_y_log10()
```

