

МИНИСТЕРСТВО ОБРАЗОВАНИЯ И НАУКИ РОССИЙСКОЙ
ФЕДЕРАЦИИ МОСКОВСКИЙ АВИАЦИОННЫЙ ИНСТИТУТ
(НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ)

ЛАБОРАТОРНАЯ РАБОТА №4
по курсу объектно-ориентированное программирование I семестр, 2021/22
уч. год

Студент Шатунова Юлия Викторовна, группа М8О-208Б-20

Преподаватель Дорохов Евгений Павлович

Условие

Задание: Вариант 26: Квадрат, очередь. Необходимо спроектировать и запрограммировать на языке C++ класс-контейнер первого уровня, содержащий одну фигуру, согласно вариантам задания. Классы должны удовлетворять следующим правилам:

1. Требования к классу фигуры аналогичны требованиям из лабораторной работы 1.
2. Классы фигур должны содержать набор следующих методов:
 - Перегруженный оператор ввода координат вершин фигуры из потока `std::istream` («»). Он должен заменить конструктор, принимающий координаты вершин из стандартного потока.
 - Перегруженный оператор вывода в поток `std::ostream` («»), заменяющий метод `Print` из лабораторной работы 1.
 - Оператор копирования (`=`)
 - Оператор сравнения с такими же фигурами (`==`)
3. Класс-контейнер должен содержать объекты фигур “по значению” (не по ссылке).
4. Класс-контейнер должен содержать набор следующих методов:
 - `push` - вставка в очередь
 - `pop` - удаление из очереди
 - `top` - первый элемент в очереди
 - `empty` - пустая ли очередь
 - `size` - количество элементов в очереди
 - Перегруженный оператор вывода в поток `std::ostream` («»)

Описание программы

Исходный код лежит в 10 файлах:

1. `main.cpp`: основная программа
2. `figure.h`: описание класса фигуры
3. `tqueue_item.h`: описание класса предмета очереди
4. `point.h`: описание класса точки
5. `tqueue.h`: описание класса очереди

6. square.h: описание класса прямоугольника, наследующегося от figures
7. point.cpp: реализация класса точки
8. tqueue.cpp: реализация класса очереди
9. square.cpp: реализация класса прямоугольника
10. tqueue_item.cpp: реализация класса предмета очереди

Выводы

Я научилась создавать простые динамические структуры данных, а также работать с объектами, передаваемыми "по значению".

Исходный код

figure.h

```
#ifndef FIGURE_H
#define FIGURE_H

#include "point.h"

class Figure {
public:
    virtual double Area() = 0;
    virtual ~Figure() {};
};

#endif // FIGURE_H
```

tqueue.h

```
#ifndef TQUEUE_H
#define TQUEUE_H

#include "tqueue_item.h"

class TQueue {
public:
    TQueue();
    TQueue(const TQueue& other);

    void Push(Square&& square);
    Square Pop();

    const Square& Top();

    bool Empty();

    size_t Length();

    friend std::ostream& operator<<(std::ostream& os, const TQueue& queue);

    void Clear();

    virtual ~TQueue();

private:
    TQueueItem* head;
    TQueueItem* tail;
    size_t num_of_elem;
};

#endif // TQUEUE_H
```

tqueue.cpp

```
#include "tqueue.h"

TQueue::TQueue() : head(nullptr), tail(nullptr), num_of_elem(0) {

}

TQueue::TQueue(const TQueue& other) {
    head = other.head;
}

std::ostream& operator<<(std::ostream& os, const TQueue& queue) {
    TQueueItem* item = queue.head;

    while (item != nullptr) {
        os << *item << " => ";
        item = item->GetNext();
    }
    return os;
}

void TQueue::Push(Square&& square) {
    auto* item = new TQueueItem(square);
    if (item != nullptr) {
        if (this->Empty()) {
            this->head = this->tail = item;
        }
        else if (num_of_elem == 1) {
            tail = item;
            head->SetNext(item);
        }
        else {
            this->tail->SetNext(item);
            tail = item;
        }
        num_of_elem++;
    }
}

Square TQueue::Pop() {
    Square result;
    if (head != nullptr) {
```

```

        TQueueItem* item = head;
        head = head->GetNext();
        result = item->GetSquare();
        item->SetNext(nullptr);
        delete item;
    }
    return result;
}

const Square& TQueue::Top() {
    if (head) {
        return head->GetSquare();
    }
}

bool TQueue::Empty() {
    return head == nullptr;
}

size_t TQueue::Length() {
    return num_of_elem;
}

void TQueue::Clear() {
    delete head;
    head = tail = nullptr;
    num_of_elem = 0;
}

TQueue::~~TQueue() {
    delete head;
}

```

tqueue_item.h

```
#ifndef TQUEUE_ITEM_H
#define TQUEUE_ITEM_H

#include "square.h"

class TQueueItem {
public:
    TQueueItem(const Square& square);
    TQueueItem(const TQueueItem& other);

    TQueueItem* SetNext(TQueueItem* next);
    TQueueItem* GetNext();

    Square GetSquare() const;

    friend std::ostream& operator<<(std::ostream& os, const TQueueItem& obj);

    virtual ~TQueueItem();

private:
    Square square;
    TQueueItem* next;
};

#endif // TQUEUE_ITEM_H
```


tqueue_item.cpp

```
#include "tqueue_item.h"
```

```
TQueueItem::TQueueItem(const Square& square) {  
    this->square = square;  
    this->next = nullptr;  
    std::cout << "Queue item is created" << std::endl;  
}
```

```
TQueueItem::TQueueItem(const TQueueItem& other) {  
    this->square = other.square;  
    this->next = other.next;  
    std::cout << "Queue item is copied" << std::endl;  
}
```

```
TQueueItem* TQueueItem::SetNext(TQueueItem* next) {  
    TQueueItem* prev = this->next;  
    this->next = next;  
    return prev;  
}
```

```
TQueueItem* TQueueItem::GetNext() {  
    return this->next;  
}
```

```
Square TQueueItem::GetSquare() const {  
    return this->square;  
}
```

```
std::ostream& operator<<(std::ostream& os, const TQueueItem& obj) {  
    os << "Item: " << obj.square << std::endl;  
    return os;  
}
```

```
TQueueItem::~TQueueItem() {  
    delete next;  
    std::cout << "The queue item is deleted" << std::endl;  
}
```

point.h

```
#ifndef POINT_H
#define POINT_H

#include <iostream>
#include <ostream>
#include <vector>
#include <cmath>

class Point {
public:
    Point();
    Point(std::istream& is);
    Point(double x, double y);

    double dist(Point& other);

    friend std::istream& operator>>(std::istream& is, Point& p);
    friend std::ostream& operator<<(std::ostream& os, Point& p);
    friend Point operator+(Point a, Point b);

    friend class Square;
    friend class Rectangle;
    friend class Trapezoid;

private:
    double x_;
    double y_;
};

#endif // POINT_H
```

point.cpp

```
#include "point.h"

Point::Point() : x_(0.0), y_(0.0) {}

Point::Point(double x, double y) : x_(x), y_(y) {}

Point::Point(std::istream& is) {
    is >> x_ >> y_;
}

double Point::dist(Point& other) {
    double dx = (other.x_ - x_);
    double dy = (other.y_ - y_);
    return std::sqrt(dx * dx + dy * dy);
}

std::istream& operator>>(std::istream& is, Point& p) {
    is >> p.x_ >> p.y_;
    return is;
}

std::ostream& operator<<(std::ostream& os, Point& p) {
    os << "(" << p.x_ << ", " << p.y_ << ")";
    return os;
}

Point operator+(Point x, Point y) {
    return Point(x.x_ + y.x_, x.y_ + y.y_);
}
```

square.h

```
#ifndef SQUARE_H
#define SQUARE_H

#include "figure.h"

class Square : public Figure {
public:
    Square();
    Square(Point a, Point b, Point c, Point d);
    Square(const Square& other);

    double Area();

    friend std::istream& operator>>(std::istream& is, Square& obj);
    friend std::ostream& operator<<(std::ostream& os, const Square& obj);

    Square& operator++();
    friend Square operator+(const Square& left, const Square& right);

    Square& operator=(const Square& other);

    virtual ~Square();

private:
    Point point_a; // lower left corner, then clockwise
    Point point_b;
    Point point_c;
    Point point_d;
};

#endif // SQUARE_H
```

square.cpp

```
#include "square.h"
```

```
Square::Square() : point_a(0.0, 0.0), point_b(0.0, 0.0), point_c(0.0, 0.0), point_d(0.0, 0.0)
    std::cout << "Default square is created" << std::endl;
}
```

```
Square::Square(Point a, Point b, Point c, Point d) : point_a(a), point_b(b), point_c(c), point_d(d)
    std::cout << "Square is created with vertices: ";
    std::cout << point_a << ", ";
    std::cout << point_b << ", ";
    std::cout << point_c << ", ";
    std::cout << point_d << std::endl;
}
```

```
Square::Square(const Square& other) : Square(other.point_a, other.point_b, other.point_c, other.point_d)
    std::cout << "Square's copy is created" << std::endl;
}
```

```
double Square::Area() {
    double side = 0.0;
    double fig_square = 0.0;
    side = point_b.dist(point_a);
    fig_square = side * side;
    return fig_square;
}
```

```
std::istream& operator>>(std::istream& is, Square& obj) {
    is >> obj.point_a >> obj.point_b >> obj.point_c >> obj.point_d;
    return is;
}
```

```
std::ostream& operator<<(std::ostream& os, const Square& obj) {
    Point a(obj.point_a);
    Point b(obj.point_b);
    Point c(obj.point_c);
    Point d(obj.point_d);
    os << "Point_a: " << a << ", ";
    os << "Point_b: " << b << ", ";
    os << "Point_c: " << c << ", ";
    os << "Point_d: " << d << std::endl;
    return os;
}
```

```

}

Square& Square::operator++() {
    point_a.x_ += 1.0;
    point_a.y_ += 1.0;
    point_b.x_ += 1.0;
    point_b.y_ += 1.0;
    point_c.x_ += 1.0;
    point_c.y_ += 1.0;
    point_d.x_ += 1.0;
    point_d.y_ += 1.0;

    return *this;
}

Square operator+(const Square& left, const Square& right) {
    return Square(left.point_a + right.point_a, left.point_b + right.point_b, left.p
}

Square& Square::operator=(const Square& other) {
    if (this == &other) {
        return *this;
    }
    else {
        point_a = other.point_a;
        point_b = other.point_b;
        point_c = other.point_c;
        point_d = other.point_d;
        std::cout << "Square is copied" << std::endl;
        return *this;
    }
}

Square::~~Square() {
    std::cout << "Square is deleted" << std::endl;
}

```

main.cpp

```
#include "tqueue.h"

int main(int argc, char** argv) {
    TQueue queue;
    Point a_1(1.0, 1.0);
    Point b_1(1.0, 2.0);
    Point c_1(2.0, 2.0);
    Point d_1(2.0, 1.0);
    Point a_2(3.0, 1.0);
    Point b_2(3.0, 3.0);
    Point c_2(5.0, 3.0);
    Point d_2(5.0, 1.0);
    Point a_3(0.0, 0.0);
    Point b_3(0.0, 4.0);
    Point c_3(4.0, 4.0);
    Point d_3(4.0, 0.0);
    queue.Push(Square(a_1, b_1, c_1, d_1));
    queue.Push(Square(a_2, b_2, c_2, c_2));
    queue.Push(Square(a_3, b_3, c_3, d_3));
    std::cout << queue;

    Square square;
    square = queue.Pop();
    std::cout << square;
    square = queue.Pop();
    std::cout << square;
    square = queue.Pop();
    std::cout << square;

    return 0;
}
```