



Smart usage of context information for the analysis, design and generation of power-aware polices for mobile sensing apps

Presented by: Rafael Perez Torres

Thesis advisors:
PhD Cesar Torres Huitzil
PhD Hiram Galeana Zapien

Cinvestav Tamaulipas

Table of contents

Problem statement

Methodology

State of art related techniques

Proposed solution

Important results

Future work

Conclusions

Introduction

- The popularity of mobile devices is a result of advances in their computation, sensing, and communication dimensions [8].
- Smartphone's sensing facilities improve interaction with user, turning them into *omni-sensors* able to *know* about its surrounding environment.
- Mobile devices have become *context-aware*, gaining understanding about user's activity and environment.
- *Context* refers to a four-dimensional space composed of *computing context*, *physical context*, *time context*, and *user context* [3].
- However, battery is not evolving at the same pace than the advances in other smartphone's characteristics [11], growing only 5% each year [15].
- The energy constraint becomes more critical when continuous access to sensors is needed, which is the core requirement of **mobile sensing applications**.

Problem antecedents




Figure: Stages of mobile sensing applications

There is a tradeoff between the accuracy of context information retrieved and the associated energy consumption [25, 24]. How to face it?

Hypothesis

Hypothesis

Intelligent policies produced through context information built from sensors data can be employed to reduce the energy consumption in a mobile device when performing continuous sensor readings.

- An intelligent policy is a special rule that defines how sensors should be accessed in order to reduce the energy consumption and achieve the requirements of a mobile app. It is intelligent in terms of self-adaptness to changes detected in context information.
- This research work is aimed at employing GPS and inertial sensors data (accelerometer) for inferring context information in terms of mobility patterns. This context information will then be exploited to adapt sensors' operation and produce power savings.

Problem statement

Problem statement: Mobility pattern identification

Given a set $V = \{v_1, v_2, \dots, v_n\}$ of data values read from sensor S in the time interval $T \in [t_1, t_2]$, identify the current mobility pattern p_S that represents the activity of user.

$$\text{PatternIdentifier}(V) \longrightarrow p_S \in \text{Patterns} \quad (1)$$

Where *Patterns* is a set of patterns that represent an interesting state in user mobility, specifically the set $\{\text{no_movement}, \text{walking}, \text{running}, \text{vehicle_transportation}\}$.

Problem statement

Problem statement: Policy generation

Given the set of detected mobility patterns $\mathcal{P} = \{p_{S_1}, p_{S_2}, \dots, p_{S_n}\}$ in data from sensors $\mathcal{S} = \{S_1, S_2, \dots, S_n\}$, parameters for assigning weight to energy e and accuracy a , and physical constraints status c of a mobile device, find a policy that select the proper set of sensors S_{new} and its associated configuration $S_{new_{conf}}$ while meeting application requirements.

$$\text{PolicyGeneration}(\mathcal{P}_S, e, a, c) \longrightarrow S_{new}, S_{new_{conf}} \quad (2)$$

The $S_{new_{conf}}$ configuration is referred as the *duty cycle* of associated sensor.

Interaction between problems




Figure: Interaction between the thesis work's problems

Problem's scenario




Figure: Basic problem's scenario

Methodology

1. Familiarization with state-of-art power-aware sensing related techniques
2. Formal definition and selection of mobility patterns to be identified
3. Research on pattern recognition algorithms focused on mobility patterns identification
4. Design of the Pattern Identification Element (PIE)
5. Research on and proposition of adaptive policies for energy efficient usage of sensors
6. Design of the Policy Generation Element (PGE)
7. Development of a middleware involving the PIE and PGE for the Android platform
8. Experimentation in terms of accuracy and energy efficiency

Taxonomy of state of art solutions




Figure: Taxonomy of solutions, seen from the sensors adaptation's perspective

Distribution of approaches




Figure: Distribution of approaches across mobile platform's layers

Solutions characteristics

Distinctive characteristics of works

- Optimization oriented (OO)
- Online learning (OL)
- User state oriented (US)

En general, podemos describirlos de forma más o menos organizada a través de...

Granularity of context information (input data type + classifier + time window length)

- Basic context information powered policies.
- Medium context information powered policies.
- High level context information policies NO ES CIERTO! NO EXISTE ESTO! ES SIMPLEMENTE UNA EVALUACIÓN INCREMENTAL. EN TODO CASO HAY QUE PONER AQUI LO QUE ESTA ENTRE PARENTESIS (CLASS+TIMEWINDOWS...)

Decomposition of related solutions

De forma general, el framework para evaluar queda como:




Figure: Decomposition of solutions

State-of-art solutions

Name	Variants	Machine learning technique	Sensors involved	Complexity	OL	OO	US
<i>G-Sense</i> [22]	User behavior learning (DC)	SDR	GPS	low			
Not given [23]	User behavior learning (DC)	SDR	GPS	low			
<i>SenseLess</i> [1]	User behavior learning (DC), Sensor replacement (CR, DR)	SDR	WPS, GPS, ACC	low			
<i>SensTrack</i> [29]	User behavior learning (DC), Sensor replacement (CR, DR)	SDR	ACC, orientation sensor, GPS, WPS	low			
Not given [17]	User behavior learning (DC, VI), Sensor replacement (CR)	SDR	ACC, magnetic field sensor, GPS	low			
<i>EnLoc</i> [6]	User behavior learning (DC, VI), Sensor replacement (DR)	SDR, Mobility Tree	WPS, GPS, cellular ID	medium		✓	
<i>EnTracked</i> [12]	User behavior learning (DC), Sensor replacement (CR)	SDR	ACC, GPS	medium		✓	

Table: Pure software solutions. (OL: Online Learning from user data, OO: Optimization Oriented solution, US: User State context insight)

State-of-art solutions

Name	Variants	Machine learning technique	Sensors involved	Complexity	OL	OO	US
Not given [2, 19]	—	Ameva algorithm	ACC	medium			
Not given [18]	Sensor replacement (CR)	DT	Temperature, humidity, pressure	medium			
Not given [26]	User behavior learning (DC)	DT	ACC	medium			
Not given [9]	Sensor replacement (CR)	KNN	Model of ACC-based harvesting device	medium			

Table: Pure software solutions. (OL: Online Learning from user data, OO: Optimization Oriented solution, US: User State context insight)

State-of-art solutions

Name	Variants	Machine learning technique	Sensors involved	Complexity	OL	OO	US
<i>SensLoc</i> [10]	User behavior learning (DC, RD), Sensor replacement (CR)	SDR	Wi-Fi fingerprinting, GPS, ACC	medium	✓		
<i>CAPS</i> [21]	User behavior learning (DC, RD), Sensor replacement (CR)	SDR	GPS, cellular ID	medium	✓		
<i>RAPS</i> [20]	User behavior learning (DC, RD), Sensor replacement (CR, DR)	SDR	WPS, GPS, ACC, Bluetooth, cellular ID	medium	✓		
<i>A-Loc</i> [13]	User behavior learning (DC, RD), Sensor replacement (CR, DR)	HMM, Bayesian estimation framework	GPS, WPS, Bluetooth, cellular ID	medium	✓	✓	
<i>SmartDC</i> [5]	User behavior learning (DC, RD), Sensor replacement (CR, DR)	HMM and LZ predictor	GPS, WPS, Wi-Fi and cellular ID fingerprinting	medium	✓	✓	

Table: Pure software solutions. (OL: Online Learning from user data, OO: Optimization Oriented solution, US: User State context insight)

State-of-art solutions

Name	Variants	Machine learning technique	Sensors involved	Complexity	OL	OO	US
<i>Jigsaw</i> [14]	User behavior learning (DC), Sensor replacement (CR)	Microphone: NB with Gaussian Mixture Model (GMM). ACC: DT. GPS: MDP.	ACC, Microphone, GPS	high		✓	✓
Not given [7]	User behavior learning (DC)	Several. KNN and NN selected as best.	ACC, GPS, WPS, cellular ID, light, device data, mobile app requirements	high			✓
<i>EEMSS</i> [27]	User behavior learning (DC), Sensor replacement (CR, DR)	GPS and ACC: SDR. Microphone: SSCH algorithm.	ACC, microphone, GPS	high			✓
<i>iLoc</i> [16]	User behavior learning (RD), Sensor replacement (CR)	HMM	Wi-Fi & GSM fingerprinting	high	✓		✓
Not given [28]	User behavior learning (DC, RD)	HMM	ACC	high	✓		✓
<i>FreeTrack</i> [4]	User behavior learning (DC, RD), Sensor replacement (CR, DR)	HMM	GPS, Wi-Fi, cellular ID, battery status	high	✓		✓

Table: Pure software solutions. (OL: Online Learning from user data, OO: Optimization Oriented solution, US: User State context insight)

Proposed solution

How are we going to be different?. At the end we can describe that:

- In the ML block, we are going to produce an enhanced-expanded spatial-time model by:
 - Classifying accelerometer data in user activity.
 - Obtaining context information from other sources:
 - ▶ Fingerprinting, battery status.
 - Obtaining speed from GPS
 - Obtaining location from GPS and WPS
- In the policy block, we will try to adapt the sensing dimension splitting the problem into:
 - Learning and detection of stay points (Already covered)
 - Learning and detection (tracking) of trajectories.
- In the HW adaptation bloc, we will use several variants of the PS approach. For instance, we will do:
 - Sensor replacement, Context related (battery) and Direct related (WPS).
 - Adapt accordingly to what is learned from user through Duty Cycling (DC) and Recycling existing Data (RD). Maybe we will use Next Value Inference (VI) in the policy, when we adapt under uncertainty. For instance, we are 80% sure that user is running, we will proceed with caution adapting duty cycle with fine granularity, this is negotiable.
- At the end, we are trying to maintain sensors within a range that allows to perform the tracking but considering the trade-off.

Proposed solution




Figure: Overview of current solution

Results

Here, we can mentioned that we have partially prooved the possibility of performing user location tracking and stay points detection using only the smartphone. This empowers us to keep building the blocks that will complement our solution.

Scientific products

I think we can mention the survey. We need to find out whether we can describe the article related to the on-device detection of stay points, highlighting its 'event-oriented' perspective, which represents the most natural way on which smartphone-based systems for LBS should work, being proactive.

Future work

Adequate the calendar-schedule explaining the apparent delay produced by the survey, but remarking its added value as a metric and as a scientific booster for improving the work.

Conclusions

In this talk:

- An introduction to the energy consumption issue in mobile sensing apps and its relevance has been presented.
- A description of the important components of our thesis work has been also given.
- An overview of the proposed methodology for solving the energy consumption issue has been provided.

Thank You
for your attention!

- [1] Fehmi Ben Abdesslem, Andrew Phillips, and Tristan Henderson. Less is more: energy-efficient mobile sensing with senseless. In *Proceedings of the 1st ACM workshop on Networking, systems, and applications for mobile handhelds.*, pages 61–62, 2009.
- [2] M. a. Álvarez De La Concepción, L. M. Soria Morillo, L. Gonzalez-Abril, and J. a. Ortega Ramírez. Discrete techniques applied to low-energy mobile human activity recognition. A new approach. *Expert Systems with Applications*, 41:6138–6146, 2014.
- [3] Guanling Chen and David Kotz. A Survey of Context-Aware Mobile Computing Research. Technical report, 2000.
- [4] Yohan Chon, Yungeun Kim, Hyojeong Shin, and Hojung Cha. Adaptive duty cycling for place-centric mobility monitoring using zero-cost information in smartphone. *IEEE Transactions on Mobile Computing*, 13(8):1694–1706, 2014.
- [5] Yohan Chon, Elmurod Talipov, Hyojeong Shin, and Hojung Cha. Mobility prediction-based smartphone energy optimization for everyday location monitoring. In *Proceedings of the 9th ACM Conference on Embedded Networked Sensor Systems - SenSys '11*, page 82, 2011.
- [6] Ionut Constandache, Shravan Gaonkar, Matt Sayler, Romit Roy Choudhury, and Landon Cox. EnLoc: Energy-efficient localization for mobile phones. In *Proceedings - IEEE INFOCOM*, number 4, pages 2716–2720, 2009.

- [7] Brad K. Donohoo, Chris Ohlsen, Sudeep Pasricha, Yi Xiang, and Charles Anderson. Context-aware energy enhancements for smart mobile devices. *IEEE Transactions on Mobile Computing*, 13(8):1720–1732, 2014.
- [8] Nayeem Islam and Roy Want. Smartphones: Past, Present, and Future. *IEEE Pervasive Computing*, 13(4):89–92, 2014.
- [9] Sara Khalifa, Mahbub Hassan, and Aruna Seneviratne. Pervasive self-powered human activity recognition without the accelerometer. In *2015 IEEE International Conference on Pervasive Computing and Communications (PerCom)*, pages 79–86. IEEE, mar 2015.
- [10] Donnie H Kim, Younghun Kim, Deborah Estrin, and Mani B Srivastava. SensLoc: Sensing Everyday Places and Paths Using Less Energy. In *Proceedings of the 8th ACM Conference on Embedded Networked Sensor Systems, SenSys '10*, pages 43–56, New York, NY, USA, 2010. ACM.
- [11] Mikkel Kjaergaard. Location-based services on mobile phones: Minimizing power consumption. *IEEE Pervasive Computing*, 11:67–73, 2012.
- [12] Mikkel Baun Kjaergaard, Jakob Langdal, Torben Godsk, and Thomas Toftkjær. EnTracked : Energy-Efficient Robust Position Tracking for Mobile Devices. In *Proceedings of the 7th international conference on Mobile systems, applications, and services*, pages 221–234, 2009.
- [13] Kaisen Lin, Aman Kansal, Dimitrios Lymberopoulos, and Feng Zhao. Energy-accuracy trade-off for continuous mobile device location. In

Proceedings of the 8th international conference on Mobile systems, applications, and services - MobiSys '10, page 285, 2010.

- [14] Hong Lu, Jun Yang, Zhigang Liu, Nicholas D. Lane, Tanzeem Choudhury, and Andrew T. Campbell. The Jigsaw continuous sensing engine for mobile phone applications. In *Proceedings of the 8th ACM Conference on Embedded Networked Sensor Systems - SenSys '10*, page 71, 2010.
- [15] Xiao Ma, Yong Cui, and Ivan Stojmenovic. Energy efficiency on location based applications in mobile cloud computing: A survey. In *Procedia Computer Science*, volume 10, pages 577–584, 2012.
- [16] Yiming Ma, Rich Hankins, and David Racz. iLoc: a framework for incremental location-state acquisition and prediction based on mobile sensors. In *Proceeding of the 18th ACM conference on Information and knowledge management - CIKM '09*, page 1367, New York, New York, USA, 2009. ACM Press.
- [17] Yemao Man and Edith C H Ngai. Energy-efficient automatic location-triggered applications on smartphones. *Computer Communications*, 50:29–40, 2014.
- [18] Sînziana Mazilu, Ulf Blanke, Alberto Calatroni, and Gerhard Tröster. Low-power ambient sensing in smartphones for continuous semantic localization. In *Lecture Notes in Computer Science (including subseries*

Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), volume 8309 LNCS, pages 166–181, Ireland, 2013. Springer.

- [19] Luis Morillo, Luis Gonzalez-Abril, Juan Ramirez, and Miguel de la Concepcion. Low Energy Physical Activity Recognition System on Smartphones. *Sensors*, 15(3):5163–5196, 2015.
- [20] Jeongyeup Paek, Joongheon Kim, and Ramesh Govindan. Energy-efficient rate-adaptive GPS-based positioning for smartphones. In *Proceedings of the 8th international conference on Mobile systems, applications, and services - MobiSys '10*, volume 223-224, page 299, New York, New York, USA, 2010. ACM Press.
- [21] Jeongyeup Paek, Kyu-Han Kim, Jatinder P. Singh, and Ramesh Govindan. Energy-efficient positioning for smartphones using Cell-ID sequence matching. In *Proceedings of the 9th international conference on Mobile systems, applications, and services - MobiSys '11*, page 293, New York, New York, USA, 2011. ACM Press.
- [22] Alfredo J. Perez, Miguel a. Labrador, and Sean J. Barbeau. G-Sense: A scalable architecture for global sensing and monitoring. *IEEE Network*, 24(August):57–64, 2010.
- [23] Rafael Perez-Torres and Cesar Torres-Huitzil. A power-aware middleware for location & context aware mobile apps with cloud computing

interaction. In *Proceedings of the 2012 World Congress on Information and Communication Technologies, WICT 2012*, pages 691–696, 2012.

- [24] Kiran K Rachuri, Cecilia Mascolo, and Mirco Musolesi. *Mobile Context Awareness*. Springer London, London, 2012.
- [25] Jaemun Sim, Yonnim Lee, and Ohbyung Kwon. Context-aware enhancement of personalization services: A method of power optimization. *Expert Systems with Applications*, 41(13):5702–5709, 2014.
- [26] Vijay Srinivasan and Thomas Phan. An accurate two-tier classifier for efficient duty-cycling of smartphone activity recognition systems. In *Proceedings of the Third International Workshop on Sensing Applications on Mobile Phones - PhoneSense '12*, pages 1–5, 2012.
- [27] Yi Wang, Jialiu Lin, Murali Annamaram, Quinn a Jacobson, Jason Hong, Bhaskar Krishnamachari, and Norman Sadeh. A framework of energy efficient mobile sensing for automatic user state recognition. In *Proceedings of the 7th international conference on Mobile systems, applications, and services*, pages 179–192, 2009.
- [28] Ozgur Yurur, Miguel Labrador, and Wilfrido Moreno. Adaptive and energy efficient context representation framework in mobile sensing. *IEEE Transactions on Mobile Computing*, 13(8):1681–1693, 2014.

- [29] Lei Zhang, Jiangchuan Liu, Hongbo Jiang, and Yong Guan. SensTrack: Energy-efficient location tracking with smartphone sensors. *IEEE Sensors Journal*, 13(10):3775–3784, 2013.