# Lexical Analysis Programming Languages


Sujit Kumar Chakrabarti

IIITB

# Finite State Automata (FSA)


- 1 Non-deterministic FSA
- 2 Deterministic FSA

#### Example 1




**Language:**  $(a|b) \star abb$ 

# Example 1




# Example 1




Language:

# Example 1




**Language:**  $(a|b) \star abb$ 

#### Example 2



Language:  $aa \star |bb\star|$ 

#### Example 2



Language:  $aa \star |bb\star|$ 

- $\blacksquare$  Finite set of states -(S)
- $\blacksquare$  Alphabet  $(\sum)$
- Transition function  $(T: S \times \sum \rightarrow 2^S)$
- Initial state  $(S_0)$
- Final/accepting states  $(F \subseteq S)$

- $\blacksquare$  Finite set of states (S)
- $\blacksquare$  Alphabet  $(\sum)$
- Transition function  $(T: S \times \sum \rightarrow 2^S)$
- Initial state  $(S_0)$
- Final/accepting states  $(F \subseteq S)$
- Acceptance of a string: When there exists a path corresponding to the input leading to an accepting state.

- $\blacksquare$  Finite set of states (S)
- Alphabet  $(\sum)$
- Transition function  $(T: S \times \sum \rightarrow 2^S)$
- Initial state  $(S_0)$
- Final/accepting states  $(F \subseteq S)$
- Acceptance of a string: When there exists a path corresponding to the input leading to an accepting state.

#### **Specific Properties**

- The same state can transition to more than one states on the same symbol
- $\epsilon$ -transitions


- Finite set of states -(S)
- Alphabet  $(\sum)$
- Transition function  $(T: S \times \sum \rightarrow S)$
- Initial state  $(S_0)$
- Final/accepting states  $(F \subseteq S)$
- Acceptance of a string: When there exists a path corresponding to the input leading to an accepting state.

- Finite set of states -(S)
- Alphabet  $(\sum)$
- Transition function  $(T: S \times \sum \to S)$
- Initial state  $(S_0)$
- Final/accepting states  $(F \subseteq S)$
- Acceptance of a string: When there exists a path corresponding to the input leading to an accepting state.


#### **Specific Properties**

- Only one next-state on the same symbol
- No  $\epsilon$ -transitions

#### Example 1




#### Example 1



Language:

# Example 1



**Language:**  $(a|b) \star abb$ 

#### NFA and DFA

- NFAs: Often more readable
- NFAs: Usually have fewer states


#### NFA and DFA

- NFAs: Often more readable
- NFAs: Usually have fewer states
- DFAs: Less readable
- DFAs: Larger number of states
- DFAs: Faster to simulate


#### NFA and DFA

- NFAs: Often more readable
- NFAs: Usually have fewer states
- DFAs: Less readable
- DFAs: Larger number of states
- DFAs: Faster to simulate
- Equally expressive ≡ Regular expressions (Regular languages)

#### Lexical Analysis Process



#### Lexical Analysis Process



#### Next

Simulation of FSAs