

Pooja Exp_8

```
In [1]: import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier
from sklearn.metrics import accuracy_score, confusion_matrix, classification_report
import matplotlib.pyplot as plt
from sklearn import tree
```

Load the Iris dataset

```
In [3]: from sklearn.datasets import load_iris
iris = load_iris()
data = pd.DataFrame(data=iris.data, columns=iris.feature_names)
data['target'] = iris.target
print(data.head())
```

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width (cm)	\
0	5.1	3.5	1.4	0.2	
1	4.9	3.0	1.4	0.2	
2	4.7	3.2	1.3	0.2	
3	4.6	3.1	1.5	0.2	
4	5.0	3.6	1.4	0.2	

	target
0	0
1	0
2	0
3	0
4	0

Split the data

```
In [5]: X = data.drop('target', axis=1)
y = data['target']
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2, random_sta
```

Create and train the Decision Tree Classifier

```
In [6]: dt_classifier = DecisionTreeClassifier(random_state=42)
dt_classifier.fit(X_train, y_train)
```

```
Out[6]: DecisionTreeClassifier(random_state=42)
```

Make predictions

```
In [7]: y_pred = dt_classifier.predict(X_test)
```

Evaluate the model

```
In [8]: accuracy = accuracy_score(y_test, y_pred)
conf_matrix = confusion_matrix(y_test, y_pred)
class_report = classification_report(y_test, y_pred)
print(f'Accuracy: {accuracy:.2f}')
print(f'Confusion Matrix:\n{conf_matrix}')
print(f'Classification Report:\n{class_report}')
```

Accuracy: 1.00

Confusion Matrix:

```
[[10  0  0]
 [ 0  9  0]
 [ 0  0 11]]
```

Classification Report:

	precision	recall	f1-score	support
0	1.00	1.00	1.00	10
1	1.00	1.00	1.00	9
2	1.00	1.00	1.00	11
accuracy			1.00	30
macro avg	1.00	1.00	1.00	30
weighted avg	1.00	1.00	1.00	30

Visualize the Decision Tree

```
In [9]: plt.figure(figsize=(12,8))
tree.plot_tree(dt_classifier, feature_names=iris.feature_names,
class_names=iris.target_names, filled=True)
plt.title('Decision Tree Classifier')
plt.show()
```

Decision Tree Classifier



